

Table of Contents Section II – Soil and Site Information

	Issue Date	Date of Last Review	Responsible Staff
<i>Use and Explanation of Soil Interpretations</i>			
<i>Explanation of Key Phrases Used in Soil Interpretations</i>			
Soils Legends	1/02	1/02	SOI
<i>* Acreage and Proportionate Extent of the Soils</i>			
Soil Descriptions - Nontechnical	1/02	1/93	SOI
<i>Use and Explanation of Nontechnical Descriptions</i>			
<i>*Nontechnical Soils Description Report</i>			
Soil Descriptions - Technical	1/02	1/02	SOI
<i>*Map Unit Description Report</i>			
Cropland Interpretations - Technical	1/02	1/02	SOI
<i>*Prime Farmland Report</i>			
<i>* Kansas Soil Rating for Plant Growth Index</i>			
<i>*Soil Properties for Conservation Planning</i>			
Rangeland, Grazed Forestland, Native Pastureland Interpretations	1/02	1/02	SOI
<i>*Rangeland Productivity Report</i>			
<i>*Range Site Descriptions</i>			
Forestland Interpretations	1/93	1/93	SOI
<i>Use and Explanation of Forestland Interpretations</i>			
<i>*Woodland Management and Productivity</i>			
Nonagricultural Interpretations	1/02	1/02	SOI
<i>*Building Site Development Report</i>			
<i>*Construction Materials Report</i>			
Recreation Interpretations	1/02	1/02	SOI
<i>*Recreational Interpretations</i>			
Wildlife Interpretations	1/02	1/02	SOI
<i>*Wildlife Interpretations Report</i>			
Pastureland and Hayland Interpretations	1/02	1/02	SOI
<i>*Yields Per Acre of Pasture and Hayland</i>			

	Issue Date	Date of Last Review	Responsible Staff
Mined Land Interpretations <i>Use and Explanation of Mined Land Interpretations</i>	1/93	1/93	SOI
Windbreak Interpretations <i>*Conservation Tree and Shrub Management Report</i>	1/02	1/02	SOI
Engineering Interpretations <i>*Engineering Index Properties</i> <i>*Physical Properties of the Soils</i> <i>*Chemical Properties of the Soils</i> <i>*Water Features</i> <i>*Soil Features</i> <i>*Water Management Report</i>	1/02	1/02	SOI
Waste Disposal Interpretations <i>*Sanitary Facilities Report</i> <i>*Agricultural Waste Management Report</i>	1/02	1/02	SOI
Water Quantity and Quality Interpretations <i>Use and Explanation of Water Quantity and Quality Interpretations</i> <i>*Appendix A – Soils Potential For Surface Loss and Leaching</i> <i>*Appendix B – Pesticide Selected Properties Database</i> <i>*Appendix C – Herbicide Selected Properties Database</i> <i>*Soil-Pesticide Interaction Screening Procedure Worksheet (Blank)</i> <i>*WIN-PST SPISP II Soil Sensitivity to Pesticide Loss Rating Report</i>	1/02	1/02	SOI
Hydric Soil Interpretations <i>Use and Explanation of Hydric Soil Interpretations</i> <i>*Hydric Soils List</i>	1/02	1/02	SOI
HEL Interpretations <i>Use and Explanation of Highly Erodible Land Interpretations</i> <i>*Highly Erodible Lands Report</i> <i>*LS and Supporting Data for 1990 Frozen HEL List</i> <i>*CRP 20 Soil Supporting Data for 1990 Frozen HEL List</i>	7/95	1/00	SOI

**County specific computer generated reports.*

ACREAGE AND PROPORTIONATE EXTENT OF THE SOILS

Brown County, Kansas: Update

Map symbol	Soil name	Acres	Percent
Ac	Aksarben Silty Clay Loam, 0 To 2 Percent Slopes-----	170	*
Ad	Aksarben Silty Clay Loam, 2 To 5 Percent Slopes-----	15,290	4.2
Ae	Aksarben Silty Clay Loam, 5 To 11 Percent Slopes-----	30,120	8.2
Bs	Burchard Clay Loam, 6 To 12 Percent Slopes-----	1,650	0.5
Bx	Burchard-Steinauer Clay Loams, 12 To 18 Percent Slopes-----	1,610	0.4
Ch	Chase Silty Clay Loam, 0 To 2 Percent Slopes, Rarely Flooded-----	5,160	1.4
Co	Contrary Silty Clay Loam, 5 To 9 Percent Slopes-----	570	0.2
Ga	Grundy Silt Loam, 0 To 2 Percent Slopes-----	2,820	0.8
Ju	Judson Silt Loam, 2 To 6 Percent Slopes-----	2,690	0.7
Kd	Kennebec Silt Loam, Channeled, Frequently Flooded-----	2,200	0.6
Ke	Kennebec Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	31,130	8.5
Kp	Kipson-Sogn Silty Clay Loams, 5 To 30 Percent Slopes-----	3,020	0.8
M-W	Miscellaneous Water-----	3	*
Ma	Marshall Silt Loam, 2 To 5 Percent Slopes-----	10,730	2.9
Mb	Marshall Silty Clay Loam, 5 To 11 Percent Slopes-----	20,680	5.6
Md	Martin Silty Clay Loam, 1 To 4 Percent Slopes-----	800	0.2
Mf	Martin Silty Clay Loam, 4 To 9 Percent Slopes-----	140	*
Mh	Mayberry Clay Loam, 2 To 6 Percent Slopes-----	1,840	0.5
Mk	Monona Silt Loam, 2 To 5 Percent Slopes-----	440	0.1
Mn	Monona Silt Loam, 5 To 11 Percent Slopes, Moderately Eroded-----	2,470	0.7
Mt	Morrill Loam, 6 To 12 Percent Slopes-----	22,450	6.1
Mw	Muscotah Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded, Overwash-----	1,450	0.4
My	Muscotah Silty Clay Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	4,300	1.2
No	Nodaway Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	1,700	0.5
Om	Olmitz Loam, 2 To 5 Percent Slopes-----	1,220	0.3
Or	Orthents, Earthen Dam-----	30	*
Pd	Padonia-Martin Silty Clay Loams, 5 To 9 Percent Slopes-----	10,650	2.9
Pe	Padonia-Martin Silty Clay Loams, 9 To 25 Percent Slopes-----	2,730	0.7
Pf	Padonia-Oska Silty Clay Loams, 5 To 9 Percent Slopes-----	630	0.2
Pm	Pawnee Clay Loam, 2 To 6 Percent Slopes-----	250	*
Pn	Pawnee Clay Loam, 6 To 12 Percent Slopes-----	37,830	10.3
Po	Pawnee Clay, 6 To 12 Percent Slopes, Moderately Eroded-----	2,260	0.6
Pt	Pits, Quarries-----	110	*
Pw	Pohocco-Netawaka Silt Loams, 11 To 17 Percent Slopes-----	2,330	0.6
Px	Pohocco-Netawaka Silt Loams, 17 To 30 Percent Slopes-----	180	*
Re	Reading Silt Loam, 0 To 2 Percent Slopes, Moderately Wet, Rarely Flooded-----	1,120	0.3
Sg	Shelby Clay Loam, 6 To 12 Percent Slopes-----	6,000	1.6
Sm	Shelby Clay Loam, 12 To 18 Percent Slopes, Moderately Eroded-----	1,490	0.4
W	Water-----	1,504	0.4
Wa	Wabash Silty Clay, 0 To 2 Percent Slopes, Occasionally Flooded-----	250	*
We	Wamego Silty Clay Loam, 3 To 7 Percent Slopes-----	4,210	1.1
Wg	Wamego-Vinland Silty Clay Loams, 3 To 15 Percent Slopes-----	4,820	1.3
Wm	Wymore Silty Clay Loam, 2 To 5 Percent Slopes-----	56,970	15.6
Wn	Wymore Silty Clay Loam, 5 To 9 Percent Slopes-----	68,217	18.6
	Total-----	366,234	100.0

* Less than 0.1 percent.

Nontechnical Soil Descriptions
Brown County, Kansas

Nontechnical soil descriptions describe soil properties or management considerations specific to a soil map unit or group of map units, shown in the NonTechnical Descriptions report. These descriptions are written in terminology that Non-technical users of soil survey information can understand. Nontechnical soil descriptions are a powerful tool for creating reports. These high quality, easy to read reports can be generated by conservation planners and other NRCS employees for distribution to land users. Soil map unit descriptions and National Soil Information System records are the basis for these descriptions.

Ac Aksarben Silty Clay Loam, 0 To 2 Percent Slopes

Aksarben soil makes up 90 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping summit divide on upland. The runoff class is medium. The parent material consists of loess. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 1.

Ad Aksarben Silty Clay Loam, 2 To 5 Percent Slopes

Aksarben soil makes up 87 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping interfluvium on upland. The runoff class is medium. The parent material consists of loess. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 2e.

Ae Aksarben Silty Clay Loam, 5 To 11 Percent Slopes

Aksarben soil makes up 85 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping hillslope on upland. The runoff class is high. The parent material consists of loess. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

Bs Burchard Clay Loam, 6 To 12 Percent Slopes

Burchard soil makes up 85 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on upland. The runoff class is high. The parent material consists of loamy till, unspecified. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

Bx Burchard-Steinauer Clay Loams, 12 To 18 Percent Slopes

Burchard soil makes up 55 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately steep backslope hillslope on upland. The runoff class is high. The parent material consists of loamy till, unspecified. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 6e.

Steinauer soil makes up 40 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately steep backslope hillslope on upland. The runoff class is high. The parent material consists of fine-loamy till, unspecified. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Limy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 6e.

Ch Chase Silty Clay Loam, 0 To 2 Percent Slopes, Rarely Flooded

Chase soil makes up 90 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on river valley. The runoff class is medium. The parent material consists of silty and clayey alluvium. This soil is somewhat poorly drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is rarely flooded and is not ponded. The top of the seasonal high water table is at 24 inches. The soil contains a maximum amount of 1 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 2w.

Nontechnical Soil Descriptions--Continued
Brown County, Kansas

Co Contrary Silty Clay Loam, 5 To 9 Percent Slopes

Contrary soil makes up 85 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping shoulder, backslope hillslope on upland. The runoff class is medium. The parent material consists of loess. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a low shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

Ga Grundy Silt Loam, 0 To 2 Percent Slopes

Grundy soil makes up 90 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping shoulder, summit divide on upland. The runoff class is high. The parent material consists of loess. This soil is somewhat poorly drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 2e.

Ju Judson Silt Loam, 2 To 6 Percent Slopes

Judson soil makes up 95 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping footslope fan remnant on upland. The runoff class is low. The parent material consists of loamy colluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 2e.

Kd Kennebec Silt Loam, Channeled, Frequently Flooded

Kennebec, CHANNELED, soil makes up 85 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is low. The parent material consists of silty alluvium. This soil is moderately well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is frequently flooded and is not ponded. The top of the seasonal high water table is at 42 inches. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 5w.

Ke Kennebec Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded

Kennebec soil makes up 89 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is low. The parent material consists of silty alluvium. This soil is moderately well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is occasionally flooded and is not ponded. The top of the seasonal high water table is at 42 inches. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 2w.

Kp Kipson-Sogn Silty Clay Loams, 5 To 30 Percent Slopes

Kipson soil makes up 60 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to steep backslope, shoulder hillslope on upland. The runoff class is very high. The parent material consists of silty residuum weathered from shale, calcareous. The soil is 7 to 20 inches deep to bedrock (paralithic). This soil is somewhat excessively drained. The slowest permeability is moderate. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 60 percent calcium carbonate. This soil is in the Limy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 6e.

Sogn soil makes up 30 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep backslope hillslope on upland. The runoff class is very high. The parent material consists of loamy residuum weathered from limestone, unspecified. The soil is 4 to 20 inches deep to bedrock (lithic). This soil is somewhat excessively drained. The slowest permeability is moderate. It has a very low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 10 percent calcium carbonate. This soil is in the Shallow Limy (pe30-37) range site. It is in the nonirrigated land capability classification 6s.

Ma Marshall Silt Loam, 2 To 5 Percent Slopes

Marshall soil makes up 97 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping summit, shoulder upland, interfluvium. The runoff class is low. The parent material consists of loamy loess. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 2e.

Nontechnical Soil Descriptions--Continued
Brown County, Kansas

Mb Marshall Silty Clay Loam, 5 To 11 Percent Slopes

Marshall soil makes up 82 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping hillslope, upland. The runoff class is medium. The parent material consists of loamy loess. This soil is well drained. The slowest permeability is moderate. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

Md Martin Silty Clay Loam, 1 To 4 Percent Slopes

Martin soil makes up 85 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping footslope hillslope on upland. The runoff class is high. The parent material consists of silty and clayey colluvium derived from limestone-shale over silty and clayey residuum weathered from limestone-shale. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. The soil contains a maximum amount of 1 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 2e.

Mf Martin Silty Clay Loam, 4 To 9 Percent Slopes

Martin soil makes up 90 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping footslope, backslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey colluvium derived from limestone-shale over silty and clayey residuum weathered from limestone-shale. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. The soil contains a maximum amount of 1 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Mh Mayberry Clay Loam, 2 To 6 Percent Slopes

Mayberry soil makes up 85 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping backslope hillslope on upland. The runoff class is high. The parent material consists of till, unspecified. This soil is moderately well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

Mk Monona Silt Loam, 2 To 5 Percent Slopes

Monona soil makes up 90 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping shoulder, summit interfluvium on upland. The runoff class is low. The parent material consists of loess. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a low shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 10 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 2e.

Mn Monona Silt Loam, 5 To 11 Percent Slopes, Moderately Eroded

Monona soil makes up 82 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope, shoulder hillslope on upland. The runoff class is medium. The parent material consists of loess. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a low shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 10 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

Mt Morrill Loam, 6 To 12 Percent Slopes

Morrill soil makes up 87 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping hillslope on upland. The runoff class is high. The parent material consists of glacial drift. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Mw Muscotah Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded, Overwash

Muscotah soil makes up 87 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is medium. The parent material consists of clayey alluvium. This soil is somewhat poorly drained. The slowest permeability is impermeable. It has a high available water capacity and a high shrink swell potential. This soil is occasionally flooded and is not ponded. The top of the seasonal high water table is at 24 inches. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 2w.

Nontechnical Soil Descriptions--Continued
Brown County, Kansas

My Muscotah Silty Clay Loam, 0 To 2 Percent Slopes, Occasionally Flooded

Muscotah soil makes up 87 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is medium. The parent material consists of clayey alluvium. This soil is somewhat poorly drained. The slowest permeability is impermeable. It has a high available water capacity and a high shrink swell potential. This soil is occasionally flooded and is not ponded. The top of the seasonal high water table is at 24 inches. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 2w.

No Nodaway Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded

Nodaway soil makes up 90 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is low. The parent material consists of silty alluvium. This soil is moderately well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is occasionally flooded and is not ponded. The top of the seasonal high water table is at 36 inches. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 2w.

Om Olmitz Loam, 2 To 5 Percent Slopes

Olmitz soil makes up 93 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping footslope fan terrace on upland. The runoff class is low. The parent material consists of fine-loamy alluvium. This soil is moderately well drained. The slowest permeability is moderate. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 42 inches. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 2e.

Pd Padonia-Martin Silty Clay Loams, 5 To 9 Percent Slopes

Padonia soil makes up 50 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on upland. The runoff class is high. The parent material consists of residuum weathered from shale, calcareous. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Martin soil makes up 40 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping footslope, backslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey colluvium derived from limestone-shale over silty and clayey residuum weathered from limestone-shale. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. The soil contains a maximum amount of 1 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Pe Padonia-Martin Silty Clay Loams, 9 To 25 Percent Slopes

Padonia soil makes up 60 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a strongly sloping to steep footslope, backslope hillslope on upland. The runoff class is very high. The parent material consists of residuum weathered from shale, calcareous. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 6e.

Martin soil makes up 30 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope, footslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey colluvium derived from limestone-shale over silty and clayey residuum weathered from limestone-shale. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. The soil contains a maximum amount of 1 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Pf Padonia-Oska Silty Clay Loams, 5 To 9 Percent Slopes

Padonia soil makes up 55 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping shoulder hillslope on upland. The runoff class is high. The parent material consists of residuum weathered from shale, calcareous. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Nontechnical Soil Descriptions--Continued
Brown County, Kansas

Oska soil makes up 40 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey residuum weathered from limestone-shale. The soil is 20 to 40 inches deep to bedrock (lithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

Pm Pawnee Clay Loam, 2 To 6 Percent Slopes

Pawnee soil makes up 85 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping shoulder, summit hillslope on upland. The runoff class is high. The parent material consists of till, unspecified. This soil is moderately well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

Pn Pawnee Clay Loam, 6 To 12 Percent Slopes

Pawnee soil makes up 83 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping shoulder, summit hillslope on upland. The runoff class is very high. The parent material consists of till, unspecified. This soil is moderately well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Po Pawnee Clay, 6 To 12 Percent Slopes, Moderately Eroded

Pawnee soil makes up 84 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on upland. The runoff class is very high. The parent material consists of till, unspecified. This soil is moderately well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Pw Pohocco-Netawaka Silt Loams, 11 To 17 Percent Slopes

Pohocco soil makes up 50 percent of the map unit. This map unit is in the Iowa and Missouri Deep Loess Hills Major Land Resource Area. This soil occurs on a strongly sloping to moderately steep shoulder hillslope on upland. The runoff class is medium. The parent material consists of fine-silty loess. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Netawaka soil makes up 40 percent of the map unit. This map unit is in the Iowa and Missouri Deep Loess Hills Major Land Resource Area. This soil occurs on a strongly sloping to moderately steep backslope hillslope, upland. The runoff class is medium. The parent material consists of fine-silty loess. This soil is somewhat excessively drained. The slowest permeability is moderate. It has a very high available water capacity and a low shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 10 percent calcium carbonate. This soil is in the Limy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Px Pohocco-Netawaka Silt Loams, 17 To 30 Percent Slopes

Pohocco soil makes up 50 percent of the map unit. This map unit is in the Iowa and Missouri Deep Loess Hills Major Land Resource Area. This soil occurs on a moderately steep to steep shoulder hillslope on upland. The runoff class is high. The parent material consists of fine-silty loess. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 6e.

Netawaka soil makes up 40 percent of the map unit. This map unit is in the Iowa and Missouri Deep Loess Hills Major Land Resource Area. This soil occurs on a moderately steep to steep shoulder, backslope hillslope on upland. The runoff class is high. The parent material consists of fine-silty loess. This soil is somewhat excessively drained. The slowest permeability is moderate. It has a very high available water capacity and a low shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 10 percent calcium carbonate. This soil is in the Limy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 6e.

Re Reading Silt Loam, 0 To 2 Percent Slopes, Moderately Wet, Rarely Flooded

Reading soil makes up 90 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is medium. The parent material consists of silty alluvium. This soil is moderately well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is rarely flooded and is not ponded. The top of the seasonal high water table is at 42 inches. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 1.

Nontechnical Soil Descriptions--Continued
Brown County, Kansas

Sg Shelby Clay Loam, 6 To 12 Percent Slopes

Shelby soil makes up 88 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope, shoulder hillslope, upland. The runoff class is high. The parent material consists of till, unspecified. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

Sm Shelby Clay Loam, 12 To 18 Percent Slopes, Moderately Eroded

Shelby soil makes up 85 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately steep backslope, shoulder hillslope on upland. The runoff class is high. The parent material consists of till, unspecified. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Wa Wabash Silty Clay, 0 To 2 Percent Slopes, Occasionally Flooded

Wabash soil makes up 85 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is high. The parent material consists of clayey alluvium. This soil is poorly drained. The slowest permeability is very slow. It has a moderate available water capacity and a very high shrink swell potential. This soil is occasionally flooded and is not ponded. The top of the seasonal high water table is at 6 inches. This soil is in the Clay Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 3w.

We Wamego Silty Clay Loam, 3 To 7 Percent Slopes

Wamego soil makes up 90 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping backslope hillslope on upland. The runoff class is high. The parent material consists of sandy and silty residuum weathered from shale, unspecified. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Wg Wamego-Vinland Silty Clay Loams, 3 To 15 Percent Slopes

Wamego soil makes up 50 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep backslope hillslope on upland. The runoff class is very high. The parent material consists of sandy and silty residuum weathered from shale, unspecified. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 6e.

Vinland soil makes up 40 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep backslope hillslope on upland. The runoff class is very high. The parent material consists of sandy and silty residuum weathered from shale, unspecified. The soil is 10 to 20 inches deep to bedrock (paralithic). This soil is somewhat excessively drained. The slowest permeability is moderate. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Shallow Savannah (pe30-37) range site. It is in the nonirrigated land capability classification 6e.

Wm Wymore Silty Clay Loam, 2 To 5 Percent Slopes

Wymore soil makes up 90 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping shoulder interfluvium on upland. The runoff class is high. The parent material consists of loess. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. The soil contains a maximum amount of 2 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

Wn Wymore Silty Clay Loam, 5 To 9 Percent Slopes

Wymore soil makes up 82 percent of the map unit. This map unit is in the Nebraska and Kansas Loess-Drift Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on upland. The runoff class is very high. The parent material consists of loess. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. The soil contains a maximum amount of 2 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

Ac—Aksarben silty clay loam, 0 to 2 percent slopes

Map Unit Composition

Aksarben: 90 percent
Minor components: 10 percent

Component Descriptions

Aksarben

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Divide on upland
Hillslope position: Summit
Parent material: Loess
Slope: 0 to 2 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 10.6 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 1

Typical Profile:

Ap—0 to 9 inches; silty clay loam
A—9 to 13 inches; silty clay loam
BA—13 to 19 inches; silty clay loam
Bt—19 to 39 inches; silty clay loam
BC—39 to 47 inches; silty clay loam
C—47 to 80 inches; silt loam

Minor Components

Marshall

Composition: About 10 percent
Geomorphic Position: interfluvial upland
Slope: 2 to 5 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Ad—Aksarben silty clay loam, 2 to 5 percent slopes

Map Unit Composition

Aksarben: 87 percent
Minor components: 13 percent

Component Descriptions

Aksarben

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Interfluvial on upland
Parent material: Loess
Slope: 2 to 5 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 10.7 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 2e

Typical Profile:

Ap—0 to 6 inches; silty clay loam
A—6 to 12 inches; silty clay loam
Bt1—12 to 18 inches; silty clay loam
Bt2—18 to 26 inches; silty clay loam
Bt3—26 to 34 inches; silty clay loam
Bt4—34 to 42 inches; silty clay loam
BC—42 to 60 inches; silty clay loam
C—60 to 80 inches; silt loam

Minor Components

Marshall

Composition: About 4 percent
Geomorphic Position: interfluvial on upland
Slope: 2 to 5 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Wymore

Composition: About 4 percent
Geomorphic Position: interfluvial on upland
Slope: 2 to 5 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Kennebec

Composition: About 3 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Judson

Composition: About 2 percent
Geomorphic Position: fan remnant on upland
Slope: 2 to 6 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Ae—Aksarben silty clay loam, 5 to 11 percent slopes

Slope: 5 to 9 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Map Unit Composition

Aksarben: 85 percent
 Minor components: 15 percent

Component Descriptions**Aksarben**

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Parent material: Loess
Slope: 5 to 11 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 10.7 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 6 inches; silty clay loam
 A—6 to 12 inches; silty clay loam
 Bt1—12 to 18 inches; silty clay loam
 Bt2—18 to 26 inches; silty clay loam
 Bt3—26 to 34 inches; silty clay loam
 Bt4—34 to 42 inches; silty clay loam
 BC—42 to 60 inches; silty clay loam
 C—60 to 80 inches; silt loam

Minor Components**Judson**

Composition: About 3 percent
Geomorphic Position: fan remnant on upland
Slope: 2 to 6 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Kennebec

Composition: About 3 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Morrill

Composition: About 3 percent
Slope: 6 to 12 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Wymore

Composition: About 3 percent
Geomorphic Position: hillslope on upland

Marshall

Composition: About 3 percent
Slope: 5 to 11 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Bs—Burchard clay loam, 6 to 12 percent slopes**Map Unit Composition**

Burchard: 85 percent
 Minor components: 15 percent

Component Descriptions**Burchard**

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Loamy till, unspecified
Slope: 6 to 12 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 9.5 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 9 inches; clay loam
 A—9 to 13 inches; clay loam
 Bt—13 to 19 inches; clay loam
 Btk—19 to 29 inches; clay loam
 Bck—29 to 37 inches; clay loam
 C—37 to 60 inches; clay loam

Minor Components**Pawnee**

Composition: About 10 percent
Geomorphic Position: hillslope on upland
Slope: 6 to 12 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Steinauer

Composition: About 5 percent
Geomorphic Position: hillslope on upland
Slope: 6 to 12 percent
Drainage class: Well drained
Ecological site: Limy Upland (pe30-37)

Bx—Burchard-Steinauer clay loams, 12 to 18 percent slopes

Map Unit Composition

Burchard: 55 percent
 Steinauer: 40 percent
 Minor components: 5 percent

Component Descriptions

Burchard

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Loamy till, unspecified
Slope: 12 to 18 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 9.4 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 6e

Typical Profile:

Ap—0 to 9 inches; clay loam
 Bt—9 to 19 inches; clay loam
 Btk—19 to 29 inches; clay loam
 BCk—29 to 37 inches; clay loam
 C—37 to 60 inches; clay loam

Steinauer

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Fine-loamy till, unspecified
Slope: 12 to 18 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 10.8 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None

Depth to seasonal water saturation: More than 6 feet

Runoff class: High

Ecological site: Limy Upland (pe30-37)

Land capability (nonirrigated): 6e

Typical Profile:

A—0 to 6 inches; clay loam
 AC—6 to 14 inches; clay loam
 C—14 to 80 inches; clay loam

Minor Components**Padonia**

Composition: About 5 percent
Geomorphic Position: hillslope on upland
Slope: 9 to 25 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Clay Upland (pe30-37)

Ch—Chase silty clay loam, 0 to 2 percent slopes, rarely flooded

Map Unit Composition

Chase: 90 percent
 Minor components: 10 percent

Component Descriptions

Chase

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Flood plain on river valley
Parent material: Silty and clayey alluvium
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 9.9 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: Rare
Depth to seasonal water saturation: About 22 to 26 inches
Runoff class: Medium
Ecological site: Loamy Lowland (pe30-37)
Land capability (nonirrigated): 2w

Typical Profile:

Ap—0 to 9 inches; silty clay loam
 BA—9 to 19 inches; silty clay loam
 Bt—19 to 41 inches; silty clay
 BC—41 to 47 inches; silty clay loam
 C—47 to 80 inches; silty clay loam

Minor Components**Kennebec**

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Muscotah

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Ecological site: Loamy Lowland (pe30-37)

Co—Contrary silty clay loam, 5 to 9 percent slopes**Map Unit Composition**

Contrary: 85 percent
 Minor components: 15 percent

Component Descriptions**Contrary**

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Shoulder, backslope
Parent material: Loess
Slope: 5 to 9 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.3 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 6 inches; silty clay loam
 Bw—6 to 32 inches; silty clay loam
 C—32 to 80 inches; silt loam

Minor Components**Morrill**

Composition: About 8 percent
Slope: 6 to 12 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Kennebec

Composition: About 7 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained

Ecological site: Loamy Lowland (pe30-37)

Ga—Grundy silt loam, 0 to 2 percent slopes**Map Unit Composition**

Grundy: 90 percent
 Minor components: 10 percent

Component Descriptions**Grundy**

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Divide on upland
Hillslope position: Shoulder, summit
Parent material: Loess
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 9.3 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 9 to 14 inches
Runoff class: High
Ecological site: Clay Upland (pe30-37)
Land capability (nonirrigated): 2e

Typical Profile:

Ap—0 to 7 inches; silt loam
 A—7 to 14 inches; silty clay loam
 Bt—14 to 41 inches; silty clay
 BC—41 to 48 inches; silty clay loam
 C—48 to 80 inches; silty clay loam

Minor Components**Haig**

Composition: About 10 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained
Ecological site: Clay Upland (pe30-37)

Ju—Judson silt loam, 2 to 6 percent slopes**Map Unit Composition**

Judson: 95 percent

Minor components: 5 percent

Component Descriptions

Judson

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills

Landform: Fan remnant on upland

Hillslope position: Footslope

Parent material: Loamy colluvium

Slope: 2 to 6 percent

Drainage class: Well drained

Slowest permeability: Moderate (About 0.60 in/hr)

Available water capacity: Very high (About 13.0 inches)

Shrink-swell potential: Moderate (About 4.5 LEP)

Flooding hazard: None

Depth to seasonal water saturation: More than 6 feet

Runoff class: Low

Ecological site: Loamy Lowland (pe30-37)

Land capability (nonirrigated): 2e

Typical Profile:

Ap—0 to 7 inches; silt loam

A—7 to 25 inches; silt loam

AB—25 to 40 inches; silty clay loam

Bw—40 to 50 inches; silty clay loam

BC—50 to 80 inches; silty clay loam

Minor Components

Kennebec

Composition: About 5 percent

Slope: 0 to 2 percent

Drainage class: Moderately well drained

Ecological site: Loamy Lowland (pe30-37)

Kd—Kennebec silt loam, channeled, frequently flooded

Map Unit Composition

Kennebec: 85 percent

Minor components: 15 percent

Component Descriptions

Kennebec

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills

Landform: Flood plain on valley

Parent material: Silty alluvium

Slope: 0 to 2 percent

Drainage class: Moderately well drained

Slowest permeability: Moderate (About 0.60 in/hr)

Available water capacity: Very high (About 13.2 inches)

Shrink-swell potential: Moderate (About 4.5 LEP)

Flooding hazard: Frequent

Ponding hazard: None

Depth to seasonal water saturation: About 39 to 55 inches

Runoff class: Low

Ecological site: Loamy Lowland (pe30-37)

Land capability (nonirrigated): 5w

Typical Profile:

Ap—0 to 8 inches; silt loam

A1—8 to 18 inches; silt loam

A2—18 to 32 inches; silt loam

A3—32 to 41 inches; silt loam

AC—41 to 54 inches; silt loam

C—54 to 60 inches; silt loam

Minor Components

Nodaway

Composition: About 8 percent

Slope: 0 to 2 percent

Drainage class: Moderately well drained

Ecological site: Loamy Lowland (pe30-37)

Kenridge

Composition: About 3 percent

Slope: 0 to 2 percent

Drainage class: Moderately well drained

Ecological site: Loamy Lowland (pe30-37)

Muscotah

Composition: About 3 percent

Slope: 0 to 2 percent

Drainage class: Somewhat poorly drained

Ecological site: Loamy Lowland (pe30-37)

Zook

Composition: About 1 percent

Slope: 0 to 2 percent

Drainage class: Poorly drained

Ecological site: Clay Lowland (pe30-37)

Ke—Kennebec silt loam, 0 to 2 percent slopes, occasionally flooded

Map Unit Composition

Kennebec: 89 percent

Minor components: 11 percent

Component Descriptions

Kennebec

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills

Landform: Flood plain on valley

Parent material: Silty alluvium

Slope: 0 to 2 percent

Drainage class: Moderately well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 13.2 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: Occasional
Ponding hazard: None
Depth to seasonal water saturation: About 39 to 55 inches
Runoff class: Low
Ecological site: Loamy Lowland (pe30-37)
Land capability (nonirrigated): 2w

Typical Profile:

Ap—0 to 8 inches; silt loam
 A1—8 to 18 inches; silt loam
 A2—18 to 32 inches; silt loam
 A3—32 to 41 inches; silt loam
 AC—41 to 54 inches; silt loam
 C—54 to 60 inches; silt loam

Minor Components

Muscotah

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Ecological site: Loamy Lowland (pe30-37)

Kenridge

Composition: About 4 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Zook

Composition: About 2 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained
Ecological site: Clay Lowland (pe30-37)

Kp—Kipson-Sogn silty clay loams, 5 to 30 percent slopes

Map Unit Composition

Kipson: 60 percent
 Sogn: 30 percent
 Minor components: 10 percent

Component Descriptions

Kipson

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope, shoulder

Parent material: Silty residuum weathered from shale, calcareous
Slope: 5 to 30 percent
Depth to restrictive feature: 7 to 20 inches to bedrock (paralithic)
Drainage class: Somewhat excessively drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Low (About 3.5 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Limy Upland (pe30-37)
Land capability (nonirrigated): 6e

Typical Profile:

A—0 to 8 inches; silty clay loam
 C—8 to 19 inches; silty clay loam
 Cr—19 to 22 inches; weathered bedrock

Sogn

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Loamy residuum weathered from limestone, unspecified
Slope: 5 to 20 percent
Depth to restrictive feature: 4 to 20 inches to bedrock (lithic)
Drainage class: Somewhat excessively drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very low (About 2.6 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Shallow Limy (pe30-37)
Land capability (nonirrigated): 6s

Typical Profile:

A—0 to 12 inches; silty clay loam
 R—12 to

Minor Components

Kennebec

Composition: About 10 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

M-W—Miscellaneous Water**Ma—Marshall silt loam, 2 to 5 percent slopes****Map Unit Composition**

Marshall: 97 percent
 Minor components: 3 percent

Component Descriptions**Marshall**

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Upland, interfluve
Hillslope position: Summit, shoulder
Parent material: Loamy loess
Slope: 2 to 5 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.1 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 2e

Typical Profile:

Ap—0 to 10 inches; silt loam
 B—10 to 32 inches; silty clay loam
 C—32 to 80 inches; silt loam

Minor Components**Aksarben**

Composition: About 3 percent
Slope: 2 to 5 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Mb—Marshall silty clay loam, 5 to 11 percent slopes**Map Unit Composition**

Marshall: 82 percent
 Minor components: 18 percent

Component Descriptions**Marshall**

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope, upland
Parent material: Loamy loess
Slope: 5 to 11 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: High (About 11.7 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 6 inches; silty clay loam
 B—6 to 44 inches; silty clay loam
 C—44 to 80 inches; silt loam

Minor Components**Contrary**

Composition: About 7 percent
Geomorphic Position: hillslope on upland
Slope: 5 to 9 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Morrill

Composition: About 5 percent
Slope: 6 to 12 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Judson

Composition: About 3 percent
Geomorphic Position: fan remnant on upland
Slope: 2 to 6 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Kennebec

Composition: About 3 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Md—Martin silty clay loam, 1 to 4 percent slopes**Map Unit Composition**

Martin: 85 percent
Minor components: 15 percent

Component Descriptions**Martin**

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Foothills
Parent material: Silty and clayey colluvium derived from limestone-shale over silty and clayey residuum weathered from limestone-shale
Slope: 1 to 4 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 9.5 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 22 to 26 inches
Runoff class: High
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 2e

Typical Profile:

Ap—0 to 6 inches; silty clay loam
BA—6 to 12 inches; silty clay loam
Bt—12 to 53 inches; silty clay
C—53 to 80 inches; silty clay

Minor Components**Chase**

Composition: About 10 percent
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Ecological site: Loamy Lowland (pe30-37)

Pawnee

Composition: About 5 percent
Geomorphic Position: hillslope on upland
Slope: 2 to 6 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Mf—Martin silty clay loam, 4 to 9 percent slopes**Map Unit Composition**

Martin: 90 percent
Minor components: 10 percent

Component Descriptions**Martin**

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Foothills, backslope
Parent material: Silty and clayey colluvium derived from limestone-shale over silty and clayey residuum weathered from limestone-shale
Slope: 4 to 12 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 9.5 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 22 to 26 inches
Runoff class: Very high
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 6 inches; silty clay loam
BA—6 to 12 inches; silty clay loam
Bt—12 to 53 inches; silty clay
C—53 to 80 inches; silty clay

Minor Components**Padonia**

Composition: About 5 percent
Geomorphic Position: hillslope on upland
Slope: 5 to 9 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Clay Upland (pe30-37)

Vinland

Composition: About 5 percent
Geomorphic Position: hillslope on upland
Slope: 3 to 15 percent
Depth to restrictive feature: 10 to 20 inches to bedrock (paralithic)
Drainage class: Somewhat excessively drained
Ecological site: Shallow Savannah (pe30-37)

Mh—Mayberry clay loam, 2 to 6 percent slopes

Map Unit Composition

Mayberry: 85 percent
Minor components: 15 percent

Component Descriptions

Mayberry

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Till, unspecified
Slope: 2 to 6 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 7.7 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 9 to 14 inches
Runoff class: High
Ecological site: Clay Upland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 10 inches; clay loam
Bt—10 to 42 inches; clay
C—42 to 80 inches; clay loam

Minor Components

Morrill

Composition: About 8 percent
Slope: 6 to 12 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Wymore

Composition: About 7 percent
Geomorphic Position: interfluvium on upland
Slope: 2 to 5 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Mk—Monona silt loam, 2 to 5 percent slopes

Map Unit Composition

Monona: 90 percent

Minor components: 10 percent

Component Descriptions

Monona

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Interfluvium on upland
Hillslope position: Shoulder, summit
Parent material: Loess
Slope: 2 to 5 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.6 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 2e

Typical Profile:

Ap—0 to 11 inches; silt loam
Bw—11 to 30 inches; silt loam
C—30 to 80 inches; silt loam

Minor Components

Pohocco

Composition: About 10 percent
Geomorphic Position: hillslope on upland
Slope: 5 to 17 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Mn—Monona silt loam, 5 to 11 percent slopes, moderately eroded

Map Unit Composition

Monona: 82 percent
Minor components: 18 percent

Component Descriptions

Monona

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope, shoulder
Parent material: Loess
Slope: 5 to 11 percent
Drainage class: Well drained

Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.5 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 6 inches; silt loam
 Bw—6 to 30 inches; silt loam
 C—30 to 80 inches; silt loam

Minor Components

Netawaka

Composition: About 10 percent
Geomorphic Position: hillslope on upland
Slope: 10 to 15 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Pohocco

Composition: About 5 percent
Geomorphic Position: hillslope on upland
Slope: 8 to 17 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Kennebec

Composition: About 3 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Mt—Morrill loam, 6 to 12 percent slopes

Map Unit Composition

Morrill: 87 percent
 Minor components: 13 percent

Component Descriptions

Morrill

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Parent material: Glacial drift
Slope: 6 to 12 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 9.2 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)

Flooding hazard: None
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Lowland (pe30-37)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 6 inches; loam
 BA—6 to 12 inches; loam
 Bt—12 to 43 inches; sandy clay loam, loam
 BC—43 to 52 inches; fine sandy loam
 C—52 to 80 inches; sand, loamy fine sand, fine sandy loam

Minor Components

Kennebec

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Pawnee

Composition: About 5 percent
Geomorphic Position: hillslope on upland
Slope: 6 to 12 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Olmitz

Composition: About 3 percent
Geomorphic Position: fan terrace on upland
Slope: 2 to 5 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe30-37)

Mw—Muscotah silt loam, 0 to 2 percent slopes, occasionally flooded, overwash

Map Unit Composition

Muscotah: 87 percent
 Minor components: 13 percent

Component Descriptions

Muscotah

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Flood plain on valley
Parent material: Clayey alluvium
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained

Slowest permeability: Impermeable (About 0.00 in/hr)
Available water capacity: High (About 11.2 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: Occasional
Depth to seasonal water saturation: About 21 to 26 inches
Runoff class: Medium
Ecological site: Loamy Lowland (pe30-37)
Land capability (nonirrigated): 2w

Typical Profile:

Ap—0 to 9 inches; silt loam
 C—9 to 16 inches; stratified silt loam to silty clay loam
 Ab—16 to 30 inches; silty clay loam
 Bwb—30 to 39 inches; silty clay
 Bgb1—39 to 61 inches; silty clay
 Bgb2—61 to 70 inches; silty clay
 Bgb3—70 to 80 inches; silty clay

Minor Components

Zook

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained
Ecological site: Clay Lowland (pe30-37)

Kennebec

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Chase

Composition: About 3 percent
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Ecological site: Loamy Lowland (pe30-37)

My—Muscotah silty clay loam, 0 to 2 percent slopes, occasionally flooded

Map Unit Composition

Muscotah: 87 percent
 Minor components: 13 percent

Component Descriptions

Muscotah

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Flood plain on valley
Parent material: Clayey alluvium
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained

Slowest permeability: Impermeable (About 0.00 in/hr)
Available water capacity: High (About 10.8 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: Occasional
Depth to seasonal water saturation: About 21 to 26 inches
Runoff class: Medium
Ecological site: Loamy Lowland (pe30-37)
Land capability (nonirrigated): 2w

Typical Profile:

Ap—0 to 9 inches; silty clay loam
 A1—9 to 16 inches; silty clay loam
 A2—16 to 23 inches; silty clay loam
 Bw1—23 to 35 inches; silty clay loam
 Bw2—35 to 44 inches; silty clay
 Bw3—44 to 60 inches; silty clay
 Bw4—60 to 70 inches; silty clay
 Bg—70 to 80 inches; silty clay

Minor Components

Kennebec

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Wabash

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained
Ecological site: Clay Lowland (pe30-37)

Chase

Composition: About 3 percent
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Ecological site: Loamy Lowland (pe30-37)

No—Nodaway silt loam, 0 to 2 percent slopes, occasionally flooded

Map Unit Composition

Nodaway: 90 percent
 Minor components: 10 percent

Component Descriptions

Nodaway

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Flood plain on valley

Parent material: Silty alluvium
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 13.0 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: Occasional
Depth to seasonal water saturation: About 33 to 38 inches
Runoff class: Low
Ecological site: Loamy Lowland (pe30-37)
Land capability (nonirrigated): 2w

Typical Profile:

Ap—0 to 7 inches; silt loam
 C1—7 to 14 inches; stratified silt loam to silty clay loam
 C2—14 to 45 inches; stratified silt loam to silty clay loam
 C3—45 to 60 inches; stratified silt loam to silty clay loam

Minor Components

Chase

Composition: About 4 percent
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Ecological site: Loamy Lowland (pe30-37)

Zook

Composition: About 3 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained
Ecological site: Clay Lowland (pe30-37)

Kennebec

Composition: About 3 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Om—Olmitz loam, 2 to 5 percent slopes

Map Unit Composition

Olmitz: 93 percent
 Minor components: 7 percent

Component Descriptions

Olmitz

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Fan terrace on upland
Hillslope position: Footslope

Parent material: Fine-loamy alluvium
Slope: 2 to 5 percent
Drainage class: Moderately well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: High (About 10.3 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 40 to 44 inches
Runoff class: Low
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 2e

Typical Profile:

Ap—0 to 7 inches; loam
 A—7 to 20 inches; loam
 Bw—20 to 42 inches; clay loam
 BC—42 to 80 inches; clay loam

Minor Components

Chase

Composition: About 4 percent
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Ecological site: Loamy Lowland (pe30-37)

Pawnee

Composition: About 3 percent
Geomorphic Position: hillslope on upland
Slope: 2 to 6 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Or—Orthents, Earthen Dam

Pd—Padonia-Martin silty clay loams, 5 to 9 percent slopes

Map Unit Composition

Padonia: 50 percent
 Martin: 40 percent
 Minor components: 10 percent

Component Descriptions

Padonia

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland

Hillslope position: Backslope

Parent material: Residuum weathered from shale, calcareous

Slope: 5 to 9 percent

Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)

Drainage class: Well drained

Slowest permeability: Slow (About 0.06 in/hr)

Available water capacity: Moderate (About 6.5 inches)

Shrink-swell potential: High (About 7.5 LEP)

Flooding hazard: None

Depth to seasonal water saturation: More than 6 feet

Runoff class: High

Ecological site: Clay Upland (pe30-37)

Land capability (nonirrigated): 4e

Typical Profile:

A—0 to 11 inches; silty clay loam

Bt—11 to 22 inches; silty clay

Btk—22 to 32 inches; silty clay

BCk—32 to 37 inches; silty clay loam

Cr—37 to 40 inches; weathered bedrock

Martin

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills

Landform: Hillslope on upland

Hillslope position: Footslope, backslope

Parent material: Silty and clayey colluvium derived from limestone-shale over silty and clayey residuum weathered from limestone-shale

Slope: 4 to 12 percent

Drainage class: Moderately well drained

Slowest permeability: Slow (About 0.06 in/hr)

Available water capacity: High (About 9.5 inches)

Shrink-swell potential: High (About 7.5 LEP)

Flooding hazard: None

Depth to seasonal water saturation: About 22 to 26 inches

Runoff class: Very high

Ecological site: Loamy Upland (pe30-37)

Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 6 inches; silty clay loam

BA—6 to 12 inches; silty clay loam

Bt—12 to 53 inches; silty clay

C—53 to 80 inches; silty clay

Minor Components

Kipson

Composition: About 10 percent

Geomorphic Position: hillslope on upland

Slope: 5 to 30 percent

Depth to restrictive feature: 7 to 20 inches to bedrock (paralithic)

Drainage class: Somewhat excessively drained

Ecological site: Limy Upland (pe30-37)

Pe—Padonia-Martin silty clay loams, 9 to 25 percent slopes

Map Unit Composition

Padonia: 60 percent

Martin: 30 percent

Minor components: 10 percent

Component Descriptions

Padonia

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills

Landform: Hillslope on upland

Hillslope position: Footslope, backslope

Parent material: Residuum weathered from shale, calcareous

Slope: 9 to 25 percent

Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)

Drainage class: Well drained

Slowest permeability: Slow (About 0.06 in/hr)

Available water capacity: Moderate (About 6.5 inches)

Shrink-swell potential: High (About 7.5 LEP)

Flooding hazard: None

Depth to seasonal water saturation: More than 6 feet

Runoff class: Very high

Ecological site: Clay Upland (pe30-37)

Land capability (nonirrigated): 6e

Typical Profile:

A—0 to 11 inches; silty clay loam

Bt—11 to 22 inches; silty clay

Btk—22 to 32 inches; silty clay

BC—32 to 37 inches; silty clay loam

Cr—37 to 41 inches; weathered bedrock

Martin

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills

Landform: Hillslope on upland

Hillslope position: Backslope, footslope

Parent material: Silty and clayey colluvium derived from limestone-shale over silty and clayey

residuum weathered from limestone-shale

Slope: 4 to 12 percent

Drainage class: Moderately well drained

Slowest permeability: Slow (About 0.06 in/hr)

Available water capacity: High (About 9.5 inches)

Shrink-swell potential: High (About 7.5 LEP)

Flooding hazard: None
Depth to seasonal water saturation: About 22 to 26 inches
Runoff class: Very high
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 6 inches; silty clay loam
 BA—6 to 12 inches; silty clay loam
 Bt—12 to 53 inches; silty clay
 C—53 to 80 inches; silty clay

Minor Components

Kipson

Composition: About 10 percent
Geomorphic Position: hillslope on upland
Slope: 5 to 30 percent
Depth to restrictive feature: 7 to 20 inches to bedrock (paralithic)
Drainage class: Somewhat excessively drained
Ecological site: Limy Upland (pe30-37)

Pf—Padonia-Oska silty clay loams, 5 to 9 percent slopes

Map Unit Composition

Padonia: 55 percent
 Oska: 40 percent
 Minor components: 5 percent

Component Descriptions

Padonia

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Shoulder
Parent material: Residuum weathered from shale, calcareous
Slope: 5 to 9 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 6.5 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Clay Upland (pe30-37)
Land capability (nonirrigated): 4e

Typical Profile:

A—0 to 11 inches; silty clay loam

Bt—11 to 22 inches; silty clay
 Btk—22 to 32 inches; silty clay
 BCk—32 to 37 inches; silty clay loam
 Cr—37 to 41 inches; weathered bedrock

Oska

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills

Landform: Hillslope on upland

Hillslope position: Backslope

Parent material: Silty and clayey residuum weathered from limestone-shale

Slope: 5 to 9 percent

Depth to restrictive feature: 20 to 40 inches to bedrock (lithic)

Drainage class: Well drained

Slowest permeability: Slow (About 0.06 in/hr)

Available water capacity: Low (About 5.8 inches)

Shrink-swell potential: High (About 7.5 LEP)

Flooding hazard: None

Depth to seasonal water saturation: More than 6 feet

Runoff class: Very high

Ecological site: Clay Upland (pe30-37)

Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 5 inches; silty clay loam
 BA—5 to 11 inches; silty clay loam
 Bt—11 to 35 inches; silty clay
 R—35 to unweathered bedrock

Minor Components

Kipson

Composition: About 5 percent
Geomorphic Position: hillslope on upland
Slope: 5 to 30 percent
Depth to restrictive feature: 7 to 20 inches to bedrock (paralithic)
Drainage class: Somewhat excessively drained
Ecological site: Limy Upland (pe30-37)

Pm—Pawnee clay loam, 2 to 6 percent slopes

Map Unit Composition

Pawnee: 85 percent
 Minor components: 15 percent

Component Descriptions

Pawnee

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills

Landform: Hillslope on upland
Hillslope position: Shoulder, summit
Parent material: Till, unspecified
Slope: 2 to 6 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 7.4 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 9 to 14 inches
Runoff class: High
Ecological site: Clay Upland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 7 inches; clay loam
 BA—7 to 12 inches; clay loam
 Bt—12 to 48 inches; clay
 C—48 to 80 inches; clay loam

Minor Components

Morrill

Composition: About 8 percent
Slope: 6 to 12 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Shelby

Composition: About 7 percent
Geomorphic Position: hillslope on upland
Slope: 6 to 12 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Pn—Pawnee clay loam, 6 to 12 percent slopes

Map Unit Composition

Pawnee: 83 percent
 Minor components: 17 percent

Component Descriptions

Pawnee

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Shoulder, summit
Parent material: Till, unspecified
Slope: 6 to 12 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 7.4 inches)

Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 9 to 14 inches
Runoff class: Very high
Ecological site: Clay Upland (pe30-37)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 7 inches; clay loam
 BA—7 to 12 inches; clay loam
 Bt—12 to 48 inches; clay
 C—48 to 80 inches; clay loam

Minor Components

Morrill

Composition: About 8 percent
Slope: 6 to 12 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Kennebec

Composition: About 6 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Olmitz

Composition: About 3 percent
Geomorphic Position: fan terrace on upland
Slope: 2 to 5 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe30-37)

Po—Pawnee clay, 6 to 12 percent slopes, moderately eroded

Map Unit Composition

Pawnee: 84 percent
 Minor components: 16 percent

Component Descriptions

Pawnee

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Till, unspecified
Slope: 6 to 12 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 6.6 inches)
Shrink-swell potential: High (About 7.5 LEP)

Flooding hazard: None
Depth to seasonal water saturation: About 9 to 14 inches
Runoff class: Very high
Ecological site: Clay Upland (pe30-37)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 5 inches; clay
 Bt—5 to 45 inches; clay
 C—45 to 80 inches; clay loam

Minor Components

Mayberry

Composition: About 7 percent
Geomorphic Position: hillslope on upland
Slope: 2 to 6 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Kennebec

Composition: About 6 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Olmitz

Composition: About 3 percent
Geomorphic Position: fan terrace on upland
Slope: 2 to 5 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe30-37)

Pt—Pits, Quarries

General Considerations: Pits are open excavations from which soil and commonly underlying material have been removed, exposing either rock or other material. Kinds include Pits, mine; Pits, gravel; and Pits, quarry. Commonly, pits are closely associated with Dumps.

Pw—Pohocco-Netawaka silt loams, 11 to 17 percent slopes

Map Unit Composition

Pohocco: 50 percent
 Netawaka: 40 percent
 Minor components: 10 percent

Component Descriptions

Pohocco

MLRA: 107 - Iowa and Missouri Deep Loess Hills

Landform: Hillslope on upland
Hillslope position: Shoulder
Parent material: Fine-silty loess
Slope: 11 to 17 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.2 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 5 inches; silt loam
 Bw—5 to 39 inches; silt loam
 C—39 to 80 inches; silt loam

Netawaka

MLRA: 107 - Iowa and Missouri Deep Loess Hills

Landform: Hillslope, upland
Hillslope position: Backslope
Parent material: Fine-silty loess
Slope: 11 to 17 percent
Drainage class: Somewhat excessively drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.5 inches)
Shrink-swell potential: Low (About 1.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Limy Upland (pe30-37)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 6 inches; silt loam
 AC—6 to 9 inches; silt loam
 C—9 to 80 inches; silt loam

Minor Components

Judson

Composition: About 10 percent
Geomorphic Position: fan remnant on upland
Slope: 2 to 6 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Px—Pohocco-Netawaka silt loams, 17 to 30 percent slopes

Map Unit Composition

Pohocco: 50 percent
Netawaka: 40 percent
Minor components: 10 percent

Component Descriptions

Pohocco

MLRA: 107 - Iowa and Missouri Deep Loess Hills
Landform: Hillslope on upland
Hillslope position: Shoulder
Parent material: Fine-silty loess
Slope: 17 to 30 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.2 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 6e

Typical Profile:

Ap—0 to 5 inches; silt loam
Bw—5 to 39 inches; silt loam
C—39 to 80 inches; silt loam

Netawaka

MLRA: 107 - Iowa and Missouri Deep Loess Hills
Landform: Hillslope on upland
Hillslope position: Shoulder, backslope
Parent material: Fine-silty loess
Slope: 17 to 30 percent
Drainage class: Somewhat excessively drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.5 inches)
Shrink-swell potential: Low (About 1.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Limy Upland (pe30-37)
Land capability (nonirrigated): 6e

Typical Profile:

Ap—0 to 6 inches; silt loam
AC—6 to 9 inches; silt loam
C—9 to 80 inches; silt loam

Minor Components

Judson

Composition: About 10 percent
Geomorphic Position: fan remnant on upland
Slope: 2 to 6 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Re—Reading silt loam, 0 to 2 percent slopes, moderately Wet, rarely flooded

Map Unit Composition

Reading: 90 percent
Minor components: 10 percent

Component Descriptions

Reading

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Flood plain on valley
Parent material: Silty alluvium
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 11.8 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: Rare
Depth to seasonal water saturation: About 40 to 44 inches
Runoff class: Medium
Ecological site: Loamy Lowland (pe30-37)
Land capability (nonirrigated): 1

Typical Profile:

A—0 to 18 inches; silt loam
Bt—18 to 48 inches; silty clay loam
BC—48 to 54 inches; silty clay loam
C—54 to 80 inches; silty clay loam

Minor Components

Zook

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained
Ecological site: Clay Lowland (pe30-37)

Chase

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained

Ecological site: Loamy Lowland (pe30-37)

Sg—Shelby clay loam, 6 to 12 percent slopes

Map Unit Composition

Shelby: 88 percent
Minor components: 12 percent

Component Descriptions

Shelby

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope, upland
Hillslope position: Backslope, shoulder
Parent material: Till, unspecified
Slope: 6 to 12 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 10.2 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

A—0 to 13 inches; clay loam
Bt—13 to 36 inches; clay loam
BC—36 to 48 inches; clay loam
C—48 to 80 inches; clay loam

Minor Components

Pawnee

Composition: About 5 percent
Geomorphic Position: hillslope on upland
Slope: 6 to 12 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Kennebec

Composition: About 4 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Olmitz

Composition: About 3 percent
Geomorphic Position: fan terrace on upland
Slope: 2 to 5 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe30-37)

Sm—Shelby clay loam, 12 to 18 percent slopes, moderately eroded

Map Unit Composition

Shelby: 85 percent
Minor components: 15 percent

Component Descriptions

Shelby

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope, shoulder
Parent material: Till, unspecified
Slope: 12 to 18 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 10.0 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 8 inches; clay loam
Bt—8 to 45 inches; clay loam
C—45 to 80 inches; clay loam

Minor Components

Pawnee

Composition: About 5 percent
Geomorphic Position: hillslope on upland
Slope: 6 to 12 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Padonia

Composition: About 4 percent
Geomorphic Position: hillslope on upland
Slope: 9 to 25 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Clay Upland (pe30-37)

Kennebec

Composition: About 3 percent
Slope: 0 to 2 percent

Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Olmitz

Composition: About 3 percent
Geomorphic Position: fan terrace on upland
Slope: 2 to 5 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe30-37)

W—Water**Wa—Wabash silty clay, 0 to 2 percent slopes, occasionally flooded****Map Unit Composition**

Wabash: 85 percent
 Minor components: 15 percent

Component Descriptions**Wabash**

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Flood plain on valley
Parent material: Clayey alluvium
Slope: 0 to 2 percent
Drainage class: Poorly drained
Slowest permeability: Very slow (About 0.00 in/hr)
Available water capacity: Moderate (About 6.4 inches)
Shrink-swell potential: Very high (About 17.0 LEP)
Flooding hazard: Occasional
Depth to seasonal water saturation: About 2 to 9 inches
Runoff class: High
Ecological site: Clay Lowland (pe30-37)
Land capability (nonirrigated): 3w

Typical Profile:

A—0 to 15 inches; silty clay
 Bg—15 to 80 inches; silty clay

Minor Components**Muscotah**

Composition: About 12 percent
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Ecological site: Loamy Lowland (pe30-37)

Kennebec

Composition: About 3 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

We—Wamego silty clay loam, 3 to 7 percent slopes**Map Unit Composition**

Wamego: 90 percent
 Minor components: 10 percent

Component Descriptions**Wamego**

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Sandy and silty residuum weathered from shale, unspecified
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Low (About 4.6 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Clay Upland (pe30-37)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 9 inches; silty clay loam
 Bt—9 to 20 inches; silty clay loam
 BC—20 to 25 inches; silty clay loam
 Cr—25 to 36 inches; weathered bedrock

Minor Components**Olmitz**

Composition: About 5 percent
Geomorphic Position: fan terrace on upland
Slope: 2 to 5 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe30-37)

Pawnee

Composition: About 5 percent
Geomorphic Position: hillslope on upland
Slope: 6 to 12 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Wg—Wamego-Vinland silty clay loams, 3 to 15 percent slopes

Map Unit Composition

Wamego: 50 percent
Vinland: 40 percent
Minor components: 10 percent

Component Descriptions

Wamego

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Sandy and silty residuum weathered from shale, unspecified
Slope: 3 to 15 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Low (About 4.6 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Upland (pe30-37)
Land capability (nonirrigated): 6e

Typical Profile:

Ap—0 to 9 inches; silty clay loam
Bt—9 to 20 inches; silty clay loam
BC—20 to 25 inches; silty clay loam
Cr—25 to 36 inches; weathered bedrock

Vinland

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Sandy and silty residuum weathered from shale, unspecified
Slope: 3 to 15 percent
Depth to restrictive feature: 10 to 20 inches to bedrock (paralithic)
Drainage class: Somewhat excessively drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Low (About 3.9 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Shallow Savannah (pe30-37)
Land capability (nonirrigated): 6e

Typical Profile:

A—0 to 8 inches; silty clay loam

Bw—8 to 12 inches; silty clay loam
C—12 to 19 inches; channery silty clay loam
Cr—19 to 23 inches; weathered bedrock

Minor Components

Pawnee

Composition: About 10 percent
Geomorphic Position: hillslope on upland
Slope: 6 to 12 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Wm—Wymore silty clay loam, 2 to 5 percent slopes

Map Unit Composition

Wymore: 90 percent
Minor components: 10 percent

Component Descriptions

Wymore

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills
Landform: Interfluvium on upland
Hillslope position: Shoulder
Parent material: Loess
Slope: 2 to 5 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 9.7 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 9 to 14 inches
Runoff class: High
Ecological site: Loamy Lowland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 7 inches; silty clay loam
BA—7 to 12 inches; silty clay
Bt1—12 to 22 inches; silty clay
Bt2—22 to 39 inches; silty clay
BC—39 to 47 inches; silty clay loam
C—47 to 80 inches; silty clay loam

Minor Components

Pawnee

Composition: About 10 percent
Geomorphic Position: hillslope on upland
Slope: 2 to 6 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Wn—Wymore silty clay loam, 5 to 9 percent slopes

Map Unit Composition

Wymore: 82 percent

Minor components: 18 percent

Component Descriptions

Wymore

MLRA: 106 - Nebraska and Kansas Loess-Drift Hills

Landform: Hillslope on upland

Hillslope position: Backslope

Parent material: Loess

Slope: 5 to 9 percent

Drainage class: Moderately well drained

Slowest permeability: Slow (About 0.06 in/hr)

Available water capacity: High (About 10.2 inches)

Shrink-swell potential: High (About 7.5 LEP)

Flooding hazard: None

Depth to seasonal water saturation: About 9 to 14 inches

Runoff class: Very high

Ecological site: Loamy Lowland (pe30-37)

Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 10 inches; silty clay loam

Bt1—10 to 18 inches; silty clay

Bt2—18 to 32 inches; silty clay

BC—32 to 43 inches; silty clay loam

C—43 to 80 inches; silty clay loam

Minor Components

Pawnee

Composition: About 8 percent

Geomorphic Position: hillslope on upland

Slope: 6 to 9 percent

Drainage class: Moderately well drained

Ecological site: Clay Upland (pe30-37)

Mayberry

Composition: About 7 percent

Geomorphic Position: hillslope on upland

Slope: 2 to 6 percent

Drainage class: Moderately well drained

Ecological site: Clay Upland (pe30-37)

Kennebec

Composition: About 3 percent

Slope: 0 to 2 percent

Drainage class: Moderately well drained

Ecological site: Loamy Lowland (pe30-37)

Prime farmland is one of several kinds of important farmland defined by the U.S. Department of Agriculture. It is of major importance in meeting the Nation's short- and long-range needs for food and fiber. Because the supply of high-quality farmland is limited, the U.S. Department of Agriculture recognizes that responsible levels of government, as well as individuals, should encourage and facilitate the wise use of our Nation's prime farmland.

Prime farmland, as defined by the U.S. Department of Agriculture, is land that has the best combination of physical and chemical characteristics for producing food, feed, forage, fiber, and oilseed crops and is available for these uses. It could be cultivated land, pastureland, forestland, or other land, but it is not urban or built-up land or water areas. The soil qualities, growing season, and moisture supply are those needed for the soil to economically produce sustained high yields of crops when proper management, including water management, and acceptable farming methods are applied. In general, prime farmland has an adequate and dependable supply of moisture from precipitation or irrigation, a favorable temperature and growing season, acceptable acidity or alkalinity, an acceptable salt and sodium content, and few or no rocks. It is permeable to water and air. It is not excessively erodible or saturated with water for long periods, and it either is not frequently flooded during the growing season or is protected from flooding. Slope ranges mainly from 0 to 6 percent. More detailed information about the criteria for prime farmland is available at the local office of the Natural Resources Conservation Service.

A recent trend in land use in some parts of the survey area has been the loss of some prime farmland to industrial and urban uses. The loss of prime farmland to other uses puts pressure on marginal lands, which generally are more erodible, droughty, and less productive and cannot be easily cultivated.

The map units in the survey area that are considered prime farmland are listed in the following table. This list does not constitute a recommendation for a particular land use. On some soils included in the list, measures that overcome a hazard or limitation, such as flooding, wetness, and droughtiness, are needed. Onsite evaluation is needed to determine whether or not the hazard or limitation has been overcome by corrective measures. The extent of each listed map unit is shown in the "Acres and Proportionate Extent of Soils" table. The location is shown on the detailed soil maps. The soil qualities that affect use and management are described in other tables in this document."

Map symbol	Mapunit name	Farmland Classification
Ac	Aksarben silty clay loam, 0 to 2 percent slopes	All areas are prime farmland
Ad	Aksarben silty clay loam, 2 to 5 percent slopes	All areas are prime farmland
Ch	Chase silty clay loam, 0 to 2 percent slopes, rarely flooded	All areas are prime farmland
Ga	Grundy silt loam, 0 to 2 percent slopes	All areas are prime farmland
Ju	Judson silt loam, 2 to 6 percent slopes	All areas are prime farmland
Ke	Kennebec silt loam, 0 to 2 percent slopes, occasionally flooded	All areas are prime farmland
Ma	Marshall silt loam, 2 to 5 percent slopes	All areas are prime farmland
Md	Martin silty clay loam, 1 to 4 percent slopes	All areas are prime farmland
Mh	Mayberry clay loam, 2 to 6 percent slopes	All areas are prime farmland
Mk	Monona silt loam, 2 to 5 percent slopes	All areas are prime farmland
Mw	Muscotah silt loam, 0 to 2 percent slopes, occasionally flooded, overwash	All areas are prime farmland
My	Muscotah silty clay loam, 0 to 2 percent slopes, occasionally flooded	All areas are prime farmland
No	Nodaway silt loam, 0 to 2 percent slopes, occasionally flooded	All areas are prime farmland
Om	Olmitz loam, 2 to 5 percent slopes	All areas are prime farmland
Pm	Pawnee clay loam, 2 to 6 percent slopes	All areas are prime farmland
Re	Reading silt loam, 0 to 2 percent slopes, moderately wet, rarely flooded	All areas are prime farmland
Wm	Wymore silty clay loam, 2 to 5 percent slopes	All areas are prime farmland
Wa	Wabash silty clay, 0 to 2 percent slopes, occasionally flooded	Prime farmland if drained

The "Soil Rating for Plant Growth, modified 1998" (SRPG) is a relative rating of the capacity of a soil to produce a specific plant under a defined management system. The index is determined from yield data on a few benchmark soils and is used to calculate yields, the net returns from crops, land assessment values, and taxes and to perform risk analysis when land management decisions are made. Specific information on plants and yields can be obtained from the local office of the Natural Resources Conservation Service or the Cooperative Extension Service.

Map symbol	Soil name	Crop Index
Ac	Aksarben Silty Clay Loam, 0 To 2 Percent Slopes-----	79
Ad	Aksarben Silty Clay Loam, 2 To 5 Percent Slopes-----	77
Ae	Aksarben Silty Clay Loam, 5 To 11 Percent Slopes-----	72
Bs	Burchard Clay Loam, 6 To 12 Percent Slopes-----	65
Bx	Burchard-Steinauer Clay Loams, 12 To 18 Percent Slopes-----	51
Ch	Chase Silty Clay Loam, 0 To 2 Percent Slopes, Rarely Flooded-----	79
Co	Contrary Silty Clay Loam, 5 To 9 Percent Slopes-----	78
Ga	Grundy Silt Loam, 0 To 2 Percent Slopes-----	73
Ju	Judson Silt Loam, 2 To 6 Percent Slopes-----	85
Kd	Kennebec Silt Loam, Channeled, Frequently Flooded-----	64
Ke	Kennebec Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	83
Kp	Kipson-Sogn Silty Clay Loams, 5 To 30 Percent Slopes-----	14
M-W	Miscellaneous Water-----	0
Ma	Marshall Silt Loam, 2 To 5 Percent Slopes-----	84
Mb	Marshall Silty Clay Loam, 5 To 11 Percent Slopes-----	77
Md	Martin Silty Clay Loam, 1 To 4 Percent Slopes-----	76
Mf	Martin Silty Clay Loam, 4 To 9 Percent Slopes-----	68
Mh	Mayberry Clay Loam, 2 To 6 Percent Slopes-----	66
Mk	Monona Silt Loam, 2 To 5 Percent Slopes-----	83
Mn	Monona Silt Loam, 5 To 11 Percent Slopes, Moderately Eroded-----	75
Mt	Morrill Loam, 6 To 12 Percent Slopes-----	72
Mw	Muscotah Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded, Overwash-----	76
My	Muscotah Silty Clay Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	74
No	Nodaway Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	79
Om	Olmitz Loam, 2 To 5 Percent Slopes-----	76
Or	Orthents, Earthen Dam-----	0
Pd	Padonia-Martin Silty Clay Loams, 5 To 9 Percent Slopes-----	57
Pe	Padonia-Martin Silty Clay Loams, 9 To 25 Percent Slopes-----	47
Pf	Padonia-Oska Silty Clay Loams, 5 To 9 Percent Slopes-----	54
Pm	Pawnee Clay Loam, 2 To 6 Percent Slopes-----	61
Pn	Pawnee Clay Loam, 6 To 12 Percent Slopes-----	58
Po	Pawnee Clay, 6 To 12 Percent Slopes, Moderately Eroded-----	51
Pt	Pits, Quarries-----	0
Pw	Pohocco-Netawaka Silt Loams, 11 To 17 Percent Slopes-----	60
Px	Pohocco-Netawaka Silt Loams, 17 To 30 Percent Slopes-----	43
Re	Reading Silt Loam, 0 To 2 Percent Slopes, Moderately Wet, Rarely Flooded-----	84
Sg	Shelby Clay Loam, 6 To 12 Percent Slopes-----	72
Sm	Shelby Clay Loam, 12 To 18 Percent Slopes, Moderately Eroded-----	62
W	Water-----	0
Wa	Wabash Silty Clay, 0 To 2 Percent Slopes, Occasionally Flooded-----	51
We	Wamego Silty Clay Loam, 3 To 7 Percent Slopes-----	37
Wg	Wamego-Vinland Silty Clay Loams, 3 To 15 Percent Slopes-----	28
Wm	Wymore Silty Clay Loam, 2 To 5 Percent Slopes-----	71
Wn	Wymore Silty Clay Loam, 5 To 9 Percent Slopes-----	72

Brown County, Kansas: Update
Field Office Thunderbook: Soils Properties for Conservation Planning

(Entries under "Erosion factors--T" apply to the entire profile. Entries under "K", "Kf", "Wind Erodibility Group" and "Wind Erodibility Index" apply only to the surface layer)

Map symbol and soil name	Percent	Irr Cap Class	Nonirr Cap Class	Prime Farmland	Hydro- logic Group	Range site name	Windbreak suitability group	Erosion factors			Wind erodi- bility group	Wind erodi- bility index
								K	Kf	T		
Ac:AKSARBEN-----	90	N/A	1	All areas are prime farmland	B	Loamy Upland (pe30-37)	8	.32	.32	5	7	38
Ad:AKSARBEN-----	87	N/A	2e	All areas are prime farmland	B	Loamy Upland (pe30-37)	8	.32	.32	5	7	38
Ae:AKSARBEN-----	85	N/A	3e	Not prime farmland	B	Loamy Upland (pe30-37)	8	.32	.32	5	7	38
Bs:BURCHARD-----	85	N/A	3e	Not prime farmland	B	Loamy Upland (pe30-37)	7	.28	.28	5	6	48
Bx:BURCHARD-----	55	N/A	6e	Not prime farmland	B	Loamy Upland (pe30-37)	7	.28	.28	5	6	48
Bx:STEINAUER-----	40	N/A	6e	Not prime farmland	B	Limy Upland (pe30-37)	5	.32	.32	5	4L	86
Ch:CHASE-----	90	N/A	2w	All areas are prime farmland	C	Loamy Lowland (pe30-37)	8	.37	.37	5	7	38
Co:CONTRARY-----	85	N/A	3e	Not prime farmland	B	Loamy Upland (pe30-37)	8	.32	.32	5	7	38
Ga:GRUNDY-----	90	N/A	2e	All areas are prime farmland	C	Clay Upland (pe30-37)	7	.37	.37	5	6	48
Ju:JUDSON-----	95	N/A	2e	All areas are prime farmland	B	Loamy Lowland (pe30-37)	7	.28	.28	5	6	48
Kd:KENNEBEC-----	85	N/A	5w	Not prime farmland	B	Loamy Lowland (pe30-37)	7	.28	.28	5	6	48
Ke:KENNEBEC-----	89	N/A	2w	All areas are prime farmland	B	Loamy Lowland (pe30-37)	7	.28	.28	5	6	48
Kp:KIPSON-----	60	N/A	6e	Not prime farmland	D	Limy Upland (pe30-37)	5	.32	.49	2	4L	86
Kp:SOGN-----	30	N/A	6s	Not prime farmland	D	Shallow Limy (pe30-37)	5	.32	.37	1	4L	86
M- W:MISCELLANEOUS WATER-----	100	N/A	N/A	Not prime farmland		Unspecified		---	---	-	---	---
Ma:MARSHALL-----	97	N/A	2e	All areas are prime farmland	B	Loamy Upland (pe30-37)	7	.28	.28	5	6	48
Mb:MARSHALL-----	82	N/A	3e	Not prime farmland	B	Loamy Upland (pe30-37)	8	.28	.28	5	7	38
Md:MARTIN-----	85	N/A	2e	All areas are prime farmland	C	Loamy Upland (pe30-37)	8	.37	.37	5	7	38

Brown County, Kansas: Update
Field Office Thunderbook: Soils Properties for Conservation Planning--Continued

Map symbol and soil name	Percent	Irr Cap Class	Nonirr Cap Class	Prime Farmland	Hydro- logic Group	Range site name	Windbreak suitability group	Erosion factors			Wind erodi- bility group	Wind erodi- bility index
								K	Kf	T		
Mf:MARTIN-----	90	N/A	4e	Not prime farmland	C	Loamy Upland (pe30-37)	8	.37	.37	5	7	38
Mh:MAYBERRY-----	85	N/A	3e	All areas are prime farmland	D	Clay Upland (pe30-37)	7	.37	.37	5	6	48
Mk:MONONA-----	90	N/A	2e	All areas are prime farmland	B	Loamy Upland (pe30-37)	7	.28	.28	5	6	48
Mn:MONONA-----	82	N/A	3e	Not prime farmland	B	Loamy Upland (pe30-37)	7	.32	.32	5	6	48
Mt:MORRILL-----	87	N/A	4e	Not prime farmland	B	Loamy Lowland (pe30-37)	7	.28	.28	5	6	48
Mw:MUSCOTAH-----	87	N/A	2w	All areas are prime farmland	D	Loamy Lowland (pe30-37)	7	.32	.32	5	6	48
My:MUSCOTAH-----	87	N/A	2w	All areas are prime farmland	D	Loamy Lowland (pe30-37)	7	.37	.37	5	6	48
No:NODAWAY-----	90	N/A	2w	All areas are prime farmland	B	Loamy Lowland (pe30-37)	7	.32	.32	5	6	48
Om:OLMITZ-----	93	N/A	2e	All areas are prime farmland	B	Loamy Upland (pe30-37)	7	.24	.24	5	6	48
Or:ORTHENTS, EARTHEN DAM-----	100	N/A	N/A	Not prime farmland		Unspecified		---	---	-	---	---
Pd:PADONIA-----	50	N/A	4e	Not prime farmland	C	Clay Upland (pe30-37)	8	.37	.37	3	7	38
Pd:MARTIN-----	40	N/A	4e	Not prime farmland	C	Loamy Upland (pe30-37)	8	.37	.37	5	7	38
Pe:PADONIA-----	60	N/A	6e	Not prime farmland	C	Clay Upland (pe30-37)	8	.37	.37	3	7	38
Pe:MARTIN-----	30	N/A	4e	Not prime farmland	C	Loamy Upland (pe30-37)	8	.37	.37	5	7	38
Pf:PADONIA-----	55	N/A	4e	Not prime farmland	C	Clay Upland (pe30-37)	8	.37	.37	3	7	38
Pf:OSKA-----	40	N/A	3e	Not prime farmland	C	Clay Upland (pe30-37)	8	.37	.37	2	7	38
Pm:PAWNEE-----	85	N/A	3e	All areas are prime farmland	D	Clay Upland (pe30-37)	7	.37	.37	5	6	48
Pn:PAWNEE-----	83	N/A	4e	Not prime farmland	D	Clay Upland (pe30-37)	7	.37	.37	5	6	48
Po:PAWNEE-----	84	N/A	4e	Not prime farmland	D	Clay Upland (pe30-37)	4	.37	.37	5	4	86

Brown County, Kansas: Update
Field Office Thunderbook: Soils Properties for Conservation Planning--Continued

Map symbol and soil name	Percent	Irr Cap Class	Nonirr Cap Class	Prime Farmland	Hydro- logic Group	Range site name	Windbreak suitability group	Erosion factors			Wind erodi- bility group	Wind erodi- bility index
								K	Kf	T		
Pt:Pits, quarries-----	100	N/A	N/A	Not prime farmland		Unspecified		---	---	-	---	0
Pw:POHOCCO-----	50	N/A	4e	Not prime farmland	B	Loamy Upland (pe30-37)	7	.37	.37	5	6	48
Pw:NETAWAKA-----	40	N/A	4e	Not prime farmland	B	Limy Upland (pe30-37)	5	.43	.43	5	4L	86
Px:POHOCCO-----	50	N/A	6e	Not prime farmland	B	Loamy Upland (pe30-37)	7	.37	.37	5	6	48
Px:NETAWAKA-----	40	N/A	6e	Not prime farmland	B	Limy Upland (pe30-37)	5	.43	.43	5	4L	86
Re:READING-----	90	N/A	1	All areas are prime farmland	B	Loamy Lowland (pe30-37)	7	.32	.32	5	6	48
Sg:SHELBY-----	88	N/A	3e	Not prime farmland	B	Loamy Upland (pe30-37)	7	.28	.28	5	6	48
Sm:SHELBY-----	85	N/A	4e	Not prime farmland	B	Loamy Upland (pe30-37)	7	.28	.28	5	6	48
W:WATER-----	100	N/A	N/A			Unspecified		---	---	-	---	---
Wa:WABASH-----	85	N/A	3w	Prime farmland if drained	D	Clay Lowland (pe30-37)	4	.28	.28	5	4	86
We:WAMEGO-----	90	N/A	4e	Not prime farmland	C	Clay Upland (pe30-37)	8	.32	.32	3	7	38
Wg:WAMEGO-----	50	N/A	6e	Not prime farmland	C	Clay Upland (pe30-37)	8	.32	.32	3	7	38
Wg:VINLAND-----	40	N/A	6e	Not prime farmland	D	Shallow Savannah (pe30-37)	8	.32	.32	2	7	38
Wm:WYMORE-----	90	N/A	3e	All areas are prime farmland	D	Loamy Lowland (pe30-37)	8	.37	.37	5	7	38
Wn:WYMORE-----	82	N/A	4e	Not prime farmland	D	Loamy Lowland (pe30-37)	8	.37	.37	5	7	38

RANGELAND PRODUCTIVITY
Brown County, Kansas

Use and Explanation of Rangeland, Grazed Forest Land, Native Pastureland Interpretations

Information in this subsection can be used to plan the use and management of soils for rangeland, grazed forest land, and native pasture. Different kinds of soils vary in their capacity to produce native grasses and other plants suitable for grazing. Information in this subsection provides groupings of similar soils and estimates of potential forage production, which can be used to determine livestock stocking rates.

Rangeland. Range is land on which the native vegetation (climax or natural potential plant community) is predominantly grasses, grasslike plants, forbs, and shrubs suitable for grazing and browsing. Range includes natural grasslands, savannas, many wetlands, some deserts, tundra, and certain shrub and forb communities. Rangeland receives no regular or frequent cultural treatment. The composition and production of the plant community are determined by soil, climate, topography, overstory canopy, and grazing management.

Grazed Forest Land. Includes land on which the understory includes, as an integral part of the forest plant community, plants that can be grazed without significantly impairing other forest values.

Native Pasture. Includes land on which the native vegetation (climax or natural potential plant community) is forest but which is used and managed primarily for production of native plants for forage. Native pasture includes cut-over forest land and forest land cleared and now managed for native or naturalized forage plants.

Rangeland

In areas that have similar climate and topography, differences in the kind and amount of vegetation produced on rangeland are closely related to the kind of soil. Effective management based on the relationship between the soils and vegetation and water.

The Rangeland, Grazed Forest land, Native Pastureland Interpretations shows, for each soil that supports rangeland vegetation, the ecological site and the potential annual production of vegetation in favorable, normal, unfavorable years. An explanation of the column headings in this table follows.

An ecological site is the product of all the environmental factors responsible for its development. It has characteristic soils that have developed over time throughout the soil development process; a characteristic hydrology, particularly infiltration and runoff, that has developed over time; and a characteristic plant community (kind and amount of vegetation). The hydrology of a site is influenced by development of the soil and plant community. The vegetation, soils, and hydrology are all interrelated. Each is influenced by the others and influences the development of the others. The plant community on an ecological site is typified by an association of species that differs from that of other ecological sites in the kind and/or proportion of species or in total production. Descriptions of ecological sites are provided in the Field Office Technical Guide, which is available in local offices of the Natural Resources Conservation Service.

Total dry-weight production is the amount of vegetation that can be expected to grow annually on well managed rangeland that is supporting the potential natural plant community. It includes all vegetation, whether or not it is palatable to grazing animals. It includes the current year's growth of leaves, twigs, and fruits of woody plants. It does not include the increase in stem diameter of trees and shrubs. It is expressed in pounds per acre of air-dry vegetation for favorable, average, and unfavorable years. In a favorable year, the amount and distribution of precipitation and the temperatures make growing conditions substantially better than average. In a normal year, growing conditions are about average. In an unfavorable year, growing conditions are well below average, generally because of low available soil moisture. Yields are adjusted to a common percent of air-dry moisture content.

Range management requires a knowledge of the kinds of soil and of the potential natural plant community. It also requires an evaluation of the present range similarity index and rangeland trend. Range similarity index is determined by comparing the present plant community with the potential natural plant community on a particular rangeland ecological site. The more closely the existing community resembles the potential community, the higher the range similarity index. Rangeland trend is defined as the direction of change in an existing plant community relative to the potential natural plant community. Further information about the range similarity index and rangeland trend is available in chapter 4 of the National Range and Pasture Handbook, which is available in local offices of the Natural Resources Conservation Service. The objective in range management is to control grazing so that the plants growing on a site are about the same in kind and amount as the potential natural plant community for that site. Such management generally results in the optimum production of vegetation, control of undesirable brush species, conservation of water, and control of erosion. Sometimes, however, an area with a range similarity index somewhat below the potential meets grazing needs, provides wildlife habitat, and protects soil and water resources.

RANGELAND PRODUCTIVITY--Continued
Brown County, Kansas

(Only the soils that support rangeland vegetation suitable for grazing are rated.) Refer to range site description to determine the percentage allowable of grasses, forbs, and shrubs for the range ecological site.

Map symbol and soil name	Ecological site	Total dry-weight production		
		Favorable year	Average year	Unfavorable year
		Lb/acre	Lb/acre	Lb/acre
Ac:				
Aksarben-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Ad:				
Aksarben-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Ae:				
Aksarben-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Bs:				
Burchard-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Bx:				
Burchard-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Steinauer-----	Limy Upland (pe30-37)	4,500	3,900	3,400
Ch:				
Chase-----	Loamy Lowland (pe30-37)	9,000	7,000	6,000
Co:				
Contrary-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Ga:				
Grundy-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Ju:				
Judson-----	Loamy Lowland (pe30-37)	9,000	7,000	6,000
Kd:				
Kennebec, CHANNELED-----	Loamy Lowland (pe30-37)	8,500	6,700	5,700
Ke:				
Kennebec-----	Loamy Lowland (pe30-37)	9,000	7,000	6,000
Kp:				
Kipson-----	Limy Upland (pe30-37)	4,500	3,900	3,400
Sogn-----	Shallow Limy (pe30-37)	3,500	2,500	1,500
M-W:				
Miscellaneous Water-----	---	---	---	---
Ma:				
Marshall-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Mb:				
Marshall-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Md:				
Martin-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Mf:				
Martin-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Mh:				
Mayberry-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Mk:				
Monona-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Mn:				
Monona-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Mt:				
Morrill-----	Loamy Lowland (pe30-37)	6,000	5,000	4,000
Mw:				
Muscotah-----	Loamy Lowland (pe30-37)	9,000	7,000	6,000
My:				
Muscotah-----	Loamy Lowland (pe30-37)	9,000	7,000	6,000
No:				
Nodaway-----	Loamy Lowland (pe30-37)	9,000	7,000	6,000
Om:				
Olmitz-----	Loamy Upland (pe30-37)	9,000	7,000	6,000
Or:				
Orthents, Earthen Dam-----	---	---	---	---
Pd:				
Padonia-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Martin-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Pe:				
Padonia-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Martin-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Pf:				
Padonia-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Oska-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Pm:				
Pawnee-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Pn:				
Pawnee-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Po:				
Pawnee-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Pt:				
Pits, Quarries-----	---	---	---	---
Pw:				
Pohocco-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Netawaka-----	Limy Upland (pe30-37)	4,500	3,900	3,400
Px:				
Pohocco-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Netawaka-----	Limy Upland (pe30-37)	4,500	3,900	3,400
Re:				
Reading-----	Loamy Lowland (pe30-37)	9,000	7,000	6,000
Sg:				
Shelby-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
Sm:				
Shelby-----	Loamy Upland (pe30-37)	6,000	5,000	4,000
W:				
Water-----	---	---	---	---

RANGELAND PRODUCTIVITY--Continued
Brown County, Kansas

(Only the soils that support rangeland vegetation suitable for grazing are rated.) Refer to range site description to determine the percentage allowable of grasses, forbs, and shrubs for the range ecological site.

Map symbol and soil name	Ecological site	Total dry-weight production		
		Favorable year	Average year	Unfavorable year
		Lb/acre	Lb/acre	Lb/acre
Wa: Wabash-----	Clay Lowland (pe30-37)	9,000	7,000	5,000
We: Wamego-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Wg: Wamego-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Wn: Vinland-----	Shallow Savannah (pe30-37)	4,500	3,900	3,400
Wm: Wymore-----	Loamy Lowland (pe30-37)	6,500	4,500	3,500
Wn: Wymore-----	Loamy Lowland (pe30-37)	6,500	4,500	3,500

BUILDING SITE DEVELOPMENT
Brown County, Kansas

Building Site Development

Soil properties influence the development of building sites, including the selection of the site, the design of the structure, construction, performance after construction, and maintenance. The following tables show the degree and kind of soil limitations that affect dwellings with and without basements, small commercial buildings, local roads and streets, shallow excavations, and lawns and landscaping.

The ratings in the tables are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect building site development. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Dwellings are single-family houses of three stories or less. For dwellings without basements, the foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of 2 feet or at the depth of maximum frost penetration, whichever is deeper. For dwellings with basements, the foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of about 7 feet. The ratings for dwellings are based on the soil properties that affect the capacity of the soil to support a load without movement and on the properties that affect excavation and construction costs. The properties that affect the load-supporting capacity include depth to a water table, ponding, flooding, subsidence, linear extensibility (shrink-swell potential), and compressibility. Compressibility is inferred from the Unified classification. The properties that affect the ease and amount of excavation include depth to a water table, ponding, flooding, slope, depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, and the amount and size of rock fragments.

Small commercial buildings are structures that are less than three stories high and do not have basements. The foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of 2 feet or at the depth of maximum frost penetration, whichever is deeper. The ratings are based on the soil properties that affect the capacity of the soil to support a load without movement and on the properties that affect excavation and construction costs. The properties that affect the load-supporting capacity include depth to a water table, ponding, flooding, subsidence, linear extensibility (shrink-swell potential), and compressibility (which is inferred from the Unified classification). The properties that affect the ease and amount of excavation include flooding, depth to a water table, ponding, slope, depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, and the amount and size of rock fragments.

Local roads and streets have an all-weather surface and carry automobile and light truck traffic all year. They have a subgrade of cut or fill soil material; a base of gravel, crushed rock, or soil material stabilized by lime or cement; and a surface of flexible material (asphalt), rigid material (concrete), or gravel with a binder. The ratings are based on the soil properties that affect the ease of excavation and grading and the traffic-supporting capacity. The properties that affect the ease of excavation and grading are depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, depth to a water table, ponding, flooding, the amount of large stones, and slope. The properties that affect the traffic-supporting capacity are soil strength (as inferred from the AASHTO group index number), subsidence, linear extensibility (shrink-swell potential), the potential for frost action, depth to a water table, and ponding.

Shallow excavations are trenches or holes dug to a maximum depth of 5 or 6 feet for graves, utility lines, open ditches, or other purposes. The ratings are based on the soil properties that influence the ease of digging and the resistance to sloughing. Depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, the amount of large stones, and dense layers influence the ease of digging, filling, and compacting. Depth to the seasonal high water table, flooding, and ponding may restrict the period when excavations can be made. Slope influences the ease of using machinery. Soil texture, depth to the water table, and linear extensibility (shrink-swell potential) influence the resistance to sloughing.

Lawns and landscaping require soils on which turf and ornamental trees and shrubs can be established and maintained. Irrigation is not considered in the ratings. The ratings are based on the soil properties that affect plant growth and trafficability after vegetation is established. The properties that affect plant growth are reaction; depth to a water table; ponding; depth to bedrock or a cemented pan; the available water capacity in the upper 40 inches; the content of salts, sodium, or calcium carbonate; and sulfidic materials. The properties that affect trafficability are flooding, depth to a water table, ponding, slope, stoniness, and the amount of sand, clay, or organic matter in the surface layer.

BUILDING SITE DEVELOPMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ac: Aksarben-----	90	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50
Ad: Aksarben-----	87	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell Slope	0.50 0.00
Ae: Aksarben-----	85	Somewhat limited Shrink-swell Slope	0.50 0.00	Somewhat limited Shrink-swell Slope	0.50 0.00	Very limited Slope Shrink-swell	1.00 0.50
Bs: Burchard-----	85	Somewhat limited Shrink-swell Slope	0.50 0.04	Somewhat limited Shrink-swell Slope	0.50 0.04	Very limited Slope Shrink-swell	1.00 0.50
Bx: Burchard-----	55	Very limited Slope Shrink-swell	1.00 0.50	Very limited Slope Shrink-swell	1.00 0.50	Very limited Slope Shrink-swell	1.00 0.50
Steinauer-----	40	Very limited Slope Shrink-swell	1.00 0.50	Very limited Slope Shrink-swell	1.00 0.50	Very limited Slope Shrink-swell	1.00 0.50
Ch: Chase-----	90	Very limited Flooding Shrink-swell Depth to saturated zone	1.00 1.00 0.44	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00	Very limited Flooding Shrink-swell Depth to saturated zone	1.00 1.00 0.44
Co: Contrary-----	85	Not limited		Not limited		Somewhat limited Slope	0.86
Ga: Grundy-----	90	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00
Ju: Judson-----	95	Not limited		Somewhat limited Shrink-swell	0.50	Somewhat limited Slope	0.00
Kd: Kennebec, CHanneled-	85	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 0.82 0.50	Very limited Flooding Shrink-swell	1.00 0.50
Ke: Kennebec-----	89	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 0.82 0.50	Very limited Flooding Shrink-swell	1.00 0.50
Kp: Kipson-----	60	Very limited Depth to soft bedrock Slope Shrink-swell	1.00 1.00 0.50	Very limited Depth to soft bedrock Slope Shrink-swell	1.00 1.00 0.50	Very limited Depth to soft bedrock Slope Shrink-swell	1.00 1.00 0.50
Sogn-----	30	Very limited Depth to hard bedrock Slope Shrink-swell	1.00 0.84 0.50	Very limited Depth to hard bedrock Slope Shrink-swell	1.00 0.84 0.50	Very limited Depth to hard bedrock Slope Shrink-swell	1.00 1.00 0.50
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Marshall-----	97	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell Slope	0.50 0.00
Mb: Marshall-----	82	Somewhat limited Shrink-swell Slope	0.50 0.00	Somewhat limited Shrink-swell Slope	0.50 0.00	Very limited Slope Shrink-swell	1.00 0.50

BUILDING SITE DEVELOPMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Md: Martin-----	85	Very limited Shrink-swell Depth to saturated zone	1.00 0.44	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Shrink-swell Depth to saturated zone	1.00 0.44
Mf: Martin-----	90	Very limited Shrink-swell Depth to saturated zone Slope	1.00 0.44 0.00	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.00	Very limited Shrink-swell Slope Depth to saturated zone	1.00 1.00 0.44
Mh: Mayberry-----	85	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.00
Mk: Monona-----	90	Somewhat limited Shrink-swell	0.50	Not limited		Somewhat limited Shrink-swell Slope	0.50 0.00
Mn: Monona-----	82	Somewhat limited Shrink-swell Slope	0.50 0.00	Somewhat limited Slope	0.00	Very limited Slope Shrink-swell	1.00 0.50
Mt: Morrill-----	87	Somewhat limited Shrink-swell Slope	0.50 0.04	Somewhat limited Shrink-swell Slope	0.50 0.04	Very limited Slope Shrink-swell	1.00 0.50
Mw: Muscotah-----	87	Very limited Flooding Shrink-swell Depth to saturated zone	1.00 0.50 0.50	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00	Very limited Flooding Shrink-swell Depth to saturated zone	1.00 0.50 0.50
My: Muscotah-----	87	Very limited Flooding Shrink-swell Depth to saturated zone	1.00 1.00 0.50	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00	Very limited Flooding Shrink-swell Depth to saturated zone	1.00 1.00 0.50
No: Nodaway-----	90	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 0.95 0.50	Very limited Flooding Shrink-swell	1.00 0.50
Om: Olmitz-----	93	Somewhat limited Shrink-swell	0.50	Somewhat limited Depth to saturated zone Shrink-swell	0.82 0.50	Somewhat limited Shrink-swell Slope	0.50 0.00
Or: Orthents, Earthen Dam-----	100	Not rated		Not rated		Not rated	
Pd: Padonia-----	50	Very limited Shrink-swell	1.00	Very limited Shrink-swell Depth to soft bedrock	1.00 0.03	Very limited Shrink-swell Slope	1.00 0.86
Martin-----	40	Very limited Shrink-swell Depth to saturated zone Slope	1.00 0.44 0.00	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.00	Very limited Shrink-swell Slope Depth to saturated zone	1.00 1.00 0.44

BUILDING SITE DEVELOPMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Pe: Padonia-----	60	Very limited Shrink-swell Slope	1.00 1.00	Very limited Shrink-swell Slope Depth to soft bedrock	1.00 1.00 0.03	Very limited Slope Shrink-swell	1.00 1.00
Martin-----	30	Very limited Shrink-swell Depth to saturated zone Slope	1.00 0.44 0.37	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.37	Very limited Shrink-swell Slope Depth to saturated zone	1.00 1.00 0.44
Pf: Padonia-----	55	Very limited Shrink-swell	1.00	Very limited Shrink-swell Depth to soft bedrock	1.00 0.03	Very limited Shrink-swell Slope	1.00 0.86
Oska-----	40	Very limited Shrink-swell Depth to hard bedrock	1.00 0.10	Very limited Shrink-swell Depth to hard bedrock	1.00 1.00	Very limited Shrink-swell Slope Depth to hard bedrock	1.00 0.86 0.10
Pm: Pawnee-----	85	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.00
Pn: Pawnee-----	83	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.04	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.04	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 1.00
Po: Pawnee-----	84	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.04	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.04	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 1.00
Pt: Pits, Quarries-----	100	Not rated		Not rated		Not rated	
Pw: Pohocco-----	50	Somewhat limited Slope Shrink-swell	0.96 0.50	Somewhat limited Slope Shrink-swell	0.96 0.50	Very limited Slope Shrink-swell	1.00 0.50
Netawaka-----	40	Somewhat limited Slope	0.96	Somewhat limited Slope	0.96	Very limited Slope	1.00
Px: Pohocco-----	50	Very limited Slope Shrink-swell	1.00 0.50	Very limited Slope Shrink-swell	1.00 0.50	Very limited Slope Shrink-swell	1.00 0.50
Netawaka-----	40	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00
Re: Reading-----	90	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 0.82 0.50	Very limited Flooding Shrink-swell	1.00 0.50
Sg: Shelby-----	88	Somewhat limited Shrink-swell Slope	0.50 0.04	Somewhat limited Shrink-swell Slope	0.50 0.04	Very limited Slope Shrink-swell	1.00 0.50
Sm: Shelby-----	85	Very limited Slope Shrink-swell	1.00 0.50	Very limited Slope Shrink-swell	1.00 0.50	Very limited Slope Shrink-swell	1.00 0.50
W: Water-----	100	Not rated		Not rated		Not rated	

BUILDING SITE DEVELOPMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Wa: Wabash-----	85	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00
We: Wamego-----	90	Somewhat limited Shrink-swell	0.50	Somewhat limited Depth to soft bedrock Shrink-swell	0.84 0.50	Somewhat limited Shrink-swell Slope	0.50 0.12
Wg: Wamego-----	50	Somewhat limited Shrink-swell Slope	0.50 0.04	Somewhat limited Depth to soft bedrock Shrink-swell Slope	0.84 0.50 0.04	Very limited Slope Shrink-swell	1.00 0.50
Vinland-----	40	Somewhat limited Depth to soft bedrock Shrink-swell Slope	1.00 0.50 0.04	Very limited Depth to soft bedrock Shrink-swell Slope	1.00 0.50 0.04	Very limited Depth to soft bedrock Slope Shrink-swell	1.00 1.00 0.50
Wm: Wymore-----	90	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 0.50	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.00
Wn: Wymore-----	82	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 0.50	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.86

BUILDING SITE DEVELOPMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ac: Aksarben-----	90	Very limited Frost action Low strength Shrink-swell	1.00 1.00 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Ad: Aksarben-----	87	Very limited Frost action Low strength Shrink-swell	1.00 1.00 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Ae: Aksarben-----	85	Very limited Frost action Low strength Shrink-swell Slope	1.00 1.00 0.50 0.00	Somewhat limited Cutbanks cave Slope	0.10 0.00	Somewhat limited Slope	0.00
Bs: Burchard-----	85	Very limited Low strength Shrink-swell Frost action Slope	1.00 0.50 0.50 0.04	Somewhat limited Cutbanks cave Slope	0.10 0.04	Somewhat limited Slope	0.04
Bx: Burchard-----	55	Very limited Low strength Slope Shrink-swell Frost action	1.00 1.00 0.50 0.50	Very limited Slope Cutbanks cave	1.00 0.10	Very limited Slope	1.00
Steinauer-----	40	Very limited Low strength Slope Shrink-swell Frost action	1.00 1.00 0.50 0.50	Very limited Slope Cutbanks cave	1.00 0.10	Very limited Slope	1.00
Ch: Chase-----	90	Very limited Frost action Low strength Shrink-swell Flooding Depth to saturated zone	1.00 1.00 1.00 0.40 0.19	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.12 0.10	Somewhat limited Depth to saturated zone	0.19
Co: Contrary-----	85	Very limited Frost action Low strength	1.00 1.00	Somewhat limited Cutbanks cave	0.10	Not limited	
Ga: Grundy-----	90	Very limited Frost action Low strength Shrink-swell Depth to saturated zone	1.00 1.00 1.00 1.00	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.12 0.10	Very limited Depth to saturated zone	1.00
Ju: Judson-----	95	Very limited Frost action Low strength	1.00 1.00	Somewhat limited Cutbanks cave	0.10	Not limited	
Kd: Kennebec, CHanneled-	85	Very limited Frost action Flooding Low strength Shrink-swell	1.00 1.00 1.00 0.50	Somewhat limited Depth to saturated zone Flooding Cutbanks cave	0.82 0.80 0.10	Very limited Flooding	1.00
Ke: Kennebec-----	89	Very limited Frost action Flooding Low strength Shrink-swell	1.00 1.00 1.00 0.50	Somewhat limited Depth to saturated zone Flooding Cutbanks cave	0.82 0.60 0.10	Somewhat limited Flooding	0.60

BUILDING SITE DEVELOPMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Kp: Kipson-----	60	Very limited Depth to soft bedrock Slope Low strength Shrink-swell	1.00 1.00 1.00 0.50	Very limited Depth to soft bedrock Slope Cutbanks cave	1.00 1.00 0.10	Very limited Depth to bedrock Slope Carbonate content Content of large stones	1.00 1.00 1.00 0.20
Sogn-----	30	Frost action Very limited Depth to hard bedrock Low strength Slope Shrink-swell	0.50 1.00 1.00 0.84 0.50	Very limited Depth to hard bedrock Slope Cutbanks cave	1.00 0.84 0.10	Droughty Very limited Depth to bedrock Slope Droughty Content of large stones	0.12 1.00 0.84 0.80 0.00
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Marshall-----	97	Very limited Frost action Low strength Shrink-swell	1.00 1.00 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Mb: Marshall-----	82	Very limited Frost action Low strength Shrink-swell Slope	1.00 1.00 0.50 0.00	Somewhat limited Cutbanks cave Slope	0.10 0.00	Somewhat limited Slope	0.00
Md: Martin-----	85	Very limited Frost action Low strength Shrink-swell Depth to saturated zone	1.00 1.00 1.00 0.19	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.28 0.10	Somewhat limited Depth to saturated zone	0.19
Mf: Martin-----	90	Very limited Frost action Low strength Shrink-swell Depth to saturated zone Slope	1.00 1.00 1.00 0.19 0.00	Very limited Depth to saturated zone Too clayey Cutbanks cave Slope	1.00 0.28 0.10 0.00	Somewhat limited Depth to saturated zone Slope	0.19 0.00
Mh: Mayberry-----	85	Very limited Frost action Low strength Shrink-swell Depth to saturated zone	1.00 1.00 1.00 1.00	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.12 0.10	Very limited Depth to saturated zone	1.00
Mk: Monona-----	90	Very limited Frost action Low strength Shrink-swell	1.00 1.00 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Mn: Monona-----	82	Very limited Frost action Low strength Shrink-swell Slope	1.00 1.00 0.50 0.00	Somewhat limited Cutbanks cave Slope	0.10 0.00	Somewhat limited Slope	0.00
Mt: Morrill-----	87	Somewhat limited Shrink-swell Frost action Low strength Slope	0.50 0.50 0.22 0.04	Somewhat limited Cutbanks cave Slope	0.10 0.04	Somewhat limited Slope	0.04

BUILDING SITE DEVELOPMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Mw: Muscotah-----	87	Very limited Flooding	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Flooding	0.60
		Low strength	1.00	Flooding	0.60	Depth to saturated zone	0.22
		Shrink-swell	0.50	Cutbanks cave	0.10		
		Frost action	0.50	Too clayey	0.03		
		Depth to saturated zone	0.22				
My: Muscotah-----	87	Very limited Flooding	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Flooding	0.60
		Low strength	1.00	Flooding	0.60	Depth to saturated zone	0.22
		Shrink-swell	1.00	Cutbanks cave	0.10		
		Frost action	0.50	Too clayey	0.03		
		Depth to saturated zone	0.22				
No: Nodaway-----	90	Very limited Frost action	1.00	Somewhat limited Depth to saturated zone	0.95	Somewhat limited Flooding	0.60
		Flooding	1.00	Flooding	0.60		
		Low strength	1.00	Cutbanks cave	0.10		
		Shrink-swell	0.50				
Om: Olmitz-----	93	Very limited Low strength	1.00	Somewhat limited Depth to saturated zone	0.82	Not limited	
		Shrink-swell	0.50	Cutbanks cave	0.10		
		Frost action	0.50				
Or: Orthents, Earthen Dam-----	100	Not rated		Not rated		Not rated	
Pd: Padonia-----	50	Very limited Low strength	1.00	Somewhat limited Cutbanks cave	0.10	Somewhat limited Depth to bedrock	0.03
		Shrink-swell	1.00	Too clayey	0.03		
		Frost action	0.50	Depth to soft bedrock	0.03		
Martin-----	40	Very limited Frost action	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Depth to saturated zone	0.19
		Low strength	1.00	Too clayey	0.28	Slope	0.00
		Shrink-swell	1.00	Cutbanks cave	0.10		
		Depth to saturated zone	0.19	Slope	0.00		
		Slope	0.00				
Pe: Padonia-----	60	Very limited Low strength	1.00	Very limited Slope	1.00	Very limited Slope	1.00
		Shrink-swell	1.00	Cutbanks cave	0.10	Depth to bedrock	0.03
		Slope	1.00	Too clayey	0.03		
		Frost action	0.50	Depth to soft bedrock	0.03		
Martin-----	30	Very limited Frost action	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Slope	0.37
		Low strength	1.00	Slope	0.37	Depth to saturated zone	0.19
		Shrink-swell	1.00	Too clayey	0.28		
		Slope	0.37	Cutbanks cave	0.10		
		Depth to saturated zone	0.19				

BUILDING SITE DEVELOPMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Pf: Padonia-----	55	Very limited Low strength Shrink-swell Frost action	1.00 1.00 0.50	Somewhat limited Cutbanks cave Too clayey Depth to soft bedrock	0.10 0.03 0.03	Somewhat limited Depth to bedrock	0.03
Oska-----	40	Very limited Low strength Shrink-swell Frost action Depth to hard bedrock	1.00 1.00 0.50 0.10	Very limited Depth to hard bedrock Too clayey Cutbanks cave	1.00 0.12 0.10	Somewhat limited Depth to bedrock	0.10
Pm: Pawnee-----	85	Very limited Frost action Low strength Shrink-swell Depth to saturated zone	1.00 1.00 1.00 1.00	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.12 0.10	Very limited Depth to saturated zone	1.00
Pn: Pawnee-----	83	Very limited Frost action Low strength Shrink-swell Depth to saturated zone Slope	1.00 1.00 1.00 1.00 0.04	Very limited Depth to saturated zone Too clayey Cutbanks cave Slope	1.00 0.12 0.10 0.04	Very limited Depth to saturated zone Slope	1.00 0.04
Po: Pawnee-----	84	Very limited Frost action Low strength Shrink-swell Depth to saturated zone Slope	1.00 1.00 1.00 1.00 0.04	Very limited Depth to saturated zone Too clayey Cutbanks cave Slope	1.00 0.12 0.10 0.04	Very limited Depth to saturated zone Too clayey Slope Droughty	1.00 1.00 0.04 0.00
Pt: Pits, Quarries-----	100	Not rated		Not rated		Not rated	
Pw: Pohocco-----	50	Very limited Frost action Low strength Slope Shrink-swell	1.00 1.00 0.96 0.50	Somewhat limited Slope Cutbanks cave	0.96 0.10	Somewhat limited Slope	0.96
Netawaka-----	40	Very limited Frost action Low strength Slope	1.00 1.00 0.96	Somewhat limited Slope Cutbanks cave	0.96 0.10	Somewhat limited Slope	0.96
Px: Pohocco-----	50	Very limited Slope Frost action Low strength Shrink-swell	1.00 1.00 1.00 0.50	Very limited Slope Cutbanks cave	1.00 0.10	Very limited Slope	1.00
Netawaka-----	40	Very limited Slope Frost action Low strength	1.00 1.00 1.00	Very limited Slope Cutbanks cave	1.00 0.10	Very limited Slope	1.00
Re: Reading-----	90	Very limited Frost action Low strength Shrink-swell Flooding	1.00 1.00 0.50 0.40	Somewhat limited Depth to saturated zone Cutbanks cave	0.82 0.10	Not limited	
Sg: Shelby-----	88	Very limited Low strength Shrink-swell Frost action Slope	1.00 0.50 0.50 0.04	Somewhat limited Cutbanks cave Slope	0.10 0.04	Somewhat limited Slope	0.04

BUILDING SITE DEVELOPMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Sm: Shelby-----	85	Very limited Low strength Slope Shrink-swell Frost action	1.00 1.00 0.50 0.50	Very limited Slope Cutbanks cave	1.00 0.10	Very limited Slope	1.00
W: Water-----	100	Not rated		Not rated		Not rated	
Wa: Wabash-----	85	Very limited Shrink-swell Depth to saturated zone Frost action Flooding Low strength	1.00 1.00 1.00 1.00 1.00	Very limited Depth to saturated zone Flooding Too clayey Cutbanks cave	1.00 0.60 0.50 0.10	Very limited Depth to saturated zone Too clayey Flooding	1.00 1.00 0.60
We: Wamego-----	90	Very limited Low strength Shrink-swell Frost action	1.00 0.50 0.50	Somewhat limited Depth to soft bedrock Cutbanks cave	0.84 0.10	Somewhat limited Depth to bedrock	0.84
Wg: Wamego-----	50	Very limited Low strength Shrink-swell Frost action Slope	1.00 0.50 0.50 0.04	Somewhat limited Depth to soft bedrock Cutbanks cave Slope	0.84 0.10 0.04	Somewhat limited Depth to bedrock Slope	0.84 0.04
Vinland-----	40	Somewhat limited Depth to soft bedrock Low strength Shrink-swell Frost action Slope	1.00 0.78 0.50 0.50 0.04	Very limited Depth to soft bedrock Cutbanks cave Slope	1.00 0.10 0.04	Very limited Depth to bedrock Slope Droughty	1.00 0.04 0.00
Wm: Wymore-----	90	Very limited Frost action Low strength Shrink-swell Depth to saturated zone	1.00 1.00 1.00 1.00	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.32 0.10	Very limited Depth to saturated zone	1.00
Wn: Wymore-----	82	Very limited Frost action Low strength Shrink-swell Depth to saturated zone	1.00 1.00 1.00 1.00	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.32 0.10	Very limited Depth to saturated zone	1.00

CONSTRUCTION MATERIALS
Brown County, Kansas

Construction Materials

The following tables give information about the soils as potential sources of gravel, sand, topsoil, reclamation material, and roadfill. Normal compaction, minor processing, and other standard construction practices are assumed.

The soils are rated good, fair, or poor as potential sources of topsoil, reclamation material, and roadfill. The features that limit the soils as sources of these materials are specified in the tables. The numerical ratings given after the specified features indicate the degree to which the features limit the soils as sources of topsoil, reclamation material, or roadfill. The lower the number, the greater the limitation.

The soils are rated as a probable or improbable source of sand and gravel. A rating of probable means that the source material is likely to be in or below the soil. The numerical ratings in these columns indicate the degree of probability. The number 0.00 indicates that the soil is an improbable source. A number between 0.00 and 1.00 indicates the degree to which the soil is a probable source of sand or gravel.

Sand and gravel are natural aggregates suitable for commercial use with a minimum of processing. They are used in many kinds of construction. Specifications for each use vary widely. In these tables, only the probability of finding material in suitable quantity is evaluated. The suitability of the material for specific purposes is not evaluated, nor are factors that affect excavation of the material. The properties used to evaluate the soil as a source of sand or gravel are gradation of grain sizes (as indicated by the Unified classification of the soil), the thickness of suitable material, and the content of rock fragments. If the lowest layer of the soil contains sand or gravel, the soil is rated as a probable source regardless of thickness. The assumption is that the sand or gravel layer below the depth of observation exceeds the minimum thickness.

Topsoil is used to cover an area so that vegetation can be established and maintained. The upper 40 inches of a soil is evaluated for use as topsoil. Also evaluated is the reclamation potential of the borrow area. The ratings are based on the soil properties that affect plant growth; the ease of excavating, loading, and spreading the material; and reclamation of the borrow area. Toxic substances, soil reaction, and the properties that are inferred from soil texture, such as available water capacity and fertility, affect plant growth. The ease of excavating, loading, and spreading is affected by rock fragments, slope, depth to a water table, soil texture, and thickness of suitable material. Reclamation of the borrow area is affected by slope, depth to a water table, rock fragments, depth to bedrock or a cemented pan, and toxic material.

The surface layer of most soils is generally preferred for topsoil because of its organic matter content. Organic matter greatly increases the absorption and retention of moisture and nutrients for plant growth.

Reclamation material is used in areas that have been drastically disturbed by surface mining or similar activities. When these areas are reclaimed, layers of soil material or unconsolidated geological material, or both, are replaced in a vertical sequence. The reconstructed soil favors plant growth. The ratings in the table do not apply to quarries and other mined areas that require an offsite source of reconstruction material. The ratings are based on the soil properties that affect erosion and stability of the surface and the productive potential of the reconstructed soil. These properties include the content of sodium, salts, and calcium carbonate; reaction; available water capacity; erodibility; texture; content of rock fragments; and content of organic matter and other features that affect fertility.

Roadfill is soil material that is excavated in one place and used in road embankments in another place. In this table, the soils are rated as a source of roadfill for low embankments, generally less than 6 feet high and less exacting in design than higher embankments.

The ratings are for the whole soil, from the surface to a depth of about 5 feet. It is assumed that soil layers will be mixed when the soil material is excavated and spread.

The ratings are based on the amount of suitable material and on soil properties that affect the ease of excavation and the performance of the material after it is in place. The thickness of the suitable material is a major consideration. The ease of excavation is affected by large stones, depth to a water table, and slope. How well the soil performs in place after it has been compacted and drained is determined by its strength (as inferred from the AASHTO classification of the soil) and linear extensibility (shrink-swell potential).

CONSTRUCTION MATERIALS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
Ac: Aksarben-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ad: Aksarben-----	87	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ae: Aksarben-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Bs: Burchard-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Bx: Burchard-----	55	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Steinauer-----	40	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ch: Chase-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Co: Contrary-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ga: Grundy-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ju: Judson-----	95	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Kd: Kennebec, CHanneled-	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ke: Kennebec-----	89	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Kp: Kipson-----	60	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Sogn-----	30	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
M-W: Miscellaneous Water-	100	Not rated		Not rated	
Ma: Marshall-----	97	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
Mb: Marshall-----	82	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Md: Martin-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Mf: Martin-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Mh: Mayberry-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Mk: Monona-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Mn: Monona-----	82	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Mt: Morrill-----	87	Poor Bottom layer Thickest layer	0.00 0.00	Fair Thickest layer Bottom layer	0.00 0.31
Mw: Muscotah-----	87	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
My: Muscotah-----	87	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
No: Nodaway-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Om: Olmitz-----	93	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Or: Orthents, Earthen Dam-----	100	Not rated		Not rated	
Pd: Padonia-----	50	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Martin-----	40	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Pe: Padonia-----	60	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Martin-----	30	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
Pf: Padonia-----	55	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Oska-----	40	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Pm: Pawnee-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Pn: Pawnee-----	83	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Po: Pawnee-----	84	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Pt: Pits, Quarries-----	100	Not rated		Not rated	
Pw: Pohocco-----	50	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Netawaka-----	40	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Px: Pohocco-----	50	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Netawaka-----	40	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Re: Reading-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Sg: Shelby-----	88	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Sm: Shelby-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
W: Water-----	100	Not rated		Not rated	
Wa: Wabash-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
We: Wamego-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Wg: Wamego-----	50	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
Vinland-----	40	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Wm: Wymore-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Wn: Wymore-----	82	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ac: Aksarben-----	90	Fair Too clayey Low content of organic matter Too acid Water erosion	0.03 0.12 0.84 0.90	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.02
Ad: Aksarben-----	87	Fair Too clayey Low content of organic matter Too acid Water erosion	0.08 0.12 0.84 0.90	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.05
Ae: Aksarben-----	85	Fair Too clayey Low content of organic matter Too acid Water erosion	0.08 0.12 0.84 0.90	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.05
Bs: Burchard-----	85	Fair Low content of organic matter Too clayey Too acid No water erosion limitation	0.12 0.68 0.92 0.99	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey Slope	0.49 0.96
Bx: Burchard-----	55	Fair Low content of organic matter Too clayey Too acid No water erosion limitation	0.12 0.68 0.92 0.99	Poor Low strength Shrink-swell	0.00 0.87	Poor Slope Too Clayey	0.00 0.49
Steinauer-----	40	Fair Low content of organic matter No water erosion limitation	0.12 0.99	Poor Low strength Shrink-swell	0.00 0.87	Poor Slope	0.00
Ch: Chase-----	90	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.88 0.99	Poor Low strength Shrink-swell Depth to saturated zone	0.00 0.23 0.53	Poor Too Clayey Depth to saturated zone	0.00 0.53
Co: Contrary-----	85	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Low strength	0.00	Good	
Ga: Grundy-----	90	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.50 0.99	Poor Low strength Depth to saturated zone Shrink-swell	0.00 0.00 0.12	Poor Too Clayey Depth to saturated zone	0.00 0.00
Ju: Judson-----	95	Fair Low content of organic matter Water erosion	0.50 0.90	Poor Low strength Shrink-swell	0.00 0.98	Good	
Kd: Kennebec, CHanneled-	85	Good		Poor Low strength Shrink-swell	0.00 0.87	Good	

CONSTRUCTION MATERIALS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ke: Kennebec-----	89	Good		Poor Low strength Shrink-swell	0.00 0.87	Good	
Kp: Kipson-----	60	Poor Depth to bedrock Carbonate content Droughty Low content of organic matter	0.00 0.00 0.06 0.88	Poor Depth to bedrock Low strength Slope Shrink-swell	0.00 0.00 0.82 0.87	Poor Depth to bedrock Carbonate content Slope Rock fragments	0.00 0.00 0.00 0.68
Sogn-----	30	Poor Droughty Depth to bedrock Too clayey	0.00 0.00 0.98	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.87	Poor Depth to bedrock Slope Too Clayey	0.00 0.16 0.93
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Marshall-----	97	Fair Low content of organic matter Water erosion Too clayey	0.12 0.90 0.99	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.65
Mb: Marshall-----	82	Fair Low content of organic matter Water erosion Too clayey	0.50 0.90 0.98	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.64
Md: Martin-----	85	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.88 0.95 0.99	Poor Low strength Shrink-swell Depth to saturated zone	0.00 0.12 0.53	Poor Too Clayey Depth to saturated zone	0.00 0.53
Mf: Martin-----	90	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.88 0.95 0.99	Poor Low strength Shrink-swell Depth to saturated zone	0.00 0.12 0.53	Poor Too Clayey Depth to saturated zone	0.00 0.53
Mh: Mayberry-----	85	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.88 0.95 0.99	Poor Low strength Depth to saturated zone Shrink-swell	0.00 0.00 0.35	Poor Too Clayey Depth to saturated zone	0.00 0.00
Mk: Monona-----	90	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Low strength	0.00	Good	
Mn: Monona-----	82	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Low strength	0.00	Good	

CONSTRUCTION MATERIALS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Mt: Morrill-----	87	Fair Low content of organic matter Too acid Too clayey	0.88 0.97 0.98	Fair Low strength Shrink-swell	0.78 0.99	Fair Too Clayey Rock fragments Slope	0.70 0.88 0.96
Mw: Muscotah-----	87	Fair Too clayey Water erosion	0.76 0.90	Poor Low strength Shrink-swell Depth to saturated zone	0.00 0.41 0.50	Fair Depth to saturated zone Too Clayey	0.50 0.76
My: Muscotah-----	87	Poor Too clayey No water erosion limitation	0.00 0.99	Poor Low strength Shrink-swell Depth to saturated zone	0.00 0.29 0.50	Poor Too Clayey Depth to saturated zone	0.00 0.50
No: Nodaway-----	90	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Low strength Shrink-swell	0.00 0.87	Good	
Om: Olmitz-----	93	Fair Too acid Too clayey	0.84 0.99	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.87
Or: Orthents, Earthen Dam-----	100	Not rated		Not rated		Not rated	
Pd: Padonia-----	50	Poor Too clayey Water erosion Depth to bedrock	0.00 0.90 0.97	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.27	Poor Too Clayey Depth to bedrock	0.00 0.97
Martin-----	40	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.88 0.95 0.99	Poor Low strength Shrink-swell Depth to saturated zone	0.00 0.12 0.53	Poor Too Clayey Depth to saturated zone	0.00 0.53
Pe: Padonia-----	60	Poor Too clayey Water erosion Depth to bedrock	0.00 0.90 0.97	Poor Depth to bedrock Low strength Shrink-swell Slope	0.00 0.00 0.27 0.92	Poor Too Clayey Slope Depth to bedrock	0.00 0.00 0.97
Martin-----	30	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.88 0.95 0.99	Poor Low strength Shrink-swell Depth to saturated zone	0.00 0.12 0.53	Poor Too Clayey Depth to saturated zone Slope	0.00 0.53 0.63
Pf: Padonia-----	55	Poor Too clayey Water erosion Depth to bedrock	0.00 0.90 0.97	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.27	Poor Too Clayey Depth to bedrock	0.00 0.97

CONSTRUCTION MATERIALS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Oska-----	40	Poor Too clayey Low content of organic matter Depth to bedrock Too acid No water erosion limitation Droughty	0.00 0.88 0.90 0.95 0.99 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.12	Poor Too Clayey Rock fragments Depth to bedrock	0.00 0.72 0.90
Pm: Pawnee-----	85	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.88 0.99	Poor Low strength Depth to saturated zone Shrink-swell	0.00 0.00 0.15	Poor Too Clayey Depth to saturated zone	0.00 0.00
Pn: Pawnee-----	83	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.88 0.99	Poor Low strength Depth to saturated zone Shrink-swell	0.00 0.00 0.15	Poor Too Clayey Depth to saturated zone Slope	0.00 0.00 0.96
Po: Pawnee-----	84	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.88 0.99	Poor Low strength Depth to saturated zone Shrink-swell	0.00 0.00 0.12	Poor Too Clayey Depth to saturated zone Slope	0.00 0.00 0.96
Pt: Pits, Quarries-----	100	Not rated		Not rated		Not rated	
Pw: Pohocco-----	50	Fair Low content of organic matter Water erosion	0.88 0.90	Poor Low strength Shrink-swell	0.00 0.87	Fair Slope	0.04
Netawaka-----	40	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Low strength	0.00	Fair Slope	0.04
Px: Pohocco-----	50	Fair Low content of organic matter Water erosion	0.88 0.90	Poor Low strength Slope Shrink-swell	0.00 0.32 0.87	Poor Slope	0.00
Netawaka-----	40	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Low strength Slope	0.00 0.32	Poor Slope	0.00
Re: Reading-----	90	Fair Water erosion Too acid Too clayey	0.90 0.95 0.98	Poor Low strength Shrink-swell	0.00 0.94	Fair Too Clayey	0.89
Sg: Shelby-----	88	Fair Too clayey Low content of organic matter Too acid No water erosion limitation	0.68 0.88 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey Slope	0.49 0.96

CONSTRUCTION MATERIALS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Sm: Shelby-----	85	Fair Low content of organic matter Too clayey Too acid No water erosion limitation	0.50 0.68 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.87	Poor Slope Too Clayey	0.00 0.44
W: Water-----	100	Not rated		Not rated		Not rated	
Wa: Wabash-----	85	Poor Too clayey Too acid	0.00 0.97	Poor Depth to saturated zone Shrink-swell Low strength	0.00 0.00 0.00	Poor Too Clayey Depth to saturated zone	0.00 0.00
We: Wamego-----	90	Fair Too clayey Depth to bedrock Droughty Water erosion Too acid	0.05 0.16 0.59 0.90 0.95	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.87	Fair Too Clayey Depth to bedrock	0.04 0.16
Wg: Wamego-----	50	Fair Too clayey Depth to bedrock Droughty Water erosion Too acid	0.05 0.16 0.59 0.90 0.95	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.87	Fair Too Clayey Depth to bedrock Slope	0.04 0.16 0.96
Vinland-----	40	Poor Depth to bedrock Droughty Water erosion Too clayey	0.00 0.21 0.90 0.98	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.22 0.87	Poor Depth to bedrock Slope Rock fragments Too Clayey	0.00 0.96 0.97 0.98
Wm: Wymore-----	90	Poor Too clayey Low content of organic matter Water erosion Too acid	0.00 0.12 0.90 0.95	Poor Low strength Depth to saturated zone Shrink-swell	0.00 0.00 0.43	Poor Too Clayey Depth to saturated zone	0.00 0.00
Wn: Wymore-----	82	Poor Too clayey Low content of organic matter Water erosion Too acid	0.00 0.12 0.90 0.95	Poor Low strength Depth to saturated zone Shrink-swell	0.00 0.00 0.55	Poor Too Clayey Depth to saturated zone	0.00 0.00

RECREATIONAL INTERPRETATIONS
Brown County, Kansas

Recreation

The soils of the survey area are rated in the following tables according to limitations that affect their suitability for recreation. The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the recreational uses. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

The ratings in the tables are based on restrictive soil features, such as wetness, slope, and texture of the surface layer. Susceptibility to flooding is considered. Not considered in the ratings, but important in evaluating a site, are the location and accessibility of the area, the size and shape of the area and its scenic quality, vegetation, access to water, potential water impoundment sites, and access to public sewer lines. The capacity of the soil to absorb septic tank effluent and the ability of the soil to support vegetation also are important. Soils that are subject to flooding are limited for recreational uses by the duration and intensity of flooding and the season when flooding occurs. In planning recreational facilities, onsite assessment of the height, duration, intensity, and frequency of flooding is essential.

The information in this table can be supplemented by other information in this survey, for example, interpretations for building site development, construction materials, sanitary facilities, and water management.

Camp areas require site preparation, such as shaping and leveling the tent and parking areas, stabilizing roads and intensively used areas, and installing sanitary facilities and utility lines. Camp areas are subject to heavy foot traffic and some vehicular traffic. The ratings are based on the soil properties that affect the ease of developing camp areas and the performance of the areas after development. Slope, stoniness, and depth to bedrock or a cemented pan are the main concerns affecting the development of camp areas.

The soil properties that affect the performance of the areas after development are those that influence trafficability and promote the growth of vegetation, especially in heavily used areas. For good trafficability, the surface of camp areas should absorb rainfall readily, remain firm under heavy foot traffic, and not be dusty when dry. The soil properties that influence trafficability are texture of the surface layer, depth to a water table, ponding, flooding, permeability, and large stones. The soil properties that affect the growth of plants are depth to bedrock or a cemented pan, permeability, and toxic substances in the soil.

Picnic areas are subject to heavy foot traffic. Most vehicular traffic is confined to access roads and parking areas. The ratings are based on the soil properties that affect the ease of developing picnic areas and that influence trafficability and the growth of vegetation after development. Slope and stoniness are the main concerns affecting the development of picnic areas. For good trafficability, the surface of picnic areas should absorb rainfall readily, remain firm under heavy foot traffic, and not be dusty when dry. The soil properties that influence trafficability are texture of the surface layer, depth to a water table, ponding, flooding, permeability, and large stones. The soil properties that affect the growth of plants are depth to bedrock or a cemented pan, permeability, and toxic substances in the soil.

Playgrounds require soils that are nearly level, are free of stones, and can withstand intensive foot traffic. The ratings are based on the soil properties that affect the ease of developing playgrounds and that influence trafficability and the growth of vegetation after development. Slope and stoniness are the main concerns affecting the development of playgrounds. For good trafficability, the surface of the playgrounds should absorb rainfall readily, remain firm under heavy foot traffic, and not be dusty when dry. The soil properties that influence trafficability are texture of the surface layer, depth to a water table, ponding, flooding, permeability, and large stones. The soil properties that affect the growth of plants are depth to bedrock or a cemented pan, permeability, and toxic substances in the soil.

Paths and trails for hiking and horseback riding should require little or no slope modification through cutting and filling. The ratings are based on the soil properties that affect trafficability and erodibility. These properties are stoniness, depth to a water table, ponding, flooding, slope, and texture of the surface layer.

Golf fairways are subject to heavy foot traffic and some light vehicular traffic. Cutting or filling may be required. Irrigation is not considered in the ratings. The ratings are based on the soil properties that affect plant growth and trafficability after vegetation is established. The properties that affect plant growth are reaction; depth to a water table; ponding; depth to bedrock or a cemented pan; the available water capacity in the upper 40 inches; the content of salts, sodium, or calcium carbonate; and sulfidic materials. The properties that affect trafficability are flooding, depth to a water table, ponding, slope, stoniness, and the amount of sand, clay, or organic matter in the surface layer. The suitability of the soil for traps, tees, roughs, and greens is not considered in the ratings.

RECREATIONAL INTERPRETATIONS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ac: Aksarben-----	90	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability	0.15
Ad: Aksarben-----	87	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability	0.15	Somewhat limited Slope	0.50
						Restricted permeability	0.15
Ae: Aksarben-----	85	Somewhat limited Restricted permeability Slope	0.15 0.00	Somewhat limited Restricted permeability Slope	0.15 0.00	Very limited Slope	1.00
						Restricted permeability	0.15
Bs: Burchard-----	85	Somewhat limited Restricted permeability Slope	0.15 0.04	Somewhat limited Restricted permeability Slope	0.15 0.04	Very limited Slope	1.00
						Restricted permeability	0.15
Bx: Burchard-----	55	Very limited Slope Restricted permeability	1.00 0.15	Very limited Slope Restricted permeability	1.00 0.15	Very limited Slope Restricted permeability	1.00 0.15
Steinauer-----	40	Very limited Slope Restricted permeability	1.00 0.15	Very limited Slope Restricted permeability	1.00 0.15	Very limited Slope Restricted permeability	1.00 0.15
Ch: Chase-----	90	Very limited Flooding	1.00	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94
		Restricted permeability Depth to saturated zone	0.94 0.44	Depth to saturated zone	0.19	Depth to saturated zone	0.44
Co: Contrary-----	85	Not limited		Not limited		Very limited Slope	1.00
Ga: Grundy-----	90	Very limited Depth to saturated zone Restricted permeability	1.00 0.94	Very limited Depth to saturated zone Restricted permeability	1.00 0.94	Very limited Depth to saturated zone Restricted permeability	1.00 0.94
Ju: Judson-----	95	Not limited		Not limited		Somewhat limited Slope	0.50
Kd: Kennebec, CHanneled-	85	Very limited Flooding	1.00	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
Ke: Kennebec-----	89	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
Kp: Kipson-----	60	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to bedrock Slope	1.00 1.00
						Content of large stones	0.20
Sogn-----	30	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Slope	1.00 1.00
						Content of large stones	0.00
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Marshall-----	97	Not limited		Not limited		Somewhat limited Slope	0.50
Mb: Marshall-----	82	Somewhat limited Slope	0.00	Somewhat limited Slope	0.00	Very limited Slope	1.00
Md: Martin-----	85	Somewhat limited		Somewhat limited		Somewhat limited	

RECREATIONAL INTERPRETATIONS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Mf: Martin-----	90	Restricted permeability	0.94	Restricted permeability	0.94	Restricted permeability	0.94
		Depth to saturated zone	0.44	Depth to saturated zone	0.19	Depth to saturated zone	0.44
						Slope	0.13
		Somewhat limited		Somewhat limited		Very limited	
Mh: Mayberry-----	85	Restricted permeability	0.94	Restricted permeability	0.94	Slope	1.00
		Depth to saturated zone	0.44	Depth to saturated zone	0.19	Restricted permeability	0.94
		Slope	0.00	Slope	0.00	Depth to saturated zone	0.44
		Very limited		Very limited		Very limited	
Mk: Monona-----	90	Depth to saturated zone	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Restricted permeability	0.94	Restricted permeability	0.94	Restricted permeability	0.94
						Slope	0.50
		Not limited		Not limited		Somewhat limited	
Mn: Monona-----	82					Slope	0.50
		Somewhat limited		Somewhat limited		Very limited	
		Slope	0.00	Slope	0.00	Slope	1.00
Mt: Morrill-----	87	Somewhat limited		Somewhat limited		Very limited	
		Restricted permeability	0.15	Restricted permeability	0.15	Slope	1.00
		Slope	0.04	Slope	0.04	Restricted permeability	0.15
						Gravel content	0.06
Mw: Muscotah-----	87	Very limited		Somewhat limited		Somewhat limited	
		Flooding	1.00	Restricted permeability	0.94	Restricted permeability	0.94
		Restricted permeability	0.94	Depth to saturated zone	0.22	Flooding	0.60
		Depth to saturated zone	0.50			Depth to saturated zone	0.50
My: Muscotah-----	87	Very limited		Somewhat limited		Somewhat limited	
		Flooding	1.00	Restricted permeability	0.94	Restricted permeability	0.94
		Restricted permeability	0.94	Depth to saturated zone	0.22	Flooding	0.60
		Depth to saturated zone	0.50			Depth to saturated zone	0.50
No: Nodaway-----	90	Very limited		Not limited		Somewhat limited	
		Flooding	1.00			Flooding	0.60
Om: Olmitz-----	93	Not limited		Not limited		Somewhat limited	
						Slope	0.50
Or: Orthents, Earthen Dam-----	100	Not rated		Not rated		Not rated	
Pd: Padonia-----	50	Somewhat limited		Somewhat limited		Very limited	
		Restricted permeability	0.94	Restricted permeability	0.94	Slope	1.00
						Restricted permeability	0.94
						Depth to bedrock	0.03
Martin-----	40	Somewhat limited		Somewhat limited		Very limited	
		Restricted permeability	0.94	Restricted permeability	0.94	Slope	1.00
		Depth to saturated zone	0.44	Depth to saturated zone	0.19	Restricted permeability	0.94
		Slope	0.00	Slope	0.00	Depth to saturated zone	0.44
Pe: Padonia-----	60	Very limited		Very limited		Very limited	
		Slope	1.00	Slope	1.00	Slope	1.00
		Restricted permeability	0.94	Restricted permeability	0.94	Restricted permeability	0.94
						Depth to bedrock	0.03
Martin-----	30	Somewhat limited		Somewhat limited		Very limited	

RECREATIONAL INTERPRETATIONS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Pf: Padonia-----	55	Restricted permeability	0.94	Restricted permeability	0.94	Slope	1.00
		Depth to saturated zone	0.44	Slope	0.37	Restricted permeability	0.94
		Slope	0.37	Depth to saturated zone	0.19	Depth to saturated zone	0.44
		Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94	Very limited Slope	1.00
						Restricted permeability	0.94
Oska-----	40	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94	Depth to bedrock	0.03
						Very limited Slope	1.00
						Restricted permeability	0.94
Pm: Pawnee-----	85	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Depth to bedrock	0.10
		Restricted permeability	0.94	Restricted permeability	0.94	Restricted permeability	0.94
						Slope	0.50
Pn: Pawnee-----	83	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Restricted permeability	0.94	Restricted permeability	0.94	Slope	1.00
		Slope	0.04	Slope	0.04	Restricted permeability	0.94
Po: Pawnee-----	84	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Too clayey	1.00	Too clayey	1.00	Slope	1.00
		Restricted permeability	0.94	Restricted permeability	0.94	Too clayey	1.00
		Slope	0.04	Slope	0.04	Restricted permeability	0.94
Pt: Pits, Quarries-----	100	Not rated		Not rated		Not rated	
Pw: Pohocco-----	50	Somewhat limited Slope	0.96	Somewhat limited Slope	0.96	Very limited Slope	1.00
Netawaka-----	40	Somewhat limited Slope	0.96	Somewhat limited Slope	0.96	Very limited Slope	1.00
Px: Pohocco-----	50	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00
Netawaka-----	40	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00
Re: Reading-----	90	Very limited Flooding	1.00	Not limited		Not limited	
Sg: Shelby-----	88	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability	0.15	Very limited Slope	1.00
		Slope	0.04	Slope	0.04	Restricted permeability	0.15
Sm: Shelby-----	85	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00
		Restricted permeability	0.15	Restricted permeability	0.15	Restricted permeability	0.15
W: Water-----	100	Not rated		Not rated		Not rated	
Wa: Wabash-----	85	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Flooding	1.00	Restricted permeability	1.00	Restricted permeability	1.00

RECREATIONAL INTERPRETATIONS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
We: Wamego-----	90	Restricted permeability	1.00	Too clayey	1.00	Too clayey	1.00
		Too clayey	1.00			Flooding	0.60
		Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94
Wg: Wamego-----	50	Slope		Slope		Slope	
						Depth to bedrock	0.87
						Depth to bedrock	0.84
Vinland-----	40	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94	Very limited Slope	1.00
		Slope	0.04	Slope	0.04	Restricted permeability	0.94
						Depth to bedrock	0.84
Wm: Wymore-----	90	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00
		Slope	0.04	Slope	0.04	Slope	1.00
						Gravel content	0.04
Wn: Wymore-----	82	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Restricted permeability	0.94	Restricted permeability	0.94	Restricted permeability	0.94
						Slope	0.50
						Restricted permeability	0.94

RECREATIONAL INTERPRETATIONS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Paths and trails		Golf fairways	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Ac: Aksarben-----	90	Not limited		Not limited	
Ad: Aksarben-----	87	Not limited		Not limited	
Ae: Aksarben-----	85	Not limited		Somewhat limited Slope	0.00
Bs: Burchard-----	85	Not limited		Somewhat limited Slope	0.04
Bx: Burchard-----	55	Somewhat limited Slope	0.00	Very limited Slope	1.00
Steinauer-----	40	Somewhat limited Slope	0.00	Very limited Slope	1.00
Ch: Chase-----	90	Not limited		Somewhat limited Depth to saturated zone	0.19
Co: Contrary-----	85	Not limited		Not limited	
Ga: Grundy-----	90	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
Ju: Judson-----	95	Not limited		Not limited	
Kd: Kennebec, CHanneled-	85	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
Ke: Kennebec-----	89	Not limited		Somewhat limited Flooding	0.60
Kp: Kipson-----	60	Somewhat limited Slope	0.18	Very limited Depth to bedrock Slope Carbonate content Content of large stones	1.00 1.00 1.00 0.20
Sogn-----	30	Not limited		Droughty Very limited Depth to bedrock Slope Droughty Content of large stones	0.12 1.00 0.84 0.80 0.00
M-W: Miscellaneous Water-	100	Not rated		Not rated	
Ma: Marshall-----	97	Not limited		Not limited	
Mb: Marshall-----	82	Not limited		Somewhat limited Slope	0.00
Md: Martin-----	85	Not limited		Somewhat limited Depth to saturated zone	0.19
Mf: Martin-----	90	Not limited		Somewhat limited Depth to saturated zone Slope	0.19 0.00
Mh: Mayberry-----	85	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
Mk: Monona-----	90	Not limited		Not limited	
Mn: Monona-----	82	Not limited		Somewhat limited Slope	0.00
Mt: Morrill-----	87	Not limited		Somewhat limited Slope	0.04
Mw: Muscotah-----	87	Not limited		Somewhat limited Flooding	0.60

RECREATIONAL INTERPRETATIONS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Paths and trails		Golf fairways	
		Rating class and limiting features	Value	Rating class and limiting features	Value
My: Muscotah-----	87	Not limited		Depth to saturated zone	0.22
No: Nodaway-----	90	Not limited		Somewhat limited Flooding	0.60
Om: Olmitz-----	93	Not limited		Depth to saturated zone	0.22
Or: Orthents, Earthen Dam-----	100	Not rated		Somewhat limited Flooding	0.60
Pd: Padonia-----	50	Not limited		Not limited	
Martin-----	40	Not limited		Not rated	
Pe: Padonia-----	60	Somewhat limited Slope	0.08	Somewhat limited Depth to bedrock	0.03
Martin-----	30	Not limited		Somewhat limited Depth to saturated zone	0.19
Pf: Padonia-----	55	Not limited		Slope	0.00
Oska-----	40	Not limited		Very limited Slope	1.00
Pm: Pawnee-----	85	Very limited Depth to saturated zone	1.00	Depth to bedrock	0.03
Pn: Pawnee-----	83	Very limited Depth to saturated zone	1.00	Somewhat limited Slope	0.37
Po: Pawnee-----	84	Very limited Depth to saturated zone Too clayey	1.00 1.00	Depth to saturated zone	0.19
Pt: Pits, Quarries-----	100	Not rated		Too clayey	1.00
Pw: Pohocco-----	50	Not limited		Slope	0.04
Netawaka-----	40	Not limited		Droughty	0.00
Px: Pohocco-----	50	Somewhat limited Slope	0.68	Not rated	
Netawaka-----	40	Somewhat limited Slope	0.68	Somewhat limited Slope	0.96
Re: Reading-----	90	Not limited		Very limited Slope	1.00
Sg: Shelby-----	88	Not limited		Very limited Slope	1.00
Sm: Shelby-----	85	Somewhat limited Slope	0.00	Not limited	
W: Water-----	100	Not rated		Somewhat limited Slope	0.04
Wa: Wabash-----	85	Very limited		Very limited Slope	1.00

RECREATIONAL INTERPRETATIONS--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Paths and trails		Golf fairways	
		Rating class and limiting features	Value	Rating class and limiting features	Value
		Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Too clayey	1.00	Too clayey	1.00
				Flooding	0.60
We: Wamego-----	90	Not limited		Somewhat limited Depth to bedrock	0.84
Wg: Wamego-----	50	Not limited		Somewhat limited Depth to bedrock	0.84
				Slope	0.04
Vinland-----	40	Not limited		Very limited Depth to bedrock	1.00
				Slope	0.04
				Droughty	0.00
Wm: Wymore-----	90	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
Wn: Wymore-----	82	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00

WILDLIFE INTERPRETATIONS
Brown County, Kansas

Use and Explanation of Wildlife Interpretations

Soils directly affect the kind and amount of vegetation that is available to wildlife as food and cover. They also affect the development of water impoundments. The kind and abundance of wildlife that populate an area depend largely on the amount and distribution of food, cover, water, and living space. If any one of these elements is missing, inadequate, or inaccessible, wildlife will be scarce or will not inhabit the area. If the soils have the potential, wildlife habitat can be created or improved by planting appropriate vegetation, properly managing the existing plant cover, and fostering the natural establishment of desirable plants.

In the Wildlife Interpretations table, the soils in the survey area are rated according to their potential for providing habitat for various kinds of wildlife. This information can be used in planning parks, wildlife refuges, nature study areas, and other developments for wildlife; in selecting soils that are suitable for establishing, improving, or maintaining specific elements of wildlife habitat; and in determining the intensity of management needed for each element of the habitat.

Suitability Ratings

The potential of the soil is rated good, fair, poor, or very poor.

Good - means that the element of wildlife habitat or the kind of habitat is easily created, improved, or maintained. Few or no limitations affect management, and satisfactory results can be expected if the soil is used for the designated purpose.

Fair - means that the element of wildlife habitat or kind of habitat can be created, improved, or maintained in most places. Moderately intensive management is required for satisfactory results.

Poor - means that limitations are severe for the designated element or kind of wildlife habitat. Habitat can be created, improved, or maintained in most places, but management is difficult and requires intensive effort.

Very Poor - means that limitations are very severe for the designated element or kind of wildlife habitat. Habitat is difficult to create, improve, or maintain in most places, and management is difficult and requires intensive effort.

Description of Wildlife Habitat Elements

Openland habitat consists of croplands, pastures, meadows, and areas that are overgrown with grasses, herbs, shrubs, and vines. These areas produce grain and seed crops, grasses and legumes, and wild herbaceous plants. The kind of wildlife attracted to these areas include bobwhite quail, pheasant, meadowlark, field sparrow, killdeer, cottontail rabbit, red fox, and coyote.

Woodland habitat consists of hardwood or conifers, or a mixture of these and associated grasses, legumes and wild herbaceous plants. Examples of wildlife attracted to this habitat are wild turkey, thrushes, woodpeckers, owl, tree squirrels, raccoon, and deer.

Wetland habitat consists of water-tolerant plants in open, marshy or swampy, shallow water areas. Examples of wildlife attracted to this habitat are ducks, geese, herons, bitterns, rails, kingfishers, shorebirds, muskrat, mink, and beaver.

The elements of wildlife habitat are described in the following paragraphs.

Grain and seed crops are domestic grains and seed-producing herbaceous plants. Soil properties and features that affect the growth of grain and seed crops are depth of the root zone, texture of the surface layer, available water capacity, wetness, slope, surface stoniness, and flooding. Soil temperature and soil moisture also are considerations. Examples of grain and seed crops are corn, wheat, oats, and barley.

Grasses and legumes are domestic perennial grasses and herbaceous legumes. Soil properties and features that affect the growth of grasses and legumes are depth of the root zone, texture of the surface layer, available water capacity, wetness, surface stoniness, flooding, and slope. Soil temperature and soil moisture also are considerations. Examples of grasses and legumes are fescue, lovegrass, bromegrass, clover, and alfalfa.

Wild herbaceous plants are native or naturally established grasses and forbs, including weeds. Soil properties and features that affect the growth of these plants are depth of the root zone, texture of the surface layer, available water capacity, wetness, surface stoniness, and flooding. Soil temperature and soil moisture also are considerations. Examples of wild herbaceous plants are bluestem, goldenrod, beggarweed, wheatgrass, and grama.

Hardwood trees and woody understory produce nuts or other fruit, buds, catkins, twigs, bark, and foliage. Soil properties and features that affect the growth of hardwood trees and shrubs are depth of the root zone, available water capacity, and wetness. Examples of these plants are oak, poplar, cherry, sweetgum, apple, hawthorn, dogwood, hickory, blackberry, and blueberry. Examples of fruit-producing shrubs that are suitable for planting on soils rated good are Russian-olive, autumn-olive, and crabapple.

Coniferous plants furnish browse and seeds. Soil properties and features that affect the growth of coniferous trees, shrubs, and ground cover are depth of the root zone, available water capacity, and wetness. Examples of coniferous plants are pine, spruce, fir, cedar, and juniper.

Shrubs are bushy woody plants that produce fruit, buds, twigs, bark, and foliage. Soil properties and features that affect the growth of shrubs are depth of the root zone, available water capacity, salinity, and soil moisture. Examples of shrubs are fragrant sumac, chokecherry, American plum, sand plum, and gorden currant.

Wetland plants are annual and perennial wild herbaceous plants that grow on moist or wet sites. Submerged or floating aquatic plants are excluded. Soil properties and features affecting wetland plants are texture of the surface layer, wetness, reaction, salinity, slope, and surface stoniness. Examples of wetland plants are smartweed, wild millet, saltgrass, cordgrass, rushes, sedges, and cattails.

Shallow water areas have an average depth of less than 5 feet. Some are naturally wet areas. Others are created by dams, levees, or other water-control structures. Soil properties and features affecting shallow water areas are depth to bedrock, wetness, surface stoniness, slope, and permeability. Examples of shallow water areas are marshes, waterfowl feeding areas, and ponds.

The habitat for various kinds of wildlife is described in the following paragraphs.

Habitat for openland wildlife consists of cropland, pasture, meadows, and areas that are overgrown with grasses, herbs, shrubs, and vines. These areas produce grain and seed crops, grasses and legumes, and wild herbaceous plants. Wildlife attracted to these areas include bobwhite quail, pheasant, meadowlark, field sparrow, cottontail, red fox and coyote.

Habitat for woodland wildlife consists of areas of deciduous and/or coniferous plants and associated grasses, legumes, and wild herbaceous plants. Wildlife attracted to these areas include wild turkey, thrushes, woodpeckers, squirrels, gray fox, raccoon, and deer.

Habitat for wetland wildlife consists of open, marshy or swampy shallow water areas. Some of the wildlife attracted to such areas are ducks, geese, herons, shore birds, muskrat, mink, and beaver.

Habitat for rangeland wildlife consists of areas of shrubs and wild herbaceous plants. Wildlife attracted to rangeland include antelope, deer, cottontail rabbit, prairie chicken, meadowlark, quail, and pheasant.

WILDLIFE INTERPRETATIONS
Brown County, Kansas

Map symbol and soil name	Potential for habitat elements								Potential as habitat for--			
	Grain and seed crops	Grasses and legumes	Wild herba- ceous plants	Hard- wood trees	Conif- erous plants	Shrubs	Wetland plants	Shallow water areas	Open- land wild- life	Wood- land wild- life	Wetland wild- life	Range- land wild- life
Ac: AKSARBEN-----	Good	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Ad: AKSARBEN-----	Good	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Ae: AKSARBEN-----	Fair	Good	Good	Good	Good	Good	Very poor	Poor	Good	Good	Very poor	Good
Bs: BURCHARD-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Bx: BURCHARD-----	Poor	Fair	Good	Good	Good	Good	Very poor	Very poor	Fair	Good	Very poor	Good
STEINAUER-----	Poor	Fair	Good	Good	Good	Good	Very poor	Very poor	Fair	Good	Very poor	Good
Ch: CHASE-----	Fair	Good	Good	Good	Good	Good	Fair	Fair	Good	Good	Fair	Good
Co: CONTRARY-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Ga: GRUNDY-----	Fair	Good	Good	Good	Good	Good	Fair	Fair	Good	Good	Fair	Good
Ju: JUDSON-----	Good	Good	Good	Good	Good	---	Poor	Poor	Good	Good	Poor	---
Kd: KENNEBEC-----	Poor	Poor	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	Good
Ke: KENNEBEC-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	Good
Kp: KIPSON-----	Poor	Poor	Fair	Fair	Fair	Fair	Very poor	Very poor	Poor	Fair	Very poor	Fair
SOGN-----	Very poor	Poor	Poor	Very poor	Very poor	Very poor	Very poor	Very poor	Very poor	Poor	Very poor	Poor
M-W: MISCELLANEOUS WATER-----	---	---	---	---	---	---	---	---	---	---	---	---
Ma: MARSHALL-----	Good	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Mb: MARSHALL-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Md: MARTIN-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	Good
Mf: MARTIN-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Mh: MAYBERRY-----	Fair	Good	Good	Fair	Fair	Good	Very poor	Very poor	Good	Fair	Very poor	Good
Mk: MONONA-----	Good	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Mn: MONONA-----	Good	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Mt: MORRILL-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good

WILDLIFE INTERPRETATIONS--Continued
Brown County, Kansas

Map symbol and soil name	Potential for habitat elements								Potential as habitat for--			
	Grain and seed crops	Grasses and legumes	Wild herba- ceous plants	Hard- wood trees	Conif- erous plants	Shrubs	Wetland plants	Shallow water areas	Open- land wild- life	Wood- land wild- life	Wetland wild- life	Range- land wild- life
Mw: MUSCOTAH-----	Fair	Good	Good	Fair	Fair	Good	Fair	Fair	Good	Fair	Fair	Fair
My: MUSCOTAH-----	Fair	Good	Good	Fair	Fair	Good	Fair	Fair	Good	Fair	Fair	Fair
No: NODAWAY-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	Good
Om: OLMITZ-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	Good
Or: ORTHENTS, EARTHEN DAM----	---	---	---	---	---	---	---	---	---	---	---	---
Pd: PADONIA-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
MARTIN-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Pe: PADONIA-----	Poor	Fair	Good	Good	Good	Good	Very poor	Very poor	Fair	Good	Very poor	Fair
MARTIN-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Pf: PADONIA-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
OSKA-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Pm: PAWNEE-----	Fair	Good	Good	Fair	Fair	Good	Very poor	Very poor	Good	Fair	Very poor	Good
Pn: PAWNEE-----	Fair	Good	Good	Fair	Fair	Good	Very poor	Very poor	Good	Fair	Very poor	Good
Po: PAWNEE-----	Poor	Fair	Fair	Poor	Poor	Fair	Very poor	Very poor	Fair	Poor	Very poor	Fair
Pt: Pits, quarries--	---	---	---	---	---	---	---	---	---	---	---	---
Pw: POHOCCO-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
NETAWAKA-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Px: POHOCCO-----	Poor	Fair	Good	Good	Good	Good	Very poor	Very poor	Fair	Good	Very poor	Fair
NETAWAKA-----	Poor	Fair	Good	Good	Good	Good	Very poor	Very poor	Fair	Good	Very poor	Fair
Re: READING-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	Good
Sg: SHELBY-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Sm: SHELBY-----	Poor	Fair	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
W: WATER-----	---	---	---	---	---	---	---	---	---	---	---	---
Wa: WABASH-----	Poor	Fair	Fair	Poor	Poor	Fair	Good	Good	Fair	Poor	Fair	Poor

WILDLIFE INTERPRETATIONS--Continued
Brown County, Kansas

Map symbol and soil name	Potential for habitat elements								Potential as habitat for--			
	Grain and seed crops	Grasses and legumes	Wild herba- ceous plants	Hard- wood trees	Conif- erous plants	Shrubs	Wetland plants	Shallow water areas	Open- land wild- life	Wood- land wild- life	Wetland wild- life	Range- land wild- life
We: WAMEGO-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
Wg: WAMEGO-----	Poor	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
VINLAND-----	Poor	Poor	Fair	Fair	Fair	Fair	Very poor	Very poor	Poor	Fair	Very poor	Fair
Wm: WYMORE-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	Good
Wn: WYMORE-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good

CONSERVATION TREE AND SHRUB MANAGEMENT
Brown County, Kansas

A Conservation Tree/Shrub Suitability Group (CTSG), formerly Windbreak Suitability Group, is a physiographic unit or area having similar climatic and edaphic characteristics that control the selection and height growth of trees and shrubs.

In this table, the Conservation Tree and Shrub Grouping is expressed as a group index number. The group index for Conservation Tree and Shrub groups (CTSG) are a guide for species best suited for different kinds of soil and for prediction height, growth, and effectiveness. The groupings can be used when selection woody plants for windbreaks, wildlife plantings riparian buffers, reforestation, other environmental plantings, recreation, landscaping, wetland restoration or enhancement and critical area plantings. CTSG's are developed to assure satisfactory species selection and adaptation to specific conditions of soil, climate and physiography. CTSG's are a guide for selection species best suited for different kinds of soil and prediction height growth and effectiveness.

All soil series mapped in the state have been placed in 10 groups of similar soil characteristics. Groups 1, 2, 3, 4, 6, and 9 are further divided into subgroups. In addition, all groups provide information by Major Land Resource Areas.

Each tree or shrub species has certain climatic and physiographic limits. Within these parameters a tree or shrub may be well or poorly suited because of soil characteristics. Each tree or shrub also has definable potentials of height growth depending on the factors just mentioned. Accurate definitions of potential heights are necessary for proper windbreak planning and design.

Windbreaks protect livestock, buildings, roads and yards from wind and snow. They also protect fruit trees and gardens, and they furnish habitat for wildlife. Several rows of low-growing and high-growing broadleaf and coniferous trees and shrubs provide the most protection.

Field windbreaks are narrow plantings made at right angles to the prevailing wind and at specific intervals across the field. The interval depends on the erodibility of the soil. Field windbreaks protect cropland and crops from wind, help to keep snow on the fields, and provide food and cover for wildlife.

Environmental plantings help to beautify and screen houses and other buildings and to abate noise. The plants, mostly evergreen shrubs and trees, are closely spaced. To ensure plant survival, a healthy planting stock of suitable species should be planted properly on a well prepared site and maintained in good condition.

Windbreaks are often planted on land that did not grow trees originally. Knowledge of how trees perform on such land can be gained only by observing and recording their performance where trees have been planted and survived. The problem is compounded by the fact that many favorite windbreak species are not indigenous to the areas in which they are planted.

The Kansas Field Office Technical Guide Notice KS-230, Conservation Tree and Shrub Plantings Suitability Groups shows the adapted species listing for each group index number. Showing the height that locally grown trees and shrubs are expected to reach in 20 years on various soils. The estimates are based on measurements and observation of established plantings that have been given adequate care. This information should be used to determine the placement of a windbreak, the area protected and the arrangement of species.

A number of attributes are included in the CTSG species tables for each group number found in this section of the Field Office Technical Guide. These attributes were rated subjectively and assigned a relative value to further assist those unfamiliar with individual species characteristics or desirability for the intended use. Definitions and explanations can be found. Additional information on planning windbreaks and screens and planting and caring for trees and shrubs can be obtained from the local office of the Natural Resources Conservation Service or of the Cooperative Extension Service or from a commercial nursery. See part 537 of the National Forestry Manual for additional information.

In the Tree and Shrub Management table interpretive ratings are given for various aspects of forest and conservation tree and shrub management. Some rating class terms indicate the degree to which the soils are suited to a specified forest management practice. Well suited indicates that the soil has features that are favorable for the specified practice and has no limitations. Good performance can be expected, and little or no maintenance is needed. Moderately well suited indicates that the soil has features that are moderately favorable for the specified practice. One or more soil properties are less than desirable and fair performance can be expected. Some maintenance is needed. Poorly suited indicates that the soil has one or more properties that are unfavorable for the specified practice. Overcoming the unfavorable properties requires special design, extra maintenance, and costly alteration. Unsited indicates that the expected performance of the soil is unacceptable for the specified practice or that extreme measures are needed to overcome the undesirable soil properties.

The paragraphs that follow indicate the soil properties considered in rating the soils for forest and conservation tree and shrub management practices. More detailed information about the criteria used in the ratings is available in the "National Forestry Manual," which is available in local offices of the Natural Resources Conservation Service or on the Internet. Also, in the Kansas Field Office Technical Guide Notice KS-230, Conservation Tree and Shrub Plantings Suitability Groups.

Ratings in the columns suitability for hand planting and suitability for mechanical planting are based on slope, depth to a restrictive layer, content of sand, plasticity index, rock fragments on or below the surface, depth to a water table, and ponding. The soils are described as well suited, moderately well suited, poorly suited, or unsited to these methods of planting. It is assumed that necessary site preparation is completed before seedlings are planted.

Ratings in the column suitability for mechanical site preparation (surface) are based on slope, depth to a restrictive layer, plasticity index, rock fragments on or below the surface, depth to a water table, and ponding. The soils are described as well suited, poorly suited, or unsited to this management activity. The part of the soil from the surface to a depth of about 1-foot is considered in the ratings.

Ratings in the column suitability for mechanical site preparation (deep) are based on slope, depth to a restrictive layer, rock fragments on or below the surface, depth to a water table, and ponding. The soils are described as well suited, poorly suited, or unsited to this management activity. The part of the soil from the surface to a depth of about 3 feet is considered in the ratings.

Ratings in the column potential for seedling mortality are based on flooding, ponding, depth to a water table, content of lime, reaction, salinity, available water capacity, soil moisture regime, soil temperature regime, aspect, and slope. The soils are described as having a low, moderate, or high potential for seedling mortality. See the National Forestry Manual, Subpart B for criteria used in rating management concerns. Specific information on plants and yields can be obtained from the local office of the Natural Resources Conservation Service or the Cooperative Extension Service.

CONSERVATION TREE AND SHRUB MANAGEMENT
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. Pines and spruces are prone to disease problems. See text for further explanation of ratings in this table.)

Map symbol and soil name	Wind break Group	Suitability for hand planting	Suitability for mechanical planting	Suitability for mechanical site preparation (surface)	Suitability for mechanical site preparation (deep)	Potential for seedling mortality
		Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features
Ac: Aksarben-----	3	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Low
Ad: Aksarben-----	3	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Ae: Aksarben-----	3	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
Bs: Burchard-----	3	Well suited	Moderately suited Slope	Well suited	Well suited	Low
Bx: Burchard-----	3	Moderately suited Stickiness	Moderately suited Slope Stickiness	Poorly suited Slope	Poorly suited Slope	Low
Steinauer-----	8	Moderately suited Stickiness	Moderately suited Slope Stickiness	Poorly suited Slope	Poorly suited Slope	Moderate Soil reaction
Ch: Chase-----	1	Moderately suited Stickiness	Moderately suited Stickiness	Poorly suited Stickiness	Well suited	Low
Co: Contrary-----	3	Well suited	Moderately suited Slope	Well suited	Well suited	Low
Ga: Grundy-----	4	Moderately suited Stickiness	Moderately suited Stickiness	Poorly suited Stickiness	Well suited	High Wetness
Ju: Judson-----	1	Well suited	Well suited	Well suited	Well suited	Low
Kd: Kennebec, CHanneled-	1	Well suited	Well suited	Well suited	Well suited	Low
Ke: Kennebec-----	1	Well suited	Well suited	Well suited	Well suited	Low
Kp: Kipson-----	10	Well suited	Poorly suited Slope Rock fragments	Poorly suited Slope	Poorly suited Slope	High Lime Soil reaction
Sogn-----	10	Well suited	Moderately suited Slope	Well suited	Unsuited Restrictive layer	Low
M-W: Miscellaneous Water-		Not rated	Not rated	Not rated	Not rated	Not rated
Ma: Marshall-----	3	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Low
Mb: Marshall-----	3	Moderately suited Stickiness	Moderately suited Slope Stickiness	Well suited	Well suited	Low
Md: Martin-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Mf: Martin-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
Mh: Mayberry-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	High Wetness
Mk: Monona-----	3	Well suited	Well suited	Well suited	Well suited	Low
Mn: Monona-----	3	Well suited	Moderately suited Slope	Well suited	Well suited	Low

CONSERVATION TREE AND SHRUB MANAGEMENT
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. Pines and spruces are prone to disease problems. See text for further explanation of ratings in this table.)

Map symbol and soil name	Wind break Group	Suitability for hand planting	Suitability for mechanical planting	Suitability for mechanical site preparation (surface)	Suitability for mechanical site preparation (deep)	Potential for seedling mortality
		Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features
Mt: Morrill-----	3	Well suited	Moderately suited Slope	Well suited	Well suited	Low
Mw: Muscotah-----	1	Well suited	Well suited	Well suited	Well suited	Low
My: Muscotah-----	1	Moderately suited Stickiness	Moderately suited Stickiness	Poorly suited Stickiness	Well suited	Low
No: Nodaway-----	1	Well suited	Well suited	Well suited	Well suited	Low
Om: Olmitz-----	1	Well suited	Well suited	Well suited	Well suited	Low
Or: Orthents, Earthen Dam-----		Not rated	Not rated	Not rated	Not rated	Not rated
Pd: Padonia-----	4	Moderately suited Stickiness	Moderately suited Slope Stickiness	Well suited	Well suited	Low
Martin-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
Pe: Padonia-----	4	Moderately suited Stickiness	Poorly suited Slope Stickiness	Poorly suited Slope	Poorly suited Slope	Low
Martin-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
Pf: Padonia-----	4	Moderately suited Stickiness	Moderately suited Slope Stickiness	Well suited	Well suited	Low
Oska-----	4	Moderately suited Stickiness	Moderately suited Stickiness Slope	Well suited	Poorly suited Restrictive layer	Low
Pm: Pawnee-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	High Wetness
Pn: Pawnee-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	High Wetness
Po: Pawnee-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	High Wetness
Pt: Pits, Quarries----		Not rated	Not rated	Not rated	Not rated	Not rated
Pw: Pohocco-----	3	Well suited	Moderately suited Slope	Well suited	Well suited	Low
Netawaka-----	8	Well suited	Moderately suited Slope	Well suited	Well suited	Moderate Soil reaction
Px: Pohocco-----	3	Well suited	Poorly suited Slope	Poorly suited Slope	Poorly suited Slope	Low
Netawaka-----	8	Well suited	Poorly suited Slope	Poorly suited Slope	Poorly suited Slope	Moderate Soil reaction
Re: Reading-----	1	Well suited	Well suited	Well suited	Well suited	Low
Sg: Shelby-----	3	Moderately suited Stickiness	Moderately suited Slope Stickiness	Well suited	Well suited	Low
Sm: Shelby-----	3	Moderately suited Stickiness	Moderately suited Slope	Poorly suited Slope	Poorly suited Slope	Low

CONSERVATION TREE AND SHRUB MANAGEMENT
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. Pines and spruces are prone to disease problems. See text for further explanation of ratings in this table.)

Map symbol and soil name	Wind break Group	Suitability for hand planting	Suitability for mechanical planting	Suitability for mechanical site preparation (surface)	Suitability for mechanical site preparation (deep)	Potential for seedling mortality
		Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features
W: Water-----		Not rated	Stickiness Not rated	Not rated	Not rated	Not rated
Wa: Wabash-----	2	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	High Wetness
We: Wamego-----	4	Moderately suited Stickiness	Moderately suited Stickiness Slope	Well suited	Well suited	Low
Wg: Wamego-----	4	Moderately suited Stickiness	Moderately suited Stickiness Slope	Well suited	Well suited	Low
Vinland-----	10	Well suited	Moderately suited Slope	Well suited	Well suited	Low
Wm: Wymore-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	High Wetness
Wn: Wymore-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	High Wetness

ENGINEERING INDEX PROPERTIES
Brown County, Kansas

Engineering Index Properties table gives the engineering classifications and the range of index properties for the layers of each soil in the survey area. Depth to the upper and lower boundaries of each layer is indicated. Texture is given in the standard terms used by the U.S. Department of Agriculture. These terms are defined according to percentages of sand, silt, and clay in the fraction of the soil that is less than 2 millimeters in diameter. Loam, for example, is soil that is 7 to 27 percent clay, 28 to 50 percent silt, and less than 52 percent sand. If the content of particles coarser than sand is 15 percent or more, an appropriate modifier is added, for example, gravelly. Textural terms are defined in the Glossary.

Classification of the soils is determined according to the Unified soil classification system (ASTM, 1998) and the system adopted by the American Association of State Highway and Transportation Officials (AASHTO, 1998). The Unified system classifies soils according to properties that affect their use as construction material. Soils are classified according to particle-size distribution of the fraction less than 3 inches in diameter and according to plasticity index, liquid limit, and organic matter content. Sandy and gravelly soils are identified as GW, GP, GM, GC, SW, SP, SM, and SC; silty and clayey soils as ML, CL, OL, MH, CH, and OH; and highly organic soils as PT. Soils exhibiting engineering properties of two groups can have a dual classification, for example, CL-ML.

The AASHTO system classifies soils according to those properties that affect roadway construction and maintenance. In this system, the fraction of a mineral soil that is less than 3 inches in diameter is classified in one of seven groups from A-1 through A-7 on the basis of particle-size distribution, liquid limit, and plasticity index. Soils in group A-1 are coarse grained and low in content of fines (silt and clay). At the other extreme, soils in group A-7 are fine grained. Highly organic soils are classified in group A-8 on the basis of visual inspection. If laboratory data are available, the A-1, A-2, and A-7 groups are further classified as A-1-a, A-1-b, A-2-4, A-2-5, A-2-6, A-2-7, A-7-5, or A-7-6. As an additional refinement, the suitability of a soil as subgrade material can be indicated by a group index number. Group index numbers range from 0 for the best subgrade material to 20 or higher for the poorest. The AASHTO classification for soils tested, with group index numbers in parentheses, is given in Engineering Index Properties table.

Rock fragments larger than 10 inches in diameter and 3 to 10 inches in diameter are indicated as a percentage of the total soil on a dry-weight basis. The percentages are estimates determined mainly by converting volume percentage in the field to weight percentage. Percentage (of soil particles) passing designated sieves is the percentage of the soil fraction less than 3 inches in diameter based on an oven-dry weight. The sieves, numbers 4, 10, 40, and 200 (USA Standard Series), have openings of 4.76, 2.00, 0.420, and 0.074 millimeters, respectively. Estimates are based on laboratory tests of soils sampled in the survey area and in nearby areas and on estimates made in the field.

Liquid limit and plasticity index (Atterberg limits) indicate the plasticity characteristics of a soil. The estimates are based on test data from the survey area or from nearby areas and on field examination. The estimates of particle-size distribution, liquid limit, and plasticity index are generally rounded to the nearest 5 percent. Thus, if the ranges of gradation and Atterberg limits extend a marginal amount (1 or 2 percentage points) across classification boundaries, the classification in the marginal zone is generally omitted in the table.

ENGINEERING INDEX PROPERTIES--Continued
Brown County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
	In				Pct	Pct					Pct	
Ac:												
Aksarben-----	0-9	Silty clay loam	CL	A-7	0	0	100	100	95-100	90-100	40-50	15-25
	9-13	Silty clay loam	CL	A-7	0	0	100	100	95-100	90-100	40-47	15-22
	13-19	Silty clay loam	CL	A-7	0	0	100	100	95-100	90-100	40-47	15-22
	19-39	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	90-100	47-55	22-27
	39-47	Silty clay loam	CL	A-7	0	0	100	100	95-100	90-100	40-47	15-22
	47-80	Silt loam	CL	A-6, A-7	0	0	100	100	95-100	85-95	35-47	14-22
Ad:												
Aksarben-----	0-6	Silty clay loam	CL	A-7	0	0	100	100	95-100	90-100	36-44	16-22
	6-12	Silty clay loam	CL	A-7	0	0	100	100	95-100	90-100	36-44	16-22
	12-18	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	90-100	51-58	29-35
	18-26	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	90-100	51-58	29-35
	26-34	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	90-100	51-58	29-35
	34-42	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	90-100	51-58	29-35
	42-60	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	90-100	43-51	23-29
	60-80	Silt loam	CH, CL	A-6, A-7	0	0	100	100	95-100	85-95	36-51	17-29
Ae:												
Aksarben-----	0-6	Silty clay loam	CL	A-7	0	0	100	100	95-100	90-100	36-44	16-22
	6-12	Silty clay loam	CL	A-7	0	0	100	100	95-100	90-100	36-44	16-22
	12-18	Silty clay loam	CH	A-7	0	0	100	100	95-100	90-100	51-58	29-35
	18-26	Silty clay loam	CH	A-7	0	0	100	100	95-100	90-100	51-58	29-35
	26-34	Silty clay loam	CH	A-7	0	0	100	100	95-100	90-100	51-58	29-35
	34-42	Silty clay loam	CH	A-7	0	0	100	100	95-100	90-100	51-58	29-35
	42-60	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	90-100	43-51	23-29
	60-80	Silt loam	CH, CL	A-6, A-7	0	0	100	100	95-100	85-95	36-51	17-29
Bs:												
Burchard-----	0-9	Clay loam	CL	A-6, A-7	---	0-5	95-100	95-100	85-95	60-80	35-50	14-24
	9-13	Clay loam	CL	A-7, A-6	---	0-5	95-100	95-100	85-95	60-80	35-50	14-24
	13-19	Clay loam	CL	A-6, A-7	---	0-5	95-100	85-100	75-95	65-80	35-50	20-30
	19-29	Clay loam	CL	A-7, A-6	---	0-5	95-100	85-100	75-95	65-80	35-50	20-30
	29-37	Clay loam	CL	A-7, A-6	---	0-5	95-100	85-100	75-95	65-80	35-50	20-30
	37-60	Clay loam	CL	A-6, A-7	---	0-5	95-100	85-100	75-95	60-80	35-50	15-30
Bx:												
Burchard-----	0-9	Clay loam	CL	A-6, A-7	---	0-5	95-100	95-100	85-95	60-80	35-50	14-24
	9-19	Clay loam	CL	A-6, A-7	---	0-5	95-100	85-100	75-95	65-80	35-50	20-30
	19-29	Clay loam	CL	A-7, A-6	---	0-5	95-100	85-100	75-95	65-80	35-50	20-30
	29-37	Clay loam	CL	A-7, A-6	---	0-5	95-100	85-100	75-95	65-80	35-50	20-30
	37-60	Clay loam	CL	A-6, A-7	---	0-5	95-100	85-100	75-95	60-80	35-50	15-30
Steinauer-----	0-6	Clay loam	CL	A-6, A-7	0	0-5	95-100	95-100	85-100	55-90	30-50	15-25
	6-14	Clay loam	CH, CL	A-6, A-7	0	0-5	95-100	95-100	90-100	70-90	30-55	12-30
	14-80	Clay loam	CH, CL	A-6, A-7	0	0-5	95-100	95-100	90-100	60-75	25-55	10-30
Ch:												
Chase-----	0-9	Silty clay loam	CL	A-7	0	0	100	100	95-100	85-95	40-50	20-30
	9-19	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	19-41	Silty clay	CH	A-7	0	0	100	100	90-100	75-95	50-70	30-45
	41-47	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	75-95	45-62	25-42
	47-80	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-95	40-65	20-40
Co:												
Contrary-----	0-6	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	85-90	30-45	10-20
	6-32	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	85-95	30-45	10-20
	32-80	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-90	30-40	5-15
Ga:												
Grundy-----	0-7	Silt loam	CL	A-6, A-7	0	0	100	100	95-100	90-100	30-45	10-20
	7-14	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	90-100	45-55	25-35
	14-41	Silty clay	CH	A-7	0	0	100	100	95-100	90-100	50-70	30-45
	41-48	Silty clay loam	CH, CH	A-7	0	0	100	100	90-100	90-100	45-60	30-40
	48-80	Silty clay loam	CH, CL	A-7	0	0	100	100	90-100	90-100	40-55	25-35
Ju:												
Judson-----	0-7	Silt loam	CL-ML, CL	A-4, A-6	0	0	100	100	100	95-100	25-35	5-15
	7-25	Silt loam	CL, CL-ML	A-4, A-6	0	0	100	100	100	95-100	25-35	5-15
	25-40	Silty clay loam	CL	A-6, A-7	0	0	100	100	100	95-100	30-50	15-25
	40-50	Silty clay loam	CL	A-6, A-7	0	0	100	100	100	95-100	30-50	15-25
	50-80	Silty clay loam	CL, CL-ML	A-4, A-6, A-7	0	0	100	100	100	95-100	25-50	5-25
Kd:												
Kennebec, CHANNELED-----	0-8	Silt loam	CL	A-6, A-7	0	0	100	100	95-100	90-100	25-45	10-20
	8-18	Silt loam	CL	A-6, A-7	0	0	100	100	95-100	90-100	25-45	10-20
	18-32	Silt loam	CL	A-6, A-7	0	0	100	100	95-100	90-100	25-45	10-20
	32-41	Silt loam	CL	A-6, A-7	0	0	100	100	95-100	90-100	25-45	10-20
	41-54	Silt loam	CL, CL-ML	A-6, A-4	0	0	100	100	95-100	90-100	25-40	5-15
	54-60	Silt loam	CL, CL-ML	A-6, A-4	0	0	100	100	95-100	90-100	25-40	5-15
Ke:												
Kennebec-----	0-8	Silt loam	CL	A-6, A-7	0	0	100	100	95-100	90-100	25-45	10-20
	8-18	Silt loam	CL	A-6, A-7	0	0	100	100	95-100	90-100	25-45	10-20
	18-32	Silt loam	CL	A-6, A-7	0	0	100	100	95-100	90-100	25-45	10-20
	32-41	Silt loam	CL	A-6, A-7	0	0	100	100	95-100	90-100	25-45	10-20
	41-54	Silt loam	CL, CL-ML	A-6, A-4	0	0	100	100	95-100	90-100	25-40	5-15
	54-60	Silt loam	CL, CL-ML	A-6, A-4	0	0	100	100	95-100	90-100	25-40	5-15
Kp:												
Kipson-----	0-8	Silty clay loam	CL	A-6, A-7	0	0-25	80-100	70-100	65-100	60-95	35-45	15-20
	8-19	Silty clay loam	CL	A-6, A-7-6	0	0-25	80-100	75-100	70-100	50-95	30-45	10-20
	19-22	Weathered bedrock			---	---	---	---	---	---	---	---
Sogn-----	0-12	Silty clay loam	CL	A-6, A-7	0	0-10	85-100	85-100	85-100	70-100	35-45	15-20
M-W:												
Miscellaneous Water-----	---	---	---	---	---	---	---	---	---	---	---	---

ENGINEERING INDEX PROPERTIES--Continued
Brown County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
	In				Pct	Pct					Pct	
Ma: Marshall-----	0-10	Silt loam	CL, CL-ML	A-4, A-6	0	0	100	100	100	95-100	25-40	5-15
	10-32	Silty clay loam		A-6, A-7	0	0	100	100	100	95-100	35-50	15-25
	32-80	Silt loam		A-6, A-7	0	0	100	100	100	95-100	35-50	15-25
Mb: Marshall-----	0-6	Silty clay loam	CL	A-6, A-7	---	0	100	100	100	95-100	35-50	15-25
	6-44	Silty clay loam	CL	A-6, A-7	---	0	100	100	100	95-100	35-50	15-25
	44-80	Silt loam	CL	A-6, A-7	---	0	100	100	100	95-100	35-50	15-25
Md: Martin-----	0-6	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	6-12	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	12-53	Silty clay	CH	A-7	0	0	100	100	90-100	75-95	55-70	35-45
	53-80	Silty clay	CH	A-7	0	0	100	100	95-100	75-95	55-70	35-45
Mf: Martin-----	0-6	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	6-12	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	12-53	Silty clay	CH	A-7	0	0	100	100	90-100	75-95	55-70	35-45
	53-80	Silty clay	CH	A-7	0	0	100	100	95-100	75-95	55-70	35-45
Mh: Mayberry-----	0-10	Clay loam	CL	A-6, A-7	0	0	100	95-100	90-100	75-100	35-50	15-25
	10-42	Clay	CH, CL	A-7	0	0	100	90-100	80-100	60-100	45-65	25-40
	42-80	Clay loam	CH, CL	A-6, A-7	0	0	95-100	95-100	85-100	70-95	35-60	15-35
Mk: Monona-----	0-11	Silt loam	CL, ML	A-6, A-7	---	0	100	100	95-100	95-100	35-50	10-25
	11-30	Silt loam	CL, ML	A-6, A-7	---	0	100	100	95-100	95-100	35-50	10-25
	30-80	Silt loam	CL	A-6	---	0	100	100	95-100	95-100	30-40	10-20
Mn: Monona-----	0-6	Silt loam	CL, ML	A-6, A-7	0	0	100	100	95-100	95-100	35-50	10-25
	6-30	Silt loam	CL, ML	A-7, A-6	0	0	100	100	95-100	95-100	35-50	10-25
	30-80	Silt loam	CL	A-6	0	0	100	100	95-100	95-100	30-40	10-20
Mt: Morrill-----	0-6	Loam	CL	A-4, A-6	0	0	95-100	75-100	65-100	50-80	25-40	7-20
	6-12	Loam	CL	A-4, A-6	0	0	95-100	75-100	65-100	50-80	25-40	7-20
	12-43	Loam, sandy clay loam	CL, SC	A-6, A-7-6	0	0	85-100	70-100	55-100	25-80	30-45	11-25
	43-52	Fine sandy loam	SM, SC-SM	A-2, A-4	0	0	90-100	70-100	45-85	25-50	0-25	NP-7
	52-80	Fine sandy loam, loamy fine sand, sand	SM, SC-SM	A-2, A-4	0	0	90-100	70-100	45-85	25-50	0-25	NP-7
Mw: Muscotah-----	0-9	Silt loam	CL	A-6, A-4	0	0	100	95-100	95-100	90-100	28-36	9-16
	9-16	Stratified silt loam to silty clay loam	CL	A-6, A-4	0	0	100	95-100	95-100	90-100	28-39	9-18
	16-30	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	30-39	Silty clay		A-7	0	0	100	100	95-100	85-95	51-66	29-41
	39-61	Silty clay		A-7	0	0	100	100	95-100	85-95	51-66	29-41
	61-70	Silty clay		A-7	0	0	100	100	95-100	85-95	51-66	29-41
	70-80	Silty clay	CH	A-7	0	0	100	100	95-100	85-95	51-66	29-41
My: Muscotah-----	0-9	Silty clay loam	CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	9-16	Silty clay loam	CL, CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	16-23	Silty clay loam		CL	A-7	0	0	100	100	95-100	85-95	36-48
	23-35	Silty clay loam	CH	A-7	0	0	100	100	95-100	85-95	51-66	29-41
	35-44	Silty clay	CH	A-7	0	0	100	100	95-100	85-95	51-66	29-41
	44-60	Silty clay	CH	A-7	0	0	100	100	95-100	85-95	51-66	29-41
	60-70	Silty clay	CH	A-7	0	0	100	100	95-100	85-95	51-66	29-41
	70-80	Silty clay	CH	A-7	0	0	100	100	95-100	85-95	51-66	29-41
No: Nodaway-----	0-7	Silt loam	CL	A-4, A-6	0	0	100	95-100	95-100	90-100	28-36	9-16
	7-14	Stratified silt loam to silty clay loam	CL	A-4, A-6	0	0	100	95-100	95-100	90-100	28-39	9-18
	14-45	Stratified silt loam to silty clay loam	CL	A-4, A-6	0	0	100	95-100	95-100	90-100	28-39	9-18
	45-60	Stratified silt loam to silty clay loam	CL	A-4, A-6	0	0	100	95-100	95-100	90-100	28-39	9-18
Om: Olmitz-----	0-7	Loam	CL	A-6	0	0	100	90-100	85-95	60-80	30-40	11-20
	7-20	Loam	CL	A-6	0	0	100	90-100	85-95	60-80	30-40	11-20
	20-42	Clay loam	CL	A-6, A-7	0	0	100	90-100	85-95	60-80	35-45	15-25
	42-80	Clay loam	CL	A-6, A-7	0	0	100	90-100	85-95	60-80	35-45	15-25
Or: Orthents, Earthen Dam---	---	---	---	---	---	---	---	---	---	---	---	

ENGINEERING INDEX PROPERTIES--Continued
Brown County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
	In				Pct	Pct					Pct	
Pd: Padonia-----	0-11	Silty clay loam	CL	A-7, A-6	0	0	100	100	90-100	80-95	35-45	15-20
	11-22	Silty clay	CH, CL	A-7	0	0	100	100	95-100	90-95	45-60	20-30
	22-32	Silty clay	CH, CL	A-7	0	0	100	100	95-100	90-95	45-60	20-30
	32-37	Silty clay loam	CL	A-7-6	0	0	100	100	90-100	80-95	45-50	20-25
	37-40	Weathered bedrock			---	---	---	---	---	---	---	---
Martin-----	0-6	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	6-12	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	12-53	Silty clay	CH	A-7	0	0	100	100	90-100	75-95	55-70	35-45
	53-80	Silty clay	CH	A-7	0	0	100	100	95-100	75-95	55-70	35-45
Pe: Padonia-----	0-11	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	80-95	35-45	15-20
	11-22	Silty clay	CH, CL	A-7	0	0	100	100	95-100	90-95	45-60	20-30
	22-32	Silty clay	CH, CL	A-7	0	0	100	100	95-100	90-95	45-60	20-30
	32-37	Silty clay loam	CL	A-7-6	0	0	100	100	90-100	80-95	45-50	20-25
	37-41	Weathered bedrock			---	---	---	---	---	---	---	---
Martin-----	0-6	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	6-12	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-95	45-55	25-35
	12-53	Silty clay	CH	A-7	0	0	100	100	90-100	75-95	55-70	35-45
	53-80	Silty clay	CH	A-7	0	0	100	100	95-100	75-95	55-70	35-45
Pf: Padonia-----	0-11	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	80-95	35-45	15-20
	11-22	Silty clay	CH, CL	A-7	0	0	100	100	95-100	90-95	45-60	20-30
	22-32	Silty clay	CH, CL	A-7	0	0	100	100	95-100	90-95	45-60	20-30
	32-37	Silty clay loam	CL	A-7-6	0	0	100	100	90-100	80-95	45-50	20-25
	37-41	Weathered bedrock			---	---	---	---	---	---	---	---
Oska-----	0-5	Silty clay loam	CL	A-6, A-7	0	0	100	100	95-100	90-100	35-50	10-25
	5-11	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	95-100	45-60	20-35
	11-35	Silty clay	CH, CL	A-7	---	0-5	85-100	65-100	60-100	55-100	45-60	20-35
	---	Unweathered bedrock			---	---	---	---	---	---	---	---
Pm: Pawnee-----	0-7	Clay loam	CL	A-6	0	0	95-100	95-100	85-100	70-90	30-40	10-20
	7-12	Clay loam	CL	A-6	0	0	95-100	95-100	85-100	70-90	30-40	10-20
	12-48	Clay	CH	A-7	0	0	95-100	95-100	85-100	70-85	50-70	25-45
	48-80	Clay loam	CH, CL	A-6, A-7	0	0	95-100	95-100	80-100	70-90	35-55	20-40
Pn: Pawnee-----	0-7	Clay loam	CL	A-6	0	0	95-100	95-100	85-100	70-90	30-40	10-20
	7-12	Clay loam	CL	A-6	0	0	95-100	95-100	85-100	70-90	30-40	10-20
	12-48	Clay	CH	A-7	0	0	95-100	95-100	85-100	70-85	50-70	25-45
	48-80	Clay loam	CH, CL	A-6, A-7	0	0	95-100	95-100	80-100	70-90	35-55	20-40
Po: Pawnee-----	0-5	Clay	CH	A-7	0	0	95-100	95-100	85-100	70-85	50-70	25-45
	5-45	Clay	CH	A-7	0	0	95-100	95-100	85-100	70-85	50-70	25-45
	45-80	Clay loam	CH, CL	A-6, A-7	0	0	95-100	95-100	80-100	70-90	35-55	20-40
Pt: Pits, Quarries-	0-60	Variable			---	---	---	---	---	---	---	---
Pw: Pohocco-----	0-5	Silt loam	ML	A-4, A-6, A-7	---	0	100	100	100	95-100	30-45	5-15
	5-39	Silt loam	CL, ML	A-7, A-6	---	0	100	100	100	95-100	35-50	10-25
	39-80	Silt loam	ML	A-4, A-6, A-7	---	0	100	100	100	95-100	30-45	5-15
Netawaka-----	0-6	Silt loam	ML	A-4	0	0	100	100	100	92-98	30-35	7-9
	6-9	Silt loam	CL, CL-ML, ML	A-4	0	0	100	100	100	92-98	25-35	6-9
	9-80	Silt loam	CL-ML, ML, CL	A-4	0	0	100	100	100	92-98	25-35	6-9
Px: Pohocco-----	0-5	Silt loam	ML	A-4, A-6, A-7	---	0	100	100	100	95-100	30-45	5-15
	5-39	Silt loam	CL, ML	A-6, A-7	---	0	100	100	100	95-100	35-50	10-25
	39-80	Silt loam	ML	A-4, A-6, A-7	---	0	100	100	100	95-100	30-45	5-15
Netawaka-----	0-6	Silt loam	CL	A-4	0	0	100	100	100	92-98	30-35	7-9
	6-9	Silt loam	CL, CL-ML, ML	A-4	0	0	100	100	100	92-98	25-35	6-9
	9-80	Silt loam	ML, CL-ML, CL	A-4	0	0	100	100	100	92-98	25-35	6-9
Re: Reading-----	0-18	Silt loam	CL	A-6	0	0	100	100	90-100	80-90	30-35	10-15
	18-48	Silty clay loam	CL	A-6, A-7	0	0	100	100	95-100	85-95	35-45	15-20
	48-54	Silty clay loam	CL	A-6, A-7	0	0	100	100	95-100	85-95	35-45	15-20
	54-80	Silty clay loam	CL	A-7	0	0	100	100	95-100	80-95	40-50	20-30
Sg: Shelby-----	0-13	Clay loam	CL	A-6, A-7	0	0	90-95	85-95	75-90	55-70	35-45	15-25
	13-36	Clay loam	CL	A-6, A-7	0	0-5	90-95	85-95	75-90	55-70	30-45	15-25
	36-48	Clay loam	CL	A-6, A-7	0	0-5	90-95	85-95	75-90	55-70	30-45	15-25
	48-80	Clay loam	CL	A-6, A-7	0	0-5	90-95	85-95	75-90	55-70	30-45	15-25
Sm: Shelby-----	0-8	Clay loam	CL	A-6, A-7	0	0	90-95	85-95	75-90	55-70	35-45	15-25
	8-45	Clay loam	CL	A-6, A-7	0	0-5	90-95	85-95	75-90	55-70	30-45	15-25
	45-80	Clay loam	CL	A-6, A-7	0	0-5	90-95	85-95	75-90	55-70	30-45	15-25
W: Water-----	---	---	---	---	---	---	---	---	---	---	---	---
Wa: Wabash-----	0-15	Silty clay	CH	A-7	0	0	100	100	100	95-100	50-75	30-50
	15-80	Silty clay	CH	A-7	0	0	100	100	100	95-100	52-78	30-55

ENGINEERING INDEX PROPERTIES--Continued
Brown County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
					Pct	Pct						
We: Wamego-----	In											
	0-9	Silty clay loam	CL	A-6	0	0	100	100	95-100	85-95	35-40	15-20
	9-20	Silty clay loam	CL	A-7	0	0	100	85-100	80-100	75-95	45-50	20-25
	20-25	Silty clay loam	CL	A-7	0	0	100	85-100	80-100	75-95	45-50	20-25
	25-36	Weathered bedrock			---	---	---	---	---	---	---	---
Wg: Wamego-----	0-9	Silty clay loam	CL	A-6	0	0	100	100	95-100	85-95	35-40	15-20
	9-20	Silty clay loam	CL	A-7	0	0	100	85-100	80-100	75-95	45-50	20-25
	20-25	Silty clay loam	CL	A-7	0	0	100	85-100	80-100	75-95	45-50	20-25
	25-36	Weathered bedrock			---	---	---	---	---	---	---	---
Vinland-----	0-8	Silty clay loam	CL	A-6, A-7	0	0-5	80-100	75-100	70-100	65-95	35-45	15-20
	8-12	Silty clay loam	CL, SC	A-6, A-7	0	0	80-100	75-100	50-100	35-95	25-45	10-20
	12-19	Channery silty clay loam	CL, SC	A-6, A-7	0	0	80-100	75-100	50-100	35-95	25-45	10-20
	19-23	Weathered bedrock			---	---	---	---	---	---	---	---
Wm: Wymore-----	0-7	Silty clay loam	CH, CL, MH, ML	A-6, A-7	0	0	100	100	95-100	95-100	36-48	16-25
	7-12	Silty clay	CH, CL, MH, ML	A-6, A-7	0	0	100	100	95-100	95-100	39-53	18-29
	12-22	Silty clay	CH	A-7	0	0	100	100	95-100	95-100	58-71	35-45
	22-39	Silty clay	CH	A-7	0	0	100	100	95-100	95-100	58-71	35-45
	39-47	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-100	43-56	23-33
	47-80	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-100	43-56	23-33
Wn: Wymore-----	0-10	Silty clay loam	CL	A-6, A-7	0	0	100	100	95-100	95-100	36-48	16-25
	10-18	Silty clay	CH	A-7	0	0	100	100	95-100	95-100	58-71	35-45
	18-32	Silty clay	CH	A-7	0	0	100	100	95-100	95-100	58-71	35-45
	32-43	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-100	43-56	23-33
	43-80	Silty clay loam	CH, CL	A-7	0	0	100	100	95-100	85-100	43-56	23-33

Physical Properties table shows estimates of some physical characteristics and features that affect soil behavior. These estimates are given for the layers of each soil in the survey area. The estimates are based on field observations and on test data for these and similar soils.

Depth to the upper and lower boundaries of each layer is indicated.

Particle size is the effective diameter of a soil particle as measured by sedimentation, sieving, or micrometric methods. Particle sizes are expressed as classes with specific effective diameter class limits. The broad classes are sand, silt, and clay, ranging from the larger to the smaller.

Sand as a soil separate consists of mineral soil particles that are 0.05 millimeter to 2 millimeters in diameter. In this table, the estimated sand content of each soil layer is given as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter.

Silt as a soil separate consists of mineral soil particles that are 0.002 to 0.05 millimeter in diameter. In this table, the estimated silt content of each soil layer is given as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter.

Clay as a soil separate consists of mineral soil particles that are less than 0.002 millimeter in diameter. In this table, the estimated clay content of each soil layer is given as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter.

The content of sand, silt, and clay affects the physical behavior of a soil. Particle size is important for engineering and agronomic interpretations, for determination of soil hydrologic qualities, and for soil classification.

The amount and kind of clay affect the fertility and physical condition of the soil and the ability of the soil to adsorb cations and to retain moisture. They influence shrink-swell potential, permeability, plasticity, the ease of soil dispersion, and other soil properties. The amount and kind of clay in a soil also affect tillage and earth moving operations.

Moist bulk density is the weight of soil (oven-dry) per unit volume. Volume is measured when the soil is at field moisture capacity, that is, the moisture content at 1/3- or 1/10-bar (33kPa or 10kPa) moisture tension. Weight is determined after the soil is dried at 105 degrees C. In the table, the estimated moist bulk density of each soil horizon is expressed in grams per cubic centimeter of soil material that is less than 2 millimeters in diameter. Bulk density data are used to compute shrink-swell potential, available water capacity, total pore space, and other soil properties. The moist bulk density of a soil indicates the pore space available for water and roots. Depending on soil texture, a bulk density of more than 1.4 can restrict water storage and root penetration. Moist bulk density is influenced by texture, kind of clay, content of organic matter, and soil structure.

Permeability ($K \rightarrow \text{sat}$) refers to the ability of a soil to transmit water or air. The term "permeability," as used in soil surveys, indicates saturated hydraulic conductivity ($K \rightarrow \text{sat}$). The estimates in the table indicate the rate of water movement, in inches per hour, when the soil is saturated. They are based on soil characteristics observed in the field, particularly structure, porosity, and texture. Permeability is considered in the design of soil drainage systems and septic tank absorption fields.

Available water capacity refers to the quantity of water that the soil is capable of storing for use by plants. The capacity for water storage is given in inches of water per inch of soil for each soil layer. The capacity varies, depending on soil properties that affect retention of water. The most important properties are the content of organic matter, soil texture, bulk density, and soil structure. Available water capacity is an important factor in the choice of plants or crops to be grown and in the design and management of irrigation systems. Available water capacity is not an estimate of the quantity of water actually available to plants at any given time.

Linear extensibility refers to the change in length of an unconfined clod as moisture content is decreased from a moist to a dry state. It is an expression of the volume change between the water content of the clod at 1/3- or 1/10-bar tension (33kPa or 10kPa tension) and oven dryness. The volume change is reported in the table as percent change for the whole soil. Volume change is influenced by the amount and type of clay minerals in the soil.

Linear extensibility is used to determine the shrink-swell potential of soils. The shrink-swell potential is low if the soil has a linear extensibility of less than 3 percent; moderate if 3 to 6 percent; high if 6 to 9 percent; and very high if more than 9 percent. If the linear extensibility is more than 3, shrinking and swelling can cause damage to buildings, roads, and other structures and to plant roots. Special design commonly is needed.

Organic matter is the plant and animal residue in the soil at various stages of decomposition. In Physical Properties table, the estimated content of organic matter is expressed as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter. The content of organic matter in a soil can be maintained by returning crop residue to the soil. Organic matter has a positive effect on available water capacity, water infiltration, soil organism activity, and tilth. It is a source of nitrogen and other nutrients for crops and soil organisms.

Erosion factors are shown in the Physical Properties table as the K factor (K_w and K_f) and the T factor. Erosion factor K indicates the susceptibility of a soil to sheet and rill erosion by water. Factor K is one of six factors used in the Universal Soil Loss Equation (USLE) and the Revised Universal Soil Loss Equation (RUSLE) to predict the average annual rate of soil loss by sheet and rill erosion in tons per acre per year. The estimates are based primarily on percentage of silt, sand, and organic matter and on soil structure and permeability. Values of K range from 0.02 to 0.69. Other factors being equal, the higher the value, the more susceptible the soil is to sheet and rill erosion by water.

Erosion factor K_w indicates the erodibility of the whole soil. The estimates are modified by the presence of rock fragments.

Erosion factor K_f indicates the erodibility of the fine-earth fraction, or the material less than 2 millimeters in size.

Erosion factor T is an estimate of the maximum average annual rate of soil erosion by wind or water that can occur without affecting crop productivity over a sustained period. The rate is in tons per acre per year.

Wind erodibility groups are made up of soils that have similar properties affecting their susceptibility to

wind erosion in cultivated areas. The soils assigned to group 1 are the most susceptible to wind erosion, and those assigned to group 8 are the least susceptible. The groups are as follows:

1. Coarse sands, sands, fine sands, and very fine sands.
2. Loamy coarse sands, loamy sands, loamy fine sands, loamy very fine sands, ash material, and sapric soil material.
3. Coarse sandy loams, sandy loams, fine sandy loams, and very fine sandy loams.
- 4L. Calcareous loams, silt loams, clay loams, and silty clay loams.
4. Clays, silty clays, noncalcareous clay loams, and silty clay loams that are more than 35 percent clay.
5. Noncalcareous loams and silt loams that are less than 20 percent clay and sandy clay loams, sandy clays, and hemic soil material.
6. Noncalcareous loams and silt loams that are more than 20 percent clay and noncalcareous clay loams that are less than 35 percent clay.
7. Silts, noncalcareous silty clay loams that are less than 35 percent clay, and fibric soil material.
8. Soils that are not subject to wind erosion because of coarse fragments on the surface or because of surface wetness.

Wind erodibility index is a numerical value indicating the susceptibility of soil to wind erosion, or the tons per acre per year that can be expected to be lost to wind erosion. There is a close correlation between wind erosion and the texture of the surface layer, the size and durability of surface clods, rock fragments, organic matter, and a calcareous reaction. Soil moisture and frozen soil layers also influence wind erosion.

Explanation of Wind Erodibility Groups

Soil erodibility by wind is directly related to the percentage of dry non-erodible surface soil aggregates larger than 0.84 mm in diameter. From this percentage, the wind erodibility index (I-factor) is determined. The I-factor is an expression of the stability of these soil aggregates against breakdown by tillage and abrasion from wind erosion. Soils are placed in Wind Erodibility Groups (WEG) having similar percentages of dry soil aggregates larger than 0.84 mm as shown in the following table.

WEG	Properties of Soil Surface Layer	Dry Soil Aggregates >0.84mm Percent	Wind Erodibility Index T/Ac/Yr (I)
1	Very fine sand, fine sand, sand, or coarse sand	1 2 3 5 7	310 1/ 250 220 180 160
2	Loamy very fine sand, loamy fine sand, loamy sand, loamy coarse sand, organic soil materials.	10	134
3	Very fine sandy loam, fine sandy loam, sandy loam, or coarse sandy loam.	25	86
4	Clay, silty clay, non-calcareous clay loam, or silty clay loam with >35 percent clay content.	25	86
4L	Calcareous 2/ loam, silt loam, clay loam, or silty clay loam.	25	86
5	Non-calcareous loam and silt loam with <20 percent clay content, or sandy clay loam, sandy clay, and hemic 3/ organic soil materials.	40	56
6	Non-calcareous loam and silt loam with >20 percent clay content, or non-calcareous clay loam with <35 percent clay content.	45	48
7	Silt, non-calcareous silty clay loam with >35 percent clay content and fibric 3/ organic soil material.	50	38
8	Soils not suitable for cultivation due to coarse fragments or wetness; wind erosion is not a problem.	--	0

1/ The "I" values for WEG 1 vary from 160 for coarse sands to 310 for very fine sands. Use an "I" of 220 as an average figure. For coarser sand that has gravel, use a lower figure. For a soil that has no gravel and very fine sand, use a higher figure. (Modification for coarse fragments is preparation.)

2/ Calcareous is a strongly or violently effervescent reaction to cold dilute (1N) HCL.

3/ See Soil Taxonomy for definition.

PHYSICAL PROPERTIES OF THE SOILS--Continued
Brown County, Kansas: Update

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permea- bility (Ksat)	Available water capacity	Linear extensi- bility	Organic matter	Erosion factors			Wind erodi- bility group	Wind erodi- bility index
										K	Kf	T		
	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
Ac:														
Aksarben----	0-9	2-8	50-70	27-35	1.35-1.55	0.60-2.00	0.17-0.23	3.0-5.9	2.0-4.0	.32	.32	5	7	38
	9-13	2-8	50-70	27-35	1.35-1.55	0.60-2.00	0.18-0.20	3.0-5.9	2.0-4.0	.32	.32			
	13-19	2-8	40-70	27-35	1.35-1.55	0.20-0.60	0.16-0.18	3.0-5.9	0.0-1.0	.43	.43			
	19-39	2-8	40-70	35-42	1.35-1.55	0.20-0.60	0.16-0.18	3.0-5.9	0.0-1.0	.43	.43			
	39-47	2-8	40-70	27-35	1.35-1.55	0.20-0.60	0.16-0.18	3.0-5.9	0.0-0.5	.43	.43			
	47-80	2-8	50-70	24-32	1.40-1.60	0.60-2.00	0.18-0.20	3.0-5.9	0.0-0.5	.43	.43			
Ad:														
Aksarben----	0-6	2-8	50-70	27-35	1.30-1.40	0.60-2.00	0.17-0.23	3.0-5.9	2.0-4.0	.32	.32	5	7	38
	6-12	2-8	50-70	27-35	1.30-1.40	0.60-2.00	0.17-0.23	3.0-5.9	2.0-4.0	.32	.32			
	12-18	2-8	40-70	35-42	1.20-1.45	0.20-0.60	0.16-0.18	3.0-5.9	0.0-1.0	.43	.43			
	18-26	2-8	40-70	35-42	1.20-1.45	0.20-0.60	0.16-0.18	3.0-5.9	0.0-1.0	.43	.43			
	26-34	2-8	40-70	35-42	1.20-1.45	0.20-0.60	0.16-0.18	3.0-5.9	0.0-1.0	.43	.43			
	34-42	2-8	40-70	35-42	1.20-1.45	0.20-0.60	0.16-0.18	3.0-5.9	0.0-1.0	.43	.43			
	42-60	2-8	50-70	27-35	1.30-1.40	0.60-2.00	0.18-0.20	3.0-5.9	0.0-0.5	.43	.43			
	60-80	2-8	50-80	24-32	1.30-1.40	0.60-2.00	0.18-0.20	3.0-5.9	0.0-0.5	.43	.43			
Ae:														
Aksarben----	0-6	2-8	50-70	27-35	1.30-1.40	0.60-2.00	0.17-0.23	3.0-5.9	2.0-4.0	.32	.32	5	7	38
	6-12	2-8	50-70	27-35	1.30-1.40	0.60-2.00	0.17-0.23	3.0-5.9	2.0-4.0	.32	.32			
	12-18	2-8	40-70	35-42	1.20-1.45	0.20-0.60	0.16-0.18	3.0-5.9	0.0-1.0	.43	.43			
	18-26	2-8	40-70	35-42	1.20-1.45	0.20-0.60	0.16-0.18	3.0-5.9	0.0-1.0	.43	.43			
	26-34	2-8	40-70	35-42	1.20-1.45	0.20-0.60	0.16-0.18	3.0-5.9	0.0-1.0	.43	.43			
	34-42	2-8	40-70	35-42	1.20-1.45	0.20-0.60	0.16-0.18	3.0-5.9	0.0-1.0	.43	.43			
	42-60	2-8	50-70	27-35	1.30-1.40	0.60-2.00	0.18-0.20	3.0-5.9	0.0-0.5	.43	.43			
	60-80	2-8	50-80	24-32	1.30-1.40	0.60-2.00	0.18-0.20	3.0-5.9	0.0-0.5	.43	.43			
Bs:														
Burchard----	0-9	20-45	25-60	20-32	1.15-1.40	0.20-0.60	0.17-0.19	3.0-5.9	2.0-4.0	.28	.28	5	6	48
	9-13	20-45	25-60	20-35	1.20-1.50	0.20-0.60	0.17-0.19	3.0-5.9	2.0-3.0	.28	.28			
	13-19	20-45	20-50	27-38	1.30-1.50	0.20-0.60	0.15-0.17	3.0-5.9	0.5-1.0	.37	.37			
	19-29	20-45	20-50	27-38	1.30-1.50	0.20-0.60	0.15-0.17	3.0-6.0	0.5-1.0	.37	.37			
	29-37	30-45	30-45	20-30	1.50-1.60	0.20-0.60	0.15-0.17	3.0-5.9	0.2-0.8	.37	.37			
	37-60	30-45	30-45	20-30	1.50-1.70	0.20-0.60	0.14-0.16	3.0-5.9	0.0-0.5	.37	.37			
Bx:														
Burchard----	0-9	20-45	25-60	20-32	1.15-1.40	0.20-0.60	0.17-0.19	3.0-5.9	2.0-4.0	.28	.28	5	6	48
	9-19	20-45	20-50	27-38	1.30-1.50	0.20-0.60	0.15-0.17	3.0-5.9	0.5-1.5	.37	.37			
	19-29	20-45	20-50	27-38	1.30-1.50	0.20-0.60	0.15-0.17	3.0-6.0	0.5-1.0	.37	.37			
	29-37	30-45	30-45	20-30	1.50-1.60	0.20-0.60	0.15-0.17	3.0-5.9	0.2-0.8	.37	.37			
	37-60	30-45	30-45	20-30	1.50-1.70	0.20-0.60	0.14-0.16	3.0-5.9	0.0-0.5	.37	.37			
Steinauer----	0-6	20-45	30-50	25-35	1.20-1.35	0.20-0.60	0.19-0.22	3.0-5.9	0.5-2.0	.32	.32	5	4L	86
	6-14	20-45	30-50	27-35	1.30-1.50	0.20-0.60	0.17-0.19	3.0-5.9	0.5-1.0	.37	.37			
	14-80	20-45	30-50	18-35	1.30-1.65	0.20-0.60	0.16-0.19	3.0-5.9	0.0-0.5	.37	.37			
Ch:														
Chase-----	0-9	2-15	45-70	27-35	1.30-1.40	0.20-0.60	0.21-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	9-19	2-15	45-70	27-40	1.30-1.40	0.20-0.60	0.18-0.20	3.0-5.9	2.0-4.0	.37	.37			
	19-41	2-15	35-60	35-55	1.35-1.45	0.06-0.20	0.11-0.19	6.0-8.9	1.0-3.0	.28	.28			
	41-47	2-15	40-60	27-55	1.35-1.45	0.06-0.20	0.11-0.18	6.0-8.9	0.5-1.0	.28	.28			
	47-80	2-15	40-60	27-50	1.35-1.45	0.06-0.20	0.11-0.18	6.0-8.9	0.5-1.0	.28	.28			
Co:														
Contrary-----	0-6	2-8	60-80	27-35	1.30-1.40	0.60-2.00	0.18-0.20	3.0-5.9	0.5-2.0	.32	.32	5	7	38
	6-32	2-8	60-80	20-30	1.30-1.40	0.60-2.00	0.20-0.22	0.0-2.9	0.5-1.0	.43	.43			
	32-80	2-8	60-80	18-27	1.20-1.40	0.60-2.00	0.20-0.22	0.0-2.9	0.0-0.5	.43	.43			
Ga:														
Grundy-----	0-7	2-8	70-85	12-27	1.35-1.50	0.60-2.00	0.22-0.24	3.0-5.9	2.0-4.0	.37	.37	5	6	48
	7-14	2-8	55-70	32-45	1.35-1.45	0.20-0.60	0.18-0.20	6.0-8.9	1.0-3.0	.37	.37			
	14-41	2-8	42-60	40-50	1.30-1.40	0.06-0.20	0.11-0.13	6.0-8.9	0.0-1.0	.37	.37			
	41-48	2-8	60-70	27-35	1.35-1.50	0.06-0.20	0.14-0.16	6.0-8.9	0.0-0.5	.37	.37			
	48-80	2-8	60-70	27-35	1.35-1.50	0.06-0.20	0.18-0.20	6.0-8.9	0.0-0.5	.37	.37			
Ju:														
Judson-----	0-7	2-8	70-80	18-27	1.30-1.35	0.60-2.00	0.21-0.23	0.0-2.9	4.0-5.0	.28	.28	5	6	48
	7-25	2-8	65-80	18-30	1.30-1.35	0.60-2.00	0.21-0.23	0.0-2.9	4.0-5.0	.28	.28			
	25-40	2-8	60-70	30-35	1.35-1.45	0.60-2.00	0.21-0.23	3.0-5.9	2.0-3.0	.43	.43			
	40-50	2-8	60-70	30-35	1.35-1.45	0.60-2.00	0.21-0.23	3.0-5.9	2.0-3.0	.43	.43			
	50-80	2-8	65-75	25-32	1.35-1.45	0.60-2.00	0.21-0.23	3.0-5.9	0.0-1.0	.43	.43			
Kd:														
Kennebec, CHANNELED---	0-8	2-8	65-75	22-27	1.25-1.35	0.60-2.00	0.22-0.24	3.0-6.0	2.3-6.0	.28	.28	5	6	48
	8-18	2-8	65-75	22-27	1.25-1.35	0.60-2.00	0.22-0.24	3.0-6.0	2.1-6.0	.28	.28			
	18-32	2-8	65-75	22-27	1.25-1.35	0.60-2.00	0.22-0.24	3.0-6.0	2.1-5.0	.28	.28			
	32-41	2-8	65-75	22-27	1.25-1.35	0.60-2.00	0.22-0.24	3.0-6.0	2.1-5.0	.28	.28			
	41-54	2-12	60-75	24-28	1.35-1.40	0.60-2.00	0.20-0.22	3.0-6.0	1.0-3.0	.43	.43			
	54-60	2-12	60-75	24-28	1.35-1.40	0.60-2.00	0.20-0.22	3.0-6.0	1.0-2.5	.43	.43			
Ke:														
Kennebec-----	0-8	2-8	65-75	22-27	1.25-1.35	0.60-2.00	0.22-0.24	3.0-6.0	5.0-6.0	.28	.28	5	6	48
	8-18	2-8	65-75	22-27	1.25-1.35	0.60-2.00	0.22-0.24	3.0-6.0	5.0-6.0	.28	.28			
	18-32	2-8	65-75	22-27	1.25-1.35	0.60-2.00	0.22-0.24	3.0-6.0	5.0-6.0	.28	.28			
	32-41	2-8	65-75	22-27	1.25-1.35	0.60-2.00	0.22-0.24	3.0-6.0	5.0-6.0	.28	.28			
	41-54	2-12	60-75	24-28	1.35-1.40	0.60-2.00	0.20-0.22	3.0-6.0	1.0-2.0	.43	.43			
	54-60	2-12	60-75	24-28	1.35-1.40	0.60-2.00	0.20-0.22	3.0-6.0	1.0-2.0	.43	.43			
Kp:														
Kipson-----	0-8	2-18	45-70	25-35	1.30-1.40	0.60-2.00	0.17-0.20	3.0-5.9	1.0-3.0	.32	.49	2	4L	86
	8-19	2-20	45-75	18-35	1.35-1.50	0.60-2.00	0.15-0.20	3.0-5.9	0.5-1.0	.32	.43			
	19-22	---	---	---	---	0.00-0.00	---	---	---	---	---			
Sogn-----	0-12	2-20	55-75	27-35	1.35-1.45	0.60-2.00	0.21-0.23	3.0-5.9	1.0-3.0	.32	.37	1	4L	86
	---	---	---	---	---	---	---	---	---	---	---			

PHYSICAL PROPERTIES OF THE SOILS--Continued
Brown County, Kansas: Update

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permeability (Ksat)	Available water capacity	Linear extensibility	Organic matter	Erosion factors			Wind erodibility group	Wind erodibility index
										K	Kf	T		
M-W: Miscellaneous Water-----	---	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
Ma: Marshall-----	0-10 10-32 32-80	2-8 2-8 2-8	65-75 60-75 65-80	25-27 27-34 22-30	1.25-1.30 1.30-1.35 1.30-1.40	0.60-2.00 0.60-2.00 0.60-2.00	0.21-0.23 0.18-0.20 0.20-0.22	0.0-2.9 3.0-5.9 3.0-5.9	3.0-4.0 0.0-1.0 0.0-0.5	.28 .43 .43	.28 .43 .43	5	6	48
Mb: Marshall-----	0-6 6-44 44-80	2-8 2-8 2-8	65-75 60-75 65-80	27-34 27-34 22-30	1.25-1.30 1.30-1.35 1.30-1.40	0.60-2.00 0.60-2.00 0.60-2.00	0.21-0.23 0.18-0.20 0.20-0.22	3.0-5.9 3.0-5.9 3.0-5.9	3.0-4.0 0.0-1.0 0.0-0.5	.28 .43 .43	.28 .43 .43	5	7	38
Md: Martin-----	0-6 6-12 12-53 53-80	2-8 2-8 2-8 2-8	60-70 55-70 38-60 38-65	27-40 27-40 40-55 27-40	1.35-1.45 1.35-1.45 1.20-1.30 1.20-1.30	0.20-0.60 0.20-0.60 0.06-0.20 0.06-0.20	0.21-0.23 0.18-0.20 0.12-0.18 0.12-0.18	3.0-5.9 6.0-8.9 6.0-8.9 6.0-8.9	2.0-4.0 0.5-2.0 0.5-1.0 0.0-0.5	.37 .28 .28 .28	.37 .28 .28 .28	5	7	38
Mf: Martin-----	0-6 6-12 12-53 53-80	2-8 2-8 2-8 2-8	60-70 55-70 35-60 35-60	27-40 27-40 40-55 27-40	1.35-1.45 1.35-1.45 1.20-1.30 1.20-1.30	0.20-0.60 0.20-0.60 0.06-0.20 0.06-0.20	0.21-0.23 0.18-0.20 0.12-0.18 0.12-0.18	3.0-5.9 6.0-8.9 6.0-8.9 6.0-8.9	2.0-4.0 0.5-2.0 0.5-1.0 0.0-0.5	.37 .28 .28 .28	.37 .28 .28 .28	5	7	38
Mh: Mayberry-----	0-10 10-42 42-80	15-40 20-50 35-55	25-45 10-35 10-45	27-40 40-50 18-45	1.40-1.50 1.40-1.65 1.40-1.50	0.20-0.60 0.06-0.20 0.06-0.20	0.17-0.23 0.10-0.11 0.09-0.16	3.0-5.9 6.0-8.9 3.0-5.9	1.0-3.0 0.5-1.0 0.0-0.5	.37 .37 .37	.37 .37 .37	5	6	48
Mk: Monona-----	0-11 11-30 30-80	2-8 2-8 2-8	65-80 65-80 65-80	20-27 24-28 18-24	1.25-1.30 1.30-1.35 1.35-1.40	0.60-2.00 0.60-2.00 0.60-2.00	0.22-0.24 0.20-0.22 0.20-0.22	3.0-5.9 3.0-5.9 0.0-2.9	3.0-4.0 0.5-1.0 0.0-0.5	.28 .43 .43	.28 .43 .43	5	6	48
Mn: Monona-----	0-6 6-30 30-80	2-8 2-8 2-8	65-80 65-80 65-80	20-27 24-28 18-24	1.25-1.30 1.30-1.35 1.35-1.40	0.60-2.00 0.60-2.00 0.60-2.00	0.22-0.24 0.20-0.22 0.20-0.22	3.0-5.9 3.0-5.9 0.0-2.9	2.0-3.0 0.5-1.0 0.0-0.5	.32 .43 .43	.32 .43 .43	5	6	48
Mt: Morrill-----	0-6 6-12 12-43 43-52 52-80	25-45 25-45 25-60 40-65 40-92	20-50 20-40 15-35 10-32 2-32	15-28 25-35 25-35 8-28 5-28	1.30-1.40 1.30-1.40 1.35-1.45 1.35-1.45 1.35-1.45	0.60-2.00 0.60-2.00 0.20-0.60 0.60-6.00 0.60-20.00	0.14-0.21 0.14-0.21 0.15-0.19 0.08-0.15 0.05-0.15	0.0-2.9 0.0-2.9 3.0-6.0 0.0-2.9 0.0-2.9	1.0-3.0 1.0-2.0 0.5-1.0 0.0-0.5 0.0-0.5	.28 .28 .32 .20 .15	.28 .28 .32 .20 .15	5	6	48
Mw: Muscotah-----	0-9 9-16 16-30 30-39 39-61 61-70 70-80	2-10 2-10 2-8 2-8 2-8 2-8 2-8	65-80 60-80 40-70 40-70 35-50 40-70 40-70	18-27 18-30 27-40 27-40 35-50 1.20-1.30 1.20-1.30	1.25-1.35 1.25-1.35 1.30-1.40 1.30-1.40 1.20-1.30 1.20-1.30 1.20-1.30	0.60-2.00 0.60-2.00 0.20-0.60 0.20-0.60 0.06-0.20 0.06-0.20 0.00-0.06	0.20-0.23 0.20-0.23 0.21-0.23 0.11-0.20 0.11-0.20 0.10-0.20 0.10-0.20	0.0-2.9 3.0-5.9 3.0-5.9 6.0-8.9 6.0-8.9 6.0-8.9 6.0-8.9	2.0-3.0 0.2-0.8 2.0-4.0 2.0-4.0 2.0-3.0 1.0-2.0 0.8-2.0	.32 .43 .43 .28 .28 .28 .28	.32 .43 .43 .28 .28 .28 .28	5	6	48
My: Muscotah-----	0-9 9-16 16-23 23-35 35-44 44-60 60-70 70-80	2-10 2-8 2-8 2-8 2-8 2-8 2-8 2-8	65-80 40-70 40-70 40-70 35-50 40-70 40-70 40-70	27-40 27-40 27-40 35-50 35-50 35-50 35-50 35-50	1.30-1.40 1.30-1.40 1.30-1.40 1.20-1.30 1.20-1.30 1.20-1.30 1.20-1.30 1.20-1.30	0.20-0.60 0.20-0.60 0.20-0.60 0.06-0.20 0.06-0.20 0.06-0.20 0.00-0.06 0.00-0.06	0.21-0.23 0.21-0.23 0.21-0.23 0.11-0.20 0.11-0.20 0.11-0.20 0.10-0.20 0.10-0.20	3.0-5.9 3.0-5.9 3.0-5.9 6.0-8.9 6.0-8.9 6.0-8.9 6.0-8.9 6.0-8.9	2.0-4.0 2.0-4.0 2.0-4.0 2.0-4.0 2.0-4.0 2.0-3.0 1.0-2.0 0.8-2.0	.37 .37 .37 .28 .28 .28 .28 .28	.37 .37 .37 .28 .28 .28 .28 .28	5	6	48
No: Nodaway-----	0-7 7-14 14-45 45-60	2-10 2-10 2-10 2-10	65-80 60-80 60-80 60-80	18-27 18-30 18-30 18-30	1.25-1.35 1.25-1.35 1.25-1.35 1.25-1.35	0.60-2.00 0.60-2.00 0.60-2.00 0.60-2.00	0.20-0.23 0.20-0.23 0.20-0.23 0.20-0.23	0.0-2.9 3.0-5.9 3.0-5.9 3.0-5.9	2.0-3.0 0.0-0.5 0.0-0.5 0.0-0.5	.32 .43 .43 .43	.32 .43 .43 .43	5	6	48
Om: Olmitz-----	0-7 7-20 20-42 42-80	25-45 20-45 20-45 20-45	30-50 30-50 30-50 30-50	20-27 24-30 27-34 27-34	1.40-1.45 1.40-1.45 1.45-1.55 1.45-1.55	0.60-2.00 0.60-2.00 0.60-2.00 0.60-2.00	0.19-0.21 0.19-0.21 0.15-0.17 0.15-0.17	3.0-5.9 3.0-5.9 3.0-5.9 3.0-5.9	3.0-4.0 2.0-3.0 1.0-2.0 1.0-2.0	.24 .28 .28 .28	.24 .28 .28 .28	5	6	48
Or: Orthents, Earthen Dam-Pd: Padonia-----	0-11 11-22 22-32 32-37 37-40	2-10 2-10 2-10 2-10 2-10	50-70 35-60 35-60 45-60 45-60	27-35 35-50 35-50 35-40 35-40	1.30-1.40 1.20-1.40 1.20-1.40 1.30-1.40 1.30-1.40	0.60-2.00 0.06-0.20 0.06-0.20 0.20-0.60 0.00-0.00	0.21-0.23 0.11-0.18 0.11-0.18 0.18-0.20 ---	3.0-5.9 6.0-8.9 6.0-8.9 3.0-5.9 ---	2.0-4.0 1.0-2.0 0.5-1.0 0.0-0.5 ---	.37 .32 .32 .43 ---	.37 .32 .32 .43 ---	3	7	38
Martin-----	0-6 6-12 12-53 53-80	2-8 2-8 2-8 2-8	60-70 55-70 35-60 35-60	27-40 27-40 40-55 27-40	1.35-1.45 1.35-1.45 1.20-1.30 1.20-1.30	0.20-0.60 0.20-0.60 0.06-0.20 0.06-0.20	0.21-0.23 0.18-0.20 0.12-0.18 0.12-0.18	3.0-5.9 6.0-8.9 6.0-8.9 6.0-8.9	2.0-4.0 0.5-2.0 0.5-1.0 0.0-0.5	.37 .28 .28 .28	.37 .28 .28 .28	5	7	38

PHYSICAL PROPERTIES OF THE SOILS--Continued
Brown County, Kansas: Update

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permea- bility (Ksat)	Available water capacity	Linear extensi- bility	Organic matter	Erosion factors			Wind erodi- bility group	Wind erodi- bility index
										K	Kf	T		
Pe:	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
Padonia-----	0-11	2-10	50-70	27-35	1.30-1.40	0.60-2.00	0.21-0.23	3.0-5.9	2.0-4.0	.37	.37	3	7	38
	11-22	2-10	35-60	35-50	1.20-1.40	0.06-0.20	0.11-0.18	6.0-8.9	1.0-2.0	.32	.32			
	22-32	2-10	35-60	35-50	1.20-1.40	0.06-0.20	0.11-0.18	6.0-8.9	0.5-1.0	.32	.32			
	32-37	2-10	45-60	35-40	1.30-1.40	0.20-0.60	0.18-0.20	3.0-5.9	0.0-0.5	.43	.43			
	37-41	---	---	---	---	0.00-0.00	---	---	---	---	---			
Martin-----	0-6	2-8	60-70	27-40	1.35-1.45	0.20-0.60	0.21-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	6-12	2-8	55-70	27-40	1.35-1.45	0.20-0.60	0.18-0.20	6.0-8.9	0.5-2.0	.28	.28			
	12-53	2-8	35-60	40-55	1.20-1.30	0.06-0.20	0.12-0.18	6.0-8.9	0.5-1.0	.28	.28			
	53-80	2-8	35-60	27-40	1.20-1.30	0.06-0.20	0.12-0.18	6.0-8.9	0.0-0.5	.28	.28			
Pf:														
Padonia-----	0-11	2-10	50-70	27-35	1.30-1.40	0.60-2.00	0.21-0.23	3.0-5.9	2.0-4.0	.37	.37	3	7	38
	11-22	2-10	35-60	35-50	1.20-1.40	0.06-0.20	0.11-0.18	6.0-8.9	1.0-2.0	.32	.32			
	22-32	2-10	35-60	35-50	1.20-1.40	0.06-0.20	0.11-0.18	6.0-8.9	0.5-1.0	.32	.32			
	32-37	2-10	45-60	35-40	1.30-1.40	0.20-0.60	0.18-0.20	3.0-5.9	0.0-0.5	.43	.43			
	37-41	---	---	---	---	0.00-0.00	---	---	---	---	---			
Oska-----	0-5	2-8	50-70	27-40	1.30-1.40	0.20-0.60	0.18-0.20	3.0-5.9	1.0-3.0	.37	.37	2	7	38
	5-11	2-8	35-55	35-50	1.35-1.45	0.06-0.20	0.14-0.18	6.0-8.9	1.0-2.0	.37	.37			
	11-35	2-10	35-55	35-50	1.35-1.45	0.06-0.20	0.14-0.18	6.0-8.9	0.5-1.0	.37	.49			
	---	---	---	---	---	0.00-0.00	---	---	---	---	---			
Pm:														
Pawnee-----	0-7	20-45	20-50	30-38	1.40-1.50	0.20-0.60	0.17-0.19	3.0-5.9	2.0-4.0	.37	.37	5	6	48
	7-12	20-45	20-50	30-38	1.40-1.50	0.20-0.60	0.17-0.19	3.0-5.9	1.0-2.0	.37	.37			
	12-48	20-45	15-40	40-48	1.50-1.70	0.06-0.20	0.09-0.11	6.0-8.9	0.5-1.0	.37	.37			
	48-80	30-50	15-40	25-35	1.40-1.50	0.06-0.20	0.14-0.16	6.0-8.9	0.0-0.5	.37	.37			
Pn:														
Pawnee-----	0-7	20-45	20-50	30-38	1.40-1.50	0.20-0.60	0.17-0.19	3.0-5.9	2.0-4.0	.37	.37	5	6	48
	7-12	20-45	20-50	30-38	1.40-1.50	0.20-0.60	0.17-0.19	3.0-5.9	1.0-2.0	.37	.37			
	12-48	20-45	15-40	40-48	1.50-1.70	0.06-0.20	0.09-0.11	6.0-8.9	0.5-1.0	.37	.37			
	48-80	30-50	15-40	25-35	1.40-1.50	0.06-0.20	0.14-0.16	6.0-8.9	0.0-0.5	.37	.37			
Po:														
Pawnee-----	0-5	20-45	15-40	40-46	1.40-1.50	0.06-0.20	0.09-0.11	6.0-8.9	1.0-2.0	.37	.37	5	4	86
	5-45	20-45	15-40	40-48	1.50-1.70	0.06-0.20	0.09-0.11	6.0-8.9	0.5-1.0	.37	.37			
	45-80	30-50	15-40	25-35	1.40-1.50	0.06-0.20	0.14-0.16	6.0-8.9	0.0-0.5	.37	.37			
Pt:														
Pits, Quarries----	0-60			---	---	---	---	---	---	---	---	-	---	0
Pw:														
Pohocco-----	0-5	2-8	65-75	20-27	1.25-1.30	0.60-2.00	0.22-0.24	3.0-5.9	0.5-2.0	.37	.37	5	6	48
	5-39	2-8	65-75	20-30	1.35-1.45	0.60-2.00	0.18-0.22	3.0-5.9	0.5-1.0	.43	.43			
	39-80	2-8	65-75	18-25	1.35-1.40	0.60-2.00	0.20-0.22	3.0-5.9	0.0-0.5	.43	.43			
Netawaka-----	0-6	2-8	75-80	15-18	1.30-1.35	0.60-2.00	0.22-0.24	0.0-2.9	1.0-2.0	.43	.43	5	4L	86
	6-9	2-8	75-85	12-18	1.30-1.35	0.60-2.00	0.20-0.22	0.0-2.9	0.5-1.0	.43	.43			
	9-80	2-8	75-85	12-18	1.30-1.35	0.60-2.00	0.20-0.22	0.0-2.9	0.0-0.5	.43	.43			
Px:														
Pohocco-----	0-5	2-8	65-75	20-27	1.25-1.30	0.60-2.00	0.22-0.24	3.0-5.9	0.5-2.0	.37	.37	5	6	48
	5-39	2-8	65-75	20-30	1.35-1.45	0.60-2.00	0.18-0.22	3.0-5.9	0.5-1.0	.43	.43			
	39-80	2-8	65-80	18-25	1.35-1.40	0.60-2.00	0.20-0.22	3.0-5.9	0.0-0.5	.43	.43			
Netawaka-----	0-6	2-8	75-80	15-18	1.30-1.35	0.60-2.00	0.22-0.24	0.0-2.9	1.0-2.0	.43	.43	5	4L	86
	6-9	2-8	75-85	12-18	1.30-1.35	0.60-2.00	0.20-0.22	0.0-2.9	0.5-1.0	.43	.43			
	9-80	2-8	75-85	12-18	1.30-1.35	0.60-2.00	0.20-0.22	0.0-2.9	0.0-0.5	.43	.43			
Re:														
Reading-----	0-18	2-10	70-80	18-27	1.35-1.40	0.60-2.00	0.22-0.24	0.0-2.9	2.0-4.0	.32	.32	5	6	48
	18-48	2-8	60-70	27-35	1.40-1.50	0.20-2.00	0.18-0.20	3.0-5.9	0.5-3.0	.43	.43			
	48-54	2-8	60-70	27-35	1.40-1.50	0.20-2.00	0.18-0.20	3.0-5.9	0.5-2.0	.43	.43			
	54-80	2-22	40-65	30-42	1.40-1.50	0.20-2.00	0.13-0.20	3.0-5.9	0.0-0.5	.43	.43			
Sg:														
Shelby-----	0-13	20-45	20-45	20-32	1.50-1.55	0.20-0.60	0.17-0.19	3.0-5.9	2.0-4.0	.28	.28	5	6	48
	13-36	20-45	20-45	32-38	1.55-1.65	0.20-0.60	0.16-0.18	3.0-5.9	0.5-1.0	.37	.37			
	36-48	20-45	20-45	30-35	1.55-1.65	0.20-0.60	0.16-0.18	3.0-5.9	0.2-0.8	.37	.37			
	48-80	20-45	20-45	25-32	1.55-1.65	0.20-0.60	0.16-0.18	3.0-5.9	0.0-0.5	.37	.37			
Sm:														
Shelby-----	0-8	20-45	20-45	27-32	1.50-1.55	0.20-0.60	0.16-0.18	3.0-5.9	1.5-3.5	.28	.28	5	6	48
	8-45	20-45	20-45	32-38	1.55-1.65	0.20-0.60	0.16-0.18	3.0-5.9	0.2-0.8	.37	.37			
	45-80	20-45	20-45	25-32	1.55-1.65	0.20-0.60	0.16-0.18	3.0-5.9	0.0-0.5	.37	.37			
W:														
Water-----	---			---	---	---	---	---	---	---	---	-	---	---
Wa:														
Wabash-----	0-15	2-10	45-60	40-46	1.25-1.45	0.00-0.06	0.12-0.14	9.0-25.0	2.0-4.0	.28	.28	5	4	86
	15-80	2-10	30-55	46-60	1.20-1.45	0.00-0.06	0.08-0.12	9.0-25.0	1.0-2.0	.28	.28			
We:														
Wamego-----	0-9	2-10	55-70	27-32	1.30-1.40	0.60-2.00	0.21-0.23	0.0-2.9	2.0-4.0	.32	.32	3	7	38
	9-20	2-22	50-65	35-42	1.50-1.70	0.06-0.20	0.12-0.20	3.0-5.9	1.0-2.0	.43	.43			
	20-25	2-22	50-65	35-42	1.50-1.70	0.06-0.20	0.12-0.20	3.0-5.9	0.5-1.0	.43	.43			
	25-36	---	---	---	---	0.00-0.00	---	---	---	---	---			
Wg:														
Wamego-----	0-9	2-10	55-70	27-32	1.30-1.40	0.60-2.00	0.21-0.23	0.0-2.9	2.0-4.0	.32	.32	3	7	38
	9-20	2-22	50-65	35-42	1.50-1.70	0.06-0.20	0.12-0.20	3.0-5.9	1.0-2.0	.43	.43			
	20-25	2-22	50-65	35-42	1.50-1.70	0.06-0.20	0.12-0.20	3.0-5.9	0.5-1.0	.43	.43			
	25-36	---	---	---	---	0.00-0.00	---	---	---	---	---			
Vinland-----	0-8	2-55	60-70	25-35	1.20-1.40	0.60-2.00	0.21-0.24	3.0-5.9	2.0-4.0	.32	.32	2	7	38
	8-12	2-55	48-80	15-35	1.30-1.60	0.60-2.00	0.15-0.22	3.0-5.9	0.5-1.0	.43	.49			
	12-19	2-55	48-80	15-35	1.30-1.60	0.60-2.00	0.15-0.22	3.0-5.9	0.5-1.0	.43	.49			
	19-23	---	---	---	---	0.00-0.00	---	---	---	---	---			

PHYSICAL PROPERTIES OF THE SOILS--Continued
Brown County, Kansas: Update

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permea- bility (Ksat)	Available water capacity	Linear extensi- bility	Organic matter	Erosion factors			Wind erodi- bility group	Wind erodi- bility index
										K	Kf	T		
	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
Wm:														
Wymore-----	0-7	2-8	50-70	27-40	1.30-1.50	0.20-0.60	0.21-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	7-12	2-8	40-65	30-45	1.30-1.50	0.06-0.20	0.13-0.23	3.0-8.9	1.0-2.0	.37	.37			
	12-22	2-8	40-60	42-55	1.30-1.50	0.06-0.20	0.11-0.14	6.0-8.9	0.5-1.0	.32	.32			
	22-39	2-8	40-60	42-55	1.30-1.50	0.06-0.20	0.11-0.14	6.0-8.9	0.5-1.0	.32	.32			
	39-47	2-8	50-70	27-40	1.30-1.50	0.20-0.60	0.18-0.20	3.0-5.9	0.0-0.5	.43	.43			
	47-80	2-8	50-70	27-40	1.30-1.50	0.20-0.60	0.18-0.20	3.0-5.9	0.0-0.5	.43	.43			
Wn:														
Wymore-----	0-10	2-8	50-70	27-40	1.30-1.50	0.20-0.60	0.21-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	10-18	2-8	40-60	42-55	1.30-1.50	0.06-0.20	0.11-0.14	6.0-8.9	0.5-1.0	.32	.32			
	18-32	2-8	40-60	42-55	1.30-1.50	0.06-0.20	0.11-0.14	6.0-8.9	0.5-1.0	.32	.32			
	32-43	2-8	50-70	27-40	1.30-1.50	0.20-0.60	0.18-0.20	3.0-5.9	0.0-0.5	.43	.43			
	43-80	2-8	50-70	27-40	1.30-1.50	0.20-0.60	0.18-0.20	3.0-5.9	0.0-0.5	.43	.43			

CHEMICAL PROPERTIES OF THE SOILS
Brown County, Kansas

The Chemical Properties table shows estimates of some characteristics and features that affect soil behavior. These estimates are given for the major layers of each soil in the survey area. The estimates are based on field observations and on test data for these and similar soils. Depth to the upper and lower boundaries of each layer is indicated.

Cation-exchange capacity is the total amount of extractable bases that can be held by the soil, expressed in terms of milliequivalents per 100 grams of soil at neutrality (pH 7.0) or at some other stated pH value. Soils having a low cation-exchange capacity hold fewer cations and may require more frequent applications of fertilizer than soils having a high cation-exchange capacity. Soils having a high cation-exchange capacity can retain cations. The ability to retain cations helps to prevent the pollution of ground water.

Effective cation-exchange capacity refers to the sum of extractable bases plus aluminum expressed in terms of milliequivalents per 100 grams of soil. It is determined for soils that have pH of less than 5.5.

Soil reaction is a measure of acidity or alkalinity and is expressed as a range in pH values. The range in pH of each major horizon is based on many field tests. For many soils, values have been verified by laboratory analyses. Soil reaction is important in selecting crops and other plants, in evaluating soil amendments for fertility and stabilization, and in determining the risk of corrosion.

Calcium carbonate equivalent is the percent of carbonates, by weight, in the fraction of the soil less than 2 millimeters in size. The availability of plant nutrients is influenced by the amount of carbonates in the soil. Incorporating nitrogen fertilizer into calcareous soils helps to prevent nitrite accumulation and ammonium-N volatilization.

Gypsum is expressed as a percent, by weight, of hydrated calcium sulfates in the fraction of the soil less than 20 millimeters in size. Gypsum is partially soluble in water and can be dissolved and removed by water. Soils that have a high content of gypsum may collapse if the gypsum is removed by percolating water.

Salinity is a measure of soluble salts in the soil at saturation. It is expressed as the electrical conductivity of the saturation extract, in millimhos per centimeter at 25 degrees C. Estimates are based on field and laboratory measurements at representative sites of nonirrigated soils. The salinity of irrigated soils is affected by the quality of the irrigation water and by the frequency of water application. Hence, the salinity of soils in individual fields can differ greatly from the value given in the table. Salinity affects the suitability of a soil for crop production, the stability of soil if used as construction material, and the potential of the soil to corrode metal and concrete.

Sodium adsorption ratio (SAR) is a measure of the amount of sodium (Na) relative to calcium (Ca) and magnesium (Mg) in the water extract from saturated soil paste. It is the ratio of the Na concentration divided by the square root of one-half of the Ca + Mg concentration. Soils that have SAR values of 13 or more may be characterized by an increased dispersion of organic matter and clay particles, reduced permeability and aeration, and a general degradation of soil structure.

CHEMICAL PROPERTIES OF THE SOILS--Continued
Brown County, Kansas

PAGE 2 of 5

Map symbol and soil name	Depth	Cation- exchange capacity	Effective Cation Exchange Capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm		
Ac:								
Aksarben-----	0-9	25-35	---	5.1-6.5	0	0	0	0
	9-13	25-35	---	5.6-6.5	0	0	0	0
	13-19	25-35	---	5.6-6.5	0	0	0	0
	19-39	25-35	---	5.1-6.5	0	0	0	0
	39-47	25-35	---	5.6-6.5	0	0	0	0
	47-80	20-30	---	6.1-7.3	0	0	0	0
Ad:								
Aksarben-----	0-6	25-35	---	5.1-6.5	0	0	0	0
	6-12	25-35	---	5.1-6.5	0	0	0	0
	12-18	25-35	---	5.1-6.5	0	0	0	0
	18-26	25-35	---	5.1-6.5	0	0	0	0
	26-34	25-35	---	5.1-6.5	0	0	0	0
	34-42	25-35	---	5.1-6.5	0	0	0	0
	42-60	25-35	---	5.6-6.5	0	0	0	0
	60-80	20-30	---	6.1-7.3	0	0	0	0
Ae:								
Aksarben-----	0-6	25-35	---	5.1-6.5	0	0	0	0
	6-12	25-35	---	5.1-6.5	0	0	0	0
	12-18	25-35	---	5.1-6.5	0	0	0	0
	18-26	25-35	---	5.1-6.5	0	0	0	0
	26-34	25-35	---	5.1-6.5	0	0	0	0
	34-42	25-35	---	5.1-6.5	0	0	0	0
	42-60	25-35	---	5.6-6.5	0	0	0	0
	60-80	20-30	---	6.1-7.3	0	0	0	0
Bs:								
Burchard-----	0-9	15-35	---	5.6-7.3	0	0	0	0
	9-13	15-35	---	6.1-7.3	0	0	0	0
	13-19	15-35	---	6.1-7.3	0	0	0	0
	19-29	18-26	---	7.4-8.4	5-10	0	0	0
	29-37	18-26	---	7.4-8.4	5-10	0	0	0
	37-60	15-25	---	7.4-8.4	10-15	0	0	0
Bx:								
Burchard-----	0-9	15-35	---	5.6-7.3	0	0	0	0
	9-19	15-35	---	6.1-7.3	0	0	0	0
	19-29	18-26	---	7.4-8.4	5-10	0	0	0
	29-37	18-26	---	7.4-8.4	5-10	0	0	0
	37-60	15-25	---	7.4-8.4	10-15	0	0	0
Steinauer-----	0-6	15-25	---	7.4-8.4	1-10	0	0	0
	6-14	15-25	---	7.9-8.4	5-10	0	0	0
	14-80	15-25	---	7.9-8.4	10-15	0	0	0
Ch:								
Chase-----	0-9	15-30	---	5.6-7.3	0	0	0	0
	9-19	15-30	---	5.6-7.3	0	0	0	0
	19-41	15-40	---	5.6-7.8	0	0	0	0
	41-47	15-40	---	5.6-7.8	0-1	0	0	0
	47-80	10-35	---	6.1-8.4	0-1	0	0	0
Co:								
Contrary-----	0-6	25-30	---	5.6-7.3	0	0	0	0
	6-32	20-25	---	5.6-7.3	0	0	0	0
	32-80	15-25	---	6.1-7.8	0-5	0	0	0
Ga:								
Grundy-----	0-7	20-30	---	6.1-7.3	0	0	0	0
	7-14	20-30	---	6.6-7.3	0	0	0	0
	14-41	30-40	---	7.4-7.8	0	0	0	0
	41-48	25-35	---	7.4-8.4	0	0	0	0
	48-80	20-30	---	7.4-8.4	0	0	0	0
Ju:								
Judson-----	0-7	25-30	---	5.6-7.3	0	0	0	0
	7-25	25-30	---	5.6-7.3	0	0	0	0
	25-40	25-30	---	5.6-7.3	0	0	0	0
	40-50	25-30	---	5.6-7.3	0	0	0	0
	50-80	25-30	---	6.1-7.8	0	0	0	0
Kd:								
Kennebec, CHANNELED-----	0-8	30-36	---	5.6-7.3	0	0	0	0
	8-18	30-36	---	5.6-7.3	0	0	0	0
	18-32	30-36	---	5.6-7.3	0	0	0	0
	32-41	30-36	---	5.6-7.3	0	0	0	0
	41-54	30-36	---	6.1-7.3	0	0	0	0
	54-60	30-36	---	6.1-7.3	0	0	0	0
Ke:								
Kennebec-----	0-8	30-36	---	5.6-7.3	0	0	0	0
	8-18	30-36	---	5.6-7.3	0	0	0	0
	18-32	30-36	---	5.6-7.3	0	0	0	0
	32-41	30-36	---	5.6-7.3	0	0	0	0
	41-54	30-36	---	6.1-7.3	0	0	0	0
	54-60	30-36	---	6.1-7.3	0	0	0	0
Kp:								
Kipson-----	0-8	20-30	---	7.4-8.4	10-20	0	0	0
	8-19	10-30	---	7.9-9.0	30-60	0	0	0
	19-22	---	---	---	---	---	---	---
Sogn-----	0-12	15-30	---	6.1-8.4	0-10	0	0	0
	---	---	---	---	---	---	---	---

CHEMICAL PROPERTIES OF THE SOILS--Continued
Brown County, Kansas

PAGE 3 of 5

Map symbol and soil name	Depth	Cation- exchange capacity	Effective Cation Exchange Capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm		
M-W: Miscellaneous Water-----	---	---	---	---	---	---	---	---
Ma: Marshall-----	0-10 10-32 32-80	25-30 25-30 20-25	--- --- ---	5.6-7.3 5.6-7.3 6.6-7.3	0 0 0	0 0 0	0 0 0	0 0 0
Mb: Marshall-----	0-6 6-44 44-80	25-30 25-30 20-25	--- --- ---	5.6-7.3 5.6-7.3 6.6-7.3	0 0 0	0 0 0	0 0 0	0 0 0
Md: Martin-----	0-6 6-12 12-53 53-80	15-30 10-30 15-35 15-25	--- --- --- ---	5.6-6.5 5.6-7.3 5.6-7.3 5.6-7.8	0 0 0 0-1	0 0 0 0	0 0 0 0	0 0 0 0
Mf: Martin-----	0-6 6-12 12-53 53-80	15-30 10-30 15-35 15-25	--- --- --- ---	5.6-6.5 5.6-7.3 5.6-7.3 5.6-7.8	0 0 0 0-1	0 0 0 0	0 0 0 0	0 0 0 0
Mh: Mayberry-----	0-10 10-42 42-80	15-35 25-40 10-30	--- --- ---	5.6-6.5 5.6-7.8 6.1-8.4	0 0 0-5	0 0 0	0 0 0	0 0 0
Mk: Monona-----	0-11 11-30 30-80	25-30 25-30 20-25	--- --- ---	5.6-7.3 6.1-7.3 6.6-8.4	0 0 0-10	0 0 0	0 0 0	0 0 0
Mn: Monona-----	0-6 6-30 30-80	25-30 25-30 25-30	--- --- ---	5.6-7.3 6.1-7.3 6.6-8.4	0 0 0-10	0 0 0	0 0 0	0 0 0
Mt: Morrell-----	0-6 6-12 12-43 43-52 52-80	10-30 10-30 15-30 5.0-15 5.0-15	--- --- --- --- ---	5.1-7.3 5.1-7.3 5.1-7.3 5.1-7.3 5.1-7.3	0 0 0 0 0	0 0 0 0 0	0 0 0 0 0	0 0 0 0 0
Mw: Muscotah-----	0-9 9-16 16-30 30-39 39-61 61-70 70-80	20-25 20-25 15-30 20-40 20-40 20-40 20-40	--- --- --- --- --- --- ---	6.1-7.3 6.1-7.3 5.6-7.3 5.6-7.3 5.6-7.3 5.6-7.3 5.6-7.3	0 0 0 0 0 0 0	0 0 0 0 0 0 0	0 0 0 0 0 0 0	0 0 0 0 0 0 0
My: Muscotah-----	0-9 9-16 16-23 23-35 35-44 44-60 60-70 70-80	30-36 15-30 15-30 20-40 20-40 20-40 20-40 20-40	--- --- --- --- --- --- --- ---	5.6-7.3 5.6-7.3 5.6-7.3 5.6-7.3 5.6-7.3 5.6-7.3 5.6-7.3 5.6-7.3	0 0 0 0 0 0 0 0	0 0 0 0 0 0 0 0	0 0 0 0 0 0 0 0	0 0 0 0 0 0 0 0
No: Nodaway-----	0-7 7-14 14-45 45-60	20-25 20-25 20-25 20-25	--- --- --- ---	6.1-7.3 6.1-7.3 6.1-7.3 6.1-7.3	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
Om: Olmitz-----	0-7 7-20 20-42 42-80	20-25 20-25 20-25 20-25	--- --- --- ---	5.6-7.3 5.6-7.3 5.1-6.5 5.1-6.5	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
Or: Orthents, Earthen Dam----	---	---	---	---	---	---	---	---
Pd: Padonia-----	0-11 11-22 22-32 32-37 37-40	15-35 15-35 15-35 15-35 ---	--- --- --- --- ---	6.1-7.3 6.6-7.8 7.4-8.4 7.4-8.4 ---	0 0 1-10 5-15 ---	0 0 0 0 ---	0 0 0 0 ---	0 0 0 0 ---
Martin-----	0-6 6-12 12-53 53-80	15-30 10-30 15-35 15-25	--- --- --- ---	5.6-6.5 5.6-7.3 5.6-7.3 5.6-7.8	0 0 0 0-1	0 0 0 0	0 0 0 0	0 0 0 0

CHEMICAL PROPERTIES OF THE SOILS--Continued
Brown County, Kansas

PAGE 4 of 5

Map symbol and soil name	Depth	Cation- exchange capacity	Effective Cation Exchange Capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm		
Pe:								
Padonia-----	0-11	15-35	---	6.1-7.3	0	0	0	0
	11-22	15-35	---	6.6-7.8	0	0	0	0
	22-32	15-35	---	7.4-8.4	1-10	0	0	0
	32-37	15-35	---	7.4-8.4	5-15	0	0	0
	37-41	---	---	---	---	---	---	---
Martin-----	0-6	15-30	---	5.6-6.5	0	0	0	0
	6-12	10-30	---	5.6-7.3	0	0	0	0
	12-53	15-35	---	5.6-7.3	0	0	0	0
	53-80	15-25	---	5.6-7.8	0-1	0	0	0
Pf:								
Padonia-----	0-11	15-35	---	6.1-7.3	0	0	0	0
	11-22	15-35	---	6.6-7.8	0	0	0	0
	22-32	15-35	---	7.4-8.4	1-10	0	0	0
	32-37	15-35	---	7.4-8.4	5-15	0	0	0
	37-41	---	---	---	---	---	---	---
Oska-----	0-5	15-30	---	5.6-6.5	0	0	0	0
	5-11	15-35	---	5.6-7.8	0	0	0	0
	11-35	15-30	---	5.6-7.8	0	0	0	0
	---	---	---	---	---	---	---	---
Pm:								
Pawnee-----	0-7	20-35	---	5.6-7.3	0	0	0	0
	7-12	20-35	---	5.6-7.3	0	0	0	0
	12-48	25-45	---	6.1-8.4	0-5	0	0	0
	48-80	15-30	---	7.4-8.4	1-15	0	0	0
Pn:								
Pawnee-----	0-7	20-35	---	5.6-7.3	0	0	0	0
	7-12	20-35	---	5.6-7.3	0	0	0	0
	12-48	25-45	---	6.1-8.4	0-5	0	0	0
	48-80	15-30	---	7.4-8.4	1-15	0	0	0
Po:								
Pawnee-----	0-5	25-40	---	5.6-7.3	0	0	0	0
	5-45	25-45	---	6.1-8.4	0-5	0	0	0
	45-80	15-30	---	7.4-8.4	1-15	0	0	0
Pt:								
Pits, Quarries--	0-60	---	---	---	---	---	---	---
Pw:								
Pohocco-----	0-5	15-25	---	6.6-7.8	0	0	0	0
	5-39	15-30	---	6.6-7.8	0	0	0	0
	39-80	15-20	---	6.6-7.8	0-5	0	0	0
Netawaka-----	0-6	10-15	---	7.4-8.4	0-5	0	0	0
	6-9	5.0-10	---	7.4-8.4	5-10	0	0	0
	9-80	5.0-10	---	7.4-8.4	5-10	0	0	0
Px:								
Pohocco-----	0-5	15-25	---	6.6-7.8	0	0	0	0
	5-39	15-30	---	6.6-7.8	0	0	0	0
	39-80	15-20	---	6.6-7.8	0-5	0	0	0
Netawaka-----	0-6	10-15	---	7.4-8.4	0-5	0	0	0
	6-9	5.0-10	---	7.4-8.4	5-10	0	0	0
	9-80	5.0-10	---	7.4-8.4	5-10	0	0	0
Re:								
Reading-----	0-18	10-25	---	5.6-6.5	0	0	0	0
	18-48	10-25	---	5.6-6.5	0	0	0	0
	48-54	10-25	---	5.6-6.5	0	0	0	0
	54-80	15-25	---	6.1-8.4	0	0	0	0
Sg:								
Shelby-----	0-13	20-25	---	5.1-7.3	0	0	0	0
	13-36	20-25	---	5.1-7.3	0	0	0	0
	36-48	20-25	---	5.1-7.3	0	0	0	0
	48-80	20-25	---	6.6-8.4	0-15	0	0	0
Sm:								
Shelby-----	0-8	20-25	---	5.1-7.3	0	0	0	0
	8-45	20-25	---	5.1-7.3	0	0	0	0
	45-80	20-25	---	6.6-8.4	0-15	0	0	0
W:								
Water-----	---	---	---	---	---	---	---	---
Wa:								
Wabash-----	0-15	30-35	---	5.1-7.3	0	0	0	0
	15-80	28-42	---	5.1-7.8	0	0	0	0
We:								
Wamego-----	0-9	15-30	---	5.6-6.5	0	0	0	0
	9-20	15-30	---	5.6-7.3	0	0	0	0
	20-25	15-30	---	5.6-7.3	0	0	0	0
	25-36	---	---	---	---	---	---	---
Wg:								
Wamego-----	0-9	15-30	---	5.6-6.5	0	0	0	0
	9-20	15-30	---	5.6-7.3	0	0	0	0
	20-25	15-30	---	5.6-7.3	0	0	0	0
	25-36	---	---	---	---	---	---	---
Vinland-----	0-8	15-30	---	5.6-7.8	0	0	0	0
	8-12	5.0-20	---	5.6-7.8	0	0	0	0
	12-19	5.0-20	---	5.6-7.8	0	0	0	0
	19-23	---	---	---	---	---	---	---

CHEMICAL PROPERTIES OF THE SOILS--Continued
Brown County, Kansas

PAGE 5 of 5

Map symbol and soil name	Depth	Cation- exchange capacity	Effective Cation Exchange Capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm		
Wm:								
Wymore-----	0-7	23-32	---	5.6-6.5	0	0	0	0
	7-12	23-36	---	5.6-6.5	0	0	0	0
	12-22	30-42	---	5.6-7.3	0	0	0	0
	22-39	30-42	---	5.6-7.3	0	0	0	0
	39-47	19-29	---	6.6-7.3	0-2	0	0	0
	47-80	19-29	---	6.6-7.3	0-2	0	0	0
Wn:								
Wymore-----	0-10	23-32	---	5.6-6.5	0	0	0	0
	10-18	30-42	---	5.6-7.3	0	0	0	0
	18-32	30-42	---	5.6-7.3	0	0	0	0
	32-43	19-29	---	6.6-7.3	0-2	0	0	0
	43-80	19-29	---	6.6-7.3	0-2	0	0	0

WATER FEATURES Brown County, Kansas

The Water Features table gives estimates of various water features. The estimates are used in land use planning that involves engineering considerations. Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The four hydrologic soil groups are:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

The months in the table indicate the portion of the year in which the feature is most likely to be a concern.

Water table refers to a saturated zone in the soil. The Water Features table indicates, by month, depth to the top (upper limit) and base (lower limit) of the saturated zone in most years. Estimates of the upper and lower limits are based mainly on observations of the water table at selected sites and on evidence of a saturated zone, namely grayish colors or mottles (redoximorphic features) in the soil. A saturated zone that lasts for less than a month is not considered a water table. Ponding is standing water in a closed depression. Unless a drainage system is installed, the water is removed only by percolation, transpiration, or evaporation. The Water Features table indicates surface water depth and the duration and frequency of ponding. Duration is expressed as very brief if less than 2 days, brief if 2 to 7 days, long if 7 to 30 days, and very long if more than 30 days. Frequency is expressed as none, rare, occasional, and frequent. None means that ponding is not probable; rare that it is unlikely but possible under unusual weather conditions (the chance of ponding is nearly 0 percent to 5 percent in any year); occasional that it occurs, on the average, once or less in 2 years (the chance of ponding is 5 to 50 percent in any year); and frequent that it occurs, on the average, more than once in 2 years (the chance of ponding is more than 50 percent in any year).

Flooding, the temporary inundation of an area, is caused by overflowing streams, by runoff from adjacent slopes, or by tides. Water standing for short periods after rainfall or snowmelt is not considered flooding, and water standing in swamps and marshes is considered ponding rather than flooding.

Duration and frequency are estimated. Duration is expressed as extremely brief if 0.1 hour to 4 hours, very brief if 4 hours to 2 days, brief if 2 to 7 days, long if 7 to 30 days, and very long if more than 30 days. Frequency is expressed as none, very rare, rare, occasional, frequent, and very frequent. None means that flooding is not probable; very rare that it is very unlikely but possible under extremely unusual weather conditions (the chance of flooding is less than 1 percent in any year); rare that it is unlikely but possible under unusual weather conditions (the chance of flooding is 1 to 5 percent in any year); occasional that it occurs infrequently under normal weather conditions (the chance of flooding is 5 to 50 percent in any year); frequent that it is likely to occur often under normal weather conditions (the chance of flooding is more than 50 percent in any year but is less than 50 percent in all months in any year); and very frequent that it is likely to occur very often under normal weather conditions (the chance of flooding is more than 50 percent in all months of any year).

The information is based on evidence in the soil profile, namely thin strata of gravel, sand, silt, or clay deposited by floodwater; irregular decrease in organic matter content with increasing depth; and little or no horizon development.

Also considered are local information about the extent and levels of flooding and the relation of each soil on the landscape to historic floods. Information on the extent of flooding based on soil data is less specific than that provided by detailed engineering surveys that delineate flood-prone areas at specific flood frequency levels.

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro- logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
			Ft	Ft	Ft				
Ac: Aksarben-----	B		---	---	---	---	---	---	---
Ad: Aksarben-----	B		---	---	---	---	---	---	---
Ae: Aksarben-----	B		---	---	---	---	---	---	---
Bs: Burchard-----	B		---	---	---	---	---	---	---
Bx: Burchard-----	B		---	---	---	---	---	---	---
Steinauer-----	B		---	---	---	---	---	---	---
Ch: Chase-----	C	January	1.8-2.2	3.8-4.2	---	---	---	---	Rare
		February	1.8-2.2	3.8-4.2	---	---	---	---	Rare
		March	1.8-2.2	3.8-4.2	---	---	---	---	Rare
		April	1.8-2.2	3.8-4.2	---	---	---	---	Rare
		May	---	---	---	---	---	---	Rare
		June	---	---	---	---	---	---	Rare
		July	---	---	---	---	---	---	Rare
		August	---	---	---	---	---	---	Rare
		September	---	---	---	---	---	---	Rare
		October	---	---	---	---	---	---	Rare
		November	---	---	---	---	---	---	Rare
		December	---	---	---	---	---	---	Rare
Co: Contrary-----	B		---	---	---	---	---	---	---
Ga: Grundy-----	C	January	0.8-1.2	2.3-2.7	---	---	---	---	None
		February	0.8-1.2	2.3-2.7	---	---	---	---	None
		March	0.8-1.2	2.3-2.7	---	---	---	---	None
		April	0.8-1.2	2.3-2.7	---	---	---	---	None
Ju: Judson-----	B		---	---	---	---	---	---	---
Kd: Kennebec, CHANNELED-----	B	January	---	---	---	---	None	---	Rare
		February	---	---	---	---	None	---	Rare
		March	3.3-4.6	>6.0	---	---	None	Brief	Frequent
		April	3.3-4.6	>6.0	---	---	None	Brief	Frequent
		May	3.3-4.6	>6.0	---	---	None	Brief	Frequent
		June	---	---	---	---	None	Brief	Frequent
		July	---	---	---	---	None	Brief	Frequent
		August	---	---	---	---	None	Brief	Frequent
		September	---	---	---	---	None	Brief	Frequent
		October	---	---	---	---	None	Brief	Frequent
		November	3.3-4.6	>6.0	---	---	None	Brief	Frequent
		December	---	---	---	---	None	---	Rare
Ke: Kennebec-----	B	January	---	---	---	---	None	---	Rare
		February	---	---	---	---	None	---	Rare
		March	3.3-4.6	>6.0	---	---	None	Very brief	Occasional
		April	3.3-4.6	>6.0	---	---	None	Very brief	Occasional
		May	3.3-4.6	>6.0	---	---	None	Very brief	Occasional
		June	---	---	---	---	None	Very brief	Occasional
		July	---	---	---	---	None	Very brief	Occasional
		August	---	---	---	---	None	Very brief	Occasional
		September	---	---	---	---	None	Very brief	Occasional
		October	---	---	---	---	None	Very brief	Occasional
		November	3.3-4.6	>6.0	---	---	None	Very brief	Occasional
		December	---	---	---	---	None	---	Rare
Kp: Kipson-----	D		---	---	---	---	---	---	---
Sogn-----	D		---	---	---	---	---	---	---
M-W: Miscellaneous Water-----	---		---	---	---	---	---	---	---
Ma: Marshall-----	B		---	---	---	---	---	---	---
Mb: Marshall-----	B		---	---	---	---	---	---	---

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro- logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
			Ft	Ft	Ft				
Md: Martin-----	C		---	---	---	---	---	---	---
		February	1.8-2.2	2.8-3.2	---	---	---	---	None
		March	1.8-2.2	2.8-3.2	---	---	---	---	None
Mf: Martin-----	C	April	1.8-2.2	2.8-3.2	---	---	---	---	None
		February	1.8-2.2	2.8-3.2	---	---	---	---	None
		March	1.8-2.2	2.8-3.2	---	---	---	---	None
Mh: Mayberry-----	D	April	1.8-2.2	2.8-3.2	---	---	---	---	None
		February	0.8-1.2	2.8-3.2	---	---	---	---	None
		March	0.8-1.2	2.8-3.2	---	---	---	---	None
Mk: Monona-----	B	April	0.8-1.2	2.8-3.2	---	---	---	---	None
Mn: Monona-----	B		---	---	---	---	---	---	---
Mt: Morrill-----	B		---	---	---	---	---	---	---
Mw: Muscotah-----	D		---	---	---	---	---	---	---
		January	1.8-2.2	>6.0	---	---	---	---	Rare
		February	1.8-2.2	>6.0	---	---	---	---	Rare
		March	1.8-2.2	>6.0	---	---	---	Brief	Occasional
		April	1.8-2.2	>6.0	---	---	---	Brief	Occasional
		May	2.8-3.2	>6.0	---	---	---	Brief	Occasional
		June	---	---	---	---	---	Brief	Occasional
		July	---	---	---	---	---	Brief	Occasional
		August	---	---	---	---	---	Brief	Occasional
		September	---	---	---	---	---	Brief	Occasional
		October	---	---	---	---	---	Brief	Occasional
		November	---	---	---	---	---	Brief	Occasional
		December	2.8-3.2	>6.0	---	---	---	---	Rare
My: Muscotah-----	D		---	---	---	---	---	---	---
		January	1.8-2.2	>6.0	---	---	---	---	Rare
		February	1.8-2.2	>6.0	---	---	---	---	Rare
		March	1.8-2.2	>6.0	---	---	---	Brief	Occasional
		April	1.8-2.2	>6.0	---	---	---	Brief	Occasional
		May	2.8-3.2	>6.0	---	---	---	Brief	Occasional
		June	---	---	---	---	---	Brief	Occasional
		July	---	---	---	---	---	Brief	Occasional
		August	---	---	---	---	---	Brief	Occasional
		September	---	---	---	---	---	Brief	Occasional
		October	---	---	---	---	---	Brief	Occasional
		November	---	---	---	---	---	Brief	Occasional
		December	2.8-3.2	>6.0	---	---	---	---	Rare
No: Nodaway-----	B		---	---	---	---	---	---	---
		January	2.8-3.2	>6.0	---	---	---	---	Rare
		February	2.8-3.2	>6.0	---	---	---	---	Rare
		March	2.8-3.2	>6.0	---	---	---	Brief	Occasional
		April	2.8-3.2	>6.0	---	---	---	Brief	Occasional
		May	---	---	---	---	---	Brief	Occasional
		June	---	---	---	---	---	Brief	Occasional
		July	---	---	---	---	---	Brief	Occasional
		August	---	---	---	---	---	Brief	Occasional
		September	---	---	---	---	---	Brief	Occasional
		October	---	---	---	---	---	Brief	Occasional
		November	---	---	---	---	---	Brief	Occasional
		December	---	---	---	---	---	---	Rare
Om: Olmitz-----	B		---	---	---	---	---	---	---
		March	3.3-3.7	>6.0	---	---	---	---	None
		April	3.3-3.7	>6.0	---	---	---	---	None
		May	3.3-3.7	>6.0	---	---	---	---	None
		June	3.3-3.7	>6.0	---	---	---	---	None
Or: Orthents, Earthen Dam-----	---		---	---	---	---	---	---	---
Pd: Padonia-----	C		---	---	---	---	---	---	---
Martin-----	C		---	---	---	---	---	---	---
		February	1.8-2.2	2.8-3.2	---	---	---	---	None
		March	1.8-2.2	2.8-3.2	---	---	---	---	None
Pe: April			1.8-2.2	2.8-3.2	---	---	---	---	None

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro- logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
Padonia-----	C		Ft	Ft	Ft				
Martin-----	C		---	---	---	---	---	---	---
Pf:									
Padonia-----	C	February	1.8-2.2	2.8-3.2	---	---	---	---	None
Oska-----	C	March	1.8-2.2	2.8-3.2	---	---	---	---	None
Pm:									
Pawnee-----	D	April	1.8-2.2	2.8-3.2	---	---	---	---	None
Pn:									
Pawnee-----	D	February	0.8-1.2	2.8-3.2	---	---	---	---	None
Po:									
Pawnee-----	D	March	0.8-1.2	2.8-3.2	---	---	---	---	None
Pt:									
Pits, Quarries-----	---	April	0.8-1.2	2.8-3.2	---	---	---	---	None
Pw:									
Pohocco-----	B	February	0.8-1.2	2.8-3.2	---	---	---	---	None
Netawaka-----	B	March	0.8-1.2	2.8-3.2	---	---	---	---	None
Px:									
Pohocco-----	B	April	0.8-1.2	2.8-3.2	---	---	---	---	None
Netawaka-----	B								
Re:									
Reading-----	B	February	3.3-3.7	>6.0	---	---	---	---	None
		March	3.3-3.7	>6.0	---	---	---	---	None
		April	3.3-3.7	>6.0	---	---	---	---	Rare
		May	---	---	---	---	---	---	Rare
		June	---	---	---	---	---	---	Rare
		July	---	---	---	---	---	---	Rare
		August	---	---	---	---	---	---	Rare
		September	---	---	---	---	---	---	Rare
		October	---	---	---	---	---	---	Rare
		November	---	---	---	---	---	---	Rare
		December	4.8-5.2	>6.0	---	---	---	---	None
Sg:									
Shelby-----	B								
Sm:									
Shelby-----	B								
W:									
Water-----	---								
Wa:									
Wabash-----	D	January	0.2-0.8	>6.0	---	---	---	---	Rare
		February	0.2-0.8	>6.0	---	---	---	---	Rare
		March	0.2-0.8	>6.0	---	---	---	Brief	Occasional
		April	0.2-0.8	>6.0	---	---	---	Brief	Occasional
		May	0.2-0.8	>6.0	---	---	---	Brief	Occasional
		June	0.8-1.2	>6.0	---	---	---	Brief	Occasional
		July	---	---	---	---	---	Brief	Occasional
		August	---	---	---	---	---	Brief	Occasional
		September	---	---	---	---	---	Brief	Occasional
		October	---	---	---	---	---	Brief	Occasional
		November	0.8-1.2	>6.0	---	---	---	Brief	Occasional
		December	0.8-1.2	>6.0	---	---	---	---	Rare
We:									
Wamego-----	C								
Wg:									
Wamego-----	C								
Vinland-----	D								

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro- logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
Wm: Wymore-----	D	February	0.8-1.2	2.8-3.2	---	---	---	---	None
		March	0.8-1.2	2.8-3.2	---	---	---	---	None
		April	0.8-1.2	2.8-3.2	---	---	---	---	None
Wn: Wymore-----	D	February	0.8-1.2	2.8-3.2	---	---	---	---	None
		March	0.8-1.2	2.8-3.2	---	---	---	---	None
		April	0.8-1.2	2.8-3.2	---	---	---	---	None

The following table gives estimates of various soil features. The estimates are used in land use planning that involves engineering considerations.

A restrictive layer is a nearly continuous layer that has one or more physical, chemical, or thermal properties that significantly impede the movement of water and air through the soil or that restrict roots or otherwise provide an unfavorable root environment. Examples are bedrock, cemented layers, dense layers, and frozen layers. The table indicates the hardness and thickness of the restrictive layer, both of which significantly affect the ease of excavation. Depth to top is the vertical distance from the soil surface to the upper boundary of the restrictive layer.

Potential for frost action is the likelihood of upward or lateral expansion of the soil caused by the formation of segregated ice lenses (frost heave) and the subsequent collapse of the soil and loss of strength on thawing. Frost action occurs when moisture moves into the freezing zone of the soil. Temperature, texture, density, permeability, content of organic matter, and depth to the water table are the most important factors considered in evaluating the potential for frost action. It is assumed that the soil is not insulated by vegetation or snow and is not artificially drained. Silty and highly structured, clayey soils that have a high water table in winter are the most susceptible to frost action. Well drained, very gravelly, or very sandy soils are the least susceptible. Frost heave and low soil strength during thawing cause damage to pavements and other rigid structures.

Risk of corrosion pertains to potential soil-induced electrochemical or chemical action that corrodes or weakens uncoated steel or concrete. The rate of corrosion of uncoated steel is related to such factors as soil moisture, particle-size distribution, acidity, and electrical conductivity of the soil. The rate of corrosion of concrete is based mainly on the sulfate and sodium content, texture, moisture content, and acidity of the soil. Special site examination and design may be needed if the combination of factors results in a severe hazard of corrosion. The steel or concrete in installations that intersect soil boundaries or soil layers is more susceptible to corrosion than the steel or concrete in installations that are entirely within one kind of soil or within one soil layer.

For uncoated steel, the risk of corrosion, expressed as low, moderate, or high, is based on soil drainage class, total acidity, electrical resistivity near field capacity, and electrical conductivity of the saturation extract.

For concrete, the risk of corrosion also is expressed as low, moderate, or high. It is based on soil texture, acidity, and amount of sulfates in the saturation extract.

Map symbol and soil name	Restrictive layer				Potential for Frost action	Risk of corrosion	
	Kind	Depth to top	Thickness	Hardness		Uncoated Steel	Concrete
		In	In				
Ac:							
Aksarben-----	---	---	---	---	High	Moderate	Moderate
Ad:							
Aksarben-----	---	---	---	---	High	Moderate	Moderate
Ae:							
Aksarben-----	---	---	---	---	High	Moderate	Moderate
Bs:							
Burchard-----	---	---	---	---	Moderate	Moderate	Low
Bx:							
Burchard-----	---	---	---	---	Moderate	Moderate	Low
Steinauer-----	---	---	---	---	Moderate	Moderate	Low
Ch:							
Chase-----	---	---	---	---	High	High	Low
Co:							
Contrary-----	---	---	---	---	High	Moderate	Moderate
Ga:							
Grundy-----	---	---	---	---	High	High	Moderate
Ju:							
Judson-----	---	---	---	---	High	Moderate	Low
Kd:							
Kennebec, CHANNELED-----	---	---	---	---	High	Moderate	Low
Ke:							
Kennebec-----	---	---	---	---	High	Moderate	Low
Kp:							
Kipson-----	7-20	Bedrock (paralithic)	---	Noncemented	Moderate	Low	Low
Sogn-----	4-20	Bedrock (lithic)	---	Indurated	Moderate	Low	Low
M-W:							
Miscellaneous Water-----	---	---	---	---	---	---	---
Ma:							
Marshall-----	---	---	---	---	High	Moderate	Moderate
Mb:							
Marshall-----	---	---	---	---	High	Moderate	Moderate
Md:							
Martin-----	---	---	---	---	High	High	Low
Mf:							
Martin-----	---	---	---	---	High	High	Low
Mh:							
Mayberry-----	---	---	---	---	High	High	Low
Mk:							
Monona-----	---	---	---	---	High	Low	Low
Mn:							
Monona-----	---	---	---	---	High	Low	Low
Mt:							
Morrill-----	---	---	---	---	Moderate	Moderate	Moderate
Mw:							
Muscotah-----	---	---	---	---	Moderate	High	Low
My:							
Muscotah-----	---	---	---	---	Moderate	High	Low
No:							
Nodaway-----	---	---	---	---	High	Moderate	Low
Om:							
Olmitz-----	---	---	---	---	Moderate	Moderate	Moderate
Or:							
Orthents, Earthen Dam----	---	---	---	---	---	---	---
Pd:							
Padonia-----	20-40	Bedrock (paralithic)	---	Noncemented	Moderate	High	Low
Martin-----	---	---	---	---	High	High	Low
Pe:							
Padonia-----	20-40	Bedrock (paralithic)	---	Noncemented	Moderate	High	Low
Martin-----	---	---	---	---	High	High	Low
Pf:							
Padonia-----	20-40	Bedrock (paralithic)	---	Noncemented	Moderate	High	Low
Oska-----	20-40	Bedrock (lithic)	---	Indurated	Moderate	High	Moderate
Pm:							
Pawnee-----	---	---	---	---	High	High	Low
Pn:							
Pawnee-----	---	---	---	---	High	High	Low
Po:							
Pawnee-----	---	---	---	---	High	High	Low
Pt:							
Pits, Quarries--	---	---	---	---	---	---	---
Pw:							
Pohocco-----	---	---	---	---	High	Moderate	Low
Netawaka-----	---	---	---	---	High	Low	Low
Px:							
Pohocco-----	---	---	---	---	High	Moderate	Low
Netawaka-----	---	---	---	---	High	Low	Low
Re:							
Reading-----	---	---	---	---	High	Moderate	Low

Map symbol and soil name	Restrictive layer				Potential for Frost action	Risk of corrosion	
	Kind	Depth to top	Thickness	Hardness		Uncoated Steel	Concrete
		In	In				
Sg: Shelby-----	---	---	---	---	Moderate	Moderate	Moderate
Sm: Shelby-----	---	---	---	---	Moderate	Moderate	Moderate
W: Water-----	---	---	---	---	Low	---	---
Wa: Wabash-----	---	---	---	---	High	High	Moderate
We: Wamego-----	20-40	Bedrock (paralithic)	---	Noncemented	Moderate	Moderate	Moderate
Wg: Wamego-----	20-40	Bedrock (paralithic)	---	Noncemented	Moderate	Moderate	Moderate
Vinland-----	10-20	Bedrock (paralithic)	---	Noncemented	Moderate	Low	Moderate
Wm: Wymore-----	---	---	---	---	High	High	Moderate
Wn: Wymore-----	---	---	---	---	High	High	Moderate

WATER MANAGEMENT
Brown County, Kansas

The soils of the survey area are rated in the Water Management table according to limitations that affect their suitability for water management. Soils are rated for pond reservoir areas, drainage, irrigation, terraces and diversions, and grassed waterways. Restrictive features that affect each soil for the specified use is also provided in the table.

The ratings in the table are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Moderately limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Limited indicates that the soil has one or more features that are significant limitations for the specified use. The limitations can be overcome, but generally require special design, soil reclamation, or installation procedures that may result in additional expense. Fair performance and moderate to high maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Limitation class terms, such as very limited or limited, etc., limitation ratings, and numerical ratings are shown for each soil feature listed. As many as three soil features may be listed for each soil component if applicable. The overall limitation rating for the soil component is based on the most severe limitation.

Pond reservoir areas hold water behind a dam or embankment. Soils best suited to this use have low seepage potential in the upper 60 inches. The seepage potential is determined by the permeability of the soil and the depth to fractured bedrock or other permeable material. Excessive slope can affect the storage capacity of the reservoir area.

Embankments, dikes, and levees are raised structures of soil material, generally less than 20 feet high, constructed to impound water or to protect land against overflow. In this table, the soils are rated as a source of material for embankment fill. The ratings apply to the soil material below the surface layer to a depth of about 5 feet. It is assumed that soil layers will be uniformly mixed and compacted during construction.

The ratings do not indicate the ability of the natural soil to support an embankment. Soil properties to a depth even greater than the height of the embankment can affect performance and safety of the embankment. Generally, deeper onsite investigation is needed to determine these properties.

Soil material in embankments must be resistant to seepage, piping, and erosion and have favorable compaction characteristics. Unfavorable features include less than 5 feet of suitable material and a high content of stones or boulders, organic matter, or salts or sodium. A high water table affects the amount of usable material. It also affects traffic ability.

Aquifer-fed excavated ponds are pits or dugouts that extend to a ground-water aquifer or to a depth below a permanent water table. Excluded are ponds that are fed only by surface runoff and embankment ponds that impound water 3 feet or more above the original surface. Excavated ponds are affected by depth to a permanent water table, permeability of the aquifer, and quality of the water as inferred from the salinity of the soil. Depth to bedrock and the content of large stones affect the ease of excavation.

Drainage is the removal of excess surface and subsurface water from the soil. How easily and effectively the soil is drained depends on the depth to bedrock, to a cemented pan, or to other layers that affect the rate of water movement; permeability; depth to a high water table or depth of standing water if the soil is subject to ponding; slope; susceptibility to flooding; subsidence of organic layers; and the potential for frost action. Excavating and grading and the stability of ditch banks are affected by depth to bedrock or to a cemented pan, large stones, slope, and the hazard of cutbanks caving. The productivity of the soil after drainage is adversely affected by extreme acidity or by toxic substances in the root zone, such as salts, sodium, and sulfur. Availability of drainage outlets is not considered in the ratings.

Irrigation is the controlled application of water to supplement rainfall and support plant growth. The design and management of an irrigation system are affected by depth to the water table, the need for drainage, flooding, available water capacity, intake rate, permeability, erosion hazard, and slope. The construction of a system is affected by large stones and depth to bedrock or to a cemented pan. The performance of a system is affected by the depth of the root zone, the amount of salts or sodium, and soil reaction.

Terraces and diversions are embankments or a combination of channels and ridges constructed across a slope to control erosion and conserve moisture by intercepting runoff. Slope, wetness, large stones, and depth to bedrock or to a cemented pan affect the construction of terraces and diversions. A restricted rooting depth, a very limited hazard of wind erosion or water erosion, an excessively coarse texture, and restricted permeability adversely affect maintenance.

Grassed waterways are natural or constructed channels, generally broad and shallow, which conduct surface water to outlets at a non-erosive velocity. Large stones, wetness, slope, and depth to bedrock or to a cemented pan affect the construction of grassed waterways. A hazard of wind erosion, low available water capacity, restricted rooting depth, toxic substances such as salts and sodium, and restricted permeability adversely affect the growth and maintenance of the grass after construction.

WATER MANAGEMENT--Continued
Brown County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
Ac: Aksarben-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
Ad: Aksarben-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
Ae: Aksarben-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
Bs: Burchard-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Bx: Burchard-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Steinauer-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Ch: Chase-----	Limitation: flooding frost action percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly
Co: Contrary-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily	Limitation: erodes easily
Ga: Grundy-----	Limitation: frost action percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
Ju: Judson-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily	Limitation: erodes easily
Kd: Kennebec, CHANNELED-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
Ke: Kennebec-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
Kp: Kipson-----	Limitation: deep to water	Limitation: slope depth to rock	Limitation: large stones slope depth to rock	Limitation: large stones slope depth to rock
Sogn-----	Limitation: deep to water	Limitation: slope depth to rock	Limitation: slope depth to rock	Limitation: slope depth to rock
M-W: Miscellaneous Water-----	---	---	---	---
Ma: Marshall-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily	Limitation: erodes easily
Mb: Marshall-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Md: Martin-----	Limitation: frost action percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly
Mf: Martin-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily slope wetness	Limitation: erodes easily percs slowly slope
Mh: Mayberry-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
Mk: Monona-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily	Limitation: erodes easily
Mn: Monona-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope

WATER MANAGEMENT--Continued
Brown County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
Mt: Morrill-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Mw: Muscotah-----	Limitation: flooding percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly
My: Muscotah-----	Limitation: flooding percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly
No: Nodaway-----	Limitation: deep to water	Limitation: flooding	Limitation: erodes easily	Limitation: erodes easily
Om: Olmitz-----	Limitation: deep to water	Limitation: slope	Favorable	Favorable
Or: Orthents, Earthen Dam----	---	---	---	---
Pd: Padonia-----	Limitation: deep to water	Limitation: percs slowly slope depth to rock	Limitation: erodes easily percs slowly depth to rock	Limitation: erodes easily percs slowly depth to rock
Martin-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily slope wetness	Limitation: erodes easily percs slowly slope
Pe: Padonia-----	Limitation: deep to water	Limitation: percs slowly slope depth to rock	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock
Martin-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily slope wetness	Limitation: erodes easily percs slowly slope
Pf: Padonia-----	Limitation: deep to water	Limitation: percs slowly slope depth to rock	Limitation: erodes easily percs slowly depth to rock	Limitation: erodes easily percs slowly depth to rock
Oska-----	Limitation: deep to water	Limitation: percs slowly slope depth to rock	Limitation: erodes easily percs slowly depth to rock	Limitation: erodes easily percs slowly depth to rock
Pm: Pawnee-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
Pn: Pawnee-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily slope wetness	Limitation: erodes easily slope wetness
Po: Pawnee-----	Limitation: frost action percs slowly slope	Limitation: slope wetness droughty	Limitation: erodes easily slope wetness	Limitation: erodes easily slope wetness
Pt: Pits, Quarries--	---	---	---	---
Pw: Pohocco-----	Limitation: deep to water	Limitation: erodes easily slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Netawaka-----	Limitation: deep to water	Limitation: erodes easily slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Px: Pohocco-----	Limitation: deep to water	Limitation: erodes easily slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Netawaka-----	Limitation: deep to water	Limitation: erodes easily slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Re: Reading-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily

WATER MANAGEMENT--Continued
Brown County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
Sg: Shelby-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Sm: Shelby-----	Limitation: deep to water	Limitation: slope	Limitation: slope	Limitation: slope
W: Water-----	---	---	---	---
Wa: Wabash-----	Limitation: flooding percs slowly	Limitation: slow intake wetness droughty	Limitation: percs slowly wetness	Limitation: percs slowly wetness droughty
We: Wamego-----	Limitation: deep to water	Limitation: percs slowly slope depth to rock	Limitation: erodes easily percs slowly depth to rock	Limitation: erodes easily percs slowly depth to rock
Wg: Wamego-----	Limitation: deep to water	Limitation: percs slowly slope depth to rock	Limitation: erodes easily percs slowly depth to rock	Limitation: erodes easily percs slowly depth to rock
Vinland-----	Limitation: deep to water	Limitation: slope depth to rock	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock
Wm: Wymore-----	Limitation: frost action percs slowly	Limitation: percs slowly wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness
Wn: Wymore-----	Limitation: frost action percs slowly	Limitation: percs slowly wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness

WATER MANAGEMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ac: Aksarben-----	90	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.00	Very limited Deep to water	1.00
Ad: Aksarben-----	87	Somewhat limited Seepage	0.70	Not limited		Very limited Deep to water	1.00
Ae: Aksarben-----	85	Somewhat limited Seepage	0.70	Not limited		Very limited Deep to water	1.00
Bs: Burchard-----	85	Somewhat limited Seepage	0.05	Not limited		Very limited Deep to water	1.00
Bx: Burchard-----	55	Somewhat limited Seepage Slope	0.05 0.03	Not limited		Very limited Deep to water	1.00
Steinauer-----	40	Somewhat limited Seepage Slope	0.05 0.03	Not limited		Very limited Deep to water	1.00
Ch: Chase-----	90	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.73	Very limited Deep to water	1.00
Co: Contrary-----	85	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.95	Very limited Deep to water	1.00
Ga: Grundy-----	90	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.78	Very limited Deep to water	1.00
Ju: Judson-----	95	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.37	Very limited Deep to water	1.00
Kd: Kennebec, CHanneled-	85	Somewhat limited Seepage	0.70	Somewhat limited Piping Depth to saturated zone	0.81 0.09	Somewhat limited Deep to water Slow refill Cutbanks cave	0.54 0.30 0.10
Ke: Kennebec-----	89	Somewhat limited Seepage	0.70	Somewhat limited Piping Depth to saturated zone	0.81 0.09	Somewhat limited Deep to water Slow refill Cutbanks cave	0.54 0.30 0.10
Kp: Kipson-----	60	Somewhat limited Depth to bedrock Slope	0.50 0.08	Very limited Thin layer Piping	1.00 0.50	Very limited Deep to water	1.00
Sogn-----	30	Very limited Seepage Depth to bedrock Slope	1.00 1.00 0.01	Very limited Thin layer Piping	1.00 0.12	Very limited Deep to water	1.00
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Marshall-----	97	Somewhat limited Seepage	0.70	Not limited		Very limited Deep to water	1.00
Mb: Marshall-----	82	Somewhat limited		Not limited		Very limited	

WATER MANAGEMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Md: Martin-----	85	Seepage	0.70			Deep to water	1.00
		Not limited		Very limited Hard to pack Depth to saturated zone	1.00 1.00	Very limited Deep to water	1.00
Mf: Martin-----	90	Not limited		Very limited Hard to pack Depth to saturated zone	1.00 1.00	Very limited Deep to water	1.00
Mh: Mayberry-----	85	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.36	Very limited Deep to water	1.00
Mk: Monona-----	90	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.37	Very limited Deep to water	1.00
Mn: Monona-----	82	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.37	Very limited Deep to water	1.00
Mt: Morrill-----	87	Very limited Seepage	1.00	Somewhat limited Seepage	0.31	Very limited Deep to water	1.00
Mw: Muscotah-----	87	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00 0.69	Somewhat limited Slow refill Cutbanks cave	0.95 0.10
My: Muscotah-----	87	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00 0.77	Very limited Slow refill Cutbanks cave	1.00 0.10
No: Nodaway-----	90	Somewhat limited Seepage	0.70	Somewhat limited Piping Depth to saturated zone	0.68 0.46	Somewhat limited Slow refill Deep to water Cutbanks cave	0.30 0.24 0.10
Om: Olmitz-----	93	Somewhat limited Seepage	0.70	Somewhat limited Depth to saturated zone Piping	0.09 0.01	Somewhat limited Deep to water Slow refill Cutbanks cave	0.54 0.30 0.10
Or: Orthents, Earthen Dam-----	100	Not rated		Not rated		Not rated	
Pd: Padonia-----	50	Somewhat limited Seepage Depth to bedrock	0.05 0.02	Somewhat limited Thin layer Hard to pack	0.61 0.09	Very limited Deep to water	1.00
Martin-----	40	Not limited		Very limited Hard to pack Depth to saturated zone	1.00 1.00	Very limited Deep to water	1.00
Pe: Padonia-----	60	Somewhat limited Slope Seepage Depth to bedrock	0.06 0.05 0.02	Somewhat limited Thin layer Hard to pack	0.61 0.09	Very limited Deep to water	1.00

WATER MANAGEMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Martin-----	30	Somewhat limited Slope	0.00	Very limited Hard to pack Depth to saturated zone	1.00 1.00	Very limited Deep to water	1.00
Pf: Padonia-----	55	Somewhat limited Seepage Depth to bedrock	0.05 0.02	Somewhat limited Thin layer Hard to pack	0.61 0.09	Very limited Deep to water	1.00
Oska-----	40	Somewhat limited Depth to bedrock	0.69	Somewhat limited Thin layer Hard to pack	0.70 0.28	Very limited Deep to water	1.00
Pm: Pawnee-----	85	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.69	Very limited Deep to water	1.00
Pn: Pawnee-----	83	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.69	Very limited Deep to water	1.00
Po: Pawnee-----	84	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.72	Very limited Deep to water	1.00
Pt: Pits, Quarries-----	100	Not rated		Not rated		Not rated	
Pw: Pohocco-----	50	Somewhat limited Seepage Slope	0.70 0.02	Somewhat limited Piping	0.81	Very limited Deep to water	1.00
Netawaka-----	40	Somewhat limited Seepage Slope	0.70 0.02	Very limited Piping	1.00	Very limited Deep to water	1.00
Px: Pohocco-----	50	Somewhat limited Seepage Slope	0.70 0.15	Somewhat limited Piping	0.81	Very limited Deep to water	1.00
Netawaka-----	40	Somewhat limited Seepage Slope	0.70 0.15	Very limited Piping	1.00	Very limited Deep to water	1.00
Re: Reading-----	90	Somewhat limited Seepage	0.57	Somewhat limited Depth to saturated zone Piping	0.09 0.00	Somewhat limited Deep to water Slow refill Cutbanks cave	0.54 0.43 0.10
Sg: Shelby-----	88	Somewhat limited Seepage	0.05	Not limited		Very limited Deep to water	1.00
Sm: Shelby-----	85	Somewhat limited Seepage Slope	0.05 0.03	Not limited		Very limited Deep to water	1.00
W: Water-----	100	Not rated		Not rated		Not rated	
Wa: Wabash-----	85	Not limited		Very limited Depth to saturated zone	1.00	Very limited Slow refill	1.00

WATER MANAGEMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
We: Wamego-----	90	Somewhat limited Depth to bedrock	0.26	Hard to pack Somewhat limited Thin layer	1.00 0.96	Cutbanks cave Very limited Deep to water	0.10 1.00
Wg: Wamego-----	50	Somewhat limited Depth to bedrock	0.26	Somewhat limited Thin layer	0.96	Very limited Deep to water	1.00
Vinland-----	40	Somewhat limited Depth to bedrock	0.50	Very limited Thin layer Piping	1.00 0.50	Very limited Deep to water	1.00
Wm: Wymore-----	90	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00 0.70	Very limited Deep to water	1.00
Wn: Wymore-----	82	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00 0.64	Very limited Deep to water	1.00

SANITARY FACILITIES
Brown County, Kansas

Sanitary Facilities

The following tables show the degree and kind of soil limitations that affect septic tank absorption fields, sewage lagoons, sanitary landfills, and daily cover for landfill. The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect these uses. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Septic tank absorption fields are areas in which effluent from a septic tank is distributed into the soil through subsurface tiles or perforated pipe. Only that part of the soil between depths of 24 and 60 inches is evaluated. The ratings are based on the soil properties that affect absorption of the effluent, construction and maintenance of the system, and public health. Permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, and flooding affect absorption of the effluent. Stones and boulders, ice, and bedrock or a cemented pan interfere with installation. Subsidence interferes with installation and maintenance. Excessive slope may cause lateral seepage and surfacing of the effluent in downslope areas.

Some soils are underlain by loose sand and gravel or fractured bedrock at a depth of less than 4 feet below the distribution lines. In these soils the absorption field may not adequately filter the effluent, particularly when the system is new. As a result, the ground water may become contaminated.

Sewage lagoons are shallow ponds constructed to hold sewage while aerobic bacteria decompose the solid and liquid wastes. Lagoons should have a nearly level floor surrounded by cut slopes or embankments of compacted soil. Nearly impervious soil material for the lagoon floor and sides is required to minimize seepage and contamination of ground water. Considered in the ratings are slope, permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, flooding, large stones, and content of organic matter.

Soil permeability is a critical property affecting the suitability for sewage lagoons. Most porous soils eventually become sealed when they are used as sites for sewage lagoons. Until sealing occurs, however, the hazard of pollution is severe. Soils that have a permeability rate of more than 2 inches per hour are too porous for the proper functioning of sewage lagoons. In these soils, seepage of the effluent can result in contamination of the ground water. Ground-water contamination is also a hazard if fractured bedrock is within a depth of 40 inches, if the water table is high enough to raise the level of sewage in the lagoon, or if floodwater overtops the lagoon.

A high content of organic matter is detrimental to proper functioning of the lagoon because it inhibits aerobic activity. Slope, bedrock, and cemented pans can cause construction problems, and large stones can hinder compaction of the lagoon floor. If the lagoon is to be uniformly deep throughout, the slope must be gentle enough and the soil material must be thick enough over bedrock or a cemented pan to make land smoothing practical.

A trench sanitary landfill is an area where solid waste is placed in successive layers in an excavated trench. The waste is spread, compacted, and covered daily with a thin layer of soil excavated at the site. When the trench is full, a final cover of soil material at least 2 feet thick is placed over the landfill. The ratings in the table are based on the soil properties that affect the risk of pollution, the ease of excavation, trafficability, and revegetation. These properties include permeability, depth to bedrock or a cemented pan, depth to a water table, ponding, slope, flooding, texture, stones and boulders, highly organic layers, soil reaction, and content of salts and sodium. Unless otherwise stated, the ratings apply only to that part of the soil within a depth of about 6 feet. For deeper trenches, onsite investigation may be needed.

Hard, nonrippable bedrock, creviced bedrock, or highly permeable strata in or directly below the proposed trench bottom can affect the ease of excavation and the hazard of ground-water pollution. Slope affects construction of the trenches and the movement of surface water around the landfill. It also affects the construction and performance of roads in areas of the landfill.

Soil texture and consistence affect the ease with which the trench is dug and the ease with which the soil can be used as daily or final cover. They determine the workability of the soil when dry and when wet. Soils that are plastic and sticky when wet are difficult to excavate, grade, or compact and are difficult to place as a uniformly thick cover over a layer of refuse.

The soil material used as the final cover for a trench landfill should be suitable for plants. It should not have excess sodium or salts and should not be too acid. The surface layer generally has the best workability, the highest content of organic matter, and the best potential for plants. Material from the surface layer should be stockpiled for use as the final cover.

SANITARY FACILITIES
Brown County, Kansas

In an area sanitary landfill, solid waste is placed in successive layers on the surface of the soil. The waste is spread, compacted, and covered daily with a thin layer of soil from a source away from the site. A final cover of soil material at least 2 feet thick is placed over the completed landfill. The ratings in the table are based on the soil properties that affect trafficability and the risk of pollution. These properties include flooding, permeability, depth to a water table, ponding, slope, and depth to bedrock or a cemented pan.

Flooding is a serious problem because it can result in pollution in areas downstream from the landfill. If permeability is too rapid or if fractured bedrock, a fractured cemented pan, or the water table is close to the surface, the leachate can contaminate the water supply. Slope is a consideration because of the extra grading required to maintain roads in the steeper areas of the landfill. Also, leachate may flow along the surface of the soils in the steeper areas and cause difficult seepage problems.

Daily cover for landfill is the soil material that is used to cover compacted solid waste in an area sanitary landfill. The soil material is obtained offsite, transported to the landfill, and spread over the waste. The ratings in the table also apply to the final cover for a landfill. They are based on the soil properties that affect workability, the ease of digging, and the ease of moving and spreading the material over the refuse daily during wet and dry periods. These properties include soil texture, depth to a water table, ponding, rock fragments, slope, depth to bedrock or a cemented pan, reaction, and content of salts, sodium, or lime.

Loamy or silty soils that are free of large stones and excess gravel are the best cover for a landfill. Clayey soils may be sticky and difficult to spread; sandy soils are subject to wind erosion.

Slope affects the ease of excavation and of moving the cover material. Also, it can influence runoff, erosion, and reclamation of the borrow area.

After soil material has been removed, the soil material remaining in the borrow area must be thick enough over bedrock, a cemented pan, or the water table to permit revegetation. The soil material used as the final cover for a landfill should be suitable for plants. It should not have excess sodium, salts, or lime and should not be too acid.

SANITARY FACILITIES--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Ac: Aksarben-----	90	Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
Ad: Aksarben-----	87	Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
Ae: Aksarben-----	85	Very limited Restricted permeability Slope	1.00 0.00	Slope Very limited Slope	0.33 1.00
Bs: Burchard-----	85	Very limited Restricted permeability Slope	1.00 0.04	Very limited Slope	1.00
Bx: Burchard-----	55	Very limited Restricted permeability Slope	1.00 1.00	Very limited Slope	1.00
Steinauer-----	40	Very limited Restricted permeability Slope	1.00 1.00	Very limited Slope	1.00
Ch: Chase-----	90	Very limited Restricted permeability Depth to saturated zone Flooding	1.00 1.00 0.40	Somewhat limited Flooding Depth to saturated zone	0.40 0.25
Co: Contrary-----	85	Somewhat limited Restricted permeability	0.50	Very limited Slope Seepage	1.00 0.50
Ga: Grundy-----	90	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Not limited	
Ju: Judson-----	95	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage Slope	0.50 0.33
Kd: Kennebec, CHanneled-	85	Very limited Flooding Depth to saturated zone Restricted permeability	1.00 1.00 0.50	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 0.50
Ke: Kennebec-----	89	Very limited Flooding Depth to saturated zone Restricted permeability	1.00 1.00 0.50	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 0.50
Kp: Kipson-----	60	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to soft bedrock Slope Seepage	1.00 1.00 0.50
Sogn-----	30	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to hard bedrock Slope	1.00 1.00
M-W: Miscellaneous Water-	100	Not rated		Not rated	
Ma: Marshall-----	97	Somewhat limited		Somewhat limited	

SANITARY FACILITIES--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Mb: Marshall-----	82	Restricted permeability	0.50	Seepage	0.50
				Slope	0.33
Md: Martin-----	85	Somewhat limited Restricted permeability	0.50	Very limited Slope	1.00
		Slope	0.00	Seepage	0.50
Mf: Martin-----	90	Very limited Restricted permeability	1.00	Somewhat limited Depth to saturated zone	0.25
		Depth to saturated zone	1.00	Slope	0.09
Mh: Mayberry-----	85	Very limited Restricted permeability	1.00	Very limited Slope	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	0.25
Mk: Monona-----	90	Slope	0.00		
		Very limited Restricted permeability	1.00	Somewhat limited Slope	0.33
Mn: Monona-----	82	Depth to saturated zone	1.00		
		Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
Mt: Morrill-----	87	Slope	0.00	Slope	0.33
		Somewhat limited Restricted permeability	0.50	Very limited Slope	1.00
Mw: Muscotah-----	87	Slope	0.00	Seepage	0.50
		Very limited Restricted permeability	1.00	Very limited Slope	1.00
My: Muscotah-----	87	Filtering capacity	1.00	Seepage	1.00
		Slope	0.04		
No: Nodaway-----	90	Very limited Flooding	1.00	Very limited Flooding	1.00
		Restricted permeability	1.00	Depth to saturated zone	1.00
Om: Olmitz-----	93	Depth to saturated zone	1.00	Seepage	0.50
		Restricted permeability	0.50		
Or: Orthents, Earthen Dam-----	100	Depth to saturated zone	1.00	Very limited Flooding	1.00
		Restricted permeability	0.50	Depth to saturated zone	1.00
Pd: Padonia-----	50	Very limited Depth to saturated zone	1.00	Seepage	0.50
		Restricted permeability	0.50		
				Slope	0.33
		Not rated		Not rated	
		Very limited Restricted permeability	1.00	Very limited Depth to soft bedrock	1.00

SANITARY FACILITIES--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Martin----- Pe: Padonia-----	40	Depth to bedrock	1.00	Slope	1.00
		Very limited		Very limited	
		Restricted	1.00	Slope	1.00
		permeability			
Martin----- Pf: Padonia-----	60	Depth to	1.00	Depth to	0.25
		saturated zone		saturated zone	
		Slope	0.00		
Martin----- Pm: Pawnee-----	30	Very limited		Very limited	
		Restricted	1.00	Depth to soft	1.00
		permeability		bedrock	
		Depth to bedrock	1.00	Slope	1.00
Martin----- Pn: Pawnee-----	30	Slope	1.00		
		Very limited		Very limited	
		Restricted	1.00	Slope	1.00
		permeability			
Martin----- Po: Pawnee-----	85	Depth to	1.00	Depth to	0.25
		saturated zone		saturated zone	
		Slope	0.37		
Oska----- Pm: Pawnee-----	55	Very limited		Very limited	
		Restricted	1.00	Depth to soft	1.00
		permeability		bedrock	
		Depth to bedrock	1.00	Slope	1.00
Oska----- Pn: Pawnee-----	40	Slope	1.00		
		Very limited		Very limited	
		Restricted	1.00	Depth to hard	1.00
		permeability		bedrock	
Oska----- Po: Pawnee-----	85	Depth to bedrock	1.00	Slope	1.00
Pm: Pawnee-----	85	Very limited		Somewhat limited	
		Restricted	1.00	Slope	0.33
		permeability			
		Depth to	1.00		
Pn: Pawnee-----	83	saturated zone			
		Very limited		Very limited	
		Restricted	1.00	Slope	1.00
		permeability			
Pn: Pawnee-----	83	Depth to	1.00		
		saturated zone			
		Slope	0.04		
Po: Pawnee-----	84	Very limited		Very limited	
		Restricted	1.00	Slope	1.00
		permeability			
		Depth to	1.00		
Pt: Pits, Quarries-----	100	saturated zone			
		Slope	0.04		
Pw: Pohocco-----	50	Not rated		Not rated	
Netawaka-----	40	Somewhat limited		Very limited	
		Slope	0.96	Slope	1.00
		Restricted	0.50	Seepage	0.50
		permeability			
Netawaka-----	40	Somewhat limited		Very limited	
		Slope	0.96	Slope	1.00
		Restricted	0.50	Seepage	0.50
		permeability			
Px: Pohocco-----	50				
		Very limited		Very limited	
		Slope	1.00	Slope	1.00
		Restricted	0.50	Seepage	0.50
Netawaka-----	40	permeability			
		Very limited		Very limited	
		Slope	1.00	Slope	1.00
		Restricted	0.50	Seepage	0.50
Re: Reading-----	90	permeability			
		Very limited		Somewhat limited	
		Depth to	1.00	Depth to	1.00
		saturated zone		saturated zone	
Sg: Shelby-----	88	Restricted	0.68	Flooding	0.40
		permeability			
		Flooding	0.40	Seepage	0.32
Sg: Shelby-----	88	Very limited		Very limited	
		Restricted	1.00	Slope	1.00
		permeability			

SANITARY FACILITIES--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Sm: Shelby-----	85	Slope Very limited Restricted permeability Slope	0.04 1.00 1.00	Very limited Slope	1.00
W: Water-----	100	Not rated		Not rated	
Wa: Wabash-----	85	Very limited Flooding Restricted permeability Depth to saturated zone	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 1.00
We: Wamego-----	90	Very limited Restricted permeability Depth to bedrock	1.00 1.00	Very limited Depth to soft bedrock Slope	1.00 0.67
Wg: Wamego-----	50	Very limited Restricted permeability Depth to bedrock Slope	1.00 1.00 0.04	Very limited Depth to soft bedrock Slope	1.00 1.00
Vinland-----	40	Very limited Depth to bedrock Slope	1.00 0.04	Very limited Depth to soft bedrock Slope Seepage	1.00 1.00 0.50
Wm: Wymore-----	90	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Somewhat limited Slope	0.33
Wn: Wymore-----	82	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Slope	1.00

SANITARY FACILITIES--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ac: Aksarben-----	90	Not limited		Not limited		Somewhat limited Too clayey	0.50
Ad: Aksarben-----	87	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
Ae: Aksarben-----	85	Somewhat limited Too clayey Slope	0.50 0.00	Somewhat limited Slope	0.00	Very limited Hard to compact Too clayey Slope	1.00 0.50 0.00
Bs: Burchard-----	85	Somewhat limited Too clayey Slope	0.50 0.04	Somewhat limited Slope	0.04	Somewhat limited Too clayey Slope	0.50 0.04
Bx: Burchard-----	55	Very limited Slope Too clayey	1.00 0.50	Very limited Slope	1.00	Very limited Slope Too clayey	1.00 0.50
Steinauer-----	40	Very limited Slope Too clayey	1.00 0.50	Very limited Slope	1.00	Very limited Hard to compact Slope Too clayey	1.00 1.00 0.50
Ch: Chase-----	90	Very limited Depth to saturated zone Too clayey Flooding	1.00 0.50 0.40	Somewhat limited Depth to saturated zone Flooding	0.75 0.40	Very limited Too clayey Hard to compact Depth to saturated zone	1.00 1.00 0.86
Co: Contrary-----	85	Not limited		Not limited		Not limited	
Ga: Grundy-----	90	Very limited Depth to saturated zone Too clayey	1.00 1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone Too clayey Hard to compact	1.00 1.00 1.00
Ju: Judson-----	95	Somewhat limited Too clayey	0.50	Not limited		Not limited	
Kd: Kennebec, CHANNELED-	85	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 1.00	Not limited	
Ke: Kennebec-----	89	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 1.00	Not limited	
Kp: Kipson-----	60	Very limited Depth to bedrock Slope Too clayey	1.00 1.00 0.50	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to bedrock Slope Carbonate content Too clayey	1.00 1.00 1.00 0.50
Sogn-----	30	Very limited Depth to bedrock Seepage Slope Too clayey	1.00 1.00 0.84 0.50	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Slope Too clayey	1.00 0.84 0.50
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Marshall-----	97	Not limited		Not limited		Not limited	
Mb: Marshall-----	82	Somewhat limited Too clayey Slope	0.50 0.00	Somewhat limited Slope	0.00	Somewhat limited Too clayey Slope	0.50 0.00
Md: Martin-----	85	Very limited Too clayey Depth to saturated zone	1.00 1.00	Somewhat limited Depth to saturated zone	0.75	Very limited Too clayey Hard to compact Depth to saturated zone	1.00 1.00 0.86
Mf: Martin-----	90	Very limited		Somewhat limited		Very limited	

SANITARY FACILITIES--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Mh: Mayberry-----	85	Too clayey	1.00	Depth to saturated zone Slope	0.75 0.00	Too clayey	1.00
		Depth to saturated zone	1.00			Hard to compact	1.00
		Slope	0.00			Depth to saturated zone	0.86
						Slope	0.00
Mk: Monona----- Mn: Monona----- Mt: Morrill----- Mw: Muscotah-----	90	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Too clayey	1.00			Too clayey	1.00
						Hard to compact	1.00
Mn: Monona----- Mt: Morrill----- Mw: Muscotah-----	82	Not limited		Not limited	0.00	Not limited	
		Somewhat limited Slope	0.00			Somewhat limited Slope	0.00
Mt: Morrill----- Mw: Muscotah-----	87	Very limited Seepage Slope	1.00 0.04	Somewhat limited Slope	0.04	Somewhat limited Slope	0.04
Mw: Muscotah----- My: Muscotah----- No: Nodaway----- Om: Olmitz----- Or: Orthents, Earthen Dam----- Pd: Padonia----- Martin----- Pe: Padonia----- Martin----- Pf: Padonia-----	87	Very limited Flooding Depth to saturated zone	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 1.00 1.00	Very limited Too clayey Hard to compact	1.00 1.00
		Too clayey	1.00			Depth to saturated zone	0.87
My: Muscotah----- No: Nodaway----- Om: Olmitz----- Or: Orthents, Earthen Dam----- Pd: Padonia----- Martin----- Pe: Padonia----- Martin----- Pf: Padonia-----	87	Very limited Flooding Depth to saturated zone	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 1.00 1.00	Very limited Too clayey Hard to compact	1.00 1.00
		Too clayey	1.00			Depth to saturated zone	0.87
No: Nodaway----- Om: Olmitz----- Or: Orthents, Earthen Dam----- Pd: Padonia----- Martin----- Pe: Padonia----- Martin----- Pf: Padonia-----	90	Very limited Flooding Depth to saturated zone	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 1.00 1.00	Somewhat limited Too clayey Depth to saturated zone	0.50 0.11
		Too clayey	0.50				
Om: Olmitz----- Or: Orthents, Earthen Dam----- Pd: Padonia----- Martin----- Pe: Padonia----- Martin----- Pf: Padonia-----	93	Very limited Depth to saturated zone	1.00 0.50	Very limited Depth to saturated zone	1.00	Somewhat limited Too clayey	0.50
		Too clayey	0.50				
Or: Orthents, Earthen Dam----- Pd: Padonia----- Martin----- Pe: Padonia----- Martin----- Pf: Padonia-----	100	Not rated		Not rated		Not rated	
Pd: Padonia----- Martin----- Pe: Padonia----- Martin----- Pf: Padonia-----	50	Very limited Depth to bedrock Too clayey	1.00 1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey	1.00 1.00
						Hard to compact	1.00
Martin----- Pe: Padonia----- Martin----- Pf: Padonia-----	40	Very limited Too clayey	1.00	Somewhat limited Depth to saturated zone Slope	0.75 0.00	Very limited Too clayey	1.00
		Depth to saturated zone	1.00			Hard to compact	1.00
		Slope	0.00			Depth to saturated zone Slope	0.86 0.00
Pe: Padonia----- Martin----- Pf: Padonia-----	60	Very limited Depth to bedrock Too clayey Slope	1.00 1.00 1.00	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to bedrock Too clayey Slope	1.00 1.00 1.00
						Hard to compact	1.00
Martin----- Pf: Padonia-----	30	Very limited Too clayey	1.00	Somewhat limited Depth to saturated zone Slope	0.75 0.37	Very limited Too clayey	1.00
		Depth to saturated zone	1.00			Hard to compact	1.00
		Slope	0.37			Depth to saturated zone Slope	0.86 0.37
Pf: Padonia-----	55	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00
		Too clayey	1.00			Too clayey	1.00

SANITARY FACILITIES--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Oska-----	40	Very limited Depth to bedrock Too clayey	1.00 1.00	Very limited Depth to bedrock	1.00	Hard to compact Very limited Depth to bedrock Too clayey Hard to compact	1.00 1.00 1.00 1.00
Pm: Pawnee-----	85	Very limited Depth to saturated zone Too clayey	1.00 1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone Too clayey Hard to compact	1.00 1.00 1.00
Pn: Pawnee-----	83	Very limited Depth to saturated zone Too clayey Slope	1.00 1.00 0.04	Very limited Depth to saturated zone Slope	1.00 0.04	Very limited Depth to saturated zone Too clayey Hard to compact Slope	1.00 1.00 1.00 0.04
Po: Pawnee-----	84	Very limited Depth to saturated zone Too clayey Slope	1.00 1.00 0.04	Very limited Depth to saturated zone Slope	1.00 0.04	Very limited Depth to saturated zone Too clayey Hard to compact Slope	1.00 1.00 1.00 0.04
Pt: Pits, Quarries-----	100	Not rated		Not rated		Not rated	
Pw: Pohocco-----	50	Somewhat limited Slope	0.96	Somewhat limited Slope	0.96	Somewhat limited Slope	0.96
Netawaka-----	40	Somewhat limited Slope	0.96	Somewhat limited Slope	0.96	Somewhat limited Slope	0.96
Px: Pohocco-----	50	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00
Netawaka-----	40	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00
Re: Reading-----	90	Very limited Depth to saturated zone Too clayey Flooding	1.00 0.50 0.40	Very limited Depth to saturated zone Flooding	1.00 0.40	Somewhat limited Too clayey	0.50
Sg: Shelby-----	88	Somewhat limited Too clayey Slope	0.50 0.04	Somewhat limited Slope	0.04	Somewhat limited Too clayey Slope	0.50 0.04
Sm: Shelby-----	85	Very limited Slope Too clayey	1.00 0.50	Very limited Slope	1.00	Very limited Slope Too clayey	1.00 0.50
W: Water-----	100	Not rated		Not rated		Not rated	
Wa: Wabash-----	85	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too clayey	1.00
		Too clayey	1.00			Hard to compact	1.00
We: Wamego-----	90	Very limited Depth to bedrock Too clayey	1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey	1.00 0.50
Wg: Wamego-----	50	Very limited Depth to bedrock Too clayey Slope	1.00 0.50 0.04	Very limited Depth to bedrock Slope	1.00 0.04	Very limited Depth to bedrock Too clayey Slope	1.00 0.50 0.04
Vinland-----	40	Very limited Depth to bedrock Too clayey Slope	1.00 0.50 0.04	Very limited Depth to bedrock Slope	1.00 0.04	Very limited Depth to bedrock Too clayey Slope	1.00 0.50 0.04
Wm: Wymore-----	90	Very limited Depth to saturated zone Too clayey	1.00 0.50	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone Too clayey Hard to compact	1.00 1.00 1.00

SANITARY FACILITIES--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Wn: Wymore-----	82	Very limited Depth to saturated zone Too clayey	1.00 0.50	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone Hard to compact Too clayey	1.00 1.00 0.50

AGRICULTURAL WASTE MANAGEMENT
Brown County, Kansas

The nature of the soil is also important in the application of organic wastes and wastewater to land as fertilizers and irrigation; it is also important when the soil is used as a medium for treatment and disposal of these wastes. Favorable soil properties are required to prevent environmental damage.

The use of organic wastes and wastewater as production resources will result in energy conservation, prevent the waste of these important resources, and prevent problems associated with their disposal. Where disposal is the goal, and a maximum amount is disposed in a minimum area to hold costs to a minimum, risk of environmental damage is the principal constraint. Where the reuse goal is pursued, and a minimum amount is applied to a maximum area to obtain the greatest benefit, environmental damage is unlikely.

Interpretations developed for waste management may include ratings for (1) manure and food processing wastes; (2) municipal sewage sludge; (3) irrigation use of wastewater; or (4) treatment of wastewater by the slow rate process, overland flow process, or rapid infiltration process. If available, these should be located in this subsection.

Soil properties are important considerations in areas where soils are used as sites for the treatment and disposal of organic waste and wastewater. Selection of soils with properties that favor waste management can help to prevent environmental damage.

The Ag-Waste tables show the degree and kind of soil limitations affecting the treatment of agricultural waste, including municipal and food-processing wastewater and effluent from lagoons or storage ponds. Municipal wastewater is the waste stream from a municipality. It contains domestic waste and may contain industrial waste. It may have received primary or secondary treatment. It is rarely untreated sewage. Food-processing wastewater results from the preparation of fruits, vegetables, milk, cheese, and meats for public consumption. In places it is high in content of sodium and chloride. In the context of these tables, the effluent in lagoons and storage ponds is from facilities used to treat or store food-processing wastewater or domestic or animal waste. Domestic and food-processing wastewater is very dilute, and the effluent from the facilities that treat or store it commonly is very low in content of carbonaceous and nitrogenous material; the content of nitrogen commonly ranges from 10 to 30 milligrams per liter. The wastewater from animal waste treatment lagoons or storage ponds, however, has much higher concentrations of these materials, mainly because the manure has not been diluted as much as the domestic waste. The content of nitrogen in this wastewater generally ranges from 50 to 2,000 milligrams per liter. When wastewater is applied, checks should be made to ensure that nitrogen, phosphorus, heavy metals, and salts are not added in excessive amounts.

The ratings in the tables are for waste management systems that not only dispose of and treat organic waste or wastewater but also are beneficial to crops (application of manure and food-processing waste, application of sewage sludge, and disposal of wastewater by irrigation) and for waste management systems that are designed only for the purpose of wastewater disposal and treatment (overland flow of wastewater, rapid infiltration of wastewater, and slow rate treatment of wastewater).

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect agricultural waste management. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are generally favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Application of manure and food-processing waste not only disposes of waste material but also can improve crop production by increasing the supply of nutrients in the soils where the material is applied. Manure is the excrement of livestock and poultry, and food-processing waste is damaged fruit and vegetables and the peelings, stems, leaves, pits, and soil particles removed in food preparation. The manure and food-processing waste are either solid, slurry, or liquid. Their nitrogen content varies. A high content of nitrogen limits the application rate. Toxic or otherwise dangerous wastes, such as those mixed with the lye used in food processing, are not considered in the ratings.

The ratings are based on the soil properties that affect absorption, plant growth, microbial activity, erodibility, the rate at which the waste is applied, and the method by which the waste is applied. The properties that affect absorption include permeability, depth to a water table, ponding, the sodium adsorption ratio, depth to bedrock or a cemented pan, and available water capacity. The properties that affect plant growth and microbial activity include reaction, the sodium adsorption ratio, salinity, and bulk density. The wind erodibility group, the soil erodibility factor K, and slope are considered in estimating the likelihood that wind erosion or water erosion will transport the waste material from the application site. Stones, cobbles, a water table, ponding, and flooding can hinder the application of waste. Permanently frozen soils are unsuitable for waste treatment.

Application of sewage sludge not only disposes of waste material but also can improve crop production by increasing the supply of nutrients in the soils where the material is applied. In the context of this table, sewage sludge is the residual product of the treatment of municipal sewage. The solid component consists mainly of cell mass, primarily bacteria cells that developed during secondary treatment and have incorporated soluble organics into their own bodies. The sludge has small amounts of sand, silt, and other solid debris. The content of nitrogen varies. Some sludge has constituents that are toxic to plants or hazardous to the food chain, such as heavy metals and exotic organic compounds, and should be analyzed chemically prior to use.

AGRICULTURAL WASTE MANAGEMENT
Brown County, Kansas

The content of water in the sludge ranges from about 98 percent to less than 40 percent. The sludge is considered liquid if it is more than about 90 percent water, slurry if it is about 50 to 90 percent water, and solid if it is less than about 50 percent water.

The ratings in the table are based on the soil properties that affect absorption, plant growth, microbial activity, erodibility, the rate at which the sludge is applied, and the method by which the sludge is applied. The properties that affect absorption, plant growth, and microbial activity include permeability, depth to a water table, ponding, the sodium adsorption ratio, depth to bedrock or a cemented pan, available water capacity, reaction, salinity, and bulk density. The wind erodibility group, the soil erodibility factor K, and slope are considered in estimating the likelihood that wind erosion or water erosion will transport the waste material from the application site. Stones, cobbles, a water table, ponding, and flooding can hinder the application of sludge. Permanently frozen soils are unsuitable for waste treatment.

Disposal of wastewater by irrigation not only disposes of municipal wastewater and wastewater from food-processing plants, lagoons, and storage ponds but also can improve crop production by increasing the amount of water available to crops. The ratings in the table are based on the soil properties that affect the design, construction, management, and performance of the irrigation system. The properties that affect design and management include the sodium adsorption ratio, depth to a water table, ponding, available water capacity, permeability, slope, and flooding. The properties that affect construction include stones, cobbles, depth to bedrock or a cemented pan, depth to a water table, and ponding.

The properties that affect performance include depth to bedrock or a cemented pan, bulk density, the sodium adsorption ratio, salinity, reaction, and the cation-exchange capacity, which is used to estimate the capacity of a soil to adsorb heavy metals. Permanently frozen soils are not suitable for disposal of wastewater by irrigation.

See the National Soil Handbook, September 1992, Part 620, for criteria used in rating soils for sanitary facilities and waste management.

AGRICULTURAL WASTE MANAGEMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food- processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ac: Aksarben-----	90	Somewhat limited Restricted permeability Too acid	0.30 0.11	Somewhat limited Too acid Restricted permeability	0.42 0.22	Somewhat limited Too acid Restricted permeability	0.42 0.22
Ad: Aksarben-----	87	Somewhat limited Restricted permeability Too acid	0.30 0.11	Somewhat limited Too acid Restricted permeability	0.42 0.22	Somewhat limited Too acid Restricted permeability Too steep for surface application	0.42 0.22 0.08
Ae: Aksarben-----	85	Somewhat limited Restricted permeability Too acid Slope	0.30 0.11 0.00	Somewhat limited Too acid Restricted permeability Slope	0.42 0.22 0.00	Very limited Too steep for surface application Too acid Restricted permeability Too steep for sprinkler application	1.00 0.42 0.22 0.10
Bs: Burchard-----	85	Somewhat limited Restricted permeability Too acid Slope	0.30 0.05 0.04	Somewhat limited Restricted permeability Too acid Slope	0.22 0.21 0.04	Very limited Too steep for surface application Restricted permeability Too steep for sprinkler application Too acid	1.00 0.22 0.22 0.21
Bx: Burchard-----	55	Very limited Slope Restricted permeability Too acid	1.00 0.30 0.05	Very limited Slope Restricted permeability Too acid	1.00 0.22 0.21	Very limited Too steep for surface application Too steep for sprinkler application Restricted permeability Too acid	1.00 1.00 0.22 0.21
Steinauer-----	40	Very limited Slope Restricted permeability	1.00 0.30	Very limited Slope Restricted permeability	1.00 0.22	Very limited Too steep for surface application Too steep for sprinkler application Restricted permeability	1.00 1.00 0.22
Ch: Chase-----	90	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Restricted permeability Depth to saturated zone Flooding	1.00 1.00 0.40	Very limited Restricted permeability Depth to saturated zone	1.00 1.00
Co: Contrary-----	85	Not limited		Not limited		Somewhat limited Too steep for surface application Too steep for sprinkler application	0.91 0.02
Ga: Grundy-----	90	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00

AGRICULTURAL WASTE MANAGEMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food- processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ju: Judson-----	95	Restricted permeability	1.00	Restricted permeability	1.00	Restricted permeability	1.00
		Not limited		Not limited		Somewhat limited Too steep for surface application	0.08
Kd: Kennebec, CHANNELED-	85	Very limited Flooding Depth to saturated zone	1.00 0.09	Very limited Flooding Depth to saturated zone	1.00 0.09	Very limited Flooding Depth to saturated zone	1.00 0.09
		Somewhat limited Flooding Depth to saturated zone	0.60 0.09	Very limited Flooding Depth to saturated zone	1.00 0.09	Somewhat limited Flooding Depth to saturated zone	0.60 0.09
Kp: Kipson-----	60	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to bedrock Too steep for surface application	1.00 1.00
		Droughty	0.94	Droughty	0.94	Too steep for sprinkler application	1.00
Sogn-----	30	Runoff limitation	0.40			Droughty	0.94
		Very limited Depth to bedrock Droughty Slope	1.00 1.00 0.84	Very limited Droughty Depth to bedrock Slope	1.00 1.00 0.84	Very limited Droughty Depth to bedrock Too steep for surface application	1.00 1.00 1.00
		Runoff limitation	0.40			Too steep for sprinkler application	0.89
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Marshall-----	97	Not limited		Not limited		Somewhat limited Too steep for surface application	0.08
Mb: Marshall-----	82	Somewhat limited Slope	0.00	Somewhat limited Slope	0.00	Very limited Too steep for surface application	1.00
						Too steep for sprinkler application	0.10
Md: Martin-----	85	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Restricted permeability Depth to saturated zone	1.00 1.00
		Too acid	0.03	Too acid	0.14	Too acid Too steep for surface application	0.14 0.00
Mf: Martin-----	90	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Restricted permeability Depth to saturated zone	1.00 1.00
		Too acid	0.03	Too acid	0.14	Too steep for surface application	1.00
		Slope	0.00	Slope	0.00	Too acid Too steep for sprinkler application	0.14 0.10

AGRICULTURAL WASTE MANAGEMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food- processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Mh: Mayberry-----	85	Very limited Depth to saturated zone Restricted permeability Runoff limitation Too acid	1.00 1.00 0.40 0.03	Very limited Depth to saturated zone Restricted permeability Too acid	1.00 1.00 0.14	Very limited Depth to saturated zone Restricted permeability Too acid Too steep for surface application	1.00 1.00 0.14 0.08
Mk: Monona-----	90	Not limited		Not limited		Somewhat limited Too steep for surface application	0.08
Mn: Monona-----	82	Somewhat limited Slope	0.00	Somewhat limited Slope	0.00	Very limited Too steep for surface application Too steep for sprinkler application	1.00 0.10
Mt: Morrill-----	87	Somewhat limited Restricted permeability Slope Too acid	0.30 0.04 0.02	Somewhat limited Restricted permeability Too acid Slope	0.22 0.07 0.04	Very limited Too steep for surface application Restricted permeability Too steep for sprinkler application Too acid	1.00 0.22 0.22 0.07
Mw: Muscotah-----	87	Very limited Restricted permeability Depth to saturated zone Flooding Runoff limitation	1.00 1.00 0.60 0.40	Very limited Restricted permeability Flooding Depth to saturated zone	1.00 1.00 1.00	Very limited Restricted permeability Depth to saturated zone Flooding	1.00 1.00 0.60
My: Muscotah-----	87	Very limited Restricted permeability Depth to saturated zone Flooding Runoff limitation	1.00 1.00 0.60 0.40	Very limited Restricted permeability Flooding Depth to saturated zone	1.00 1.00 1.00	Very limited Restricted permeability Depth to saturated zone Flooding	1.00 1.00 0.60
No: Nodaway-----	90	Somewhat limited Flooding Depth to saturated zone	0.60 0.46	Very limited Flooding Depth to saturated zone	1.00 0.46	Somewhat limited Flooding Depth to saturated zone	0.60 0.46
Om: Olmitz-----	93	Somewhat limited Depth to saturated zone	0.09	Somewhat limited Depth to saturated zone	0.09	Somewhat limited Depth to saturated zone Too steep for surface application	0.09 0.08
Or: Orthents, Earthen Dam-----	100	Not rated		Not rated		Not rated	
Pd: Padonia-----	50	Very limited Restricted permeability Depth to bedrock	1.00 0.03	Very limited Restricted permeability Depth to bedrock	1.00 0.03	Very limited Restricted permeability Too steep for surface application Depth to bedrock	1.00 0.91 0.03

AGRICULTURAL WASTE MANAGEMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food-processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Martin-----	40	Very limited		Very limited		Too steep for sprinkler application	0.02
		Restricted permeability	1.00	Restricted permeability	1.00	Very limited	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Restricted permeability	1.00
		Too acid	0.03	Too acid	0.14	Depth to saturated zone	1.00
		Slope	0.00	Slope	0.00	Too steep for surface application	0.14
Pe: Padonia-----	60					Too acid	0.10
		Very limited		Very limited		Too steep for sprinkler application	
		Restricted permeability	1.00	Restricted permeability	1.00	Too steep for surface application	1.00
		Slope	1.00	Slope	1.00	Restricted permeability	1.00
Martin-----	30	Depth to bedrock	0.03	Depth to bedrock	0.03	Too steep for sprinkler application	1.00
		Very limited		Very limited		Depth to bedrock	0.03
		Restricted permeability	1.00	Restricted permeability	1.00	Very limited	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Restricted permeability	1.00
		Slope	0.37	Slope	0.37	Too steep for surface application	1.00
Pf: Padonia-----	55	Too acid	0.03	Too acid	0.14	Depth to saturated zone	0.59
		Very limited		Very limited		Too steep for sprinkler application	0.14
		Restricted permeability	1.00	Restricted permeability	1.00	Too acid	
		Depth to bedrock	0.03	Depth to bedrock	0.03	Very limited	1.00
Oska-----	40	Restricted permeability	1.00	Restricted permeability	1.00	Restricted permeability	1.00
		Depth to bedrock	0.10	Too acid	0.14	Too steep for surface application	0.91
		Too acid	0.03	Depth to bedrock	0.10	Too steep for surface application	0.14
		Droughty	0.00	Droughty	0.00	Too acid	0.10
						Depth to bedrock	0.02
Pm: Pawnee-----	85					Too steep for sprinkler application	
		Very limited		Very limited		Very limited	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Restricted permeability	1.00	Restricted permeability	1.00	Restricted permeability	1.00
Pn: Pawnee-----	83	Runoff limitation	0.40			Too steep for surface application	0.08
		Very limited		Very limited		Very limited	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Restricted permeability	1.00	Restricted permeability	1.00	Restricted permeability	1.00
		Runoff limitation	0.40	Slope	0.04	Too steep for surface application	1.00

AGRICULTURAL WASTE MANAGEMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food- processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Po: Pawnee-----	84	Slope	0.04			Too steep for sprinkler application	0.22
		Very limited		Very limited		Very limited	
		Depth to	1.00	Depth to	1.00	Depth to	1.00
		saturated zone		saturated zone		saturated zone	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
Pt: Pits, Quarries-----	100	permeability		permeability		permeability	
		Runoff limitation	0.40	Slope	0.04	Too steep for surface application	1.00
		Slope	0.04			Too steep for sprinkler application	0.22
		Not rated		Not rated		Not rated	
Pw: Pohocco-----	50	Somewhat limited		Somewhat limited		Very limited	
		Slope	0.96	Slope	0.96	Too steep for surface application	1.00
						Too steep for sprinkler application	0.97
Netawaka-----	40	Somewhat limited		Somewhat limited		Very limited	
		Slope	0.96	Slope	0.96	Too steep for surface application	1.00
						Too steep for sprinkler application	0.97
Px: Pohocco-----	50	Very limited		Very limited		Very limited	
		Slope	1.00	Slope	1.00	Too steep for surface application	1.00
						Too steep for sprinkler application	1.00
Netawaka-----	40	Very limited		Very limited		Very limited	
		Slope	1.00	Slope	1.00	Too steep for surface application	1.00
						Too steep for sprinkler application	1.00
Re: Reading-----	90	Somewhat limited		Somewhat limited		Somewhat limited	
		Depth to	0.09	Flooding	0.40	Too acid	0.14
		saturated zone				Depth to	
Sg: Shelby-----	88	Too acid	0.03	Too acid	0.14	saturated zone	0.09
				Depth to	0.09		
		Saturated zone					
		Somewhat limited		Somewhat limited		Very limited	
		Restricted	0.30	Restricted	0.22	Too steep for surface application	1.00
Sg: Shelby-----	88	permeability		permeability		Too steep for surface application	
		Slope	0.04	Too acid	0.07	Restricted	0.22
		Too acid	0.02	Slope	0.04	permeability	0.22
Sm: Shelby-----	85	Too steep for sprinkler application		Too steep for sprinkler application		Too steep for sprinkler application	0.07
		Too acid		Too acid		Too acid	
Sm: Shelby-----	85	Very limited		Very limited		Very limited	
		Slope	1.00	Slope	1.00	Too steep for surface application	1.00
						Too steep for sprinkler application	1.00
Sm: Shelby-----	85	Restricted		Restricted		Too steep for sprinkler application	
		permeability	0.30	permeability	0.22		

AGRICULTURAL WASTE MANAGEMENT--Continued
Brown County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food- processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
W: Water-----	100	Too acid	0.02	Too acid	0.07	Restricted permeability Too acid	0.22 0.07
		Not rated		Not rated		Not rated	
Wa: Wabash-----	85	Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Depth to	1.00	Depth to	1.00	Depth to	1.00
We: Wamego-----	90	saturated zone		saturated zone		saturated zone	
		Flooding	0.60	Flooding	1.00	Flooding	0.60
		Runoff limitation	0.40	Too acid	0.07	Too acid	0.07
		Too acid	0.02				
Wg: Wamego-----	50	Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Depth to bedrock	0.84	Depth to bedrock	0.84	Depth to bedrock	0.84
Vinland-----	40	Droughty	0.41	Droughty	0.41	Droughty	0.41
		Slope	0.04	Too acid	0.14	Too steep for	0.41
		Too acid	0.03	Slope	0.04	sprinkler	0.22
						application	
Wm: Wymore-----	90	Very limited		Very limited		Very limited	
		Depth to	1.00	Depth to	1.00	Depth to	1.00
		saturated zone		saturated zone		saturated zone	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
Wn: Wymore-----	82	permeability		permeability		permeability	
		Runoff limitation	0.40	Too acid	0.14	Too acid	0.14
		Too acid	0.03			Too steep for	0.08
						surface	
		Very limited		Very limited		Very limited	
		Depth to	1.00	Depth to	1.00	Depth to	1.00
		saturated zone		saturated zone		saturated zone	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Runoff limitation	0.40	Too acid	0.14	Too steep for	0.91
		Too acid	0.03			surface	
						application	
		Too acid				Too acid	0.14
						Too steep for	0.02
						sprinkler	
						application	

WIN-PST SPISP II
SOIL SENSITIVITY TO PESTICIDE LOSS RATING REPORT

Soils Data Table: SOIL_KS Sort Order: MUSYM

Brown County, Kansas: KS013

						SPISP II Ratings		
MUSYM/SEQ#	COMPONENT/TEXTURE/MU%	HYD	KFACT	SURFACE DEPTH	% OM	Leaching	Solution	Adsorbed
						(SLP)	Runoff (SSRP)	Runoff (SARP)
Ac 1	AKSARBEN SICL 90%	B	0.32	9"	3.0%	I	I	I
Ad 1	AKSARBEN SICL 87%	B	0.32	6"	3.0%	I	I	I
Ae 1	AKSARBEN SICL 85%	B	0.32	6"	3.0%	I	I	I
Bs 1	BURCHARD CL 85%	B	0.28	9"	3.0%	I	I	I
Bx 1	BURCHARD CL 55%	B	0.28	9"	3.0%	I	I	H (s)
Bx 2	STEINAUER CL 40%	B	0.32	6"	1.3%	H	I	H (s)
Ch 1	CHASE SICL 90%	C	0.37	9"	3.0%	H (w)	H	H
Co 1	CONTRARY SICL 85%	B	0.32	6"	1.3%	H	I	I
Ga 1	GRUNDY SIL 90%	C	0.37	7"	3.0%	H (w)	H	H
Ju 1	JUDSON SIL 95%	B	0.28	7"	4.5%	I	I	I
Kd 1	KENNEBEC SIL 85%	B	0.28	8"	5.5%	I	I	I
Ke 1	KENNEBEC SIL 89%	B	0.28	8"	5.5%	I	I	I
Kp 1	KIPSON SICL 60%	D	0.32	8"	2.0%	V	H	H (s)
Kp 2	SOGN SICL 30%	D	0.32	12"	2.0%	V	H	H (s)
M-W 1	MISCELLANEOUS WATER 100%		0.00	0"	0.0%	?	?	?
Ma 1	MARSHALL SIL 97%	B	0.28	10"	3.5%	I	I	I
Mb 1	MARSHALL SICL 82%	B	0.28	6"	3.5%	I	I	I
Md 1	MARTIN SICL 85%	C	0.37	6"	3.0%	H (w)	H	H
Mf 1	MARTIN SICL 90%	C	0.37	6"	3.0%	H (w)	H	H
Mh 1	MAYBERRY CL 85%	D	0.37	10"	2.0%	H (w)	H	H
Mk 1	MONONA SIL 90%	B	0.28	11"	3.5%	I	I	I
Mn 1	MONONA SIL 82%	B	0.32	6"	2.5%	I	I	I
Mt 1	MORRILL L 87%	B	0.28	6"	2.0%	I	I	I
Mw 1	MUSCOTAH SIL 87%	D	0.32	9"	2.5%	H (w)	H	H
My 1	MUSCOTAH SICL 87%	D	0.37	9"	3.0%	H (w)	H	H
No 1	NODAWAY SIL 90%	B	0.32	7"	2.5%	I	I	I
Om 1	OLMITZ L 93%	B	0.24	7"	3.5%	I	I	I

WIN-PST SPISP II
SOIL SENSITIVITY TO PESTICIDE LOSS RATING REPORT

Soils Data Table: SOIL_KS Sort Order: MUSYM

Brown County, Kansas: KS013

Or 1	ORTHENTS, EARTHEN DAM 100%		0.00	0"	0.0% ?	?	?
Pd 1	PADONIA SICL 50%	C	0.37	11"	3.0% L	H	H
Pd 2	MARTIN SICL 40%	C	0.37	6"	3.0% H (w)	H	H
Pe 1	PADONIA SICL 60%	C	0.37	11"	3.0% L	H	H (s)
Pe 2	MARTIN SICL 30%	C	0.37	6"	3.0% H (w)	H	H
Pf 1	PADONIA SICL 55%	C	0.37	11"	3.0% L	H	H
Pf 2	OSKA SICL 40%	C	0.37	5"	2.0% L	H	H
Pm 1	PAWNEE CL 85%	D	0.37	7"	3.0% H (w)	H	H
Pn 1	PAWNEE CL 83%	D	0.37	7"	3.0% H (w)	H	H
Po 1	PAWNEE C 84%	D	0.37	5"	1.5% H (w)	H	H
Pt 1	Pits, quarries VAR 100%		0.00	60"	0.0% ?	?	?
Pw 1	POHOCCO SIL 50%	B	0.37	5"	1.3% H	I	H (s)
Pw 2	NETAWAKA SIL 40%	B	0.43	6"	1.5% H	I	H (s)
Px 1	POHOCCO SIL 50%	B	0.37	5"	1.3% H	I	H (s)
Px 2	NETAWAKA SIL 40%	B	0.43	6"	1.5% H	I	H (s)
Re 1	READING SIL 90%	B	0.32	18"	3.0% L	I	I
Sg 1	SHELBY CL 88%	B	0.28	13"	3.0% I	I	I
Sm 1	SHELBY CL 85%	B	0.28	8"	2.5% I	I	H (s)
W 1	WATER 100%		0.00	0"	0.0% ?	?	?
Wa 1	WABASH SIC 85%	D	0.28	15"	3.0% H (w)	H	H
We 1	WAMEGO SICL 90%	C	0.32	9"	3.0% L	H	H
Wg 1	WAMEGO SICL 50%	C	0.32	9"	3.0% L	H	H
Wg 2	VINLAND SICL 40%	D	0.32	8"	3.0% V	H	H
Wm 1	WYMORE SICL 90%	D	0.37	7"	3.0% H (w)	H	H
Wn 1	WYMORE SICL 82%	D	0.37	10"	3.0% H (w)	H	H
Wn 2	KENNEBEC SIL 3%	B	0.28	8"	5.5% I	I	I

(.\REPORTS\SOILS.TXT generated on 12/12/01 at 12:11:15)

H -- High
I -- Intermediate
L -- Low
V -- Very Low

Conditions that affect ratings:

- m -- There are macropores in the surface horizon deeper than 24"
- w -- The high water table comes within 24" of the surface during the growing season
- s -- The field slope is greater than 15%

SPISP II S-Ratings:

- SLP -- Soil Leaching Potential
- SSRP -- Soil Solution Runoff Potential
- SARP -- Soil Adsorbed Runoff Potential

In this section, hydric soils are defined and described and the hydric soils in the survey area are listed. The three essential characteristics of wetlands are hydrophytic vegetation, hydric soils, and wetland hydrology (Cowardin and others, 1979; U.S. Army Corps of Engineers, 1987; National Research Council, 1995; Tiner, 1985). Criteria for each of the characteristics must be met for areas to be identified as wetlands. Undrained hydric soils that have natural vegetation should support a dominant population of ecological wetland plant species. Hydric soils that have been converted to other uses should be capable of being restored to wetlands.

Hydric soils are defined by the National Technical Committee for Hydric Soils (NTCHS) as soils that formed under conditions of saturation, flooding, or ponding long enough during the growing season to develop anaerobic conditions in the upper part (Federal Register, 1994). These soils are either saturated or inundated long enough during the growing season to support the growth and reproduction of hydrophytic vegetation.

The NTCHS definition identifies general soil properties that are associated with wetness. In order to determine whether a specific soil is a hydric soil or nonhydric soil, however, more specific information, such as information about the depth and duration of the water table, is needed. Thus, criteria that identify those estimated soil properties unique to hydric soils have been established (Federal Register, 1995). These criteria are used to identify a phase of a soil series that normally is associated with wetlands. The criteria used are selected estimated soil properties that are described in "Soil Taxonomy" (USDA, 1999) and "Keys to Soil Taxonomy" (USDA, 1998) and in the "Soil Survey Manual" (USDA, 1993).

If soils are wet enough for a long enough period to be considered hydric, they should exhibit certain properties that can be easily observed in the field. These visible properties are indicators of hydric soils. The indicators used to make onsite determinations of hydric soils in this survey area are specified in "Field Indicators of Hydric Soils in the United States" (Hurt and others, 1996).

Hydric soils are identified by examining and describing the soil to a depth of about 20 inches. This depth may be greater if determination of an appropriate indicator so requires. It is always recommended that soils be excavated and described to the depth necessary for an understanding of the redoximorphic processes. Then, using the completed soil descriptions, soil scientists can compare the soil features required by each indicator and specify which indicators have been matched with the conditions observed in the soil. The soil can be identified as a hydric soil if at least one of the approved indicators is present.

Map units in the Hydric Soil Interpretations table meet the definition of hydric soils and, in addition, have at least one of the hydric soil indicators. This list can help in planning land uses; however, onsite investigation is recommended to determine the hydric soils on a specific site (National Research Council, 1995; Hurt and others, 1996).

Map units that are made up of hydric soils may have small areas, or inclusions, of nonhydric soils in the higher positions on the landform, and map units made up of nonhydric soils may have inclusions of hydric soils in the lower positions on the landform.

These map units, in general, do not meet the definition of hydric soils because they do not have one of the hydric soil indicators. A portion of these map units, however, may include hydric soils. Onsite investigation is recommended to determine whether hydric soils occur and the location of the included hydric soils.

HYDRIC SOIL INTERPRETATIONS
HYDRIC SOILS LIST
Brown County, Kansas

PAGE 2 of 5

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
Ac: AKSARBEN SILTY CLAY LOAM, 0 TO 2 PERCENT SLOPES	AKSARBEN	No	divide	---	---	---	---
	MARSHALL	No	interfluv	---	---	---	---
Ad: AKSARBEN SILTY CLAY LOAM, 2 TO 5 PERCENT SLOPES	AKSARBEN	No	interfluv	---	---	---	---
	MARSHALL	No	interfluv	---	---	---	---
	WYMORE	No	interfluv	---	---	---	---
	KENNEBEC	No	flood plain	---	---	---	---
	JUDSON	No	fan remnant	---	---	---	---
Ae: AKSARBEN SILTY CLAY LOAM, 5 TO 11 PERCENT SLOPES	JUDSON	No	fan remnant	---	---	---	---
	KENNEBEC	No	flood plain	---	---	---	---
	MARSHALL	No	hillslope	---	---	---	---
	MORRILL	No	hillslope	---	---	---	---
	WYMORE	No	hillslope	---	---	---	---
	AKSARBEN	No	hillslope	---	---	---	---
Bs: BURCHARD CLAY LOAM, 6 TO 12 PERCENT SLOPES	BURCHARD	No	hillslope	---	---	---	---
	PAWNEE	No	hillslope	---	---	---	---
	STEINAUER	No	hillslope	---	---	---	---
Bx: BURCHARD-STEINAUER CLAY LOAMS, 12 TO 18 PERCENT SLOPES	BURCHARD	No	hillslope	---	---	---	---
	STEINAUER	No	hillslope	---	---	---	---
	PADONIA	No	hillslope	---	---	---	---
Ch: CHASE SILTY CLAY LOAM, 0 TO 2 PERCENT SLOPES, RARELY FLOODED	CHASE	No	flood plain	---	---	---	---
	KENNEBEC	No	flood plain	---	---	---	---
	MUSCOTAH	No	flood plain	---	---	---	---
Co: CONTRARY SILTY CLAY LOAM, 5 TO 9 PERCENT SLOPES	CONTRARY	No	hillslope	---	---	---	---
	MORRILL	No	hillslope	---	---	---	---
	KENNEBEC	No	flood plain	---	---	---	---
Ga: GRUNDY SILT LOAM, 0 TO 2 PERCENT SLOPES	GRUNDY	No	divide	---	---	---	---
	HAIG	Yes	divide	3,2B3	YES	NO	YES
Ju: JUDSON SILT LOAM, 2 TO 6 PERCENT SLOPES	JUDSON	No	fan remnant	---	---	---	---
	KENNEBEC	No	flood plain	---	---	---	---
Kd: KENNEBEC SILT LOAM, CHANNELED, FREQUENTLY FLOODED	KENNEBEC	No	flood plain	---	---	---	---
	NODAWAY	No	flood plain	---	---	---	---
	KENRIDGE	No	flood plain	---	---	---	---
	MUSCOTAH	No	flood plain	---	---	---	---
	ZOOK	Yes	flood plain	2B3	YES	NO	NO
Ke: KENNEBEC SILT LOAM, 0 TO 2 PERCENT SLOPES, OCCASIONALLY FLOODED	KENNEBEC	No	flood plain	---	---	---	---
	MUSCOTAH	No	flood plain	---	---	---	---
	KENRIDGE	No	flood plain	---	---	---	---
	ZOOK	Yes	flood plain	2B3	YES	NO	NO
Kp: KIPSON-SOGN SILTY CLAY LOAMS, 5 TO 30 PERCENT SLOPES	KIPSON	No	hillslope	---	---	---	---
	SOGN	No	hillslope	---	---	---	---
	KENNEBEC	No	flood plain	---	---	---	---
M-W: MISCELLANEOUS WATER	MISCELLANEOUS WATER	Unranked	---	---	---	---	---
Ma: MARSHALL SILT LOAM, 2 TO 5 PERCENT SLOPES	MARSHALL	No	interfluv	---	---	---	---
	AKSARBEN	No	interfluv	---	---	---	---

HYDRIC SOIL INTERPRETATIONS
HYDRIC SOILS LIST
Brown County, Kansas

PAGE 3 of 5

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
Mb: MARSHALL SILTY CLAY LOAM, 5 TO 11 PERCENT SLOPES	MARSHALL	No	hillslope	---	---	---	---
	CONTRARY	No	hillslope	---	---	---	---
	MORRILL	No	hillslope	---	---	---	---
	JUDSON	No	fan remnant	---	---	---	---
	KENNEBEC	No	flood plain	---	---	---	---
Md: MARTIN SILTY CLAY LOAM, 1 TO 4 PERCENT SLOPES	MARTIN	No	hillslope	---	---	---	---
	CHASE	No	flood plain	---	---	---	---
Mf: MARTIN SILTY CLAY LOAM, 4 TO 9 PERCENT SLOPES	PAWNEE	No	hillslope	---	---	---	---
	MARTIN	No	hillslope	---	---	---	---
Mh: MAYBERRY CLAY LOAM, 2 TO 6 PERCENT SLOPES	PADONIA	No	hillslope	---	---	---	---
	VINLAND	No	hillslope	---	---	---	---
Mk: MONONA SILT LOAM, 2 TO 5 PERCENT SLOPES	MAYBERRY	No	hillslope	---	---	---	---
	MORRILL	No	hillslope	---	---	---	---
Mn: MONONA SILT LOAM, 5 TO 11 PERCENT SLOPES, MODERATELY ERODED	WYMORE	No	interfluve	---	---	---	---
	MONONA	No	interfluve	---	---	---	---
Mt: MORRILL LOAM, 6 TO 12 PERCENT SLOPES	POHOCCO	No	hillslope	---	---	---	---
	MONONA	No	hillslope	---	---	---	---
Mw: MUSCOTAH SILT LOAM, 0 TO 2 PERCENT SLOPES, OCCASIONALLY FLOODED, OVERWASH	NETAWAKA	No	hillslope	---	---	---	---
	POHOCCO	No	hillslope	---	---	---	---
My: MUSCOTAH SILTY CLAY LOAM, 0 TO 2 PERCENT SLOPES, OCCASIONALLY FLOODED	KENNEBEC	No	flood plain	---	---	---	---
	MORRILL	No	hillslope	---	---	---	---
No: NODAWAY SILT LOAM, 0 TO 2 PERCENT SLOPES, OCCASIONALLY FLOODED	KENNEBEC	No	flood plain	---	---	---	---
	PAWNEE	No	flood plain	---	---	---	---
Om: OLMITZ LOAM, 2 TO 5 PERCENT SLOPES	OLMITZ	No	fan terrace	---	---	---	---
	CHASE	No	flood plain	---	---	---	---
Or: ORTHENTS, EARTHEN DAM	PAWNEE	No	hillslope	---	---	---	---
	ORTHENTS, EARTHEN DAM	---	---	---	---	---	---
Pd: PADONIA-MARTIN SILTY CLAY LOAMS, 5 TO 9 PERCENT SLOPES	PADONIA	No	hillslope	---	---	---	---
	MARTIN	No	hillslope	---	---	---	---
	KIPSON	No	hillslope	---	---	---	---

HYDRIC SOIL INTERPRETATIONS
HYDRIC SOILS LIST
Brown County, Kansas

PAGE 4 of 5

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
Pe: PADONIA-MARTIN SILTY CLAY LOAMS, 9 TO 25 PERCENT SLOPES	PADONIA	No	hillslope	---	---	---	---
	MARTIN KIPSON	No No	hillslope hillslope	---	---	---	---
Pf: PADONIA-OSKA SILTY CLAY LOAMS, 5 TO 9 PERCENT SLOPES	PADONIA	No	hillslope	---	---	---	---
	OSKA KIPSON	No No	hillslope hillslope	---	---	---	---
Pm: PAWNEE CLAY LOAM, 2 TO 6 PERCENT SLOPES	PAWNEE	No	hillslope	---	---	---	---
	MORRILL SHELBY	No No	hillslope hillslope	---	---	---	---
Pn: PAWNEE CLAY LOAM, 6 TO 12 PERCENT SLOPES	PAWNEE	No	hillslope	---	---	---	---
	MORRILL KENNEBEC OLMITZ	No No No	hillslope flood plain fan terrace	---	---	---	---
Po: PAWNEE CLAY, 6 TO 12 PERCENT SLOPES, MODERATELY ERODED	PAWNEE	No	hillslope	---	---	---	---
	MAYBERRY KENNEBEC OLMITZ	No No No	hillslope flood plain fan terrace	---	---	---	---
Pt: PITS, QUARRIES	Pits, quarries	Unranked	---	---	---	---	---
Pw: POHOCCO-NETAWAKA SILT LOAMS, 11 TO 17 PERCENT SLOPES	POHOCCO	No	hillslope	---	---	---	---
	NETAWAKA JUDSON	No No	hillslope fan remnant	---	---	---	---
Px: POHOCCO-NETAWAKA SILT LOAMS, 17 TO 30 PERCENT SLOPES	POHOCCO	No	hillslope	---	---	---	---
	NETAWAKA JUDSON	No No	hillslope fan remnant	---	---	---	---
Re: READING SILT LOAM, 0 TO 2 PERCENT SLOPES, MODERATELY WET, RARELY FLOODED	READING	No	flood plain	---	---	---	---
	CHASE ZOOK	No Yes	flood plain flood plain	---	---	---	---
Sg: SHELBY CLAY LOAM, 6 TO 12 PERCENT SLOPES	SHELBY	No	hillslope	---	---	---	---
	PAWNEE KENNEBEC OLMITZ	No No No	hillslope flood plain fan terrace	---	---	---	---
Sm: SHELBY CLAY LOAM, 12 TO 18 PERCENT SLOPES, MODERATELY ERODED	SHELBY	No	hillslope	---	---	---	---
	PAWNEE PADONIA KENNEBEC OLMITZ	No No No No	hillslope hillslope flood plain fan terrace	---	---	---	---
W: WATER	WATER	Yes	---	4,3	NO	YES	YES
Wa: WABASH SILTY CLAY, 0 TO 2 PERCENT SLOPES, OCCASIONALLY FLOODED	WABASH	Yes	flood plain	2B3	YES	NO	NO
	MUSCOTAH KENNEBEC	No No	flood plain flood plain	---	---	---	---
We: WAMEGO SILTY CLAY LOAM, 3 TO 7 PERCENT SLOPES	WAMEGO	No	hillslope	---	---	---	---
	OLMITZ PAWNEE	No No	fan terrace hillslope	---	---	---	---

HYDRIC SOIL INTERPRETATIONS
HYDRIC SOILS LIST
Brown County, Kansas

PAGE 5 of 5

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
Wg: WAMEGO-VINLAND SILTY CLAY LOAMS, 3 TO 15 PERCENT SLOPES	WAMEGO	No	hillslope	---	---	---	---
	VINLAND PAWNEE	No	hillslope	---	---	---	---
Wm: WYMORE SILTY CLAY LOAM, 2 TO 5 PERCENT SLOPES	WYMORE	No	interfluve	---	---	---	---
	PAWNEE	No	hillslope	---	---	---	---
Wn: WYMORE SILTY CLAY LOAM, 5 TO 9 PERCENT SLOPES	WYMORE	No	hillslope	---	---	---	---
	PAWNEE	No	hillslope	---	---	---	---
	MAYBERRY	No	hillslope	---	---	---	---
	KENNEBEC	No	flood plain	---	---	---	---

FOOTNOTE: There may be small areas of included soils or miscellaneous areas that are significant to use and management of the soil; yet are too small to delineate on the soil map at the map's original scale. These may be designated as spot symbols and are defined in the published Soil Survey Report or the USDA-NRCS Technical Guide, Part II. Areas mapped as water or any map unit that contains one of the following conventional symbols is considered a hydric soil map unit: marshes or swamps; wet spots; depressions; streams, lakes and ponds.

1. All Histosols except Folists, or
2. Soils in Aquic suborders, great groups, or subgroups, Albolls suborder, Aquisalids, Pachic subgroups, or Cumulic subgroups that are:
 - a. Somewhat poorly drained with a water table equal to 0.0 foot (ft) from the surface during the growing season, or
 - b. poorly drained or very poorly drained and have either:
 - (1) water table equal to 0.0 ft during the growing season if textures are coarse sand, sand, or fine sand in all layers within 20 inches (in), or for other soils
 - (2) water table at less than or equal to 0.5 ft from the surface during the growing season if permeability is equal to or greater than 6.0 in/hour (h) in all layers within 20 in, or
 - (3) water table at less than or equal to 1.0 ft from the surface during the growing season if permeability is less than 6.0 in/h in any layer within 20 in, or
3. Soils that are frequently ponded for long duration or very long duration during the growing season, or
4. Soils that are frequently flooded for long duration or very long duration during the growing season.