

SANITARY FACILITIES
Cloud County, Kansas

Sanitary Facilities

The following tables show the degree and kind of soil limitations that affect septic tank absorption fields, sewage lagoons, sanitary landfills, and daily cover for landfill. The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect these uses. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Septic tank absorption fields are areas in which effluent from a septic tank is distributed into the soil through subsurface tiles or perforated pipe. Only that part of the soil between depths of 24 and 60 inches is evaluated. The ratings are based on the soil properties that affect absorption of the effluent, construction and maintenance of the system, and public health. Permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, and flooding affect absorption of the effluent. Stones and boulders, ice, and bedrock or a cemented pan interfere with installation. Subsidence interferes with installation and maintenance. Excessive slope may cause lateral seepage and surfacing of the effluent in downslope areas.

Some soils are underlain by loose sand and gravel or fractured bedrock at a depth of less than 4 feet below the distribution lines. In these soils the absorption field may not adequately filter the effluent, particularly when the system is new. As a result, the ground water may become contaminated.

Sewage lagoons are shallow ponds constructed to hold sewage while aerobic bacteria decompose the solid and liquid wastes. Lagoons should have a nearly level floor surrounded by cut slopes or embankments of compacted soil. Nearly impervious soil material for the lagoon floor and sides is required to minimize seepage and contamination of ground water. Considered in the ratings are slope, permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, flooding, large stones, and content of organic matter.

Soil permeability is a critical property affecting the suitability for sewage lagoons. Most porous soils eventually become sealed when they are used as sites for sewage lagoons. Until sealing occurs, however, the hazard of pollution is severe. Soils that have a permeability rate of more than 2 inches per hour are too porous for the proper functioning of sewage lagoons. In these soils, seepage of the effluent can result in contamination of the ground water. Ground-water contamination is also a hazard if fractured bedrock is within a depth of 40 inches, if the water table is high enough to raise the level of sewage in the lagoon, or if floodwater overtops the lagoon.

A high content of organic matter is detrimental to proper functioning of the lagoon because it inhibits aerobic activity. Slope, bedrock, and cemented pans can cause construction problems, and large stones can hinder compaction of the lagoon floor. If the lagoon is to be uniformly deep throughout, the slope must be gentle enough and the soil material must be thick enough over bedrock or a cemented pan to make land smoothing practical.

A trench sanitary landfill is an area where solid waste is placed in successive layers in an excavated trench. The waste is spread, compacted, and covered daily with a thin layer of soil excavated at the site. When the trench is full, a final cover of soil material at least 2 feet thick is placed over the landfill. The ratings in the table are based on the soil properties that affect the risk of pollution, the ease of excavation, trafficability, and revegetation. These properties include permeability, depth to bedrock or a cemented pan, depth to a water table, ponding, slope, flooding, texture, stones and boulders, highly organic layers, soil reaction, and content of salts and sodium. Unless otherwise stated, the ratings apply only to that part of the soil within a depth of about 6 feet. For deeper trenches, onsite investigation may be needed.

Hard, nonrippable bedrock, creviced bedrock, or highly permeable strata in or directly below the proposed trench bottom can affect the ease of excavation and the hazard of ground-water pollution. Slope affects construction of the trenches and the movement of surface water around the landfill. It also affects the construction and performance of roads in areas of the landfill.

Soil texture and consistence affect the ease with which the trench is dug and the ease with which the soil can be used as daily or final cover. They determine the workability of the soil when dry and when wet. Soils that are plastic and sticky when wet are difficult to excavate, grade, or compact and are difficult to place as a uniformly thick cover over a layer of refuse.

The soil material used as the final cover for a trench landfill should be suitable for plants. It should not have excess sodium or salts and should not be too acid. The surface layer generally has the best workability, the highest content of organic matter, and the best potential for plants. Material from the surface layer should be stockpiled for use as the final cover.

SANITARY FACILITIES
Cloud County, Kansas

In an area sanitary landfill, solid waste is placed in successive layers on the surface of the soil. The waste is spread, compacted, and covered daily with a thin layer of soil from a source away from the site. A final cover of soil material at least 2 feet thick is placed over the completed landfill. The ratings in the table are based on the soil properties that affect trafficability and the risk of pollution. These properties include flooding, permeability, depth to a water table, ponding, slope, and depth to bedrock or a cemented pan.

Flooding is a serious problem because it can result in pollution in areas downstream from the landfill. If permeability is too rapid or if fractured bedrock, a fractured cemented pan, or the water table is close to the surface, the leachate can contaminate the water supply. Slope is a consideration because of the extra grading required to maintain roads in the steeper areas of the landfill. Also, leachate may flow along the surface of the soils in the steeper areas and cause difficult seepage problems.

Daily cover for landfill is the soil material that is used to cover compacted solid waste in an area sanitary landfill. The soil material is obtained offsite, transported to the landfill, and spread over the waste. The ratings in the table also apply to the final cover for a landfill. They are based on the soil properties that affect workability, the ease of digging, and the ease of moving and spreading the material over the refuse daily during wet and dry periods. These properties include soil texture, depth to a water table, ponding, rock fragments, slope, depth to bedrock or a cemented pan, reaction, and content of salts, sodium, or lime.

Loamy or silty soils that are free of large stones and excess gravel are the best cover for a landfill. Clayey soils may be sticky and difficult to spread; sandy soils are subject to wind erosion.

Slope affects the ease of excavation and of moving the cover material. Also, it can influence runoff, erosion, and reclamation of the borrow area.

After soil material has been removed, the soil material remaining in the borrow area must be thick enough over bedrock, a cemented pan, or the water table to permit revegetation. The soil material used as the final cover for a landfill should be suitable for plants. It should not have excess sodium, salts, or lime and should not be too acid.

SANITARY FACILITIES--Continued
Cloud County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

| Map symbol and soil name | Pct of map unit | Septic tank absorption fields | | Sewage lagoons | |
|-----------------------------|--------------------------|--|------------------|--|--------------------------|
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| 027CT: Crete----- | 83 | Very limited Restricted permeability | 1.00 | Somewhat limited Slope | 0.67 |
| 027EU: Eudora----- | 85 | Very limited Flooding Restricted permeability | 1.00 0.50 | Very limited Flooding Seepage | 1.00 0.50 |
| 027HE: Haynie----- | 65 | Very limited Flooding Restricted permeability | 1.00 0.50 | Very limited Flooding Seepage | 1.00 0.50 |
| Sarpy----- | 34 | Very limited Flooding Filtering capacity | 1.00 1.00 | Very limited Flooding Seepage Slope | 1.00 1.00 0.00 |
| 027HN: Hobbs----- | 93 | Very limited Flooding Restricted permeability | 1.00 0.50 | Very limited Flooding Seepage | 1.00 0.50 |
| 089ND: Nibson----- | 100 | Very limited Depth to bedrock Slope | 1.00 1.00 | Very limited Depth to soft bedrock Slope Seepage | 1.00 1.00 0.50 |
| 123AB: Armo----- | 100 | Somewhat limited Restricted permeability | 0.50 | Somewhat limited Slope Seepage | 0.67 0.50 |
| 123AC: Armo----- | 100 | Somewhat limited Restricted permeability Slope | 0.50 0.37 | Very limited Slope Seepage | 1.00 0.50 |
| 123HB: Harney----- | 100 | Very limited Restricted permeability | 1.00 | Somewhat limited Seepage Slope | 0.50 0.00 |
| 123HE: Harney----- | 80 | Very limited Restricted permeability | 1.00 | Somewhat limited Slope Seepage | 0.67 0.50 |
| Mento----- | 20 | Very limited Restricted permeability Depth to bedrock | 1.00 0.69 | Somewhat limited Slope Depth to hard bedrock | 0.33 0.26 |
| 123LA: Lancaster----- | 70 | Very limited Depth to bedrock Restricted permeability | 1.00 0.50 | Very limited Depth to soft bedrock Seepage Slope | 1.00 0.50 0.33 |
| Armo----- | 30 | Somewhat limited Restricted permeability | 0.50 | Somewhat limited Slope Seepage | 0.67 0.50 |
| 123NA: New Cambria----- | 100 | Very limited Restricted permeability Flooding | 1.00 0.40 | Somewhat limited Flooding | 0.40 |
| 123NC: Nibson----- | 100 | Very limited Depth to bedrock Slope | 1.00 1.00 | Very limited Depth to soft bedrock Slope Seepage | 1.00 1.00 0.50 |
| 123RB: Roxbury----- | 100 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 |

SANITARY FACILITIES--Continued
Cloud County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

| Map symbol and soil name | Pct of map unit | Septic tank absorption fields | | Sewage lagoons | |
|-----------------------------|--------------------------|--|-------|--|-------|
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| 123RC: Roxbury----- | 100 | Restricted permeability | 0.50 | Seepage | 0.50 |
| | | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 |
| | | Restricted permeability | 0.50 | Seepage | 0.50 |
| 123WA: Wakeen----- | 100 | Very limited Depth to bedrock | 1.00 | Very limited Depth to soft bedrock | 1.00 |
| | | Restricted permeability | 0.50 | Slope | 0.67 |
| | | | | Seepage | 0.50 |
| 143EE: Edalgo----- | 60 | Very limited Restricted permeability | 1.00 | Very limited Depth to soft bedrock | 1.00 |
| | | Depth to bedrock | 1.00 | Slope | 1.00 |
| | | Slope | 0.16 | | |
| Hedville----- | 40 | Very limited Depth to bedrock | 1.00 | Very limited Depth to hard bedrock | 1.00 |
| | | Slope | 1.00 | Slope | 1.00 |
| | | | | Content of large stones | 0.00 |
| 143GE: Geary----- | 100 | Somewhat limited Restricted permeability | 0.50 | Somewhat limited Seepage | 0.50 |
| | | | | Slope | 0.00 |
| | | | | | |
| 143HE: Hedville----- | 70 | Very limited Depth to bedrock | 1.00 | Very limited Depth to hard bedrock | 1.00 |
| | | Slope | 1.00 | Slope | 1.00 |
| | | | | Content of large stones | 0.00 |
| Rock Outcrop----- | 30 | Not rated | | Not rated | |
| 143HP: Hobbs----- | 55 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 |
| | | Restricted permeability | 0.50 | Seepage | 0.50 |
| | | | | | |
| Geary----- | 45 | Somewhat limited Restricted permeability | 0.50 | Very limited Slope | 1.00 |
| | | Slope | 0.04 | Seepage | 0.50 |
| | | | | | |
| 143LA: Lancaster----- | 100 | Very limited Depth to bedrock | 1.00 | Very limited Depth to soft bedrock | 1.00 |
| | | Restricted permeability | 0.50 | Slope | 0.67 |
| | | | | Seepage | 0.50 |
| 143RO: Roxbury----- | 100 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 |
| | | Restricted permeability | 0.50 | Seepage | 0.50 |
| | | | | | |
| 157BK: Geary----- | 55 | Very limited Restricted permeability | 1.00 | Very limited Slope | 1.00 |
| | | Slope | 1.00 | Seepage | 0.50 |
| | | | | | |
| Hobbs----- | 29 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 |
| | | Restricted permeability | 0.50 | Seepage | 0.50 |
| | | | | | |
| 157CH: Crete----- | 75 | Very limited Restricted permeability | 1.00 | Somewhat limited Slope | 0.67 |
| | | | | | |
| | | | | | |
| 157ED: Eudora----- | 90 | Somewhat limited Restricted permeability | 0.50 | Somewhat limited Seepage | 0.50 |
| | | Flooding | 0.40 | Flooding | 0.40 |
| | | | | | |

SANITARY FACILITIES--Continued
Cloud County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

| Map symbol and soil name | Pct of map unit | Septic tank absorption fields | | Sewage lagoons | |
|-----------------------------|--------------------------|--|----------------------|--|----------------------|
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| 157KN: Kenesaw----- | 90 | Somewhat limited Restricted permeability Slope | 0.50 0.00 | Very limited Slope Seepage | 1.00 0.50 |
| 157SD: Inavale----- | 100 | Very limited Filtering capacity | 1.00 | Very limited Seepage Slope | 1.00 0.67 |
| 201CG: Cass----- | 89 | Very limited Flooding Filtering capacity | 1.00 1.00 | Very limited Flooding Seepage | 1.00 1.00 |
| 201CS: Crete----- | 95 | Very limited Restricted permeability | 1.00 | Somewhat limited Seepage Slope | 0.32 0.00 |
| 201SA: Sarpy----- | 90 | Very limited Filtering capacity Flooding | 1.00 0.40 | Very limited Seepage Flooding Slope | 1.00 0.40 0.00 |
| Aa: Hobbs----- | 83 | Very limited Flooding Restricted permeability | 1.00 0.50 | Very limited Flooding Seepage | 1.00 0.50 |
| Ah: Saltine----- | 98 | Very limited Flooding Depth to saturated zone Restricted permeability | 1.00 1.00 1.00 | Very limited Flooding Depth to saturated zone | 1.00 1.00 |
| Ar: Armo----- | 75 | Somewhat limited Restricted permeability | 0.50 | Somewhat limited Slope Seepage | 0.67 0.50 |
| Ba: Hastings----- | 58 | Very limited Restricted permeability Slope | 1.00 0.16 | Very limited Slope Seepage | 1.00 0.50 |
| Hobbs----- | 40 | Very limited Flooding Restricted permeability | 1.00 0.50 | Very limited Flooding Seepage | 1.00 0.50 |
| Br: Bridgeport----- | 98 | Very limited Flooding Restricted permeability | 1.00 0.50 | Very limited Flooding Seepage | 1.00 0.50 |
| Ca: Cozad----- | 50 | Very limited Flooding Filtering capacity Restricted permeability | 1.00 1.00 0.50 | Very limited Flooding Seepage | 1.00 1.00 |
| Cass----- | 25 | Very limited Flooding Filtering capacity | 1.00 1.00 | Very limited Flooding Seepage | 1.00 1.00 |
| Cb: Cass----- | 100 | Very limited Filtering capacity Flooding | 1.00 0.40 | Very limited Seepage Flooding Slope | 1.00 0.40 0.00 |
| Cf: Munjor----- | 50 | Very limited Flooding Filtering capacity | 1.00 1.00 | Very limited Flooding Seepage | 1.00 1.00 |
| Inavale----- | 49 | Very limited | | Very limited | |

SANITARY FACILITIES--Continued
Cloud County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

| Map symbol and soil name | Pct of map unit | Septic tank absorption fields | | Sewage lagoons | |
|-----------------------------|--------------------------|--|--------------|---|----------------------|
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| | | Flooding Filtering capacity | 1.00 1.00 | Flooding Seepage | 1.00 1.00 |
| CLP: Clay Pits----- | 100 | Not rated | | Not rated | |
| Cr: Crete----- | 100 | Very limited Restricted permeability | 1.00 | Not limited | |
| Cs: Crete----- | 80 | Very limited Restricted permeability | 1.00 | Somewhat limited Slope | 0.00 |
| Ct: Crete----- | 80 | Very limited Restricted permeability | 1.00 | Somewhat limited Slope | 0.33 |
| Cu: Crete----- | 78 | Very limited Restricted permeability | 1.00 | Somewhat limited Slope | 0.33 |
| De: Detroit----- | 83 | Very limited Restricted permeability Flooding | 1.00 0.40 | Somewhat limited Flooding | 0.40 |
| Eu: Eudora----- | 100 | Somewhat limited Restricted permeability Flooding | 0.50 0.40 | Somewhat limited Seepage Flooding | 0.50 0.40 |
| Ge: Geary----- | 70 | Somewhat limited Restricted permeability | 0.50 | Somewhat limited Slope Seepage | 0.67 0.50 |
| GRP: Gravel Pits----- | 100 | Not rated | | Not rated | |
| Gs: Geary----- | 70 | Somewhat limited Restricted permeability | 0.50 | Somewhat limited Slope Seepage | 0.67 0.50 |
| Hb: Hastings----- | 85 | Very limited Restricted permeability | 1.00 | Somewhat limited Seepage Slope | 0.50 0.00 |
| Hc: Hastings----- | 80 | Very limited Restricted permeability | 1.00 | Somewhat limited Slope Seepage | 0.67 0.50 |
| Hd: Hastings----- | 85 | Very limited Restricted permeability | 1.00 | Somewhat limited Seepage Slope | 0.50 0.33 |
| He: Hedville----- | 75 | Very limited Depth to bedrock Slope | 1.00 1.00 | Very limited Depth to hard bedrock Slope Content of large stones | 1.00 1.00 0.00 |
| Ho: Hobbs----- | 73 | Very limited Flooding Restricted permeability | 1.00 0.50 | Very limited Flooding Seepage | 1.00 0.50 |
| Hr: Hord----- | 79 | Somewhat limited Restricted permeability Flooding | 0.50 0.40 | Somewhat limited Seepage Flooding | 0.50 0.40 |
| Hu: Humbarger----- | 74 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 |

SANITARY FACILITIES--Continued
Cloud County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

| Map symbol and soil name | Pct of map unit | Septic tank absorption fields | | Sewage lagoons | |
|------------------------------|--------------------------|--|-------|--|-------|
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| Kp: Kipson----- | 65 | Filtering capacity | 1.00 | Seepage | 1.00 |
| | | Restricted permeability | 0.50 | | |
| | | Very limited Depth to bedrock | 1.00 | Very limited Depth to soft bedrock | 1.00 |
| Lh: Lancaster----- | 55 | Slope | 1.00 | Slope | 1.00 |
| | | | | Seepage | 0.50 |
| | | Very limited Restricted permeability | 1.00 | Very limited Depth to soft bedrock | 1.00 |
| Hedville----- | 28 | Depth to bedrock | 1.00 | Slope | 1.00 |
| | | Slope | 0.04 | Seepage | 0.50 |
| | | Very limited Depth to bedrock | 1.00 | Very limited Depth to hard bedrock | 1.00 |
| Lm: Longford----- | 70 | Slope | 1.00 | Slope | 1.00 |
| | | | | Content of large stones | 0.00 |
| | | Very limited Restricted permeability | 1.00 | Somewhat limited Slope | 0.00 |
| Ln: Longford----- | 65 | Very limited Restricted permeability | 1.00 | Somewhat limited Slope | 0.67 |
| | | | | | |
| Lo: Longford----- | 65 | Very limited Restricted permeability | 1.00 | Somewhat limited Slope | 0.67 |
| | | | | | |
| M-W: Miscellaneous Water- | 100 | Not rated | | Not rated | |
| Mc: McCook----- | 98 | Somewhat limited Restricted permeability | 0.50 | Somewhat limited Seepage | 0.50 |
| | | Flooding | 0.40 | Flooding | 0.40 |
| Mr: Muir----- | 84 | Somewhat limited Restricted permeability | 0.50 | Somewhat limited Seepage | 0.50 |
| | | Flooding | 0.40 | Flooding | 0.40 |
| Nc: New Cambria----- | 83 | Very limited Restricted permeability | 1.00 | Somewhat limited Flooding | 0.40 |
| | | Flooding | 0.40 | | |
| Nu: Nuckolls----- | 85 | Somewhat limited Restricted permeability | 0.50 | Very limited Slope | 1.00 |
| | | Slope | 0.00 | Seepage | 0.50 |
| Nx: Nuckolls----- | 85 | Somewhat limited Restricted permeability | 0.50 | Very limited Slope | 1.00 |
| | | Slope | 0.00 | Seepage | 0.50 |
| QUA: Quarries----- | 100 | Not rated | | Not rated | |
| Rx: Roxbury----- | 78 | Somewhat limited Restricted permeability | 0.50 | Somewhat limited Seepage | 0.50 |
| | | Flooding | 0.40 | Flooding | 0.40 |
| Sa: Inavale----- | 85 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 |
| | | Filtering capacity | 1.00 | Seepage | 1.00 |
| SAP: Sand Pits----- | 100 | Not rated | | Not rated | |
| Sd: Inavale----- | 100 | Very limited | | Very limited | |

SANITARY FACILITIES--Continued
Cloud County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

| Map symbol and soil name | Pct of map unit | Septic tank absorption fields | | Sewage lagoons | |
|-----------------------------|--------------------------|---------------------------------------|-------|---------------------------------------|-------|
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| St: Sutphen----- | 85 | Filtering capacity | 1.00 | Seepage | 1.00 |
| | | | | Slope | 0.67 |
| | | Very limited | | Very limited | |
| | | Restricted | 1.00 | Ponding | 1.00 |
| To: Tobin----- | 78 | permeability | 1.00 | Flooding | 0.40 |
| | | Ponding | 0.40 | | |
| | | Flooding | | | |
| | | Very limited | 1.00 | Very limited | 1.00 |
| W: Water----- | 100 | Flooding | 0.50 | Flooding | 0.50 |
| | | Restricted | | Seepage | |
| | | permeability | | | |
| | | Very limited | 1.00 | Very limited | 1.00 |
| Wa: Wakeen----- | 70 | Slope | | Slope | |
| | | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to soft | 1.00 |
| | | Restricted | 0.50 | bedrock | |
| | | permeability | | Slope | 0.67 |
| | | | | Seepage | 0.50 |

SANITARY FACILITIES--Continued
Cloud County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

| Map symbol and soil name | Pct of map unit | Trench sanitary landfill | | Area sanitary landfill | | Daily cover for landfill | |
|-----------------------------|--------------------------|--|------------------------------|---|--------------|--|------------------------------|
| | | Rating class and limiting features | Value | Rating class and limiting features | Value | Rating class and limiting features | Value |
| 027CT: Crete----- | 83 | Somewhat limited Too clayey | 0.50 | Not limited | | Somewhat limited Too clayey | 0.50 |
| 027EU: Eudora----- | 85 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 | Not limited | |
| 027HE: Haynie----- | 65 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 | Not limited | |
| Sarpy----- | 34 | Very limited Flooding Seepage Too Sandy | 1.00 1.00 1.00 | Very limited Flooding Seepage | 1.00 1.00 | Very limited Too Sandy Seepage | 1.00 1.00 |
| 027HN: Hobbs----- | 93 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 | Not limited | |
| 089ND: Nibson----- | 100 | Very limited Depth to bedrock Seepage Slope Too clayey | 1.00 1.00 1.00 0.50 | Very limited Depth to bedrock Slope | 1.00 1.00 | Very limited Depth to bedrock Slope Too clayey | 1.00 1.00 0.50 |
| 123AB: Armo----- | 100 | Somewhat limited Too clayey | 0.50 | Not limited | | Somewhat limited Too clayey | 0.50 |
| 123AC: Armo----- | 100 | Somewhat limited Too clayey Slope | 0.50 0.37 | Somewhat limited Slope | 0.37 | Somewhat limited Too clayey Slope | 0.50 0.37 |
| 123HB: Harney----- | 100 | Somewhat limited Too clayey | 0.50 | Not limited | | Very limited Hard to compact Too clayey | 1.00 0.50 |
| 123HE: Harney----- | 80 | Not limited | | Not limited | | Not limited | |
| Mento----- | 20 | Very limited Depth to bedrock Seepage Too clayey | 1.00 1.00 0.50 | Somewhat limited Depth to bedrock | 0.26 | Somewhat limited Too clayey Depth to bedrock | 0.50 0.26 |
| 123LA: Lancaster----- | 70 | Very limited Depth to bedrock Seepage Too clayey | 1.00 1.00 0.50 | Very limited Depth to bedrock | 1.00 | Very limited Depth to bedrock Too clayey | 1.00 0.50 |
| Armo----- | 30 | Somewhat limited Too clayey | 0.50 | Not limited | | Somewhat limited Too clayey | 0.50 |
| 123NA: New Cambria----- | 100 | Very limited Too clayey Flooding | 1.00 0.40 | Somewhat limited Flooding | 0.40 | Very limited Too clayey Hard to compact | 1.00 1.00 |
| 123NC: Nibson----- | 100 | Very limited Depth to bedrock Slope Seepage Too clayey | 1.00 1.00 1.00 0.50 | Very limited Depth to bedrock Slope | 1.00 1.00 | Very limited Depth to bedrock Slope Too clayey | 1.00 1.00 0.50 |
| 123RB: Roxbury----- | 100 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 | Not limited | |
| 123RC: Roxbury----- | 100 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 | Not limited | |
| 123WA: Wakeen----- | 100 | Very limited Depth to bedrock Seepage Too clayey | 1.00 1.00 0.50 | Very limited Depth to bedrock | 1.00 | Very limited Depth to bedrock Too clayey | 1.00 0.50 |
| 143EE: Edalgo----- | 60 | Very limited Depth to bedrock Too clayey Seepage Slope | 1.00 1.00 1.00 0.16 | Very limited Depth to bedrock Slope | 1.00 0.16 | Very limited Depth to bedrock Too clayey Hard to compact Slope | 1.00 1.00 1.00 0.16 |
| Hedville----- | 40 | Very limited Depth to bedrock Slope Seepage | 1.00 1.00 1.00 | Very limited Depth to bedrock Slope | 1.00 1.00 | Very limited Depth to bedrock Slope Gravel content | 1.00 1.00 0.00 |
| 143GE: Geary----- | 100 | Somewhat limited Too clayey | 0.50 | Not limited | | Somewhat limited Too clayey | 0.50 |
| 143HE: Hedville----- | 70 | Very limited | | Very limited | | Very limited | |

SANITARY FACILITIES--Continued
Cloud County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

| Map symbol and soil name | Pct of map unit | Trench sanitary landfill | | Area sanitary landfill | | Daily cover for landfill | |
|--------------------------|-----------------|---|------------------------------|---|--------------|---|----------------------|
| | | Rating class and limiting features | Value | Rating class and limiting features | Value | Rating class and limiting features | Value |
| Rock Outcrop----- | 30 | Depth to bedrock Slope Seepage Not rated | 1.00 1.00 1.00 | Depth to bedrock Slope Not rated | 1.00 1.00 | Depth to bedrock Slope Gravel content Not rated | 1.00 1.00 0.00 |
| 143HP: Hobbs----- | 55 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 | Very limited Hard to compact | 1.00 |
| Geary----- | 45 | Somewhat limited Too clayey Slope | 0.50 0.04 | Somewhat limited Slope | 0.04 | Somewhat limited Too clayey Slope | 0.50 0.04 |
| 143LA: Lancaster----- | 100 | Very limited Depth to bedrock Seepage Too clayey | 1.00 1.00 0.50 | Very limited Depth to bedrock | 1.00 | Very limited Depth to bedrock Too clayey | 1.00 0.50 |
| 143RO: Roxbury----- | 100 | Very limited Flooding Too clayey | 1.00 0.50 | Very limited Flooding | 1.00 | Somewhat limited Too clayey | 0.50 |
| 157BK: Geary----- | 55 | Very limited Slope Too clayey | 1.00 0.50 | Very limited Slope | 1.00 | Very limited Slope Too clayey | 1.00 0.50 |
| Hobbs----- | 29 | Very limited Flooding Too clayey | 1.00 0.50 | Very limited Flooding | 1.00 | Somewhat limited Too clayey | 0.50 |
| 157CH: Crete----- | 75 | Somewhat limited Too clayey | 0.50 | Not limited | | Somewhat limited Too clayey | 0.50 |
| 157ED: Eudora----- | 90 | Somewhat limited Flooding | 0.40 | Somewhat limited Flooding | 0.40 | Not limited | |
| 157KN: Kenesaw----- | 90 | Somewhat limited Slope | 0.00 | Somewhat limited Slope | 0.00 | Somewhat limited Slope | 0.00 |
| 157SD: Inavale----- | 100 | Very limited Seepage Too Sandy | 1.00 1.00 | Very limited Seepage | 1.00 | Very limited Seepage Too Sandy | 1.00 0.50 |
| 201CG: Cass----- | 89 | Very limited Flooding Seepage Too Sandy | 1.00 1.00 1.00 | Very limited Flooding Seepage | 1.00 1.00 | Very limited Too Sandy Seepage | 1.00 1.00 |
| 201CS: Crete----- | 95 | Not limited | | Not limited | | Very limited Hard to compact | 1.00 |
| 201SA: Sarpy----- | 90 | Very limited Seepage Too Sandy Flooding | 1.00 1.00 0.40 | Very limited Seepage Flooding | 1.00 0.40 | Very limited Seepage Too Sandy | 1.00 0.50 |
| Aa: Hobbs----- | 83 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 | Not limited | |
| Ah: Saltine----- | 98 | Very limited Flooding Depth to saturated zone Sodium content Too clayey | 1.00 1.00 1.00 0.50 | Very limited Flooding Depth to saturated zone | 1.00 1.00 | Very limited Sodium content Too clayey Depth to saturated zone | 1.00 0.50 0.47 |
| Ar: Armo----- | 75 | Somewhat limited Too clayey | 0.50 | Not limited | | Somewhat limited Too clayey | 0.50 |
| Ba: Hastings----- | 58 | Somewhat limited Too clayey Slope | 0.50 0.16 | Somewhat limited Slope | 0.16 | Very limited Hard to compact Too clayey Slope | 1.00 0.50 0.16 |
| Hobbs----- | 40 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 | Not limited | |
| Br: Bridgeport----- | 98 | Very limited Flooding | 1.00 | Very limited Flooding | 1.00 | Not limited | |
| Ca: Cozad----- | 50 | Very limited Flooding Seepage | 1.00 1.00 | Very limited Flooding | 1.00 | Not limited | |
| Cass----- | 25 | Very limited | | Very limited | | Very limited | |

SANITARY FACILITIES--Continued
Cloud County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

| Map symbol and soil name | Pct of map unit | Trench sanitary landfill | | Area sanitary landfill | | Daily cover for landfill | |
|-----------------------------|--------------------------|---------------------------------------|-------|---------------------------------------|-------|---------------------------------------|-------|
| | | Rating class and limiting features | Value | Rating class and limiting features | Value | Rating class and limiting features | Value |
| Cb: Cass----- | 100 | Flooding | 1.00 | Flooding | 1.00 | Too Sandy | 1.00 |
| | | Seepage | 1.00 | Seepage | 1.00 | Seepage | 1.00 |
| | | Too Sandy | 1.00 | | | | |
| Cf: Munjor----- | 50 | Very limited | | Very limited | | Very limited | |
| | | Seepage | 1.00 | Seepage | 1.00 | Too Sandy | 1.00 |
| | | Too Sandy | 1.00 | Flooding | 0.40 | Seepage | 1.00 |
| Inavale----- | 49 | Flooding | 1.00 | Very limited | | Very limited | |
| | | Seepage | 1.00 | Flooding | 1.00 | Too Sandy | 1.00 |
| | | Too Sandy | 1.00 | Seepage | 1.00 | Seepage | 1.00 |
| CLP: Clay Pits----- | 100 | Very limited | | Very limited | | Very limited | |
| | | Flooding | 1.00 | Flooding | 1.00 | Seepage | 1.00 |
| | | Seepage | 1.00 | Seepage | 1.00 | Too Sandy | 0.50 |
| Cr: Crete----- | 100 | Too Sandy | 1.00 | Too Sandy | 1.00 | Too Sandy | 0.50 |
| | | Flooding | 1.00 | Flooding | 1.00 | Seepage | 1.00 |
| | | Seepage | 1.00 | Seepage | 1.00 | Too Sandy | 0.50 |
| Cs: Crete----- | 80 | Not rated | | Not rated | | Not rated | |
| | | Very limited | | Very limited | | Very limited | |
| | | Too clayey | 1.00 | Too clayey | 1.00 | Too clayey | 1.00 |
| Ct: Crete----- | 80 | Hard to compact | | Hard to compact | | Hard to compact | |
| | | Very limited | | Very limited | | Very limited | |
| | | Too clayey | 1.00 | Too clayey | 1.00 | Too clayey | 1.00 |
| Cu: Crete----- | 78 | Hard to compact | | Hard to compact | | Hard to compact | |
| | | Very limited | | Very limited | | Very limited | |
| | | Too clayey | 1.00 | Too clayey | 1.00 | Too clayey | 1.00 |
| De: Detroit----- | 83 | Somewhat limited | | Somewhat limited | | Somewhat limited | |
| | | Too clayey | 0.50 | Too clayey | 0.50 | Too clayey | 0.50 |
| | | Flooding | 0.40 | Flooding | 0.40 | Flooding | 0.40 |
| Eu: Eudora----- | 100 | Very limited | | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 |
| | | Slope | 1.00 | Slope | 1.00 | Slope | 1.00 |
| Ge: Geary----- | 70 | Seepage | 1.00 | Seepage | 1.00 | Seepage | 1.00 |
| | | Too clayey | 0.50 | Too clayey | 0.50 | Too clayey | 0.50 |
| | | Flooding | 0.40 | Flooding | 0.40 | Flooding | 0.40 |
| GRP: Gravel Pits----- | 100 | Very limited | | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 |
| | | Slope | 1.00 | Slope | 1.00 | Slope | 1.00 |
| Gs: Geary----- | 70 | Seepage | 1.00 | Seepage | 1.00 | Seepage | 1.00 |
| | | Too clayey | 0.50 | Too clayey | 0.50 | Too clayey | 0.50 |
| | | Flooding | 0.40 | Flooding | 0.40 | Flooding | 0.40 |
| Hb: Hastings----- | 85 | Very limited | | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 |
| | | Slope | 1.00 | Slope | 1.00 | Slope | 1.00 |
| Hc: Hastings----- | 80 | Seepage | 1.00 | Seepage | 1.00 | Seepage | 1.00 |
| | | Too clayey | 0.50 | Too clayey | 0.50 | Too clayey | 0.50 |
| | | Flooding | 0.40 | Flooding | 0.40 | Flooding | 0.40 |
| Hd: Hastings----- | 85 | Very limited | | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 |
| | | Slope | 1.00 | Slope | 1.00 | Slope | 1.00 |
| He: Hedville----- | 75 | Seepage | 1.00 | Seepage | 1.00 | Seepage | 1.00 |
| | | Too clayey | 0.50 | Too clayey | 0.50 | Too clayey | 0.50 |
| | | Flooding | 0.40 | Flooding | 0.40 | Flooding | 0.40 |
| Ho: Hobbs----- | 73 | Very limited | | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 |
| | | Slope | 1.00 | Slope | 1.00 | Slope | 1.00 |
| Hr: Hord----- | 79 | Seepage | 1.00 | Seepage | 1.00 | Seepage | 1.00 |
| | | Too clayey | 0.50 | Too clayey | 0.50 | Too clayey | 0.50 |
| | | Flooding | 0.40 | Flooding | 0.40 | Flooding | 0.40 |
| Hu: Humbarger----- | 74 | Very limited | | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 | Depth to bedrock | 1.00 |
| | | Slope | 1.00 | Slope | 1.00 | Slope | 1.00 |
| Kp: Kipson----- | 65 | Seepage | 1.00 | Seepage | 1.00 | Seepage | 1.00 |
| | | Too clayey | 0.50 | Too clayey | 0.50 | Too clayey | 0.50 |
| | | Flooding | 0.40 | Flooding | 0.40 | Flooding | 0.40 |

SANITARY FACILITIES--Continued
Cloud County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

| Map symbol and soil name | Pct of map unit | Trench sanitary landfill | | Area sanitary landfill | | Daily cover for landfill | |
|------------------------------|--------------------------|---|----------------------|---|--------------|---|----------------------|
| | | Rating class and limiting features | Value | Rating class and limiting features | Value | Rating class and limiting features | Value |
| | | Slope Seepage Too clayey | 1.00 1.00 0.50 | Slope | 1.00 | Slope Carbonate content Too clayey | 1.00 1.00 0.50 |
| Lh: Lancaster----- | 55 | Very limited Depth to bedrock Slope | 1.00 0.04 | Very limited Depth to bedrock Slope | 1.00 0.04 | Very limited Depth to bedrock Slope | 1.00 0.04 |
| Hedville----- | 28 | Very limited Depth to bedrock Slope Seepage | 1.00 1.00 1.00 | Very limited Depth to bedrock Slope | 1.00 1.00 | Very limited Depth to bedrock Slope Gravel content | 1.00 1.00 0.00 |
| Lm: Longford----- | 70 | Somewhat limited Too clayey | 0.50 | Not limited | | Very limited Hard to compact Too clayey | 1.00 0.50 |
| Ln: Longford----- | 65 | Somewhat limited Too clayey | 0.50 | Not limited | | Very limited Hard to compact Too clayey | 1.00 0.50 |
| Lo: Longford----- | 65 | Somewhat limited Too clayey | 0.50 | Not limited | | Very limited Hard to compact Too clayey | 1.00 0.50 |
| M-W: Miscellaneous Water- | 100 | Not rated | | Not rated | | Not rated | |
| Mc: Mccook----- | 98 | Somewhat limited Flooding | 0.40 | Somewhat limited Flooding | 0.40 | Not limited | |
| Mr: Muir----- | 84 | Somewhat limited Too clayey Flooding | 0.50 0.40 | Somewhat limited Flooding | 0.40 | Somewhat limited Too clayey | 0.50 |
| Nc: New Cambria----- | 83 | Very limited Too clayey Flooding | 1.00 0.40 | Somewhat limited Flooding | 0.40 | Very limited Too clayey Hard to compact | 1.00 1.00 |
| Nu: Nuckolls----- | 85 | Somewhat limited Slope | 0.00 | Somewhat limited Slope | 0.00 | Somewhat limited Slope | 0.00 |
| Nx: Nuckolls----- | 85 | Somewhat limited Slope | 0.00 | Somewhat limited Slope | 0.00 | Somewhat limited Slope | 0.00 |
| QUA: Quarries----- | 100 | Not rated | | Not rated | | Not rated | |
| Rx: Roxbury----- | 78 | Somewhat limited Flooding | 0.40 | Somewhat limited Flooding | 0.40 | Not limited | |
| Sa: Inavale----- | 85 | Very limited Flooding Seepage Too Sandy | 1.00 1.00 1.00 | Very limited Flooding Seepage | 1.00 1.00 | Very limited Seepage Too Sandy | 1.00 0.50 |
| SAP: Sand Pits----- | 100 | Not rated | | Not rated | | Not rated | |
| Sd: Inavale----- | 100 | Very limited Seepage Too Sandy | 1.00 1.00 | Very limited Seepage | 1.00 | Very limited Seepage Too Sandy | 1.00 0.50 |
| St: Sutphen----- | 85 | Very limited Ponding Too clayey Flooding | 1.00 0.50 0.40 | Very limited Ponding Flooding | 1.00 0.40 | Very limited Ponding Hard to compact Too clayey | 1.00 1.00 0.50 |
| To: Tobin----- | 78 | Very limited Flooding Too clayey | 1.00 0.50 | Very limited Flooding | 1.00 | Somewhat limited Too clayey | 0.50 |
| W: Water----- | 100 | Very limited Slope | 1.00 | Very limited Slope | 1.00 | Very limited Slope | 1.00 |
| Wa: Wakeen----- | 70 | Very limited Depth to bedrock Seepage Too clayey | 1.00 1.00 0.50 | Very limited Depth to bedrock | 1.00 | Very limited Depth to bedrock Too clayey | 1.00 0.50 |

