

<b>Table of Contents</b> <b>Section II – Soil and Site Information</b>
---

	<b>Issue Date</b>	<b>Date of Last Review</b>	<b>Responsible Staff</b>
<i>Use and Explanation of Soil Interpretations</i>			
<i>Explanation of Key Phrases Used in Soil Interpretations</i>			
<b>Soils Legends</b>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<i>* Acreage and Proportionate Extent of the Soils</i>			
<b>Soil Descriptions - Nontechnical</b>	<b>1/02</b>	<b>1/93</b>	<b>SOI</b>
<i>Use and Explanation of Nontechnical Descriptions</i>			
<i>*Nontechnical Soils Description Report</i>			
<b>Soil Descriptions - Technical</b>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<i>*Map Unit Description Report</i>			
<b>Cropland Interpretations - Technical</b>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<i>*Prime Farmland Report</i>			
<i>* Kansas Soil Rating for Plant Growth Index</i>			
<i>*Soil Properties for Conservation Planning</i>			
<b>Rangeland, Grazed Forestland, Native Pastureland Interpretations</b>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<i>*Rangeland Productivity Report</i>			
<i>*Range Site Descriptions</i>			
<b>Forestland Interpretations</b>	<b>1/93</b>	<b>1/93</b>	<b>SOI</b>
<i>Use and Explanation of Forestland Interpretations</i>			
<i>*Woodland Management and Productivity</i>			
<b>Nonagricultural Interpretations</b>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<i>*Building Site Development Report</i>			
<i>*Construction Materials Report</i>			
<b>Recreation Interpretations</b>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<i>*Recreational Interpretations</i>			
<b>Wildlife Interpretations</b>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<i>*Wildlife Interpretations Report</i>			
<b>Pastureland and Hayland Interpretations</b>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<i>*Yields Per Acre of Pasture and Hayland</i>			

	<b>Issue Date</b>	<b>Date of Last Review</b>	<b>Responsible Staff</b>
<b>Mined Land Interpretations</b> <i>Use and Explanation of Mined Land Interpretations</i>	<b>1/93</b>	<b>1/93</b>	<b>SOI</b>
<b>Windbreak Interpretations</b> <i>*Conservation Tree and Shrub Management Report</i>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<b>Engineering Interpretations</b> <i>*Engineering Index Properties</i> <i>*Physical Properties of the Soils</i> <i>*Chemical Properties of the Soils</i> <i>*Water Features</i> <i>*Soil Features</i> <i>*Water Management Report</i>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<b>Waste Disposal Interpretations</b> <i>*Sanitary Facilities Report</i> <i>*Agricultural Waste Management Report</i>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<b>Water Quantity and Quality Interpretations</b> <i>Use and Explanation of Water Quantity and Quality Interpretations</i> <i>*Appendix A – Soils Potential For Surface Loss and Leaching</i> <i>*Appendix B – Pesticide Selected Properties Database</i> <i>*Appendix C – Herbicide Selected Properties Database</i> <i>*Soil-Pesticide Interaction Screening Procedure Worksheet (Blank)</i> <i>*WIN-PST SPISP II Soil Sensitivity to Pesticide Loss Rating Report</i>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<b>Hydric Soil Interpretations</b> <i>Use and Explanation of Hydric Soil Interpretations</i> <i>*Hydric Soils List</i>	<b>1/02</b>	<b>1/02</b>	<b>SOI</b>
<b>HEL Interpretations</b> <i>Use and Explanation of Highly Erodible Land Interpretations</i> <i>*Highly Erodible Lands Report</i> <i>*LS and Supporting Data for 1990 Frozen HEL List</i> <i>*CRP 20 Soil Supporting Data for 1990 Frozen HEL List</i>	<b>7/95</b>	<b>1/00</b>	<b>SOI</b>

*\*County specific computer generated reports.*

## ACREAGE AND PROPORTIONATE EXTENT OF THE SOILS

Linn County, Kansas: Published

Map symbol	Soil name	Acres	Percent
003CD	Collinsville Complex, 2 To 15 Percent Slopes-----	747	0.2
003DE	Dennis Silty Clay Loam, 1 To 4 Percent Slopes, Eroded-----	2	*
003EH	Eram Soils, 4 To 7 Percent Slopes, Eroded-----	1	*
003EK	Eram-Clareson Complex, 1 To 15 Percent Slopes-----	27	*
003LE	Leanna Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	2	*
003LH	Lula Silt Loam, 0 To 3 Percent Slopes-----	152	*
003SE	Stony Land-Talihina Complex, 15 To 45 Percent Slopes-----	6	*
003WF	Woodson Silt Loam, 1 To 3 Percent Slopes-----	509	0.1
011CA	Catoosa Silt Loam, 0 To 2 Percent Slopes-----	3,624	0.9
059CM	Clareson-Eram Silty Clay Loams, 3 To 15 Percent Slopes-----	489	0.1
AED	Arents, Earthen Dam-----	57	*
Bb	Bates Loam, 1 To 4 Percent Slopes-----	4,730	1.2
Bc	Bates Loam, 4 To 8 Percent Slopes-----	2,319	0.6
Cb	Catoosa Silt Loam, 1 To 3 Percent Slopes-----	47,362	12.2
Cm	Clareson-Rock Outcrop Complex, 2 To 15 Percent Slopes-----	42,207	10.9
De	Dennis Silt Loam, 1 To 3 Percent Slopes-----	19,897	5.1
Df	Dennis Silt Loam, 3 To 6 Percent Slopes-----	2,952	0.8
Ec	Eram Silty Clay Loam, 1 To 4 Percent Slopes-----	12,962	3.3
Ed	Eram Silty Clay Loam, 4 To 8 Percent Slopes-----	12,947	3.3
Ef	Eram-Lebo Silty Clay Loams, 5 To 20 Percent Slopes-----	15,918	4.1
Hp	Hepler Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	334	*
INT	Aquolls-----	1,018	0.3
Ke	Kenoma Silt Loam, 1 To 4 Percent Slopes-----	47,998	12.4
La	Lanton Silt Loam, Occasionally Flooded-----	4,487	1.2
Lb	Lebo Channery Silty Clay Loam, 15 To 30 Percent Slopes-----	12,300	3.2
M-W	Miscellaneous Water-----	35	*
Mb	Mason Silt Loam, 0 To 2 Percent Slopes, Rarely Flooded-----	2,539	0.7
Nf	Newtonia Silt Loam, 0 To 1 Percent Slopes-----	448	0.1
Ng	Newtonia Silt Loam, 1 To 4 Percent Slopes-----	9,539	2.5
Nh	Newtonia Silt Loam, 4 To 8 Percent Slopes-----	1,805	0.5
Oh	Okemah Silt Loam, 0 To 3 Percent Slopes-----	6,073	1.6
Om	Kanima Silty Clay Loam, 15 To 50 Percent Slopes-----	3,576	0.9
Op	Kanima Silty Clay Loam, 2 To 15 Percent Slopes-----	364	*
Ot	Osage Silty Clay Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	5,400	1.4
Ov	Osage Silty Clay, Occasionally Flooded-----	15,784	4.1
Pc	Parsons Silt Loam, 0 To 2 Percent Slopes-----	18,691	4.8
Po	Pits, Quarries-----	248	*
Sn	Summit Silty Clay Loam, 1 To 4 Percent Slopes-----	28,400	7.3
So	Summit Silty Clay Loam, 4 To 8 Percent Slopes-----	8,631	2.2
Vb	Verdigris Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	10,233	2.6
Vc	Verdigris Silt Loam, 0 To 2 Percent Slopes, Frequently Flooded-----	15,220	3.9
W	Water-----	6,512	1.7
We	Welda Silt Loam, 2 To 5 Percent Slopes-----	228	*
Wo	Woodson Silt Loam, 0 To 2 Percent Slopes-----	21,163	5.5
	Total-----	387,936	100.0

\* Less than 0.1 percent.

# Nontechnical Soil Descriptions Linn County, Kansas

Nontechnical soil descriptions describe soil properties or management considerations specific to a soil map unit or group of map units, shown in the NonTechnical Descriptions report. These descriptions are written in terminology that Non-technical users of soil survey information can understand. Nontechnical soil descriptions are a powerful tool for creating reports. These high quality, easy to read reports can be generated by conservation planners and other NRCS employees for distribution to land users. Soil map unit descriptions and National Soil Information System records are the basis for these descriptions.

## 003CD Collinsville Complex, 2 To 15 Percent Slopes

Collinsville soil makes up 65 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately steep summit, shoulder hillslope on upland. The runoff class is low. The parent material consists of sandstone residuum. The soil is 4 to 20 inches deep to bedrock (lithic). This soil is somewhat excessively drained. The slowest permeability is moderately rapid. It has a very low available water capacity and a low shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Shallow Sandstone (pe35-42) range site. It is in the nonirrigated land capability classification 6e.

Collinsville Taxadjunct soil makes up 20 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately steep summit, shoulder hillslope on upland. The runoff class is low. The parent material consists of sandstone residuum. The soil is 4 to 26 inches deep to bedrock (lithic). This soil is somewhat excessively drained. The slowest permeability is moderately rapid. It has a low available water capacity and a low shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Shallow Sandstone (pe35-42) range site. It is in the nonirrigated land capability classification 6e.

## 003DE Dennis Silty Clay Loam, 1 To 4 Percent Slopes, Eroded

Dennis, eroded, soil makes up 95 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately steep backslope hillslope on upland. The runoff class is medium. The parent material consists of silty and clayey residuum weathered from shale, unspecified. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 15 inches. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 3e.

## 003EH Eram Soils, 4 To 7 Percent Slopes, Eroded

Eram, eroded, soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately sloping backslope hillslope on upland. The runoff class is high. The parent material consists of silty and clayey residuum weathered from shale, unspecified. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is moderately well drained. The slowest permeability is moderately slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 6e.

## 003EK Eram-Clareson Complex, 1 To 15 Percent Slopes

Eram soil makes up 60 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately steep backslope hillslope on upland. The runoff class is high. The parent material consists of silty and clayey residuum weathered from shale, unspecified. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is moderately well drained. The slowest permeability is moderately slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 4e.

Clareson soil makes up 20 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately steep backslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey residuum weathered from limestone, unspecified. The soil is 20 to 40 inches deep to bedrock (lithic). This soil is well drained. The slowest permeability is slow. It has a very low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Shallow Flats (pe35-42) range site. It is in the nonirrigated land capability classification 6s.

## 003LE Leanna Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded

Leanna, drained, soil makes up 88 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level flood plain on river valley. The runoff class is medium. The parent material consists of silty and clayey alluvium. This soil is somewhat poorly drained. The slowest permeability is slow. It has a high available water capacity and a very high shrink swell potential. This soil is occasionally flooded and is not ponded. The top of the seasonal high water table is at 15 inches. This soil is in the Clay Lowland (pe35-42) range site. It is in the nonirrigated land capability classification 2w.

Nontechnical Soil Descriptions--Continued  
Linn County, Kansas

003LH Lula Silt Loam, 0 To 3 Percent Slopes

Lula soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level to gently sloping summit hillslope on upland. The runoff class is low. The parent material consists of residuum weathered from limestone, unspecified. The soil is 40 to 60 inches deep to bedrock (lithic). This soil is well drained. The slowest permeability is slow. It has a moderate available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 2e.

003SE Stony Land-Talihina Complex, 15 To 45 Percent Slopes

Talihina soil makes up 20 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep backslope hillslope on upland. The runoff class is high. The parent material consists of clayey residuum weathered from shale. The soil is 10 to 20 inches deep to bedrock (paralithic). This soil is moderately well drained. The slowest permeability is moderately slow. It has a very low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 15 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 6e.

003WF Woodson Silt Loam, 1 To 3 Percent Slopes

Woodson soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping paleoterrace on upland. The runoff class is high. The parent material consists of silty and clayey alluvium over silty and clayey residuum weathered from shale, clayey. This soil is somewhat poorly drained. The slowest permeability is very slow. It has a moderate available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 3e.

011CA Catoosa Silt Loam, 0 To 2 Percent Slopes

Catoosa soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level to gently sloping summit upland, ridge. The runoff class is medium. The parent material consists of residuum weathered from limestone. The soil is 20 to 40 inches deep to bedrock (lithic). This soil is well drained. The slowest permeability is moderately slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 2e.

059CM Clareson-Eram Silty Clay Loams, 3 To 15 Percent Slopes

Clareson soil makes up 55 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep backslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey residuum weathered from limestone. The soil is 20 to 40 inches deep to bedrock (lithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Shallow Flats (pe35-42) range site. It is in the nonirrigated land capability classification 6e.

Eram soil makes up 30 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey residuum weathered from shale. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is moderately well drained. The slowest permeability is slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 6e.

Bb Bates Loam, 1 To 4 Percent Slopes

Bates soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping summit, backslope hillslope on ridge on upland. The runoff class is medium. The parent material consists of sandy and silty residuum weathered from sandstone, unspecified over sandy and silty residuum weathered from sandstone-shale. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 2e.

Bc Bates Loam, 4 To 8 Percent Slopes

Bates soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on upland. The runoff class is high. The parent material consists of sandy and silty residuum weathered from sandstone, unspecified over sandy and silty residuum weathered from sandstone-shale. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 3e.

Nontechnical Soil Descriptions--Continued  
Linn County, Kansas

**Cb Catoosa Silt Loam, 1 To 3 Percent Slopes**

Catoosa soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping summit hillslope on ridge on upland. The runoff class is low. The parent material consists of residuum weathered from limestone. The soil is 20 to 40 inches deep to bedrock (lithic). This soil is well drained. The slowest permeability is moderately slow. It has a low available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 2e.

**Cm Clareson-Rock Outcrop Complex, 2 To 15 Percent Slopes**

Clareson soil makes up 60 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a strongly sloping to moderately steep summit hillslope on ridge on upland. The runoff class is high. The parent material consists of silty and clayey residuum weathered from limestone, unspecified. The soil is 20 to 40 inches deep to bedrock (lithic). This soil is well drained. The slowest permeability is moderately slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Shallow Flats (pe35-42) range site. It is in the nonirrigated land capability classification 6e.

**De Dennis Silt Loam, 1 To 3 Percent Slopes**

Dennis soil makes up 90 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping backslope, footslope hillslope on divide on upland. The runoff class is medium. The parent material consists of silty and clayey residuum weathered from shale, unspecified. This soil is moderately well drained. The slowest permeability is moderately slow. It has a high available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 28 inches. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 2e.

**Df Dennis Silt Loam, 3 To 6 Percent Slopes**

Dennis soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately sloping backslope hillslope on upland. The runoff class is high. The parent material consists of silty and clayey residuum weathered from shale, unspecified. This soil is moderately well drained. The slowest permeability is moderately slow. It has a high available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 28 inches. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 3e.

**Ec Eram Silty Clay Loam, 1 To 4 Percent Slopes**

Eram soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping backslope hillslope on ridge on upland. The runoff class is medium. The parent material consists of silty and clayey residuum weathered from shale, unspecified. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is moderately well drained. The slowest permeability is moderately slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 28 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 3e.

**Ed Eram Silty Clay Loam, 4 To 8 Percent Slopes**

Eram soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on ridge on upland. The runoff class is high. The parent material consists of silty and clayey residuum weathered from shale, unspecified. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is moderately well drained. The slowest permeability is moderately slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 28 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 4e.

**Ef Eram-Lebo Silty Clay Loams, 5 To 20 Percent Slopes**

Eram soil makes up 50 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on upland. The runoff class is high. The parent material consists of silty and clayey residuum weathered from shale, unspecified. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is moderately well drained. The slowest permeability is moderately slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 28 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 6e.

Lebo soil makes up 30 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a strongly sloping to moderately steep backslope hillslope on upland. The runoff class is high. The parent material consists of residuum weathered from shale-sandstone. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is impermeable. It has a moderate available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 6e.

Nontechnical Soil Descriptions--Continued  
Linn County, Kansas

**Hp Hepler Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded**

Hepler soil makes up 90 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on river valley. The runoff class is medium. The parent material consists of silty alluvium. This soil is somewhat poorly drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is occasionally flooded and is not ponded. The top of the seasonal high water table is at 24 inches. This soil is in the Loamy Lowland (pe35-42) range site. It is in the nonirrigated land capability classification 2w.

**INT Aquolls**

Aquolls soil makes up 100 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level depression on terrace on river valley. The runoff class is negligible. The parent material consists of alluvium. This soil is very poorly drained. It has a very low available water capacity and a low shrink swell potential. This soil is not flooded and is occasional ponded. The top of the seasonal high water table is at 0 inches. It is in the nonirrigated land capability classification 5w.

**Ke Kenoma Silt Loam, 1 To 4 Percent Slopes**

Kenoma soil makes up 90 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping backslope hillslope on ridge on paleoterrace on upland. The runoff class is high. The parent material consists of loess over ancient clayey alluvium and/or residuum weathered from limestone and shale. This soil is moderately well drained. The slowest permeability is very slow. It has a high available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil contains a very slightly saline horizon. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 3e.

**La Lanton Silt Loam, Occasionally Flooded**

Lanton soil makes up 90 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level flood plain on river valley. The runoff class is medium. The parent material consists of silty and clayey alluvium. This soil is somewhat poorly drained. The slowest permeability is slow. It has a high available water capacity and a low shrink swell potential. This soil is occasionally flooded and is not ponded. The top of the seasonal high water table is at 18 inches. This soil is in the Loamy Lowland (pe35-42) range site. It is in the nonirrigated land capability classification 2w.

**Lb Lebo Channery Silty Clay Loam, 15 To 30 Percent Slopes**

Lebo soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately steep to steep backslope hillslope on upland. The runoff class is very high. The parent material consists of residuum weathered from shale-sandstone. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is impermeable. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 6e.

**Mb Mason Silt Loam, 0 To 2 Percent Slopes, Rarely Flooded**

Mason soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level stream terrace on river valley. The runoff class is low. The parent material consists of silty alluvium. This soil is well drained. The slowest permeability is slow. It has a high available water capacity and a moderate shrink swell potential. This soil is rarely flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Lowland (pe35-42) range site. It is in the nonirrigated land capability classification 1.

**Nf Newtonia Silt Loam, 0 To 1 Percent Slopes**

Newtonia soil makes up 90 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level summit ridge on paleoterrace on upland. The runoff class is low. The parent material consists of loess over ancient silty and clayey alluvium over residuum weathered from limestone. This soil is well drained. The slowest permeability is slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 1.

**Ng Newtonia Silt Loam, 1 To 4 Percent Slopes**

Newtonia soil makes up 90 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping backslope hillslope on ridge on upland. The runoff class is low. The parent material consists of loess over ancient silty and clayey alluvium over residuum weathered from limestone. This soil is well drained. The slowest permeability is slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 2e.

Nontechnical Soil Descriptions--Continued  
Linn County, Kansas

Nh Newtonia Silt Loam, 4 To 8 Percent Slopes

Newtonia soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on upland. The runoff class is medium. The parent material consists of loess over ancient silty and clayey alluvium over residuum weathered from limestone. This soil is well drained. The slowest permeability is slow. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 3e.

Oh Okemah Silt Loam, 0 To 3 Percent Slopes

Okemah soil makes up 90 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level to gently sloping footslope hillslope on stream terrace on upland. The runoff class is medium. The parent material consists of silty and clayey colluvium and/or silty and clayey residuum weathered from shale. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 28 inches. This soil is in the Loamy Upland (pe35-42) range site. It is in the nonirrigated land capability classification 1.

Om Kanima Silty Clay Loam, 15 To 50 Percent Slopes

Kanima soil makes up 100 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately steep to very steep backslope hillslope on upland. The runoff class is very high. The parent material consists of mine spoil or earthy fill. This soil is excessively drained. The slowest permeability is moderately slow. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. It is in the nonirrigated land capability classification 7s.

Op Kanima Silty Clay Loam, 2 To 15 Percent Slopes

Kanima soil makes up 100 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately steep backslope hillslope on upland. The runoff class is high. The parent material consists of mine spoil or earthy fill. This soil is excessively drained. The slowest permeability is moderately slow. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. It is in the nonirrigated land capability classification 6s.

Ot Osage Silty Clay Loam, 0 To 2 Percent Slopes, Occasionally Flooded

Osage soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level flood plain on river valley. The runoff class is high. The parent material consists of clayey alluvium. This soil is poorly drained. The slowest permeability is very slow. It has a moderate available water capacity and a very high shrink swell potential. This soil is occasionally flooded and is occasional ponded. The top of the seasonal high water table is at 6 inches. This soil is in the Clay Lowland (pe35-42) range site. It is in the nonirrigated land capability classification 2w.

Ov Osage Silty Clay, Occasionally Flooded

Osage soil makes up 90 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level flood plain on river valley. The runoff class is high. The parent material consists of clayey alluvium. This soil is poorly drained. The slowest permeability is very slow. It has a moderate available water capacity and a very high shrink swell potential. This soil is occasionally flooded and is occasional ponded. The top of the seasonal high water table is at 6 inches. This soil is in the Clay Lowland (pe35-42) range site. It is in the nonirrigated land capability classification 3w.

Pc Parsons Silt Loam, 0 To 2 Percent Slopes

Parsons soil makes up 90 percent of the map unit. This map unit is in the This soil occurs on a nearly level divide on paleoterrace on upland. The runoff class is high. The parent material consists of loess over ancient clayey alluvium and/or residuum weathered from shale. This soil is somewhat poorly drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 2s.

Sn Summit Silty Clay Loam, 1 To 4 Percent Slopes

Summit soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping footslope hillslope on upland. The runoff class is medium. The parent material consists of silty and clayey colluvium and/or silty and clayey residuum weathered from calcareous shale. This soil is moderately well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 30 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 2e.



Nontechnical Soil Descriptions--Continued  
Linn County, Kansas

---

So Summit Silty Clay Loam, 4 To 8 Percent Slopes

Summit soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping footslope hillslope on upland. The runoff class is medium. The parent material consists of silty and clayey colluvium and/or silty and clayey residuum weathered from calcareous shale. This soil is moderately well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 30 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 3e.

Vb Verdigris Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded

Verdigris soil makes up 90 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on river valley. The runoff class is low. The parent material consists of silty alluvium. This soil is moderately well drained. The slowest permeability is moderately slow. It has a very high available water capacity and a low shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Lowland (pe35-42) range site. It is in the nonirrigated land capability classification 2w.

Vc Verdigris Silt Loam, 0 To 2 Percent Slopes, Frequently Flooded

Verdigris soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on river valley. The runoff class is low. The parent material consists of silty alluvium. This soil is moderately well drained. The slowest permeability is moderately slow. It has a very high available water capacity and a low shrink swell potential. This soil is frequently flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Lowland (pe35-42) range site. It is in the nonirrigated land capability classification 5w.

We Welda Silt Loam, 2 To 5 Percent Slopes

Welda soil makes up 90 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping stream terrace on upland. The runoff class is medium. The parent material consists of silty and clayey sediments. This soil is well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Savannah (pe35-42) range site. It is in the nonirrigated land capability classification 2e.

Wo Woodson Silt Loam, 0 To 2 Percent Slopes

Woodson soil makes up 85 percent of the map unit. This map unit is in the Cherokee Prairies Major Land Resource Area. This soil occurs on a nearly level to gently sloping divide on paleoterrace on upland. The runoff class is high. The parent material consists of silty loess over ancient clayey alluvium and/or silty and clayey residuum weathered from clayey shale. This soil is somewhat poorly drained. The slowest permeability is very slow. It has a moderate available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. This soil is in the Clay Upland (pe35-42) range site. It is in the nonirrigated land capability classification 2s.

## 003CD—Collinsville complex, 2 to 15 percent slopes

### Map Unit Composition

Collinsville: 65 percent  
Collinsville Taxadjunct: 20 percent  
Minor components: 15 percent

### Component Descriptions

#### Collinsville

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Summit, shoulder  
*Parent material:* Sandstone residuum  
*Slope:* 2 to 15 percent  
*Depth to restrictive feature:* 4 to 20 inches to bedrock (lithic)  
*Drainage class:* Somewhat excessively drained  
*Slowest permeability:* Moderately rapid (About 2.00 in/hr)  
*Available water capacity:* Very low (About 1.4 inches)  
*Shrink-swell potential:* Low (About 1.7 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Low  
*Ecological site:* Shallow Sandstone (pe35-42)  
*Land capability (nonirrigated):* 6e

#### Typical Profile:

H1—0 to 6 inches; loam  
H2—6 to 11 inches; channery loam  
R—11 to 15 inches; unweathered bedrock

#### Collinsville Taxadjunct

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Summit, shoulder  
*Parent material:* Sandstone residuum  
*Slope:* 2 to 15 percent  
*Depth to restrictive feature:* 4 to 26 inches to bedrock (lithic)  
*Drainage class:* Somewhat excessively drained  
*Slowest permeability:* Moderately rapid (About 2.00 in/hr)  
*Available water capacity:* Low (About 3.1 inches)  
*Shrink-swell potential:* Low (About 1.7 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Low  
*Ecological site:* Shallow Sandstone (pe35-42)  
*Land capability (nonirrigated):* 6e

#### Typical Profile:

H1—0 to 6 inches; loam  
H2—6 to 23 inches; channery loam  
R—23 to 27 inches; unweathered bedrock

### Minor Components

#### Dennis

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

#### Talihina

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 2 to 7 percent  
*Depth to restrictive feature:* 10 to 20 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

#### Eram

*Composition:* About 3 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 2 to 7 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

#### Summit

*Composition:* About 2 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 4 to 7 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

## 003DE—Dennis silty clay loam, 1 to 4 percent slopes, eroded

### Map Unit Composition

Dennis: 95 percent  
Minor components: 5 percent

### Component Descriptions

#### Dennis

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Backslope  
*Parent material:* Silty and clayey residuum weathered from shale, unspecified  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)

*Available water capacity:* High (About 9.5 inches)  
*Shrink-swell potential:* High (About 7.6 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* About 12 to 18 inches  
*Runoff class:* Medium  
*Ecological site:* Loamy Upland (pe35-42)  
*Land capability (nonirrigated):* 3e

*Typical Profile:*

H1—0 to 10 inches; silty clay loam  
 H2—10 to 21 inches; silty clay loam  
 H3—21 to 47 inches; silty clay  
 H4—47 to 60 inches; silty clay

**Minor Components**

**Eram**

*Phase:* Eroded  
*Composition:* About 3 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 1 to 4 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**Kenoma**

*Phase:* Eroded  
*Composition:* About 2 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**003EH—Eram Soils, 4 to 7 percent slopes, eroded**

**Map Unit Composition**

Eram: 85 percent  
 Minor components: 15 percent

**Component Descriptions**

**Eram**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Backslope  
*Parent material:* Silty and clayey residuum weathered from shale, unspecified  
*Slope:* 4 to 7 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained

*Slowest permeability:* Moderately slow (About 0.20 in/hr)  
*Available water capacity:* Low (About 5.2 inches)  
*Shrink-swell potential:* High (About 7.5 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* About 6 to 18 inches  
*Runoff class:* High  
*Ecological site:* Clay Upland (pe35-42)  
*Land capability (nonirrigated):* 6e

*Typical Profile:*

H1—0 to 15 inches; silty clay loam  
 H2—15 to 33 inches; silty clay loam  
 Cr—33 to 37 inches;

**Minor Components**

**Talihina**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 4 to 15 percent  
*Depth to restrictive feature:* 10 to 20 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**Dennis**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Collinsville**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 2 to 15 percent  
*Depth to restrictive feature:* 4 to 20 inches to bedrock (lithic)  
*Drainage class:* Somewhat excessively drained  
*Ecological site:* Shallow Sandstone (pe35-42)

**003EK—Eram-Clareson complex, 1 to 15 percent slopes**

**Map Unit Composition**

Eram: 60 percent  
 Clareson: 20 percent  
 Minor components: 20 percent

**Component Descriptions**

**Eram**

*MLRA:* 112 - Cherokee Prairies

*Landform:* Hillslope on upland  
*Hillslope position:* Backslope  
*Parent material:* Silty and clayey residuum weathered from shale, unspecified  
*Slope:* 1 to 15 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Slowest permeability:* Moderately slow (About 0.20 in/hr)  
*Available water capacity:* Low (About 5.0 inches)  
*Shrink-swell potential:* High (About 7.5 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* About 6 to 18 inches  
*Runoff class:* High  
*Ecological site:* Clay Upland (pe35-42)  
*Land capability (nonirrigated):* 4e

*Typical Profile:*

H1—0 to 9 inches; silty clay loam  
H2—9 to 33 inches; silty clay loam  
Cr—33 to 37 inches;

**Clareson**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Backslope  
*Parent material:* Silty and clayey residuum weathered from limestone, unspecified  
*Slope:* 1 to 15 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* Very low (About 1.9 inches)  
*Shrink-swell potential:* Moderate (About 4.6 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Very high  
*Ecological site:* Shallow Flats (pe35-42)  
*Land capability (nonirrigated):* 6s

*Typical Profile:*

H1—0 to 7 inches; flaggy silty clay loam  
H2—7 to 16 inches; very flaggy silty clay  
H3—16 to 24 inches; extremely flaggy silty clay  
R—24 to 32 inches; unweathered bedrock

**Minor Components**

**Rock outcrop**

*Composition:* About 5 percent

**Talihina**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 4 to 15 percent  
*Depth to restrictive feature:* 10 to 20 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**Summit**

*Composition:* About 4 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 4 to 7 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Catoosa**

*Composition:* About 3 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 0 to 3 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Dennis**

*Composition:* About 3 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

**003LE—Leanna silt loam, 0 to 2 percent slopes, occasionally flooded**

**Map Unit Composition**

Leanna: 88 percent  
Minor components: 12 percent

**Component Descriptions**

**Leanna**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Flood plain on river valley  
*Parent material:* Silty and clayey alluvium  
*Slope:* 0 to 1 percent  
*Drainage class:* Somewhat poorly drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* High (About 10.4 inches)  
*Shrink-swell potential:* Very high (About 10.7 LEP)  
*Flooding hazard:* Occasional  
*Depth to seasonal water saturation:* About 6 to 24 inches  
*Runoff class:* Medium

*Ecological site:* Clay Lowland (pe35-42)  
*Land capability (nonirrigated):* 2w

*Typical Profile:*

H1—0 to 17 inches; silt loam  
 H2—17 to 37 inches; silty clay  
 H3—37 to 64 inches; silty clay

**Minor Components**

**Lanton**

*Composition:* About 3 percent  
*Slope:* 0 to 1 percent  
*Drainage class:* Poorly drained  
*Ecological site:* Loamy Lowland (pe35-42)

**Osage**

*Composition:* About 3 percent  
*Slope:* 0 to 1 percent  
*Drainage class:* Poorly drained  
*Ecological site:* Clay Lowland (pe35-42)

**Verdigris**

*Composition:* About 3 percent  
*Slope:* 0 to 2 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Lowland (pe35-42)

**Woodson**

*Composition:* About 3 percent  
*Geomorphic Position:* divide on upland  
*Slope:* 1 to 3 percent  
*Drainage class:* Somewhat poorly drained  
*Ecological site:* Clay Upland (pe35-42)

**003LH—Lula silt loam, 0 to 3 percent slopes**

**Map Unit Composition**

Lula: 85 percent  
 Minor components: 15 percent

**Component Descriptions**

**Lula**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Summit  
*Parent material:* Residuum weathered from limestone, unspicified  
*Slope:* 0 to 3 percent  
*Depth to restrictive feature:* 40 to 60 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* Moderate (About 8.8 inches)

*Shrink-swell potential:* Moderate (About 4.5 LEP)

*Flooding hazard:* None

*Depth to seasonal water saturation:* More than 6 feet

*Runoff class:* Low

*Ecological site:* Loamy Upland (pe35-42)

*Land capability (nonirrigated):* 2e

*Typical Profile:*

H1—0 to 13 inches; silt loam  
 H2—13 to 29 inches; silty clay loam  
 H3—29 to 49 inches; silty clay loam  
 R—49 to 53 inches; unweathered bedrock

**Minor Components**

**Catoosa**

*Composition:* About 5 percent  
*Slope:* 0 to 3 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Clareson**

*Composition:* About 5 percent  
*Slope:* 1 to 15 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Shallow Flats (pe35-42)

**Kenoma**

*Composition:* About 5 percent  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**003SE—stony Land-Talihina complex, 15 to 45 percent slopes**

**Map Unit Composition**

Stony Land: 60 percent  
 Talihina: 20 percent  
 Minor components: 20 percent

**Component Descriptions**

**Stony Land**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Parent material:* Residuum  
*Slope:* 15 to 45 percent  
*Drainage class:* Excessively drained  
*Depth to seasonal water saturation:* More than 6 feet

*Land capability (nonirrigated): 7e*

### **Talihina**

*MLRA: 112 - Cherokee Prairies*

*Landform: Hillslope on upland*

*Hillslope position: Backslope*

*Parent material: Clayey residuum weathered from shale*

*Slope: 4 to 15 percent*

*Depth to restrictive feature: 10 to 20 inches to bedrock (paralithic)*

*Drainage class: Moderately well drained*

*Slowest permeability: Moderately slow (About 0.20 in/hr)*

*Available water capacity: Very low (About 2.5 inches)*

*Shrink-swell potential: High (About 8.1 LEP)*

*Flooding hazard: None*

*Depth to seasonal water saturation: About 6 to 24 inches*

*Runoff class: High*

*Ecological site: Clay Upland (pe35-42)*

*Land capability (nonirrigated): 6e*

#### *Typical Profile:*

H1—0 to 7 inches; silty clay loam

H2—7 to 12 inches; silty clay loam

H3—12 to 15 inches; silty clay loam

Cr—15 to 19 inches; weathered bedrock

### **Minor Components**

#### **Clareson**

*Composition: About 5 percent*

*Geomorphic Position: hillslope on upland*

*Slope: 1 to 15 percent*

*Depth to restrictive feature: 20 to 40 inches to bedrock (lithic)*

*Drainage class: Well drained*

*Ecological site: Shallow Flats (pe35-42)*

#### **Dennis**

*Composition: About 5 percent*

*Geomorphic Position: hillslope on upland*

*Slope: 1 to 4 percent*

*Drainage class: Moderately well drained*

*Ecological site: Loamy Upland (pe35-42)*

#### **Eram**

*Composition: About 5 percent*

*Geomorphic Position: hillslope on upland*

*Slope: 1 to 15 percent*

*Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)*

*Drainage class: Moderately well drained*

*Ecological site: Clay Upland (pe35-42)*

#### **Summit**

*Composition: About 5 percent*

*Geomorphic Position: hillslope on upland*

*Slope: 4 to 7 percent*

*Drainage class: Moderately well drained*

*Ecological site: Loamy Upland (pe35-42)*

## **003WF—Woodson silt loam, 1 to 3 percent slopes**

### **Map Unit Composition**

Woodson: 85 percent

Minor components: 15 percent

### **Component Descriptions**

#### **Woodson**

*MLRA: 112 - Cherokee Prairies*

*Landform: Paleoterrace on upland*

*Parent material: Silty and clayey alluvium over silty and clayey residuum weathered from shale,*

*clayey*

*Slope: 1 to 3 percent*

*Drainage class: Somewhat poorly drained*

*Slowest permeability: Very slow (About 0.00 in/hr)*

*Available water capacity: Moderate (About 8.7 inches)*

*Shrink-swell potential: Very high (About 13.5 LEP)*

*Flooding hazard: None*

*Depth to seasonal water saturation: About 4 to 9 inches*

*Runoff class: High*

*Ecological site: Clay Upland (pe35-42)*

*Land capability (nonirrigated): 3e*

#### *Typical Profile:*

H1—0 to 8 inches; silt loam

H2—8 to 29 inches; silty clay

H3—29 to 64 inches; silty clay

### **Minor Components**

#### **Eram**

*Composition: About 5 percent*

*Geomorphic Position: hillslope on upland*

*Slope: 1 to 2 percent*

*Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)*

*Drainage class: Moderately well drained*

*Ecological site: Clay Upland (pe35-42)*

#### **Kenoma**

*Composition: About 5 percent*

*Geomorphic Position: hillslope on upland*

*Slope: 1 to 4 percent*

*Drainage class: Moderately well drained*

*Ecological site: Clay Upland (pe35-42)*

#### **Summit**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 1 to 2 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

*Geomorphic Position:* ridge on paleoterrace  
 on upland  
*Slope:* 1 to 3 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

## 011CA—Catoosa silt loam, 0 to 2 percent slopes

### Map Unit Composition

Catoosa: 85 percent  
 Minor components: 15 percent

### Component Descriptions

#### Catoosa

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Upland, ridge  
*Hillslope position:* Summit  
*Parent material:* Residuum weathered from limestone  
*Slope:* 0 to 2 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Slowest permeability:* Moderately slow (About 0.20 in/hr)  
*Available water capacity:* Low (About 4.6 inches)  
*Shrink-swell potential:* High (About 7.4 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Medium  
*Ecological site:* Loamy Upland (pe35-42)  
*Land capability (nonirrigated):* 2e

#### Typical Profile:

H1—0 to 11 inches; silt loam  
 H2—11 to 16 inches; silty clay loam  
 H3—16 to 27 inches; silty clay loam  
 R—27 to 35 inches; unweathered bedrock

### Minor Components

#### Clareson

*Composition:* About 10 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 1 to 4 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Shallow Flats (pe35-42)

#### Kenoma

*Composition:* About 5 percent

## 059CM—Clareson-Eram silty clay loams, 3 to 15 percent slopes

### Map Unit Composition

Clareson: 55 percent  
 Eram: 30 percent  
 Minor components: 15 percent

### Component Descriptions

#### Clareson

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Backslope  
*Parent material:* Silty and clayey residuum weathered from limestone  
*Slope:* 3 to 15 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* Low (About 3.2 inches)  
*Shrink-swell potential:* Moderate (About 5.6 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Very high  
*Ecological site:* Shallow Flats (pe35-42)  
*Land capability (nonirrigated):* 6e

#### Typical Profile:

H1—0 to 7 inches; silty clay loam  
 H2—7 to 15 inches; silty clay loam  
 H3—15 to 26 inches; flaggy silty clay loam  
 R—26 to 34 inches; unweathered bedrock

#### Eram

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Backslope  
*Parent material:* Silty and clayey residuum weathered from shale  
*Slope:* 3 to 12 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)

*Available water capacity:* Low (About 5.6 inches)  
*Shrink-swell potential:* High (About 7.3 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* About 9 to 14 inches  
*Runoff class:* Very high  
*Ecological site:* Clay Upland (pe35-42)  
*Land capability (nonirrigated):* 6e

*Typical Profile:*

H1—0 to 7 inches; silty clay loam  
 H2—7 to 38 inches; silty clay  
 Cr—38 to 46 inches; weathered bedrock

**Minor Components**

**Bates**

*Composition:* About 10 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 3 to 7 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Rock outcrop**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland

**AED—Arents, Earthen Dam**

**Bb—Bates loam, 1 to 4 percent slopes**

**Map Unit Composition**

Bates: 85 percent  
 Minor components: 15 percent

**Component Descriptions**

**Bates**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on ridge on upland  
*Hillslope position:* Summit, backslope  
*Parent material:* Sandy and silty residuum weathered from sandstone, unspecified over sandy and silty residuum weathered from sandstone-shale  
*Slope:* 1 to 4 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* Low (About 5.6 inches)

*Shrink-swell potential:* Moderate (About 3.3 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Medium  
*Ecological site:* Loamy Upland (pe35-42)  
*Land capability (nonirrigated):* 2e

*Typical Profile:*

H1—0 to 10 inches; loam  
 H2—10 to 21 inches; clay loam  
 H3—21 to 31 inches; gravelly clay loam  
 Cr—31 to 35 inches;

**Minor Components**

**Rock outcrop**

*Composition:* About 5 percent

**Dennis**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on divide on upland  
*Slope:* 1 to 3 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Eram**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 1 to 4 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**Bc—Bates loam, 4 to 8 percent slopes**

**Map Unit Composition**

Bates: 85 percent  
 Minor components: 15 percent

**Component Descriptions**

**Bates**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Backslope  
*Parent material:* Sandy and silty residuum weathered from sandstone, unspecified over sandy and silty residuum weathered from sandstone-shale  
*Slope:* 4 to 8 percent



*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* Low (About 5.4 inches)  
*Shrink-swell potential:* Moderate (About 3.3 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* High  
*Ecological site:* Loamy Upland (pe35-42)  
*Land capability (nonirrigated):* 3e

*Typical Profile:*

H1—0 to 7 inches; loam  
 H2—7 to 18 inches; clay loam  
 H3—18 to 31 inches; gravelly clay loam  
 Cr—31 to 35 inches;

**Minor Components**

**Dennis**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 3 to 6 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Eram**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 4 to 8 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**Lebo**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 15 to 30 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Cb—Catoosa silt loam, 1 to 3 percent slopes**

**Map Unit Composition**

Catoosa: 85 percent  
 Minor components: 15 percent

**Component Descriptions**

**Catoosa**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on ridge on upland  
*Hillslope position:* Summit  
*Parent material:* Residuum weathered from limestone  
*Slope:* 1 to 3 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Slowest permeability:* Moderately slow (About 0.20 in/hr)  
*Available water capacity:* Low (About 5.7 inches)  
*Shrink-swell potential:* Very high (About 9.1 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Low  
*Ecological site:* Loamy Upland (pe35-42)  
*Land capability (nonirrigated):* 2e

*Typical Profile:*

H1—0 to 12 inches; silt loam  
 H2—12 to 25 inches; silty clay loam  
 H3—25 to 29 inches; silty clay  
 R—29 to 33 inches; unweathered bedrock

**Minor Components**

**Clareson**

*Composition:* About 4 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 7 to 15 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Shallow Flats (pe35-42)

**Kenoma**

*Composition:* About 4 percent  
*Geomorphic Position:* hillslope on ridge on paleoterrace on upland  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**Summit**

*Composition:* About 4 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**Eram**

*Composition:* About 3 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 1 to 4 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained

*Ecological site:* Clay Upland (pe35-42)

## **Cm—Clareson-Rock outcrop complex, 2 to 15 percent slopes**

### **Map Unit Composition**

Clareson: 60 percent  
Rock outcrop: 20 percent  
Minor components: 20 percent

### **Component Descriptions**

#### **Clareson**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on ridge on upland  
*Hillslope position:* Summit  
*Parent material:* Silty and clayey residuum weathered from limestone, unspecified  
*Slope:* 7 to 15 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Slowest permeability:* Moderately slow (About 0.20 in/hr)  
*Available water capacity:* Low (About 3.9 inches)  
*Shrink-swell potential:* High (About 6.2 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* High  
*Ecological site:* Shallow Flats (pe35-42)  
*Land capability (nonirrigated):* 6e

#### *Typical Profile:*

H1—0 to 11 inches; silty clay loam  
H2—11 to 16 inches; flaggy silty clay loam  
H3—16 to 33 inches; very flaggy silty clay  
R—33 to 37 inches; unweathered bedrock

#### **Rock outcrop**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Ridge on upland  
*Hillslope position:* Shoulder  
*Drainage class:* Well drained  
*Depth to seasonal water saturation:* More than 6 feet  
*Land capability (nonirrigated):* 8

#### **Minor Components**

##### **Catoosa**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 1 to 3 percent

*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Loamy Upland (pe35-42)

#### **Eram**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 4 to 8 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

#### **Lebo**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 15 to 30 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Well drained  
*Ecological site:* Loamy Upland (pe35-42)

#### **Summit**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 4 to 8 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

## **De—Dennis silt loam, 1 to 3 percent slopes**

### **Map Unit Composition**

Dennis: 90 percent  
Minor components: 10 percent

### **Component Descriptions**

#### **Dennis**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on divide on upland  
*Hillslope position:* Backslope, footslope  
*Parent material:* Silty and clayey residuum weathered from shale, unspecified  
*Slope:* 1 to 3 percent  
*Drainage class:* Moderately well drained  
*Slowest permeability:* Moderately slow (About 0.20 in/hr)  
*Available water capacity:* High (About 10.6 inches)  
*Shrink-swell potential:* Very high (About 9.4 LEP)  
*Flooding hazard:* None

*Depth to seasonal water saturation:* About 24 to 36 inches

*Runoff class:* Medium

*Ecological site:* Loamy Upland (pe35-42)

*Land capability (nonirrigated):* 2e

**Typical Profile:**

H1—0 to 11 inches; silt loam

H2—11 to 17 inches; silty clay loam

H3—17 to 25 inches; silty clay

H4—25 to 60 inches; silty clay

**Minor Components**

**Bates**

*Composition:* About 4 percent

*Geomorphic Position:* hillslope on ridge on upland

*Slope:* 1 to 4 percent

*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)

*Drainage class:* Well drained

*Ecological site:* Loamy Upland (pe35-42)

**Eram**

*Composition:* About 3 percent

*Geomorphic Position:* hillslope on ridge on upland

*Slope:* 1 to 4 percent

*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)

*Drainage class:* Moderately well drained

*Ecological site:* Clay Upland (pe35-42)

**Kenoma**

*Composition:* About 3 percent

*Geomorphic Position:* hillslope on ridge on paleoterrace on upland

*Slope:* 1 to 4 percent

*Drainage class:* Moderately well drained

*Ecological site:* Clay Upland (pe35-42)

**Df—Dennis silt loam, 3 to 6 percent slopes**

**Map Unit Composition**

Dennis: 85 percent

Minor components: 15 percent

**Component Descriptions**

**Dennis**

*MLRA:* 112 - Cherokee Prairies

*Landform:* Hillslope on upland

*Hillslope position:* Backslope

*Parent material:* Silty and clayey residuum weathered from shale, unspecified

*Slope:* 3 to 6 percent

*Drainage class:* Moderately well drained

*Slowest permeability:* Moderately slow (About 0.20 in/hr)

*Available water capacity:* High (About 10.6 inches)

*Shrink-swell potential:* Very high (About 9.4 LEP)

*Flooding hazard:* None

*Depth to seasonal water saturation:* About 24 to 36 inches

*Runoff class:* High

*Ecological site:* Loamy Upland (pe35-42)

*Land capability (nonirrigated):* 3e

**Typical Profile:**

H1—0 to 10 inches; silt loam

H2—10 to 16 inches; silty clay loam

H3—16 to 24 inches; silty clay

H4—24 to 60 inches; silty clay

**Minor Components**

**Kenoma**

*Composition:* About 5 percent

*Geomorphic Position:* hillslope on ridge on paleoterrace on upland

*Slope:* 1 to 4 percent

*Drainage class:* Moderately well drained

*Ecological site:* Clay Upland (pe35-42)

**Bates**

*Composition:* About 5 percent

*Geomorphic Position:* hillslope on upland

*Slope:* 4 to 8 percent

*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)

*Drainage class:* Well drained

*Ecological site:* Loamy Upland (pe35-42)

**Eram**

*Composition:* About 5 percent

*Geomorphic Position:* hillslope on ridge on upland

*Slope:* 4 to 8 percent

*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)

*Drainage class:* Moderately well drained

*Ecological site:* Clay Upland (pe35-42)

**Ec—Eram silty clay loam, 1 to 4 percent slopes**

**Map Unit Composition**

Eram: 85 percent

Minor components: 15 percent

## Component Descriptions

### Eram

*MLRA:* 112 - Cherokee Prairies

*Landform:* Hillslope on ridge on upland

*Hillslope position:* Backslope

*Parent material:* Silty and clayey residuum weathered from shale, unspecified

*Slope:* 1 to 4 percent

*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)

*Drainage class:* Moderately well drained

*Slowest permeability:* Moderately slow (About 0.20 in/hr)

*Available water capacity:* Low (About 4.2 inches)

*Shrink-swell potential:* High (About 6.4 LEP)

*Flooding hazard:* None

*Depth to seasonal water saturation:* About 24 to 36 inches

*Runoff class:* Medium

*Ecological site:* Clay Upland (pe35-42)

*Land capability (nonirrigated):* 3e

#### Typical Profile:

H1—0 to 10 inches; silty clay loam

H2—10 to 27 inches; silty clay

Cr—27 to 31 inches;

### Minor Components

#### Dennis

*Composition:* About 4 percent

*Geomorphic Position:* hillslope on divide on upland

*Slope:* 1 to 3 percent

*Drainage class:* Moderately well drained

*Ecological site:* Loamy Upland (pe35-42)

#### Bates

*Composition:* About 4 percent

*Geomorphic Position:* hillslope on ridge on upland

*Slope:* 1 to 4 percent

*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)

*Drainage class:* Well drained

*Ecological site:* Loamy Upland (pe35-42)

#### Catoosa

*Composition:* About 4 percent

*Geomorphic Position:* hillslope on ridge on upland

*Slope:* 1 to 3 percent

*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)

*Drainage class:* Well drained

*Ecological site:* Loamy Upland (pe35-42)

#### Summit

*Composition:* About 3 percent

*Geomorphic Position:* hillslope on upland

*Slope:* 1 to 4 percent

*Drainage class:* Moderately well drained

*Ecological site:* Clay Upland (pe35-42)

## Ed—Eram silty clay loam, 4 to 8 percent slopes

### Map Unit Composition

Eram: 85 percent

Minor components: 15 percent

## Component Descriptions

### Eram

*MLRA:* 112 - Cherokee Prairies

*Landform:* Hillslope on ridge on upland

*Hillslope position:* Backslope

*Parent material:* Silty and clayey residuum weathered from shale, unspecified

*Slope:* 4 to 8 percent

*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)

*Drainage class:* Moderately well drained

*Slowest permeability:* Moderately slow (About 0.20 in/hr)

*Available water capacity:* Low (About 4.2 inches)

*Shrink-swell potential:* High (About 6.4 LEP)

*Flooding hazard:* None

*Depth to seasonal water saturation:* About 24 to 36 inches

*Runoff class:* High

*Ecological site:* Clay Upland (pe35-42)

*Land capability (nonirrigated):* 4e

#### Typical Profile:

H1—0 to 9 inches; silty clay loam

H2—9 to 27 inches; silty clay

Cr—27 to 31 inches;

### Minor Components

#### Dennis

*Composition:* About 4 percent

*Geomorphic Position:* hillslope on upland

*Slope:* 3 to 6 percent

*Drainage class:* Moderately well drained

*Ecological site:* Loamy Upland (pe35-42)

#### Lebo

*Composition:* About 4 percent

*Geomorphic Position:* hillslope on upland

*Slope:* 15 to 30 percent

*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)

*Drainage class:* Well drained

*Ecological site:* Loamy Upland (pe35-42)

**Bates**

*Composition:* About 4 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 4 to 8 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Summit**

*Composition:* About 3 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 4 to 8 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**Ef—Eram-Lebo silty clay loams, 5 to 20 percent slopes****Map Unit Composition**

Eram: 50 percent  
 Lebo: 30 percent  
 Minor components: 20 percent

**Component Descriptions****Eram**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Backslope  
*Parent material:* Silty and clayey residuum weathered from shale, unspecified  
*Slope:* 5 to 12 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Slowest permeability:* Moderately slow (About 0.20 in/hr)  
*Available water capacity:* Low (About 4.1 inches)  
*Shrink-swell potential:* High (About 6.4 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* About 24 to 36 inches  
*Runoff class:* High  
*Ecological site:* Clay Upland (pe35-42)  
*Land capability (nonirrigated):* 6e

*Typical Profile:*

H1—0 to 8 inches; silty clay loam  
 H2—8 to 27 inches; silty clay  
 Cr—27 to 31 inches; weathered bedrock

**Lebo**

*MLRA:* 112 - Cherokee Prairies

*Landform:* Hillslope on upland  
*Hillslope position:* Backslope  
*Parent material:* Residuum weathered from shale-sandstone  
*Slope:* 8 to 20 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Well drained  
*Slowest permeability:* Impermeable (About 0.00 in/hr)  
*Available water capacity:* Moderate (About 6.3 inches)  
*Shrink-swell potential:* Very high (About 9.4 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* High  
*Ecological site:* Loamy Upland (pe35-42)  
*Land capability (nonirrigated):* 6e

*Typical Profile:*

H1—0 to 12 inches; silty clay  
 H2—12 to 28 inches; silty clay  
 H3—28 to 38 inches; extremely channery silty clay loam  
 Cr—38 to 42 inches; weathered bedrock

**Minor Components****Clareson**

*Composition:* About 10 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 7 to 15 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Shallow Flats (pe35-42)

**Dennis**

*Composition:* About 10 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 3 to 6 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Hp—Hepler silt loam, 0 to 2 percent slopes, occasionally flooded****Map Unit Composition**

Hepler: 90 percent  
 Minor components: 10 percent

## Component Descriptions

### Hepler

*MLRA:* 112 - Cherokee Prairies

*Landform:* Flood plain on river valley

*Parent material:* Silty alluvium

*Slope:* 0 to 2 percent

*Drainage class:* Somewhat poorly drained

*Slowest permeability:* Moderately slow (About 0.20 in/hr)

*Available water capacity:* High (About 10.6 inches)

*Shrink-swell potential:* Moderate (About 3.2 LEP)

*Flooding hazard:* Occasional

*Depth to seasonal water saturation:* About 12 to 36 inches

*Runoff class:* Medium

*Ecological site:* Loamy Lowland (pe35-42)

*Land capability (nonirrigated):* 2w

### Typical Profile:

H1—0 to 9 inches; silt loam

H2—9 to 25 inches; silt loam

H3—25 to 40 inches; silty clay loam

H4—40 to 60 inches; silty clay loam

### Minor Components

#### Mason

*Composition:* About 10 percent

*Slope:* 0 to 1 percent

*Drainage class:* Well drained

*Ecological site:* Loamy Lowland (pe35-42)

## INT—Aquolls

### Map Unit Composition

Aquolls: 100 percent

## Component Descriptions

### Aquolls

*MLRA:* 112 - Cherokee Prairies

*Landform:* Depression on terrace on river valley

*Parent material:* Alluvium

*Slope:* 0 to 1 percent

*Drainage class:* Very poorly drained

*Flooding hazard:* None

*Ponding hazard:* Occasional

*Depth to seasonal water saturation:* About 0 to 0 inches

*Runoff class:* Negligible

*Land capability (nonirrigated):* 5w

### Typical Profile:

H1—0 to 72 inches; variable

*General Considerations:* This map unit was formerly labeled as an Intermittent Water spot symbol. These depressional areas contain soils that are occasionally ponded for long duration.

## Ke—Kenoma silt loam, 1 to 4 percent slopes

### Map Unit Composition

Kenoma: 90 percent

Minor components: 10 percent

## Component Descriptions

### Kenoma

*MLRA:* 112 - Cherokee Prairies

*Landform:* Hillslope on ridge on paleoterrace on upland

*Hillslope position:* Backslope

*Parent material:* Loess over ancient clayey alluvium and/or residuum weathered from limestone and

shale

*Slope:* 1 to 4 percent

*Drainage class:* Moderately well drained

*Slowest permeability:* Very slow (About 0.00 in/hr)

*Available water capacity:* High (About 9.0 inches)

*Shrink-swell potential:* Very high (About 9.9 LEP)

*Flooding hazard:* None

*Depth to seasonal water saturation:* More than 6 feet

*Runoff class:* High

*Ecological site:* Clay Upland (pe35-42)

*Land capability (nonirrigated):* 3e

### Typical Profile:

H1—0 to 10 inches; silt loam

H2—10 to 22 inches; silty clay

H3—22 to 44 inches; silty clay

H4—44 to 60 inches; silty clay

### Minor Components

#### Dennis

*Composition:* About 4 percent

*Geomorphic Position:* hillslope on divide on upland

*Slope:* 1 to 3 percent

*Drainage class:* Moderately well drained

*Ecological site:* Loamy Upland (pe35-42)

#### **Eram**

*Composition:* About 3 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 1 to 4 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

#### **Catoosa**

*Composition:* About 3 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 1 to 3 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Loamy Upland (pe35-42)

### **La—Lanton silt loam, occasionally flooded**

#### **Map Unit Composition**

Lanton: 90 percent  
 Minor components: 10 percent

#### **Component Descriptions**

##### **Lanton**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Flood plain on river valley  
*Parent material:* Silty and clayey alluvium  
*Slope:* 0 to 1 percent  
*Drainage class:* Somewhat poorly drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* High (About 10.7 inches)  
*Shrink-swell potential:* Low (About 2.2 LEP)  
*Flooding hazard:* Occasional  
*Depth to seasonal water saturation:* About 12 to 24 inches  
*Runoff class:* Medium  
*Ecological site:* Loamy Lowland (pe35-42)  
*Land capability (nonirrigated):* 2w

##### *Typical Profile:*

H1—0 to 14 inches; silt loam  
 H2—14 to 38 inches; silt loam  
 H3—38 to 53 inches; silt loam, silty clay loam  
 H4—53 to 60 inches; silty clay loam

#### **Minor Components**

#### **Osage**

*Composition:* About 10 percent  
*Slope:* 0 to 1 percent  
*Drainage class:* Poorly drained  
*Ecological site:* Clay Lowland (pe35-42)

### **Lb—Lebo channery silty clay loam, 15 to 30 percent slopes**

#### **Map Unit Composition**

Lebo: 85 percent  
 Minor components: 15 percent

#### **Component Descriptions**

##### **Lebo**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Backslope  
*Parent material:* Residuum weathered from shale-sandstone  
*Slope:* 15 to 30 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Well drained  
*Slowest permeability:* Impermeable (About 0.00 in/hr)  
*Available water capacity:* Moderate (About 6.2 inches)  
*Shrink-swell potential:* High (About 8.4 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Very high  
*Ecological site:* Loamy Upland (pe35-42)  
*Land capability (nonirrigated):* 6e

##### *Typical Profile:*

H1—0 to 11 inches; gravelly silty clay loam  
 H2—11 to 27 inches; channery silty clay loam  
 H3—27 to 38 inches; extremely channery silty clay loam  
 Cr—38 to 42 inches;

#### **Minor Components**

##### **Clareson**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 7 to 15 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Shallow Flats (pe35-42)

**Rock outcrop**

*Composition:* About 5 percent  
*Geomorphic Position:* ridge on upland  
*Drainage class:* Well drained

**Eram**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 4 to 8 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (paralithic)  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

*Slope:* 0 to 1 percent  
*Drainage class:* Poorly drained  
*Ecological site:* Clay Lowland (pe35-42)

**Hepler**

*Composition:* About 5 percent  
*Slope:* 0 to 2 percent  
*Drainage class:* Somewhat poorly drained  
*Ecological site:* Loamy Lowland (pe35-42)

**Verdigris**

*Composition:* About 5 percent  
*Slope:* 0 to 2 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Lowland (pe35-42)

**M-W—Miscellaneous Water****Mb—Mason silt loam, 0 to 2 percent slopes, rarely flooded****Map Unit Composition**

Mason: 85 percent  
 Minor components: 15 percent

**Component Descriptions****Mason**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Stream terrace on river valley  
*Parent material:* Silty alluvium  
*Slope:* 0 to 1 percent  
*Drainage class:* Well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* High (About 10.6 inches)  
*Shrink-swell potential:* Moderate (About 4.5 LEP)  
*Flooding hazard:* Rare  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Low  
*Ecological site:* Loamy Lowland (pe35-42)  
*Land capability (nonirrigated):* 1

*Typical Profile:*

H1—0 to 18 inches; silt loam  
 H2—18 to 50 inches; silty clay loam  
 H3—50 to 60 inches; silty clay loam

**Minor Components****Osage**

*Composition:* About 5 percent

**Nf—Newtonia silt loam, 0 to 1 percent slopes****Map Unit Composition**

Newtonia: 90 percent  
 Minor components: 10 percent

**Component Descriptions****Newtonia**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Ridge on paleoterrace on upland  
*Hillslope position:* Summit  
*Parent material:* Loess over ancient silty and clayey alluvium over residuum weathered from limestone  
*Slope:* 0 to 1 percent  
*Drainage class:* Well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* High (About 11.3 inches)  
*Shrink-swell potential:* Moderate (About 3.8 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Low  
*Ecological site:* Loamy Upland (pe35-42)  
*Land capability (nonirrigated):* 1

*Typical Profile:*

H1—0 to 13 inches; silt loam  
 H2—13 to 26 inches; silty clay loam  
 H3—26 to 49 inches; silty clay loam  
 H4—49 to 60 inches; silty clay loam

**Minor Components****Kenoma**



*Composition:* About 10 percent  
*Geomorphic Position:* hillslope on ridge on paleoterrace on upland  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

## **Ng—Newtonia silt loam, 1 to 4 percent slopes**

### **Map Unit Composition**

Newtonia: 90 percent  
 Minor components: 10 percent

### **Component Descriptions**

#### **Newtonia**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on ridge on upland  
*Hillslope position:* Backslope  
*Parent material:* Loess over ancient silty and clayey alluvium over residuum weathered from limestone  
*Slope:* 1 to 4 percent  
*Drainage class:* Well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* High (About 11.3 inches)  
*Shrink-swell potential:* Moderate (About 3.8 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Low  
*Ecological site:* Loamy Upland (pe35-42)  
*Land capability (nonirrigated):* 2e

#### *Typical Profile:*

H1—0 to 13 inches; silt loam  
 H2—13 to 26 inches; silty clay loam  
 H3—26 to 49 inches; silty clay loam  
 H4—49 to 60 inches; silty clay loam

### **Minor Components**

#### **Welda**

*Composition:* About 10 percent  
*Slope:* 2 to 5 percent  
*Drainage class:* Well drained  
*Ecological site:* Savannah (pe35-42)

## **Nh—Newtonia silt loam, 4 to 8 percent slopes**

### **Map Unit Composition**

Newtonia: 85 percent  
 Minor components: 15 percent

### **Component Descriptions**

#### **Newtonia**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Backslope  
*Parent material:* Loess over ancient silty and clayey alluvium over residuum weathered from limestone  
*Slope:* 4 to 8 percent  
*Drainage class:* Well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* High (About 11.2 inches)  
*Shrink-swell potential:* Moderate (About 3.8 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Medium  
*Ecological site:* Loamy Upland (pe35-42)  
*Land capability (nonirrigated):* 3e

#### *Typical Profile:*

H1—0 to 11 inches; silt loam  
 H2—11 to 24 inches; silty clay loam  
 H3—24 to 47 inches; silty clay loam  
 H4—47 to 60 inches; silty clay loam

### **Minor Components**

#### **Kenoma**

*Composition:* About 15 percent  
*Geomorphic Position:* hillslope on ridge on paleoterrace on upland  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

## **Oh—Okemah silt loam, 0 to 3 percent slopes**

### **Map Unit Composition**

Okemah: 90 percent  
 Minor components: 10 percent

## Component Descriptions

### Okemah

*MLRA:* 112 - Cherokee Prairies

*Landform:* Hillslope on stream terrace on upland

*Hillslope position:* Footslope

*Parent material:* Silty and clayey colluvium and/or silty and clayey residuum weathered from shale

*Slope:* 0 to 3 percent

*Drainage class:* Moderately well drained

*Slowest permeability:* Slow (About 0.06 in/hr)

*Available water capacity:* Moderate (About 9.0 inches)

*Shrink-swell potential:* High (About 7.5 LEP)

*Flooding hazard:* None

*Depth to seasonal water saturation:* About 24 to 36 inches

*Runoff class:* Medium

*Ecological site:* Loamy Upland (pe35-42)

*Land capability (nonirrigated):* 1

#### Typical Profile:

H1—0 to 12 inches; silt loam

H2—12 to 18 inches; silty clay loam

H3—18 to 24 inches; silty clay

H4—24 to 60 inches; silty clay

### Minor Components

#### Woodson

*Composition:* About 10 percent

*Slope:* 0 to 2 percent

*Drainage class:* Somewhat poorly drained

*Ecological site:* Clay Upland (pe35-42)

## Om—Kanima silty clay loam, 15 to 50 percent slopes

### Map Unit Composition

Kanima: 100 percent

## Component Descriptions

### Kanima

*MLRA:* 112 - Cherokee Prairies

*Landform:* Hillslope on upland

*Hillslope position:* Backslope

*Parent material:* Mine spoil or earthy fill

*Slope:* 15 to 50 percent

*Drainage class:* Excessively drained

*Slowest permeability:* Moderately slow (About 0.20 in/hr)

*Available water capacity:* Low (About 4.5 inches)

*Shrink-swell potential:* Moderate (About 3.3 LEP)

*Flooding hazard:* None

*Depth to seasonal water saturation:* More than 6 feet

*Runoff class:* Very high

*Land capability (nonirrigated):* 7s

#### Typical Profile:

H1—0 to 6 inches; channery silty clay loam

H2—6 to 60 inches; very channery silty clay loam

## Op—Kanima silty clay loam, 2 to 15 percent slopes

### Map Unit Composition

Kanima: 100 percent

## Component Descriptions

### Kanima

*MLRA:* 112 - Cherokee Prairies

*Landform:* Hillslope on upland

*Hillslope position:* Backslope

*Parent material:* Mine spoil or earthy fill

*Slope:* 2 to 15 percent

*Drainage class:* Excessively drained

*Slowest permeability:* Moderately slow (About 0.20 in/hr)

*Available water capacity:* Low (About 4.5 inches)

*Shrink-swell potential:* Moderate (About 3.3 LEP)

*Flooding hazard:* None

*Depth to seasonal water saturation:* More than 6 feet

*Runoff class:* High

*Land capability (nonirrigated):* 6s

#### Typical Profile:

H1—0 to 6 inches; channery silty clay loam

H2—6 to 60 inches; very channery silty clay loam

## Ot—Osage silty clay loam, 0 to 2 percent slopes, occasionally flooded

### Map Unit Composition

Osage: 85 percent

Minor components: 15 percent

### Component Descriptions

#### Osage

*MLRA:* 112 - Cherokee Prairies

*Landform:* Flood plain on river valley

*Parent material:* Clayey alluvium

*Slope:* 0 to 1 percent

*Drainage class:* Poorly drained

*Slowest permeability:* Very slow (About 0.00 in/hr)

*Available water capacity:* Moderate (About 7.7 inches)

*Shrink-swell potential:* Very high (About 13.5 LEP)

*Flooding hazard:* Occasional

*Ponding hazard:* Occasional

*Depth to seasonal water saturation:* About 0 to 12 inches

*Runoff class:* High

*Ecological site:* Clay Lowland (pe35-42)

*Land capability (nonirrigated):* 2w

#### Typical Profile:

H1—0 to 15 inches; silty clay loam

H2—15 to 44 inches; silty clay

H3—44 to 60 inches; silty clay

### Minor Components

#### Lanton

*Composition:* About 10 percent

*Slope:* 0 to 1 percent

*Drainage class:* Somewhat poorly drained

*Ecological site:* Loamy Lowland (pe35-42)

#### Verdigris

*Composition:* About 5 percent

*Slope:* 0 to 2 percent

*Drainage class:* Moderately well drained

*Ecological site:* Loamy Lowland (pe35-42)

*Slope:* 0 to 1 percent

*Drainage class:* Poorly drained

*Slowest permeability:* Very slow (About 0.00 in/hr)

*Available water capacity:* Moderate (About 6.9 inches)

*Shrink-swell potential:* Very high (About 14.5 LEP)

*Flooding hazard:* Occasional

*Ponding hazard:* Occasional

*Depth to seasonal water saturation:* About 0 to 12 inches

*Runoff class:* High

*Ecological site:* Clay Lowland (pe35-42)

*Land capability (nonirrigated):* 3w

#### Typical Profile:

H1—0 to 8 inches; silty clay

H2—8 to 23 inches; silty clay

H3—23 to 44 inches; silty clay

H4—44 to 60 inches; silty clay

### Minor Components

#### Lanton

*Composition:* About 5 percent

*Slope:* 0 to 1 percent

*Drainage class:* Somewhat poorly drained

*Ecological site:* Loamy Lowland (pe35-42)

#### Verdigris

*Composition:* About 5 percent

*Slope:* 0 to 2 percent

*Drainage class:* Moderately well drained

*Ecological site:* Loamy Lowland (pe35-42)

## Pc—Parsons silt loam, 0 to 2 percent slopes

### Map Unit Composition

Parsons: 90 percent

Minor components: 10 percent

### Component Descriptions

#### Parsons

*MLRA:* -

*Landform:* Divide on paleoterrace on upland

*Parent material:* Loess over ancient clayey alluvium and/or residuum weathered from shale

*Slope:* 0 to 1 percent

*Drainage class:* Somewhat poorly drained

*Slowest permeability:* Slow (About 0.06 in/hr)

*Available water capacity:* High (About 9.0 inches)

## Ov—Osage silty clay, occasionally flooded

### Map Unit Composition

Osage: 90 percent

Minor components: 10 percent

### Component Descriptions

#### Osage

*MLRA:* 112 - Cherokee Prairies

*Landform:* Flood plain on river valley

*Parent material:* Clayey alluvium

*Shrink-swell potential:* High (About 7.7 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* About 6 to 18 inches  
*Runoff class:* High  
*Ecological site:* Clay Upland (pe35-42)  
*Land capability (nonirrigated):* 2s

*Typical Profile:*

H1—0 to 9 inches; silt loam  
 H2—9 to 13 inches; silt loam  
 H3—13 to 60 inches; silty clay

**Minor Components**

**Dennis**

*Composition:* About 10 percent  
*Geomorphic Position:* hillslope on divide on upland  
*Slope:* 1 to 3 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Po—Pits, Quarries**

*General Considerations:* Pits are open excavations from which soil and commonly underlying material have been removed, exposing either rock or other material. Kinds include Pits, mine; Pits, gravel; and Pits, quarry. Commonly, pits are closely associated with Dumps.

**Sn—Summit silty clay loam, 1 to 4 percent slopes**

**Map Unit Composition**

Summit: 85 percent  
 Minor components: 15 percent

**Component Descriptions**

**Summit**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Footslope  
*Parent material:* Silty and clayey colluvium and/or silty and clayey residuum weathered from calcareous shale  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)

*Available water capacity:* Moderate (About 8.1 inches)  
*Shrink-swell potential:* High (About 8.2 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* About 24 to 36 inches  
*Runoff class:* Medium  
*Ecological site:* Clay Upland (pe35-42)  
*Land capability (nonirrigated):* 2e

*Typical Profile:*

H1—0 to 11 inches; silty clay loam  
 H2—11 to 24 inches; silty clay  
 H3—24 to 33 inches; silty clay  
 H4—33 to 60 inches; silty clay

**Minor Components**

**Catoosa**

*Composition:* About 15 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 1 to 3 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Loamy Upland (pe35-42)

**So—Summit silty clay loam, 4 to 8 percent slopes**

**Map Unit Composition**

Summit: 85 percent  
 Minor components: 15 percent

**Component Descriptions**

**Summit**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Hillslope on upland  
*Hillslope position:* Footslope  
*Parent material:* Silty and clayey colluvium and/or silty and clayey residuum weathered from calcareous shale  
*Slope:* 4 to 8 percent  
*Drainage class:* Moderately well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* Moderate (About 8.0 inches)  
*Shrink-swell potential:* High (About 8.2 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* About 24 to 36 inches  
*Runoff class:* Medium  
*Ecological site:* Clay Upland (pe35-42)  
*Land capability (nonirrigated):* 3e

*Typical Profile:*

H1—0 to 9 inches; silty clay loam  
 H2—9 to 22 inches; silty clay  
 H3—22 to 31 inches; silty clay  
 H4—31 to 60 inches; silty clay

**Minor Components****Catoosa**

*Composition:* About 10 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 1 to 3 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Dennis**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 3 to 6 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Vb—Verdigris silt loam, 0 to 2 percent slopes, occasionally flooded****Map Unit Composition**

Verdigris: 90 percent  
 Minor components: 10 percent

**Component Descriptions****Verdigris**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Flood plain on river valley  
*Parent material:* Silty alluvium  
*Slope:* 0 to 2 percent  
*Drainage class:* Moderately well drained  
*Slowest permeability:* Moderately slow (About 0.20 in/hr)  
*Available water capacity:* High (About 11.9 inches)  
*Shrink-swell potential:* Low (About 2.2 LEP)  
*Flooding hazard:* Occasional  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Low  
*Ecological site:* Loamy Lowland (pe35-42)  
*Land capability (nonirrigated):* 2w

*Typical Profile:*

H1—0 to 9 inches; silt loam  
 H2—9 to 32 inches; silt loam  
 H3—32 to 52 inches; silt loam

H4—52 to 60 inches; silt loam

**Minor Components****Osage**

*Composition:* About 10 percent  
*Slope:* 0 to 1 percent  
*Drainage class:* Poorly drained  
*Ecological site:* Clay Lowland (pe35-42)

**Vc—Verdigris silt loam, 0 to 2 percent slopes, frequently flooded****Map Unit Composition**

Verdigris: 85 percent  
 Minor components: 15 percent

**Component Descriptions****Verdigris**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Flood plain on river valley  
*Parent material:* Silty alluvium  
*Slope:* 0 to 2 percent  
*Drainage class:* Moderately well drained  
*Slowest permeability:* Moderately slow (About 0.20 in/hr)  
*Available water capacity:* High (About 11.9 inches)  
*Shrink-swell potential:* Low (About 2.2 LEP)  
*Flooding hazard:* Frequent  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Low  
*Ecological site:* Loamy Lowland (pe35-42)  
*Land capability (nonirrigated):* 5w

*Typical Profile:*

H1—0 to 9 inches; silt loam  
 H2—9 to 32 inches; silt loam  
 H3—32 to 52 inches; silt loam  
 H4—52 to 60 inches; silt loam

**Minor Components****Osage**

*Composition:* About 10 percent  
*Slope:* 0 to 1 percent  
*Drainage class:* Poorly drained  
*Ecological site:* Clay Lowland (pe35-42)

**Summit**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**W—Water****We—Welda silt loam, 2 to 5 percent slopes****Map Unit Composition**

Welda: 90 percent  
 Minor components: 10 percent

**Component Descriptions****Welda**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Stream terrace on upland  
*Parent material:* Silty and clayey sediments  
*Slope:* 2 to 5 percent  
*Drainage class:* Well drained  
*Slowest permeability:* Slow (About 0.06 in/hr)  
*Available water capacity:* High (About 11.2 inches)  
*Shrink-swell potential:* High (About 7.4 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* More than 6 feet  
*Runoff class:* Medium  
*Ecological site:* Savannah (pe35-42)  
*Land capability (nonirrigated):* 2e

*Typical Profile:*

H1—0 to 7 inches; silt loam  
 H2—7 to 10 inches; silty clay loam  
 H3—10 to 35 inches; silty clay  
 H4—35 to 60 inches; clay loam

**Minor Components****Catoosa**

*Composition:* About 10 percent  
*Geomorphic Position:* hillslope on ridge on upland  
*Slope:* 1 to 3 percent  
*Depth to restrictive feature:* 20 to 40 inches to bedrock (lithic)  
*Drainage class:* Well drained  
*Ecological site:* Loamy Upland (pe35-42)

**Wo—Woodson silt loam, 0 to 2 percent slopes****Map Unit Composition**

Woodson: 85 percent  
 Minor components: 15 percent

**Component Descriptions****Woodson**

*MLRA:* 112 - Cherokee Prairies  
*Landform:* Divide on paleoterrace on upland  
*Parent material:* Silty loess over ancient clayey alluvium and/or silty and clayey residuum weathered from clayey shale  
*Slope:* 0 to 2 percent  
*Drainage class:* Somewhat poorly drained  
*Slowest permeability:* Very slow (About 0.00 in/hr)  
*Available water capacity:* Moderate (About 8.6 inches)  
*Shrink-swell potential:* Very high (About 13.5 LEP)  
*Flooding hazard:* None  
*Depth to seasonal water saturation:* About 6 to 24 inches  
*Runoff class:* High  
*Ecological site:* Clay Upland (pe35-42)  
*Land capability (nonirrigated):* 2s

*Typical Profile:*

H1—0 to 7 inches; silt loam  
 H2—7 to 30 inches; silty clay  
 H3—30 to 40 inches; silty clay  
 H4—40 to 60 inches; silty clay

**Minor Components****Summit**

*Composition:* About 10 percent  
*Geomorphic Position:* hillslope on upland  
*Slope:* 1 to 4 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Clay Upland (pe35-42)

**Okemah**

*Composition:* About 5 percent  
*Geomorphic Position:* hillslope on stream terrace on upland  
*Slope:* 0 to 3 percent  
*Drainage class:* Moderately well drained  
*Ecological site:* Loamy Upland (pe35-42)

Prime farmland is one of several kinds of important farmland defined by the U.S. Department of Agriculture. It is of major importance in meeting the Nation's short- and long-range needs for food and fiber. Because the supply of high-quality farmland is limited, the U.S. Department of Agriculture recognizes that responsible levels of government, as well as individuals, should encourage and facilitate the wise use of our Nation's prime farmland.

Prime farmland, as defined by the U.S. Department of Agriculture, is land that has the best combination of physical and chemical characteristics for producing food, feed, forage, fiber, and oilseed crops and is available for these uses. It could be cultivated land, pastureland, forestland, or other land, but it is not urban or built-up land or water areas. The soil qualities, growing season, and moisture supply are those needed for the soil to economically produce sustained high yields of crops when proper management, including water management, and acceptable farming methods are applied. In general, prime farmland has an adequate and dependable supply of moisture from precipitation or irrigation, a favorable temperature and growing season, acceptable acidity or alkalinity, an acceptable salt and sodium content, and few or no rocks. It is permeable to water and air. It is not excessively erodible or saturated with water for long periods, and it either is not frequently flooded during the growing season or is protected from flooding. Slope ranges mainly from 0 to 6 percent. More detailed information about the criteria for prime farmland is available at the local office of the Natural Resources Conservation Service.

A recent trend in land use in some parts of the survey area has been the loss of some prime farmland to industrial and urban uses. The loss of prime farmland to other uses puts pressure on marginal lands, which generally are more erodible, droughty, and less productive and cannot be easily cultivated.

The map units in the survey area that are considered prime farmland are listed in the following table. This list does not constitute a recommendation for a particular land use. On some soils included in the list, measures that overcome a hazard or limitation, such as flooding, wetness, and droughtiness, are needed. Onsite evaluation is needed to determine whether or not the hazard or limitation has been overcome by corrective measures. The extent of each listed map unit is shown in the "Acres and Proportionate Extent of Soils" table. The location is shown on the detailed soil maps. The soil qualities that affect use and management are described in other tables in this document."

Map symbol	Mapunit name	Farmland Classification
003DE	Dennis silty clay loam, 1 to 4 percent slopes, eroded	All areas are prime farmland
003LH	Lula silt loam, 0 to 3 percent slopes	All areas are prime farmland
003WF	Woodson silt loam, 1 to 3 percent slopes	All areas are prime farmland
011CA	Catoosa silt loam, 0 to 2 percent slopes	All areas are prime farmland
Bb	Bates loam, 1 to 4 percent slopes	All areas are prime farmland
Bc	Bates loam, 4 to 8 percent slopes	All areas are prime farmland
Cb	Catoosa silt loam, 1 to 3 percent slopes	All areas are prime farmland
De	Dennis silt loam, 1 to 3 percent slopes	All areas are prime farmland
Df	Dennis silt loam, 3 to 6 percent slopes	All areas are prime farmland
Ec	Eram silty clay loam, 1 to 4 percent slopes	All areas are prime farmland
Ke	Kenoma silt loam, 1 to 4 percent slopes	All areas are prime farmland
Mb	Mason silt loam, 0 to 2 percent slopes, rarely flooded	All areas are prime farmland
Nf	Newtonia silt loam, 0 to 1 percent slopes	All areas are prime farmland
Ng	Newtonia silt loam, 1 to 4 percent slopes	All areas are prime farmland
Nh	Newtonia silt loam, 4 to 8 percent slopes	All areas are prime farmland
Oh	Okemah silt loam, 0 to 3 percent slopes	All areas are prime farmland
Pc	Parsons silt loam, 0 to 2 percent slopes	All areas are prime farmland
Sn	Summit silty clay loam, 1 to 4 percent slopes	All areas are prime farmland
So	Summit silty clay loam, 4 to 8 percent slopes	All areas are prime farmland
Vb	Verdigris silt loam, 0 to 2 percent slopes, occasionally flooded	All areas are prime farmland
We	Welda silt loam, 2 to 5 percent slopes	All areas are prime farmland
Wo	Woodson silt loam, 0 to 2 percent slopes	All areas are prime farmland
003LE	Leanna silt loam, 0 to 2 percent slopes, occasionally flooded	Prime farmland if drained
Hp	Hepler silt loam, 0 to 2 percent slopes, occasionally flooded	Prime farmland if drained
La	Lanton silt loam, occasionally flooded	Prime farmland if drained
Ot	Osage silty clay loam, 0 to 2 percent slopes, occasionally flooded	Prime farmland if drained
Ov	Osage silty clay, occasionally flooded	Prime farmland if drained



The "Soil Rating for Plant Growth, modified 1998" (SRPG) is a relative rating of the capacity of a soil to produce a specific plant under a defined management system. The index is determined from yield data on a few benchmark soils and is used to calculate yields, the net returns from crops, land assessment values, and taxes and to perform risk analysis when land management decisions are made. Specific information on plants and yields can be obtained from the local office of the Natural Resources Conservation Service or the Cooperative Extension Service.

Map symbol	Soil name	Crop Index
003CD	Collinsville Complex, 2 To 15 Percent Slopes-----	14
003DE	Dennis Silty Clay Loam, 1 To 4 Percent Slopes, Eroded-----	69
003EH	Eram Soils, 4 To 7 Percent Slopes, Eroded-----	47
003EK	Eram-Clareson Complex, 1 To 15 Percent Slopes-----	40
003LE	Leanna Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	75
003LH	Lula Silt Loam, 0 To 3 Percent Slopes-----	71
003SE	Stony Land-Talihina Complex, 15 To 45 Percent Slopes-----	7
003WF	Woodson Silt Loam, 1 To 3 Percent Slopes-----	77
011CA	Catoosa Silt Loam, 0 To 2 Percent Slopes-----	43
059CM	Clareson-Eram Silty Clay Loams, 3 To 15 Percent Slopes-----	39
AED	Arents, Earthen Dam-----	0
Bb	Bates Loam, 1 To 4 Percent Slopes-----	44
Bc	Bates Loam, 4 To 8 Percent Slopes-----	43
Cb	Catoosa Silt Loam, 1 To 3 Percent Slopes-----	55
Cm	Clareson-Rock Outcrop Complex, 2 To 15 Percent Slopes-----	33
De	Dennis Silt Loam, 1 To 3 Percent Slopes-----	65
Df	Dennis Silt Loam, 3 To 6 Percent Slopes-----	62
Ec	Eram Silty Clay Loam, 1 To 4 Percent Slopes-----	42
Ed	Eram Silty Clay Loam, 4 To 8 Percent Slopes-----	39
Ef	Eram-Lebo Silty Clay Loams, 5 To 20 Percent Slopes-----	43
Hp	Hepler Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	67
INT	Aquolls-----	12
Ke	Kenoma Silt Loam, 1 To 4 Percent Slopes-----	77
La	Lanton Silt Loam, Occasionally Flooded-----	81
Lb	Lebo Channery Silty Clay Loam, 15 To 30 Percent Slopes-----	26
M-W	Miscellaneous Water-----	0
Mb	Mason Silt Loam, 0 To 2 Percent Slopes, Rarely Flooded-----	78
Nf	Newtonia Silt Loam, 0 To 1 Percent Slopes-----	83
Ng	Newtonia Silt Loam, 1 To 4 Percent Slopes-----	81
Nh	Newtonia Silt Loam, 4 To 8 Percent Slopes-----	79
Oh	Okemah Silt Loam, 0 To 3 Percent Slopes-----	75
Om	Kanima Silty Clay Loam, 15 To 50 Percent Slopes-----	6
Op	Kanima Silty Clay Loam, 2 To 15 Percent Slopes-----	45
Ot	Osage Silty Clay Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	59
Ov	Osage Silty Clay, Occasionally Flooded-----	54
Pc	Parsons Silt Loam, 0 To 2 Percent Slopes-----	75
Po	Pits, Quarries-----	0
Sn	Summit Silty Clay Loam, 1 To 4 Percent Slopes-----	72
So	Summit Silty Clay Loam, 4 To 8 Percent Slopes-----	69
Vb	Verdigris Silt Loam, 0 To 2 Percent Slopes, Occasionally Flooded-----	85
Vc	Verdigris Silt Loam, 0 To 2 Percent Slopes, Frequently Flooded-----	68
W	Water-----	0
We	Welda Silt Loam, 2 To 5 Percent Slopes-----	68
Wo	Woodson Silt Loam, 0 To 2 Percent Slopes-----	77

Linn County, Kansas: Published  
Field Office Thunderbook: Soils Properties for Conservation Planning

(Entries under "Erosion factors--T" apply to the entire profile. Entries under "K", "Kf", "Wind Erodibility Group" and "Wind Erodibility Index" apply only to the surface layer)

Map symbol and soil name	Percent	Irr Cap Class	Nonirr Cap Class	Prime Farmland	Hydro- logic Group	Range site name	Windbreak suitability group	Erosion factors			Wind erodi- bility group	Wind erodi- bility index
								K	Kf	T		
003CD:COLLINSVIL LE-----	65	N/A	6e	Not prime farmland	D	Shallow Sandstone (pe35- 42)	6	.32	.32	1	5	56
003CD:COLLINSVIL LE Taxadjunct--	20	N/A	6e	Not prime farmland	D	Shallow Sandstone (pe35- 42)	6	.32	.32	1	5	56
003DE:DENNIS----	95	N/A	3e	All areas are prime farmland	C	Loamy Upland (pe35-42)	7	.43	.43	5	6	48
003EH:ERAM-----	85	N/A	6e	Not prime farmland	C	Clay Upland (pe35-42)	8	.37	.37	3	7	38
003EK:ERAM-----	60	N/A	4e	Not prime farmland	C	Clay Upland (pe35-42)	8	.37	.37	3	7	38
003EK:CLARESON--	20	N/A	6s	Not prime farmland	C	Shallow Flats (pe35-42)	9	.24	.55	2	8	0
003LE:LEANNA----	88	N/A	2w	Prime farmland if drained	D	Clay Lowland (pe35-42)	7	.32	.32	3	6	48
003LH:LULA-----	85	N/A	2e	All areas are prime farmland	B	Loamy Upland (pe35-42)	7	.37	.37	3	6	48
003SE:STONY LAND	60	N/A	7e	Not prime farmland		Unspecified		---	---	-	---	0
003SE:TALIHINA--	20	N/A	6e	Not prime farmland	D	Clay Upland (pe35-42)	4	.37	.37	2	4	86
003WF:WOODSON---	85	N/A	3e	All areas are prime farmland	D	Clay Upland (pe35-42)	7	.43	.43	3	6	48
011CA:CATOOSA---	85	N/A	2e	All areas are prime farmland	B	Loamy Upland (pe35-42)	7	.37	.37	2	6	48
059CM:CLARESON--	55	N/A	6e	Not prime farmland	C	Shallow Flats (pe35-42)	8	.32	.32	2	7	38
059CM:ERAM-----	30	N/A	6e	Not prime farmland	C	Clay Upland (pe35-42)	8	.37	.37	3	7	38
AED:ARENTS, EARTHEN DAM----	100	N/A	8	Not prime farmland		Unspecified		---	---	-	---	---
Bb:BATES-----	85	N/A	2e	All areas are prime farmland	B	Loamy Upland (pe35-42)	6	.32	.32	3	5	56
Bc:BATES-----	85	N/A	3e	All areas are prime farmland	B	Loamy Upland (pe35-42)	6	.32	.32	3	5	56
Cb:CATOOSA-----	85	N/A	2e	All areas are prime farmland	B	Loamy Upland (pe35-42)	7	.37	.37	2	6	48

Linn County, Kansas: Published  
Field Office Thunderbook: Soils Properties for Conservation Planning--Continued

Map symbol and soil name	Percent	Irr Cap Class	Nonirr Cap Class	Prime Farmland	Hydro- logic Group	Range site name	Windbreak suitability group	Erosion factors			Wind erodi- bility group	Wind erodi- bility index
								K	Kf	T		
Cm:CLARESON-----	60	N/A	6e	Not prime farmland	C	Shallow Flats (pe35-42)	8	.32	.32	2	7	38
Cm:ROCK OUTCROP--	20	N/A	8	Not prime farmland	D	Unspecified		---	---	-	---	0
De:DENNIS-----	90	N/A	2e	All areas are prime farmland	C	Loamy Upland (pe35-42)	7	.43	.43	5	6	48
Df:DENNIS-----	85	N/A	3e	All areas are prime farmland	C	Loamy Upland (pe35-42)	7	.43	.43	5	6	48
Ec:ERAM-----	85	N/A	3e	All areas are prime farmland	C	Clay Upland (pe35-42)	8	.37	.37	3	7	38
Ed:ERAM-----	85	N/A	4e	Not prime farmland	C	Clay Upland (pe35-42)	8	.37	.37	3	7	38
Ef:ERAM-----	50	N/A	6e	Not prime farmland	C	Clay Upland (pe35-42)	8	.37	.37	3	7	38
Ef:LEBO-----	30	N/A	6e	Not prime farmland	B	Loamy Upland (pe35-42)	8	.32	.37	3	7	38
Hp:HEPLER-----	90	N/A	2w	Prime farmland if drained	C	Loamy Lowland (pe35-42)	7	.37	.37	5	6	48
INT:AQUOLLS-----	100	N/A	5w	Not prime farmland	C	Unspecified		---	---	-	---	0
Ke:KENOMA-----	90	N/A	3e	All areas are prime farmland	D	Clay Upland (pe35-42)	7	.43	.43	3	6	48
La:LANTON-----	90	N/A	2w	Prime farmland if drained	C	Loamy Lowland (pe35-42)	7	.37	.37	5	6	48
Lb:LEBO-----	85	N/A	6e	Not prime farmland	B	Loamy Upland (pe35-42)	9	.24	.37	3	8	0
M- W:MISCELLANEOUS WATER-----	100	N/A	N/A	Not prime farmland		Unspecified		---	---	-	---	---
Mb:MASON-----	85	N/A	1	All areas are prime farmland	B	Loamy Lowland (pe35-42)	7	.37	.37	5	6	48
Nf:NEWTONIA-----	90	N/A	1	All areas are prime farmland	B	Loamy Upland (pe35-42)	7	.37	.37	5	6	48
Ng:NEWTONIA-----	90	N/A	2e	All areas are prime farmland	B	Loamy Upland (pe35-42)	7	.37	.37	5	6	48
Nh:NEWTONIA-----	85	N/A	3e	All areas are prime farmland	B	Loamy Upland (pe35-42)	7	.37	.37	5	6	48

Linn County, Kansas: Published  
Field Office Thunderbook: Soils Properties for Conservation Planning--Continued

Map symbol and soil name	Percent	Irr Cap Class	Nonirr Cap Class	Prime Farmland	Hydro- logic Group	Range site name	Windbreak suitability group	Erosion factors			Wind erodi- bility group	Wind erodi- bility index
								K	Kf	T		
Oh:OKEMAH-----	90	N/A	1	All areas are prime farmland	C	Loamy Upland (pe35-42)	7	.43	.43	5	6	48
Om:KANIMA-----	100	N/A	7s	Not prime farmland	C	Unspecified	8	.28	.37	5	7	38
Op:KANIMA-----	100	N/A	6s	Not prime farmland	C	Unspecified	8	.28	.37	5	7	38
Ot:OSAGE-----	85	N/A	2w	Prime farmland if drained	D	Clay Lowland (pe35-42)	4	.37	.37	5	4	86
Ov:OSAGE-----	90	N/A	3w	Prime farmland if drained	D	Clay Lowland (pe35-42)	4	.28	.28	5	4	86
Pc:PARSONS-----	90	N/A	2s	All areas are prime farmland	D	Clay Upland (pe35-42)	7	.49	.49	4	6	48
Po:Pits, quarries-----	100	N/A	N/A	Not prime farmland		Unspecified		---	---	-	---	0
Sn:SUMMIT-----	85	N/A	2e	All areas are prime farmland	C	Clay Upland (pe35-42)	4	.37	.37	5	4	86
So:SUMMIT-----	85	N/A	3e	All areas are prime farmland	C	Clay Upland (pe35-42)	4	.37	.37	5	4	86
Vb:VERDIGRIS----	90	N/A	2w	All areas are prime farmland	B	Loamy Lowland (pe35-42)	7	.32	.32	5	6	48
Vc:VERDIGRIS----	85	N/A	5w	Not prime farmland	B	Loamy Lowland (pe35-42)	7	.32	.32	5	6	48
W:WATER-----	100	N/A	N/A			Unspecified		---	---	-	---	---
We:WELDA-----	90	N/A	2e	All areas are prime farmland	C	Savannah (pe35- 42)	7	.37	.37	5	6	48
Wo:WOODSON-----	85	N/A	2s	All areas are prime farmland	D	Clay Upland (pe35-42)	7	.43	.43	3	6	48

RANGELAND PRODUCTIVITY  
Linn County, Kansas

### Use and Explanation of Rangeland, Grazed Forest Land, Native Pastureland Interpretations

Information in this subsection can be used to plan the use and management of soils for rangeland, grazed forest land, and native pasture. Different kinds of soils vary in their capacity to produce native grasses and other plants suitable for grazing. Information in this subsection provides groupings of similar soils and estimates of potential forage production, which can be used to determine livestock stocking rates.

**Rangeland.** Range is land on which the native vegetation (climax or natural potential plant community) is predominantly grasses, grasslike plants, forbs, and shrubs suitable for grazing and browsing. Range includes natural grasslands, savannas, many wetlands, some deserts, tundra, and certain shrub and forb communities. Rangeland receives no regular or frequent cultural treatment. The composition and production of the plant community are determined by soil, climate, topography, overstory canopy, and grazing management.

**Grazed Forest Land.** Includes land on which the understory includes, as an integral part of the forest plant community, plants that can be grazed without significantly impairing other forest values.

**Native Pasture.** Includes land on which the native vegetation (climax or natural potential plant community) is forest but which is used and managed primarily for production of native plants for forage. Native pasture includes cut-over forest land and forest land cleared and now managed for native or naturalized forage plants.

#### Rangeland

In areas that have similar climate and topography, differences in the kind and amount of vegetation produced on rangeland are closely related to the kind of soil. Effective management based on the relationship between the soils and vegetation and water.

The Rangeland, Grazed Forest land, Native Pastureland Interpretations shows, for each soil that supports rangeland vegetation, the ecological site and the potential annual production of vegetation in favorable, normal, unfavorable years. An explanation of the column headings in this table follows.

An ecological site is the product of all the environmental factors responsible for its development. It has characteristic soils that have developed over time throughout the soil development process; a characteristic hydrology, particularly infiltration and runoff, that has developed over time; and a characteristic plant community (kind and amount of vegetation). The hydrology of a site is influenced by development of the soil and plant community. The vegetation, soils, and hydrology are all interrelated. Each is influenced by the others and influences the development of the others. The plant community on an ecological site is typified by an association of species that differs from that of other ecological sites in the kind and/or proportion of species or in total production. Descriptions of ecological sites are provided in the Field Office Technical Guide, which is available in local offices of the Natural Resources Conservation Service.

Total dry-weight production is the amount of vegetation that can be expected to grow annually on well managed rangeland that is supporting the potential natural plant community. It includes all vegetation, whether or not it is palatable to grazing animals. It includes the current year's growth of leaves, twigs, and fruits of woody plants. It does not include the increase in stem diameter of trees and shrubs. It is expressed in pounds per acre of air-dry vegetation for favorable, average, and unfavorable years. In a favorable year, the amount and distribution of precipitation and the temperatures make growing conditions substantially better than average. In a normal year, growing conditions are about average. In an unfavorable year, growing conditions are well below average, generally because of low available soil moisture. Yields are adjusted to a common percent of air-dry moisture content.

Range management requires a knowledge of the kinds of soil and of the potential natural plant community. It also requires an evaluation of the present range similarity index and rangeland trend. Range similarity index is determined by comparing the present plant community with the potential natural plant community on a particular rangeland ecological site. The more closely the existing community resembles the potential community, the higher the range similarity index. Rangeland trend is defined as the direction of change in an existing plant community relative to the potential natural plant community. Further information about the range similarity index and rangeland trend is available in chapter 4 of the National Range and Pasture Handbook, which is available in local offices of the Natural Resources Conservation Service. The objective in range management is to control grazing so that the plants growing on a site are about the same in kind and amount as the potential natural plant community for that site. Such management generally results in the optimum production of vegetation, control of undesirable brush species, conservation of water, and control of erosion. Sometimes, however, an area with a range similarity index somewhat below the potential meets grazing needs, provides wildlife habitat, and protects soil and water resources.

RANGELAND PRODUCTIVITY--Continued  
Linn County, Kansas

(Only the soils that support rangeland vegetation suitable for grazing are rated.) Refer to range site description to determine the percentage allowable of grasses, forbs, and shrubs for the range ecological site.

Map symbol and soil name	Ecological site	Total dry-weight production		
		Favorable year	Average year	Unfavorable year
		Lb/acre	Lb/acre	Lb/acre
003CD:				
Collinsville-----	Shallow Sandstone (pe35-42)	4,000	3,000	2,000
Collinsville Taxadjunct-----	Shallow Sandstone (pe35-42)	4,000	3,000	2,000
003DE:				
Dennis, eroded-----	Loamy Upland (pe35-42)	6,250	4,750	3,250
003EH:				
Eram, eroded-----	Clay Upland (pe35-42)	6,000	4,200	3,000
003EK:				
Eram-----	Clay Upland (pe35-42)	6,000	4,000	2,500
Clareson-----	Shallow Flats (pe35-42)	5,000	4,000	3,000
003LE:				
Leanna, drained-----	Clay Lowland (pe35-42)	10,000	8,000	5,000
003LH:				
Lula-----	Loamy Upland (pe35-42)	7,000	5,500	4,500
003SE:				
Stony Land-----	---	---	---	---
Talihina-----	Clay Upland (pe35-42)	4,500	3,200	2,250
003WF:				
Woodson-----	Clay Upland (pe35-42)	6,000	4,500	2,500
011CA:				
Catoosa-----	Loamy Upland (pe35-42)	6,250	4,750	3,250
059CM:				
Clareson-----	Shallow Flats (pe35-42)	5,000	4,000	2,500
Eram-----	Clay Upland (pe35-42)	6,000	4,200	3,000
AED:				
Arents, Earthen Dam-----	---	---	---	---
Bb:				
Bates-----	Loamy Upland (pe35-42)	7,000	5,500	4,500
Bc:				
Bates-----	Loamy Upland (pe35-42)	7,000	5,500	4,500
Cb:				
Catoosa-----	Loamy Upland (pe35-42)	6,500	5,000	4,000
Cm:				
Clareson-----	Shallow Flats (pe35-42)	5,000	4,000	3,000
Rock Outcrop-----	---	---	---	---
De:				
Dennis-----	Loamy Upland (pe35-42)	7,000	5,500	4,500
Df:				
Dennis-----	Loamy Upland (pe35-42)	7,000	5,500	4,500
Ec:				
Eram-----	Clay Upland (pe35-42)	6,000	4,200	3,000
Ed:				
Eram-----	Clay Upland (pe35-42)	6,000	4,200	3,000
Ef:				
Eram-----	Clay Upland (pe35-42)	6,000	4,000	2,500
Lebo-----	Loamy Upland (pe35-42)	6,250	4,750	3,250
Hp:				
Hepler-----	Loamy Lowland (pe35-42)	10,000	8,500	6,000
INT:				
Aquolls-----	---	---	---	---
Ke:				
Kenoma-----	Clay Upland (pe35-42)	6,000	4,500	2,500
La:				
Lanton-----	Loamy Lowland (pe35-42)	10,000	7,000	5,500
Lb:				
Lebo-----	Loamy Upland (pe35-42)	6,000	5,000	4,000
M-W:				
Miscellaneous Water-----	---	---	---	---
Mb:				
Mason-----	Loamy Lowland (pe35-42)	11,500	9,400	8,000
Nf:				
Newtonia-----	Loamy Upland (pe35-42)	7,000	4,500	3,200
Ng:				
Newtonia-----	Loamy Upland (pe35-42)	7,000	4,500	3,200
Nh:				
Newtonia-----	Loamy Upland (pe35-42)	7,000	4,500	3,200
Oh:				
Okemah-----	Loamy Upland (pe35-42)	7,000	5,500	4,500
Om:				
Kanima-----	---	---	---	---
Op:				
Kanima-----	---	---	---	---
Ot:				
Osage-----	Clay Lowland (pe35-42)	9,000	8,000	6,000
Ov:				
Osage-----	Clay Lowland (pe35-42)	9,000	8,000	6,000
Pc:				
Parsons-----	Clay Upland (pe35-42)	6,000	4,500	2,500
Po:				
Pits, Quarries-----	---	---	---	---
Sn:				
Summit-----	Clay Upland (pe35-42)	6,000	4,000	2,500
So:				
Summit-----	Clay Upland (pe35-42)	6,000	4,000	2,500
Vb:				

RANGELAND PRODUCTIVITY--Continued  
Linn County, Kansas

(Only the soils that support rangeland vegetation suitable for grazing are rated.) Refer to range site description to determine the percentage allowable of grasses, forbs, and shrubs for the range ecological site.

Map symbol and soil name	Ecological site	Total dry-weight production		
		Favorable year	Average year	Unfavorable year
		Lb/acre	Lb/acre	Lb/acre
Verdigris----- Vc:	Loamy Lowland (pe35-42)	10,000	8,500	6,000
Verdigris----- W:	Loamy Lowland (pe35-42)	9,000	7,000	5,500
Water----- We:	---	---	---	---
Welda----- Wo:	Savannah (pe35-42)	5,500	4,500	3,500
Woodson-----	Clay Upland (pe35-42)	6,000	4,500	2,500

BUILDING SITE DEVELOPMENT  
Linn County, Kansas

Building Site Development

Soil properties influence the development of building sites, including the selection of the site, the design of the structure, construction, performance after construction, and maintenance. The following tables show the degree and kind of soil limitations that affect dwellings with and without basements, small commercial buildings, local roads and streets, shallow excavations, and lawns and landscaping.

The ratings in the tables are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect building site development. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Dwellings are single-family houses of three stories or less. For dwellings without basements, the foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of 2 feet or at the depth of maximum frost penetration, whichever is deeper. For dwellings with basements, the foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of about 7 feet. The ratings for dwellings are based on the soil properties that affect the capacity of the soil to support a load without movement and on the properties that affect excavation and construction costs. The properties that affect the load-supporting capacity include depth to a water table, ponding, flooding, subsidence, linear extensibility (shrink-swell potential), and compressibility. Compressibility is inferred from the Unified classification. The properties that affect the ease and amount of excavation include depth to a water table, ponding, flooding, slope, depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, and the amount and size of rock fragments.

Small commercial buildings are structures that are less than three stories high and do not have basements. The foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of 2 feet or at the depth of maximum frost penetration, whichever is deeper. The ratings are based on the soil properties that affect the capacity of the soil to support a load without movement and on the properties that affect excavation and construction costs. The properties that affect the load-supporting capacity include depth to a water table, ponding, flooding, subsidence, linear extensibility (shrink-swell potential), and compressibility (which is inferred from the Unified classification). The properties that affect the ease and amount of excavation include flooding, depth to a water table, ponding, slope, depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, and the amount and size of rock fragments.

Local roads and streets have an all-weather surface and carry automobile and light truck traffic all year. They have a subgrade of cut or fill soil material; a base of gravel, crushed rock, or soil material stabilized by lime or cement; and a surface of flexible material (asphalt), rigid material (concrete), or gravel with a binder. The ratings are based on the soil properties that affect the ease of excavation and grading and the traffic-supporting capacity. The properties that affect the ease of excavation and grading are depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, depth to a water table, ponding, flooding, the amount of large stones, and slope. The properties that affect the traffic-supporting capacity are soil strength (as inferred from the AASHTO group index number), subsidence, linear extensibility (shrink-swell potential), the potential for frost action, depth to a water table, and ponding.

Shallow excavations are trenches or holes dug to a maximum depth of 5 or 6 feet for graves, utility lines, open ditches, or other purposes. The ratings are based on the soil properties that influence the ease of digging and the resistance to sloughing. Depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, the amount of large stones, and dense layers influence the ease of digging, filling, and compacting. Depth to the seasonal high water table, flooding, and ponding may restrict the period when excavations can be made. Slope influences the ease of using machinery. Soil texture, depth to the water table, and linear extensibility (shrink-swell potential) influence the resistance to sloughing.

Lawns and landscaping require soils on which turf and ornamental trees and shrubs can be established and maintained. Irrigation is not considered in the ratings. The ratings are based on the soil properties that affect plant growth and trafficability after vegetation is established. The properties that affect plant growth are reaction; depth to a water table; ponding; depth to bedrock or a cemented pan; the available water capacity in the upper 40 inches; the content of salts, sodium, or calcium carbonate; and sulfidic materials. The properties that affect trafficability are flooding, depth to a water table, ponding, slope, stoniness, and the amount of sand, clay, or organic matter in the surface layer.



BUILDING SITE DEVELOPMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
003CD: Collinsville-----	65	Very limited Depth to hard bedrock Slope	1.00 0.04	Very limited Depth to hard bedrock Slope	1.00 0.04	Very limited Depth to hard bedrock Slope	1.00 1.00
Collinsville Taxadjunct-----	20	Somewhat limited  Depth to hard bedrock	 0.95	Very limited  Depth to hard bedrock	 1.00	Somewhat limited  Depth to hard bedrock Slope	 0.95 0.48
003DE: Dennis, eroded-----	95	Very limited Shrink-swell  Depth to saturated zone	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Shrink-swell  Depth to saturated zone	1.00 1.00
003EH: Eram, eroded-----	85	Very limited Shrink-swell  Depth to saturated zone	1.00 1.00	Very limited Depth to saturated zone Shrink-swell  Depth to soft bedrock	1.00 1.00 0.20	Very limited Shrink-swell  Depth to saturated zone Slope	1.00 1.00 0.48
003EK: Eram-----	60	Very limited Shrink-swell  Depth to saturated zone Slope	1.00 1.00 0.00	Very limited Depth to saturated zone Shrink-swell  Depth to soft bedrock Slope	1.00 1.00 0.20 0.00	Very limited Shrink-swell  Depth to saturated zone Slope	1.00 1.00 1.00
Clareson-----	20	Very limited Content of large stones Depth to hard bedrock Slope	1.00 0.90 0.00	Very limited Depth to hard bedrock Content of large stones Slope	1.00 1.00 0.00	Very limited Content of large stones Slope  Depth to hard bedrock	1.00 1.00 0.90
003LE: Leanna, drained-----	88	Very limited Flooding Shrink-swell  Depth to saturated zone	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00	Very limited Flooding Shrink-swell  Depth to saturated zone	1.00 1.00 1.00
003LH: Lula-----	85	Somewhat limited Shrink-swell	0.50	Somewhat limited Depth to hard bedrock Shrink-swell	0.54 0.50	Somewhat limited Shrink-swell	0.50
003SE: Stony Land-----	60	Not rated		Not rated		Not rated	
Talihina-----	20	Very limited Depth to soft bedrock Shrink-swell Depth to saturated zone Slope	1.00 1.00 1.00 0.84	Very limited Depth to saturated zone Shrink-swell Depth to soft bedrock Slope	1.00 1.00 1.00 0.84	Very limited Depth to soft bedrock Shrink-swell Depth to saturated zone Slope	1.00 1.00 1.00 1.00
003WF: Woodson-----	85	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00
011CA: Catoosa-----	85	Very limited Shrink-swell  Depth to hard bedrock	1.00 0.74	Very limited Depth to hard bedrock Shrink-swell	1.00 1.00	Very limited Shrink-swell  Depth to hard bedrock	1.00 0.74

BUILDING SITE DEVELOPMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
059CM: Clareson-----	55	Somewhat limited Shrink-swell	0.96	Very limited Depth to hard bedrock	1.00	Very limited Slope	1.00
		Depth to hard bedrock	0.79	Shrink-swell	0.96	Shrink-swell	0.96
		Content of large stones	0.16	Content of large stones	0.16	Depth to hard bedrock	0.79
		Slope	0.04	Slope	0.04	Content of large stones	0.16
Eram-----	30	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Shrink-swell	1.00	Shrink-swell	1.00	Shrink-swell	1.00
		Slope	0.00	Depth to soft bedrock	0.01	Slope	1.00
				Slope	0.00		
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
Bb: Bates-----	85	Somewhat limited Shrink-swell	0.02	Somewhat limited Depth to soft bedrock	0.35	Somewhat limited Shrink-swell	0.02
				Shrink-swell	0.02		
Bc: Bates-----	85	Not limited		Somewhat limited Depth to soft bedrock	0.35	Somewhat limited Slope	0.48
Cb: Catoosa-----	85	Somewhat limited Shrink-swell	0.56	Very limited Depth to hard bedrock	1.00	Somewhat limited Shrink-swell	0.56
		Depth to hard bedrock	0.54	Shrink-swell	0.56	Depth to hard bedrock	0.54
Cm: Clareson-----	60	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
		Slope	0.37	Depth to hard bedrock	1.00	Slope	1.00
		Content of large stones	0.26	Slope	0.37	Content of large stones	0.26
		Depth to hard bedrock	0.20	Content of large stones	0.26	Depth to hard bedrock	0.20
Rock Outcrop-----	20	Not rated		Not rated		Not rated	
De: Dennis-----	90	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
		Depth to saturated zone	0.03	Depth to saturated zone	1.00	Depth to saturated zone	0.03
Df: Dennis-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
		Depth to saturated zone	0.03	Depth to saturated zone	1.00	Slope	0.12
						Depth to saturated zone	0.03
Ec: Eram-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
		Depth to saturated zone	0.03	Depth to saturated zone	1.00	Depth to saturated zone	0.03
				Depth to soft bedrock	0.71		
Ed: Eram-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
		Depth to saturated zone	0.03	Depth to saturated zone	1.00	Slope	0.48
				Depth to soft bedrock	0.71	Depth to saturated zone	0.03

BUILDING SITE DEVELOPMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ef: Eram-----	50	Very limited Shrink-swell Slope  Depth to saturated zone	1.00 0.04  0.03	Very limited Shrink-swell Depth to saturated zone Depth to soft bedrock Slope	1.00 1.00  0.71 0.04	Very limited Shrink-swell Slope  Depth to saturated zone	1.00 1.00  0.03
Lebo-----	30	Somewhat limited Shrink-swell Slope	0.99 0.96	Very limited Shrink-swell Slope Depth to soft bedrock	0.99 0.96 0.01	Very limited Slope Shrink-swell	1.00 0.99
Hp: Hepler-----	90	Very limited Flooding Depth to saturated zone	1.00 0.39	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 1.00 0.00	Very limited Flooding Depth to saturated zone	1.00 0.39
INT: Aquolls-----	100	Very limited Depth to saturated zone Ponding	1.00 1.00	Very limited Depth to saturated zone Ponding	1.00 1.00	Very limited Depth to saturated zone Ponding	1.00 1.00
Ke: Kenoma-----	90	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
La: Lanton-----	90	Very limited Flooding Depth to saturated zone	1.00 0.99	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 0.99
Lb: Lebo-----	85	Very limited Slope Shrink-swell	1.00 0.99	Very limited Slope Shrink-swell Depth to soft bedrock	1.00 0.99 0.01	Very limited Slope Shrink-swell	1.00 0.99
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Mb: Mason-----	85	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50
Nf: Newtonia-----	90	Somewhat limited Shrink-swell	0.01	Somewhat limited Shrink-swell	0.01	Somewhat limited Shrink-swell	0.01
Ng: Newtonia-----	90	Somewhat limited Shrink-swell	0.01	Somewhat limited Shrink-swell	0.01	Somewhat limited Shrink-swell	0.01
Nh: Newtonia-----	85	Somewhat limited Shrink-swell	0.01	Somewhat limited Shrink-swell	0.01	Somewhat limited Slope Shrink-swell	0.48 0.01
Oh: Okemah-----	90	Very limited Shrink-swell Depth to saturated zone	1.00 0.03	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Shrink-swell Depth to saturated zone	1.00 0.03
Om: Kanima-----	100	Very limited Slope Shrink-swell	1.00 0.02	Very limited Slope Shrink-swell	1.00 0.02	Very limited Slope Shrink-swell	1.00 0.02
Op: Kanima-----	100	Somewhat limited Slope Shrink-swell	0.04 0.02	Somewhat limited Slope Shrink-swell	0.04 0.02	Very limited Slope Shrink-swell	1.00 0.02
Ot: Osage-----	85	Very limited Ponding Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00 1.00	Very limited Ponding Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00 1.00	Very limited Ponding Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00 1.00

BUILDING SITE DEVELOPMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ov: Osage-----	90	Very limited Ponding Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00 1.00	Very limited Ponding Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00 1.00	Very limited Ponding Flooding Depth to saturated zone Shrink-swell	1.00 1.00 1.00 1.00
Pc: Parsons-----	90	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Shrink-swell Depth to saturated zone	1.00 1.00
Po: Pits, Quarries-----	100	Not rated		Not rated		Not rated	
Sn: Summit-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Shrink-swell	1.00
So: Summit-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Shrink-swell Slope	1.00 0.48
Vb: Verdigris-----	90	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
Vc: Verdigris-----	85	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
W: Water-----	100	Not rated		Not rated		Not rated	
We: Welda-----	90	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.00
Wo: Woodson-----	85	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Shrink-swell Depth to saturated zone	1.00 1.00

BUILDING SITE DEVELOPMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
003CD: Collinsville-----	65	Very limited Depth to hard bedrock Slope	1.00 0.04	Very limited Depth to hard bedrock Cutbanks cave Slope	1.00 0.10 0.04	Very limited Depth to bedrock Droughty Slope Content of large stones	1.00 0.04 0.03
Collinsville Taxadjunct-----	20	Somewhat limited  Depth to hard bedrock	 0.95	Very limited  Depth to hard bedrock Cutbanks cave	 1.00 0.10	Somewhat limited  Depth to bedrock Droughty Content of large stones	 0.95 0.40 0.03
003DE: Dennis, eroded-----	95	Very limited Shrink-swell  Depth to saturated zone	1.00 0.94	Very limited Depth to saturated zone Cutbanks cave  Too clayey	1.00 0.10 0.02	Somewhat limited Depth to saturated zone	0.94
003EH: Eram, eroded-----	85	Very limited Shrink-swell  Depth to saturated zone	1.00 1.00	Very limited Depth to saturated zone Depth to soft bedrock Too clayey Cutbanks cave	1.00 0.20 0.12 0.10	Very limited Depth to saturated zone Depth to bedrock	1.00 0.20
003EK: Eram-----	60	Very limited Shrink-swell  Depth to saturated zone Slope	1.00 1.00 0.00	Very limited Depth to saturated zone Depth to soft bedrock Cutbanks cave Slope	1.00 0.20 0.10 0.00	Very limited Depth to saturated zone Depth to bedrock Slope	1.00 0.20 0.00
Clareson-----	20	Very limited Content of large stones Depth to hard bedrock Slope	1.00 0.90 0.00	Very limited Depth to hard bedrock Content of large stones Too clayey Cutbanks cave Slope	1.00 1.00 1.00 0.10 0.00	Very limited Droughty  Content of large stones Depth to bedrock Slope	1.00 1.00 0.90 0.00
003LE: Leanna, drained-----	88	Very limited Flooding  Shrink-swell Depth to saturated zone	1.00 1.00 0.94	Very limited Depth to saturated zone Flooding Too clayey  Cutbanks cave	1.00 0.60 0.12 0.10	Somewhat limited Depth to saturated zone Flooding	0.94 0.60
003LH: Lula-----	85	Somewhat limited Shrink-swell	0.50	Somewhat limited Depth to hard bedrock Cutbanks cave	0.54 0.10	Not limited	
003SE: Stony Land-----	60	Not rated		Not rated		Not rated	
Talihina-----	20	Very limited Depth to soft bedrock Shrink-swell  Depth to saturated zone Slope	1.00 1.00 0.94 0.84	Very limited Depth to soft bedrock Depth to saturated zone Slope  Cutbanks cave	1.00 1.00 0.84 0.10	Very limited Depth to bedrock Depth to saturated zone Slope  Droughty	1.00 0.94 0.84 0.83
003WF: Woodson-----	85	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.92 0.10	Very limited Depth to saturated zone	1.00

BUILDING SITE DEVELOPMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
011CA: Catoosa-----	85	Very limited Shrink-swell	1.00	Very limited Depth to hard bedrock	1.00	Somewhat limited Depth to bedrock	0.74
		Depth to hard bedrock	0.74	Cutbanks cave	0.10		
059CM: Clareson-----	55	Somewhat limited Shrink-swell	0.96	Very limited Depth to hard bedrock	1.00	Somewhat limited Depth to bedrock	0.80
		Depth to hard bedrock	0.79	Content of large stones	0.16	Droughty	0.31
		Content of large stones	0.16	Cutbanks cave	0.10	Content of large stones	0.11
		Slope	0.04	Slope	0.04	Slope	0.04
Eram-----	30	Very limited Shrink-swell	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Too clayey	0.12	Depth to bedrock	0.01
		Slope	0.00	Cutbanks cave	0.10	Slope	0.00
				Depth to soft bedrock	0.01		
				Slope	0.00		
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
Bb: Bates-----	85	Somewhat limited Shrink-swell	0.02	Very limited Cutbanks cave	1.00	Somewhat limited Depth to bedrock	0.35
				Depth to soft bedrock	0.35		
Bc: Bates-----	85	Not limited		Very limited Cutbanks cave	1.00	Somewhat limited Depth to bedrock	0.35
				Depth to soft bedrock	0.35		
Cb: Catoosa-----	85	Somewhat limited Shrink-swell	0.56	Very limited Depth to hard bedrock	1.00	Somewhat limited Depth to bedrock	0.54
		Depth to hard bedrock	0.54	Too clayey	0.88		
				Cutbanks cave	0.10		
Cm: Clareson-----	60	Very limited Shrink-swell	1.00	Very limited Depth to hard bedrock	1.00	Somewhat limited Slope	0.37
		Slope	0.37	Too clayey	1.00	Depth to bedrock	0.20
		Content of large stones	0.26	Slope	0.37	Droughty	0.00
		Depth to hard bedrock	0.20	Content of large stones	0.26		
				Cutbanks cave	0.10		
Rock Outcrop-----	20	Not rated		Not rated		Not rated	
De: Dennis-----	90	Very limited Shrink-swell	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Depth to saturated zone	0.02
		Depth to saturated zone	0.02	Too clayey	0.59		
				Cutbanks cave	0.10		
Df: Dennis-----	85	Very limited Shrink-swell	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Depth to saturated zone	0.02
		Depth to saturated zone	0.02	Too clayey	0.59		
				Cutbanks cave	0.10		

BUILDING SITE DEVELOPMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ec: Eram-----	85	Very limited Shrink-swell	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Depth to bedrock	0.71
		Depth to saturated zone	0.02	Too clayey	0.88	Depth to saturated zone	0.02
				Depth to soft bedrock	0.71		
				Cutbanks cave	0.10		
Ed: Eram-----	85	Very limited Shrink-swell	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Depth to bedrock	0.71
		Depth to saturated zone	0.02	Too clayey	0.88	Depth to saturated zone	0.02
				Depth to soft bedrock	0.71		
				Cutbanks cave	0.10		
Ef: Eram-----	50	Very limited Shrink-swell	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Depth to bedrock	0.71
		Slope	0.04	Too clayey	0.88	Slope	0.04
		Depth to saturated zone	0.02	Depth to soft bedrock	0.71	Depth to saturated zone	0.02
				Cutbanks cave	0.10		
				Slope	0.04		
Lebo-----	30	Very limited Shrink-swell	0.99	Somewhat limited Slope	0.96	Very limited Too clayey	1.00
		Slope	0.96	Too clayey	0.50	Slope	0.96
				Cutbanks cave	0.10	Depth to bedrock	0.01
				Depth to soft bedrock	0.01		
Hp: Hepler-----	90	Very limited Flooding	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Flooding	0.60
		Depth to saturated zone	0.19	Flooding	0.60	Depth to saturated zone	0.19
				Cutbanks cave	0.10		
INT: Aguolls-----	100	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Ponding	1.00	Ponding	1.00	Ponding	1.00
				Cutbanks cave	0.10		
Ke: Kenoma-----	90	Very limited Shrink-swell	1.00	Somewhat limited Too clayey	0.41	Not limited	
				Cutbanks cave	0.10		
La: Lanton-----	90	Very limited Flooding	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Depth to saturated zone	0.78
		Depth to saturated zone	0.78	Flooding	0.60	Flooding	0.60
				Cutbanks cave	0.10		
Lb: Lebo-----	85	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00
		Shrink-swell	0.99	Too clayey	0.50	Too clayey	1.00
				Cutbanks cave	0.10	Gravel content	0.08
				Depth to soft bedrock	0.01	Depth to bedrock	0.01
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Mb: Mason-----	85	Somewhat limited Shrink-swell	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
		Flooding	0.40				
Nf: Newtonia-----	90	Somewhat limited Shrink-swell	0.01	Somewhat limited Cutbanks cave	0.10	Not limited	
Ng: Newtonia-----	90	Somewhat limited Shrink-swell	0.01	Somewhat limited Cutbanks cave	0.10	Not limited	

BUILDING SITE DEVELOPMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Nh: Newtonia-----	85	Somewhat limited Shrink-swell	0.01	Somewhat limited Cutbanks cave	0.10	Not limited	
Oh: Okemah-----	90	Very limited Shrink-swell	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Depth to saturated zone	0.02
		Depth to saturated zone	0.02	Too clayey	0.12		
				Cutbanks cave	0.10		
Om: Kanima-----	100	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00
		Shrink-swell	0.02	Cutbanks cave	0.10	Too clayey	1.00
						Droughty	0.37
Op: Kanima-----	100	Somewhat limited Slope	0.04	Somewhat limited Cutbanks cave	0.10	Very limited Too clayey	1.00
		Shrink-swell	0.02	Slope	0.04	Droughty	0.37
						Slope	0.04
Ot: Osage-----	85	Very limited Shrink-swell	1.00	Very limited Ponding	1.00	Very limited Ponding	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Too clayey	1.00	Flooding	0.60
		Flooding	1.00	Flooding	0.60		
				Cutbanks cave	0.10		
Ov: Osage-----	90	Very limited Shrink-swell	1.00	Very limited Ponding	1.00	Very limited Ponding	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Too clayey	1.00	Too clayey	1.00
		Flooding	1.00	Flooding	0.60	Flooding	0.60
				Cutbanks cave	0.10		
Pc: Parsons-----	90	Very limited Shrink-swell	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Too clayey	0.59		
				Cutbanks cave	0.10		
Po: Pits, Quarries-----	100	Not rated		Not rated		Not rated	
Sn: Summit-----	85	Very limited Shrink-swell	1.00	Very limited Depth to saturated zone	1.00	Not limited	
				Too clayey	0.12		
				Cutbanks cave	0.10		
So: Summit-----	85	Very limited Shrink-swell	1.00	Very limited Depth to saturated zone	1.00	Not limited	
				Too clayey	0.12		
				Cutbanks cave	0.10		
Vb: Verdigris-----	90	Very limited Flooding	1.00	Somewhat limited Flooding	0.60	Somewhat limited Flooding	0.60
				Cutbanks cave	0.10		
Vc: Verdigris-----	85	Very limited Flooding	1.00	Somewhat limited Flooding	0.80	Very limited Flooding	1.00
				Cutbanks cave	0.10		
W: Water-----	100	Not rated		Not rated		Not rated	
We: Welda-----	90	Very limited Shrink-swell	1.00	Somewhat limited Cutbanks cave	0.10	Not limited	
		Frost action	0.50	Too clayey	0.01		



BUILDING SITE DEVELOPMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Wo: Woodson-----	85	Very limited Shrink-swell	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Too clayey	0.92		
				Cutbanks cave	0.10		

CONSTRUCTION MATERIALS  
Linn County, Kansas

### Construction Materials

The following tables give information about the soils as potential sources of gravel, sand, topsoil, reclamation material, and roadfill. Normal compaction, minor processing, and other standard construction practices are assumed.

The soils are rated good, fair, or poor as potential sources of topsoil, reclamation material, and roadfill. The features that limit the soils as sources of these materials are specified in the tables. The numerical ratings given after the specified features indicate the degree to which the features limit the soils as sources of topsoil, reclamation material, or roadfill. The lower the number, the greater the limitation.

The soils are rated as a probable or improbable source of sand and gravel. A rating of probable means that the source material is likely to be in or below the soil. The numerical ratings in these columns indicate the degree of probability. The number 0.00 indicates that the soil is an improbable source. A number between 0.00 and 1.00 indicates the degree to which the soil is a probable source of sand or gravel.

Sand and gravel are natural aggregates suitable for commercial use with a minimum of processing. They are used in many kinds of construction. Specifications for each use vary widely. In these tables, only the probability of finding material in suitable quantity is evaluated. The suitability of the material for specific purposes is not evaluated, nor are factors that affect excavation of the material. The properties used to evaluate the soil as a source of sand or gravel are gradation of grain sizes (as indicated by the Unified classification of the soil), the thickness of suitable material, and the content of rock fragments. If the lowest layer of the soil contains sand or gravel, the soil is rated as a probable source regardless of thickness. The assumption is that the sand or gravel layer below the depth of observation exceeds the minimum thickness.

Topsoil is used to cover an area so that vegetation can be established and maintained. The upper 40 inches of a soil is evaluated for use as topsoil. Also evaluated is the reclamation potential of the borrow area. The ratings are based on the soil properties that affect plant growth; the ease of excavating, loading, and spreading the material; and reclamation of the borrow area. Toxic substances, soil reaction, and the properties that are inferred from soil texture, such as available water capacity and fertility, affect plant growth. The ease of excavating, loading, and spreading is affected by rock fragments, slope, depth to a water table, soil texture, and thickness of suitable material. Reclamation of the borrow area is affected by slope, depth to a water table, rock fragments, depth to bedrock or a cemented pan, and toxic material.

The surface layer of most soils is generally preferred for topsoil because of its organic matter content. Organic matter greatly increases the absorption and retention of moisture and nutrients for plant growth.

Reclamation material is used in areas that have been drastically disturbed by surface mining or similar activities. When these areas are reclaimed, layers of soil material or unconsolidated geological material, or both, are replaced in a vertical sequence. The reconstructed soil favors plant growth. The ratings in the table do not apply to quarries and other mined areas that require an offsite source of reconstruction material. The ratings are based on the soil properties that affect erosion and stability of the surface and the productive potential of the reconstructed soil. These properties include the content of sodium, salts, and calcium carbonate; reaction; available water capacity; erodibility; texture; content of rock fragments; and content of organic matter and other features that affect fertility.

Roadfill is soil material that is excavated in one place and used in road embankments in another place. In this table, the soils are rated as a source of roadfill for low embankments, generally less than 6 feet high and less exacting in design than higher embankments.

The ratings are for the whole soil, from the surface to a depth of about 5 feet. It is assumed that soil layers will be mixed when the soil material is excavated and spread.

The ratings are based on the amount of suitable material and on soil properties that affect the ease of excavation and the performance of the material after it is in place. The thickness of the suitable material is a major consideration. The ease of excavation is affected by large stones, depth to a water table, and slope. How well the soil performs in place after it has been compacted and drained is determined by its strength (as inferred from the AASHTO classification of the soil) and linear extensibility (shrink-swell potential).

CONSTRUCTION MATERIALS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
003CD: Collinsville-----	65	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Collinsville Taxadjunct-----	20	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
003DE: Dennis, eroded-----	95	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
003EH: Eram, eroded-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
003EK: Eram-----	60	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Clareson-----	20	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
003LE: Leanna, drained----	88	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
003LH: Lula-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
003SE: Stony Land-----	60	Not rated		Not rated	
Talihina-----	20	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
003WF: Woodson-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
011CA: Catoosa-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
059CM: Clareson-----	55	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Eram-----	30	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
AED: Arents, Earthen Dam-	100	Not rated		Not rated	
Bb: Bates-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Bc: Bates-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
Cb: Catoosa-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Cm: Clareson-----	60	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Rock Outcrop-----	20	Not rated		Not rated	
De: Dennis-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Df: Dennis-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ec: Eram-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ed: Eram-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ef: Eram-----	50	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Lebo-----	30	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Hp: Hepler-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
INT: Aquolls-----	100	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ke: Kenoma-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
La: Lanton-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Lb: Lebo-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
M-W: Miscellaneous Water-	100	Not rated		Not rated	
Mb: Mason-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
Nf: Newtonia-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ng: Newtonia-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Nh: Newtonia-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Oh: Okemah-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Om: Kanima-----	100	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Op: Kanima-----	100	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ot: Osage-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ov: Osage-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Pc: Parsons-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Po: Pits, Quarries-----	100	Not rated		Not rated	
Sn: Summit-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
So: Summit-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Vb: Verdigris-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Vc: Verdigris-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
W: Water-----	100	Not rated		Not rated	
We: Welda-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
Wo: Woodson-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
003CD: Collinsville-----	65	Poor Droughty Depth to bedrock Too acid	0.00 0.00 0.84	Poor Depth to bedrock	0.00	Poor Depth to bedrock Rock fragments Slope	0.00 0.76 0.96
Collinsville Taxadjunct-----	20	Poor Droughty Depth to bedrock Too acid	0.00 0.05 0.84	Poor Depth to bedrock	0.00	Fair Rock fragments Depth to bedrock	0.04 0.05
003DE: Dennis, eroded-----	95	Poor Too clayey  Low content of organic matter Too acid Water erosion	0.00  0.18 0.61 0.90	Fair Depth to saturated zone Shrink-swell	0.04 0.12	Poor Too Clayey  Depth to saturated zone	0.00  0.04
003EH: Eram, eroded-----	85	Poor Too clayey Low content of organic matter Depth to bedrock Too acid Droughty No water erosion limitation	0.00 0.50 0.79 0.84 0.90 0.99	Poor Depth to bedrock Depth to saturated zone Shrink-swell	0.00 0.00 0.26	Poor Too Clayey Depth to saturated zone Depth to bedrock	0.00 0.00 0.79
003EK: Eram-----	60	Fair Too clayey  Low content of organic matter Depth to bedrock Droughty Too acid No water erosion limitation	0.02  0.50 0.79 0.80 0.84 0.99	Poor Depth to bedrock  Depth to saturated zone Shrink-swell	0.00 0.00 0.12	Poor Depth to saturated zone Too Clayey Depth to bedrock	0.00 0.01 0.79
Clareson-----	20	Poor Droughty Cobble content Too clayey Depth to bedrock	0.00 0.00 0.00 0.10	Poor Depth to bedrock Cobble content	0.00 0.00	Poor Rock fragments Too Clayey Depth to bedrock	0.00 0.00 0.10
003LE: Leanna, drained----	88	Poor Too clayey Too acid  No water erosion limitation	0.00 0.61 0.99	Fair Shrink-swell Depth to saturated zone	0.03 0.04	Poor Too Clayey Depth to saturated zone	0.00 0.04
003LH: Lula-----	85	Fair Low content of organic matter Too acid Too clayey No water erosion limitation	0.32 0.61 0.92 0.99	Fair Depth to bedrock  Shrink-swell	0.46 0.89	Fair Hard to reclaim Too Clayey Too acid	0.50 0.80 0.99
003SE: Stony Land-----	60	Not rated		Not rated		Not rated	
Talihina-----	20	Poor Droughty Depth to bedrock  Too clayey No water erosion limitation	0.00 0.00 0.08 0.99	Poor Depth to bedrock Depth to saturated zone Shrink-swell	0.00 0.04 0.12	Poor Depth to bedrock Depth to saturated zone Too Clayey Slope	0.00 0.04 0.08 0.16

CONSTRUCTION MATERIALS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
003WF: Woodson-----	85	Poor Too clayey  Low content of organic matter Water erosion Too acid	0.00  0.50 0.90 0.95	Poor Depth to saturated zone Shrink-swell	0.00  0.00	Poor Too Clayey  Depth to saturated zone	0.00  0.00
011CA: Catoosa-----	85	Fair Depth to bedrock Droughty Too acid No water erosion limitation	0.26 0.62 0.95 0.21 0.99	Poor Depth to bedrock Shrink-swell	0.00 0.32	Fair Depth to bedrock	0.26
059CM: Clareson-----	55	Fair Droughty Too clayey Depth to bedrock Cobble content	0.01 0.02 0.21 0.85	Poor Depth to bedrock Cobble content Shrink-swell	0.00 0.55 0.64	Poor Rock fragments Too Clayey Depth to bedrock Slope	0.00 0.02 0.21 0.96
Eram-----	30	Poor Too clayey  Too acid  Droughty Depth to bedrock No water erosion limitation	0.00  0.95  0.98 0.99 0.99	Poor Depth to bedrock  Depth to saturated zone Shrink-swell	0.00  0.00 0.16	Poor Depth to saturated zone Too Clayey Depth to bedrock	0.00  0.00 0.99
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
Bb: Bates-----	85	Fair Too acid Depth to bedrock Droughty	0.61 0.65 0.98	Poor Depth to bedrock	0.00	Fair Depth to bedrock Too acid	0.65 0.99
Bc: Bates-----	85	Fair Too clayey Too acid Depth to bedrock Low content of organic matter Droughty	0.32 0.61 0.65 0.88 0.94	Poor Depth to bedrock	0.00	Fair Too Clayey Depth to bedrock Too acid	0.23 0.65 0.99
Cb: Catoosa-----	85	Fair Depth to bedrock Too clayey Too acid Droughty No water erosion limitation	0.46 0.82 0.84 0.99 0.99	Poor Depth to bedrock Shrink-swell	0.00 0.73	Fair Depth to bedrock Too Clayey	0.46 0.77
Cm: Clareson-----	60	Poor Too clayey Droughty Low content of organic matter Cobble content Depth to bedrock	0.00 0.20 0.50 0.74 0.79	Poor Depth to bedrock Cobble content Shrink-swell	0.00 0.11 0.59	Poor Rock fragments Too Clayey Slope  Depth to bedrock	0.00 0.00 0.63 0.79
Rock Outcrop-----	20	Not rated		Not rated		Not rated	



CONSTRUCTION MATERIALS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
De: Dennis-----	90	Poor Too clayey Low content of organic matter Too acid Water erosion	0.00 0.02 0.20 0.90	Fair Shrink-swell Depth to saturated zone	0.06 0.80	Poor Too Clayey Depth to saturated zone	0.00 0.80
Df: Dennis-----	85	Poor Too clayey Low content of organic matter Too acid Water erosion	0.00 0.02 0.20 0.90	Fair Shrink-swell Depth to saturated zone	0.05 0.80	Poor Too Clayey Depth to saturated zone	0.00 0.80
Ec: Eram-----	85	Poor Too clayey Depth to bedrock Droughty  Low content of organic matter Too acid No water erosion limitation	0.00 0.29 0.35  0.88 0.95 0.99	Poor Depth to bedrock Shrink-swell Depth to saturated zone	0.00 0.37 0.80	Poor Too Clayey Depth to bedrock Depth to saturated zone	0.00 0.29 0.80
Ed: Eram-----	85	Poor Too clayey Depth to bedrock Droughty  Low content of organic matter Too acid No water erosion limitation	0.00 0.29 0.34  0.88 0.95 0.99	Poor Depth to bedrock Shrink-swell Depth to saturated zone	0.00 0.37 0.80	Poor Too Clayey Depth to bedrock Depth to saturated zone	0.00 0.29 0.80
Ef: Eram-----	50	Poor Too clayey Depth to bedrock Droughty  Low content of organic matter Too acid No water erosion limitation	0.00 0.29 0.31  0.88 0.95 0.99	Poor Depth to bedrock Shrink-swell Depth to saturated zone	0.00 0.37 0.80	Poor Too Clayey Depth to bedrock Depth to saturated zone Slope	0.00 0.29 0.80 0.96
Lebo-----	30	Poor Too clayey Depth to bedrock	0.00 0.99	Poor Depth to bedrock Shrink-swell	0.00 0.72	Poor Too Clayey Slope Depth to bedrock	0.00 0.04 0.99
Hp: Hepler-----	90	Fair Low content of organic matter Too acid No water erosion limitation	0.12 0.20 0.99	Fair Depth to saturated zone	0.53	Fair Depth to saturated zone	0.53
INT: Aquolls-----	100	Poor Low content of organic matter	0.00	Poor Depth to saturated zone	0.00	Poor Depth to saturated zone	0.00
Ke: Kenoma-----	90	Poor Too clayey Low content of organic matter Water erosion Too acid	0.00 0.88 0.90 0.95	Poor Shrink-swell	0.00	Poor Too Clayey	0.00

CONSTRUCTION MATERIALS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
La: Lanton-----	90	Fair No water erosion limitation	0.99	Fair Depth to saturated zone	0.12	Fair Depth to saturated zone	0.12
Lb: Lebo-----	85	Poor Too clayey Depth to bedrock	0.00 0.99	Poor Depth to bedrock Slope Shrink-swell	0.00 0.08 0.95	Poor Slope Too Clayey Depth to bedrock	0.00 0.00 0.99
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Mb: Mason-----	85	Fair Too acid No water erosion limitation	0.97 0.99	Fair Shrink-swell	0.95	Good	
Nf: Newtonia-----	90	Fair Too acid Too clayey No water erosion limitation	0.84 0.98 0.99	Fair Shrink-swell	0.99	Fair Too Clayey	0.76
Ng: Newtonia-----	90	Fair Too acid Too clayey No water erosion limitation	0.84 0.98 0.99	Fair Shrink-swell	0.99	Fair Too Clayey	0.76
Nh: Newtonia-----	85	Fair Too acid Too clayey No water erosion limitation	0.84 0.98 0.99	Fair Shrink-swell	0.99	Fair Too Clayey	0.76
Oh: Okemah-----	90	Poor Too clayey Low content of organic matter Too acid Water erosion	0.00 0.02 0.84 0.90	Fair Shrink-swell Depth to saturated zone	0.17 0.80	Poor Too Clayey Depth to saturated zone	0.00 0.80
Om: Kanima-----	100	Poor Too clayey Low content of organic matter Droughty Too acid	0.00 0.02 0.57 0.97	Poor Slope Shrink-swell	0.00 0.99	Poor Hard to reclaim Slope  Too Clayey Rock fragments Hard to reclaim	0.00 0.00  0.00 0.04 0.99
Op: Kanima-----	100	Poor Too clayey Low content of organic matter Droughty Too acid	0.00 0.02 0.57 0.97	Fair Shrink-swell	0.99	Poor Hard to reclaim Too Clayey  Rock fragments Slope Hard to reclaim	0.00 0.00  0.04 0.96 0.99
Ot: Osage-----	85	Poor Too clayey  No water erosion limitation	0.00  0.99	Poor Depth to saturated zone Shrink-swell	0.00 0.00	Poor Depth to saturated zone Too Clayey	0.00 0.00
Ov: Osage-----	90	Poor Too clayey	0.00	Poor Depth to saturated zone Shrink-swell	0.00 0.00	Poor Depth to saturated zone Too Clayey	0.00 0.00

CONSTRUCTION MATERIALS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Pc: Parsons-----	90	Poor Too clayey  Low content of organic matter Water erosion Too acid	0.00  0.12 0.68 0.84	Poor Depth to saturated zone Shrink-swell	0.00  0.18	Poor Too Clayey  Depth to saturated zone	0.00  0.00
Po: Pits, Quarries-----	100	Not rated		Not rated		Not rated	
Sn: Summit-----	85	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.88 0.99	Fair Shrink-swell Depth to saturated zone	0.15 0.89	Poor Too Clayey Depth to saturated zone	0.00 0.89
So: Summit-----	85	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.88 0.99	Fair Shrink-swell Depth to saturated zone	0.14 0.89	Poor Too Clayey Depth to saturated zone	0.00 0.89
Vb: Verdigris-----	90	Good		Good		Good	
Vc: Verdigris-----	85	Good		Good		Good	
W: Water-----	100	Not rated		Not rated		Not rated	
We: Welda-----	90	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.50 0.61 0.99	Fair Shrink-swell	0.50	Poor Too Clayey Too acid	0.00 0.99
Wo: Woodson-----	85	Poor Too clayey Water erosion  Too acid	0.00 0.90  0.95	Poor Shrink-swell Depth to saturated zone	0.00 0.00	Poor Too Clayey Depth to saturated zone	0.00 0.00

RECREATIONAL INTERPRETATIONS  
Linn County, Kansas

## Recreation

The soils of the survey area are rated in the following tables according to limitations that affect their suitability for recreation. The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the recreational uses. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

The ratings in the tables are based on restrictive soil features, such as wetness, slope, and texture of the surface layer. Susceptibility to flooding is considered. Not considered in the ratings, but important in evaluating a site, are the location and accessibility of the area, the size and shape of the area and its scenic quality, vegetation, access to water, potential water impoundment sites, and access to public sewer lines. The capacity of the soil to absorb septic tank effluent and the ability of the soil to support vegetation also are important. Soils that are subject to flooding are limited for recreational uses by the duration and intensity of flooding and the season when flooding occurs. In planning recreational facilities, onsite assessment of the height, duration, intensity, and frequency of flooding is essential.

The information in this table can be supplemented by other information in this survey, for example, interpretations for building site development, construction materials, sanitary facilities, and water management.

Camp areas require site preparation, such as shaping and leveling the tent and parking areas, stabilizing roads and intensively used areas, and installing sanitary facilities and utility lines. Camp areas are subject to heavy foot traffic and some vehicular traffic. The ratings are based on the soil properties that affect the ease of developing camp areas and the performance of the areas after development. Slope, stoniness, and depth to bedrock or a cemented pan are the main concerns affecting the development of camp areas.

The soil properties that affect the performance of the areas after development are those that influence trafficability and promote the growth of vegetation, especially in heavily used areas. For good trafficability, the surface of camp areas should absorb rainfall readily, remain firm under heavy foot traffic, and not be dusty when dry. The soil properties that influence trafficability are texture of the surface layer, depth to a water table, ponding, flooding, permeability, and large stones. The soil properties that affect the growth of plants are depth to bedrock or a cemented pan, permeability, and toxic substances in the soil.

Picnic areas are subject to heavy foot traffic. Most vehicular traffic is confined to access roads and parking areas. The ratings are based on the soil properties that affect the ease of developing picnic areas and that influence trafficability and the growth of vegetation after development. Slope and stoniness are the main concerns affecting the development of picnic areas. For good trafficability, the surface of picnic areas should absorb rainfall readily, remain firm under heavy foot traffic, and not be dusty when dry. The soil properties that influence trafficability are texture of the surface layer, depth to a water table, ponding, flooding, permeability, and large stones. The soil properties that affect the growth of plants are depth to bedrock or a cemented pan, permeability, and toxic substances in the soil.

Playgrounds require soils that are nearly level, are free of stones, and can withstand intensive foot traffic. The ratings are based on the soil properties that affect the ease of developing playgrounds and that influence trafficability and the growth of vegetation after development. Slope and stoniness are the main concerns affecting the development of playgrounds. For good trafficability, the surface of the playgrounds should absorb rainfall readily, remain firm under heavy foot traffic, and not be dusty when dry. The soil properties that influence trafficability are texture of the surface layer, depth to a water table, ponding, flooding, permeability, and large stones. The soil properties that affect the growth of plants are depth to bedrock or a cemented pan, permeability, and toxic substances in the soil.

Paths and trails for hiking and horseback riding should require little or no slope modification through cutting and filling. The ratings are based on the soil properties that affect trafficability and erodibility. These properties are stoniness, depth to a water table, ponding, flooding, slope, and texture of the surface layer.

Golf fairways are subject to heavy foot traffic and some light vehicular traffic. Cutting or filling may be required. Irrigation is not considered in the ratings. The ratings are based on the soil properties that affect plant growth and trafficability after vegetation is established. The properties that affect plant growth are reaction; depth to a water table; ponding; depth to bedrock or a cemented pan; the available water capacity in the upper 40 inches; the content of salts, sodium, or calcium carbonate; and sulfidic materials. The properties that affect trafficability are flooding, depth to a water table, ponding, slope, stoniness, and the amount of sand, clay, or organic matter in the surface layer. The suitability of the soil for traps, tees, roughs, and greens is not considered in the ratings.

RECREATIONAL INTERPRETATIONS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
003CD: Collinsville-----	65	Very limited Depth to bedrock Slope	1.00 0.04	Very limited Depth to bedrock Slope	1.00 0.04	Very limited Depth to bedrock Slope Gravel content Content of large stones	1.00 1.00 0.28 0.03
Collinsville Taxadjunct-----	20	Not limited		Not limited		Very limited  Slope Depth to bedrock Gravel content Content of large stones	1.00 0.95 0.28 0.03
003DE: Dennis, eroded-----	95	Very limited Depth to saturated zone Restricted permeability	1.00 0.94	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.94	Very limited Depth to saturated zone Restricted permeability Slope	1.00 1.00 0.94 0.13
003EH: Eram, eroded-----	85	Very limited Depth to saturated zone Restricted permeability	1.00 0.15	Very limited Depth to saturated zone Restricted permeability	1.00 0.15	Very limited Depth to saturated zone Slope  Depth to bedrock Restricted permeability	1.00 1.00 1.00 0.20 0.15
003EK: Eram-----	60	Very limited Depth to saturated zone Restricted permeability Slope	1.00 0.15 0.00	Very limited Depth to saturated zone Restricted permeability Slope	1.00 0.15 0.00	Very limited Depth to saturated zone Slope  Depth to bedrock Restricted permeability	1.00 1.00 1.00 0.20 0.15
Clareson-----	20	Somewhat limited Restricted permeability Content of large stones Slope	0.94 0.01 0.00	Somewhat limited Restricted permeability Content of large stones Slope	0.94 0.01 0.00	Very limited Slope  Content of large stones Restricted permeability Depth to bedrock	1.00 1.00 0.94 0.90
003LE: Leanna, drained-----	88	Very limited Flooding  Depth to saturated zone Restricted permeability	1.00 1.00 0.94	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.94	Very limited Depth to saturated zone Restricted permeability Flooding	1.00 0.94 0.60
003LH: Lula-----	85	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability Slope	0.94 0.00
003SE: Stony Land-----	60	Not rated		Not rated		Not rated	
Talihina-----	20	Very limited Depth to bedrock Depth to saturated zone Slope  Restricted permeability	1.00 1.00 0.84 0.15	Very limited Depth to bedrock Depth to saturated zone Slope  Restricted permeability	1.00 0.94 0.84 0.15	Very limited Depth to bedrock Slope  Depth to saturated zone Restricted permeability	1.00 1.00 1.00 0.15
003WF: Woodson-----	85	Very limited Depth to saturated zone Restricted permeability	1.00 1.00	Very limited Depth to saturated zone Restricted permeability	1.00 1.00	Very limited Depth to saturated zone Restricted permeability Slope	1.00 1.00 1.00 0.00
011CA: Catoosa-----	85	Somewhat limited		Somewhat limited		Somewhat limited	

RECREATIONAL INTERPRETATIONS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
059CM: Clareson-----	55	Restricted permeability	0.15	Restricted permeability	0.15	Restricted permeability	0.15
		Somewhat limited Restricted permeability Slope	0.94	Somewhat limited Restricted permeability Slope	0.94	Very limited Slope	1.00
			0.04		0.04	Restricted permeability Depth to bedrock Content of large stones	0.94 0.80 0.11
Eram-----	30	Very limited Depth to saturated zone Restricted permeability Slope	1.00	Very limited Depth to saturated zone Restricted permeability Slope	1.00	Very limited Depth to saturated zone	1.00
			0.94		0.94	Slope	1.00
			0.00		0.00	Restricted permeability Depth to bedrock	0.94 0.01
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
Bb: Bates-----	85	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability Depth to bedrock Slope	0.94 0.35 0.13
Bc: Bates-----	85	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94	Very limited Slope	1.00
Cb: Catoosa-----	85	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability	0.15	Restricted permeability Depth to bedrock	0.94 0.35
						Somewhat limited Restricted permeability Slope	0.15 0.00
Cm: Clareson-----	60	Somewhat limited Slope Restricted permeability	0.37	Somewhat limited Slope Restricted permeability	0.37	Very limited Slope	1.00
			0.15		0.15	Depth to bedrock	0.20
						Restricted permeability	0.15
Rock Outcrop-----	20	Not rated		Not rated		Not rated	
De: Dennis-----	90	Somewhat limited Restricted permeability Depth to saturated zone	0.15 0.03	Somewhat limited Restricted permeability Depth to saturated zone	0.15 0.02	Somewhat limited Restricted permeability Depth to saturated zone Slope	0.15 0.03 0.00
Df: Dennis-----	85	Somewhat limited Restricted permeability Depth to saturated zone	0.15	Somewhat limited Restricted permeability Depth to saturated zone	0.15	Somewhat limited Slope	0.87
			0.03		0.02	Restricted permeability Depth to saturated zone	0.15 0.03
Ec: Eram-----	85	Somewhat limited Restricted permeability Depth to saturated zone	0.15	Somewhat limited Restricted permeability Depth to saturated zone	0.15	Somewhat limited Depth to bedrock	0.71
			0.03		0.02	Restricted permeability Slope	0.15 0.13
						Depth to saturated zone	0.03
Ed: Eram-----	85	Somewhat limited Restricted permeability Depth to saturated zone	0.15	Somewhat limited Restricted permeability Depth to saturated zone	0.15	Very limited Slope	1.00
			0.03		0.02	Depth to bedrock	0.71

RECREATIONAL INTERPRETATIONS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ef: Eram-----	50	Somewhat limited Restricted permeability Slope Depth to saturated zone	0.15  0.04 0.03	Somewhat limited Restricted permeability Slope Depth to saturated zone	0.15  0.04 0.02	Restricted permeability	0.15
						Depth to saturated zone	0.03
						Very limited Slope	1.00
						Depth to bedrock	0.71
						Restricted permeability	0.15
Lebo-----	30	Very limited Too clayey Slope Restricted permeability	1.00 0.96 0.94	Very limited Too clayey Slope Restricted permeability	1.00 0.96 0.94	Depth to saturated zone	0.03
						Very limited Slope	1.00
						Too clayey	1.00
						Restricted permeability	0.94
						Gravel content	0.32
Hp: Hepler-----	90	Very limited Flooding  Depth to saturated zone Restricted permeability	1.00  0.39 0.15	Somewhat limited Depth to saturated zone Restricted permeability	0.19  0.15	Depth to bedrock	0.01
						Somewhat limited Flooding	0.60
						Depth to saturated zone	0.39
						Restricted permeability	0.15
INT: Aquolls-----	100	Very limited Depth to saturated zone Restricted permeability Ponding	1.00  1.00 1.00	Very limited Depth to saturated zone Restricted permeability Ponding	1.00  1.00 1.00	Restricted permeability	1.00
						Depth to saturated zone	1.00
						Ponding	1.00
Ke: Kenoma-----	90	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94
						Slope	0.13
La: Lanton-----	90	Very limited Flooding  Depth to saturated zone Restricted permeability	1.00  0.99 0.15	Somewhat limited Depth to saturated zone Restricted permeability	0.78  0.15	Somewhat limited Depth to saturated zone	0.99
						Flooding	0.60
						Restricted permeability	0.15
Lb: Lebo-----	85	Very limited Slope Too clayey Restricted permeability Gravel content	1.00 1.00 0.94 0.08	Very limited Slope Too clayey Restricted permeability Gravel content	1.00 1.00 0.94 0.08	Very limited Slope	1.00
						Gravel content	1.00
						Too clayey	1.00
						Restricted permeability	0.94
						Depth to bedrock	0.01
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Mb: Mason-----	85	Very limited Flooding	1.00	Not limited		Not limited	
Nf: Newtonia-----	90	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability	0.15
Ng: Newtonia-----	90	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability Slope	0.15 0.13
Nh: Newtonia-----	85	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability	0.15	Very limited Slope	1.00
Oh: Okemah-----	90	Somewhat limited		Somewhat limited		Restricted permeability	0.15
						Somewhat limited	

RECREATIONAL INTERPRETATIONS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Om: Kanima-----	100	Restricted permeability	0.94	Restricted permeability	0.94	Restricted permeability	0.94
		Depth to saturated zone	0.03	Depth to saturated zone	0.02	Depth to saturated zone	0.03
		Slope		Slope		Slope	0.00
Op: Kanima-----	100	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00
		Too clayey	1.00	Too clayey	1.00	Too clayey	1.00
		Restricted permeability	0.15	Restricted permeability	0.15	Gravel content	0.37
Ot: Osage-----	85	Restricted permeability				Restricted permeability	0.15
		Very limited Too clayey	1.00	Very limited Too clayey	1.00	Very limited Slope	1.00
		Restricted permeability	0.15	Restricted permeability	0.15	Too clayey	1.00
Ov: Osage-----	90	Slope	0.04	Slope	0.04	Gravel content	0.37
						Restricted permeability	0.15
Pc: Parsons-----	90	Very limited Depth to saturated zone	1.00	Very limited Ponding	1.00	Very limited Depth to saturated zone	1.00
		Flooding	1.00	Depth to saturated zone	1.00	Ponding	1.00
		Ponding	1.00	Restricted permeability	0.94	Restricted permeability	0.94
Po: Pits, Quarries-----	100	Restricted permeability	0.94			Flooding	0.60
Sn: Summit-----	85	Very limited Depth to saturated zone	1.00	Very limited Ponding	1.00	Very limited Depth to saturated zone	1.00
		Restricted permeability	0.94	Depth to saturated zone	1.00	Ponding	1.00
				Too clayey	1.00	Too clayey	1.00
So: Summit-----	85	Restricted permeability	0.94	Restricted permeability	0.94	Restricted permeability	0.94
						Flooding	0.60
Vb: Verdigris-----	90	Very limited Floodings	1.00	Very limited Ponding	1.00	Very limited Depth to saturated zone	1.00
		Restricted permeability	0.15	Depth to saturated zone	1.00	Ponding	1.00
				Too clayey	1.00	Too clayey	1.00
Vc: Verdigris-----	85	Restricted permeability	0.94	Restricted permeability	0.94	Restricted permeability	0.94
						Flooding	0.60
						Restricted permeability	0.15
W: Water-----	100	Very limited Floodings	1.00	Very limited Ponding	1.00	Very limited Depth to saturated zone	1.00
		Restricted permeability	0.15	Depth to saturated zone	1.00	Ponding	1.00
				Too clayey	1.00	Too clayey	1.00
We: Welda-----	90	Restricted permeability	0.94	Restricted permeability	0.94	Restricted permeability	0.94
						Flooding	0.60
						Restricted permeability	0.15



RECREATIONAL INTERPRETATIONS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Wo: Woodson-----	85					Slope	0.50
		Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Restricted permeability	0.94	Restricted permeability	0.94	Restricted permeability	0.94

RECREATIONAL INTERPRETATIONS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Paths and trails		Golf fairways	
		Rating class and limiting features	Value	Rating class and limiting features	Value
003CD: Collinsville-----	65	Not limited		Very limited Depth to bedrock Droughty Slope Content of large stones	1.00 1.00 0.04 0.03
Collinsville Taxadjunct-----	20	Not limited		Somewhat limited  Depth to bedrock Droughty Content of large stones	0.95 0.40 0.03
003DE: Dennis, eroded-----	95	Somewhat limited Depth to saturated zone	0.86	Somewhat limited Depth to saturated zone	0.94
003EH: Eram, eroded-----	85	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone Depth to bedrock	1.00 0.20
003EK: Eram-----	60	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone Depth to bedrock Slope	1.00 0.20 0.00
Clareson-----	20	Somewhat limited Content of large stones	0.01	Very limited Droughty  Content of large stones Depth to bedrock Slope	1.00 1.00 0.90 0.00
003LE: Leanna, drained-----	88	Somewhat limited Depth to saturated zone	0.86	Somewhat limited Depth to saturated zone Flooding	0.94 0.60
003LH: Lula-----	85	Not limited		Not limited	
003SE: Stony Land-----	60	Not rated		Not rated	
Talihina-----	20	Somewhat limited Depth to saturated zone	0.86	Very limited Depth to bedrock  Depth to saturated zone Slope Droughty	1.00 0.94 0.84 0.83
003WF: Woodson-----	85	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
011CA: Catoosa-----	85	Not limited		Somewhat limited Depth to bedrock	0.74
059CM: Clareson-----	55	Not limited		Somewhat limited Depth to bedrock Droughty Content of large stones Slope	0.80 0.31 0.11 0.04
Eram-----	30	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone Depth to bedrock Slope	1.00 0.01 0.00
AED: Arents, Earthen Dam-	100	Not rated		Not rated	
Bb: Bates-----	85	Not limited		Somewhat limited Depth to bedrock	0.35
Bc: Bates-----	85	Not limited		Somewhat limited	

RECREATIONAL INTERPRETATIONS--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Paths and trails		Golf fairways	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Ch: Catoosa-----	85	Not limited		Depth to bedrock	0.35
Cm: Clareson-----	60	Not limited		Somewhat limited Depth to bedrock	0.54
Rock Outcrop-----	20	Not rated		Somewhat limited Slope	0.37
				Depth to bedrock	0.20
				Droughty	0.00
				Not rated	
De: Dennis-----	90	Not limited		Somewhat limited Depth to saturated zone	0.02
Df: Dennis-----	85	Not limited		Somewhat limited Depth to saturated zone	0.02
Ec: Eram-----	85	Not limited		Somewhat limited Depth to bedrock	0.71
				Depth to saturated zone	0.02
Ed: Eram-----	85	Not limited		Somewhat limited Depth to bedrock	0.71
				Depth to saturated zone	0.02
Ef: Eram-----	50	Not limited		Somewhat limited Depth to bedrock	0.71
				Slope	0.04
				Depth to saturated zone	0.02
Lebo-----	30	Very limited Too clayey	1.00	Very limited Too clayey	1.00
				Slope	0.96
				Depth to bedrock	0.01
Hp: Hepler-----	90	Not limited		Somewhat limited Flooding	0.60
				Depth to saturated zone	0.19
INT: Aquolls-----	100	Very limited Depth to saturated zone Ponding	1.00	Very limited Depth to saturated zone	1.00
			1.00	Ponding	1.00
Ke: Kenoma-----	90	Not limited		Not limited	
La: Lanton-----	90	Somewhat limited Depth to saturated zone	0.50	Somewhat limited Depth to saturated zone	0.78
				Flooding	0.60
Lb: Lebo-----	85	Very limited Too clayey Slope	1.00 0.92	Very limited Slope	1.00
				Too clayey	1.00
				Gravel content	0.08
				Depth to bedrock	0.01
M-W: Miscellaneous Water-	100	Not rated		Not rated	
Mb: Mason-----	85	Not limited		Not limited	
Nf: Newtonia-----	90	Not limited		Not limited	
Ng: Newtonia-----	90	Not limited		Not limited	
Nh: Newtonia-----	85	Not limited		Not limited	
Oh: Okemah-----	90	Not limited		Somewhat limited Depth to saturated zone	0.02
Om: Kanima-----	100	Very limited		Very limited	

Map symbol and soil name	Pct of map unit	Paths and trails		Golf fairways	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Op: Kanima-----	100	Slope Too clayey	1.00 1.00	Slope Too clayey Droughty	1.00 1.00 0.37
Ot: Osage-----	85	Very limited Too clayey	1.00	Very limited Too clayey Droughty Slope	1.00 0.37 0.04
Ov: Osage-----	90	Very limited Depth to saturated zone Ponding	1.00 1.00	Very limited Ponding	1.00
Pc: Parsons-----	90	Very limited Depth to saturated zone Ponding	1.00 1.00	Depth to saturated zone Flooding	1.00 0.60
Po: Pits, Quarries-----	100	Too clayey	1.00	Very limited Ponding	1.00
Sn: Summit-----	85	Very limited Depth to saturated zone	1.00	Depth to saturated zone Too clayey Flooding	1.00 1.00 0.60
So: Summit-----	85	Not rated		Very limited Depth to saturated zone	1.00
Vb: Verdigris-----	90	Not limited		Not rated	
Vc: Verdigris-----	85	Not limited		Not limited	
W: Water-----	100	Not limited		Not limited	
We: Welda-----	90	Not limited		Somewhat limited Flooding	0.60
Wo: Woodson-----	85	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
		Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00

# WILDLIFE INTERPRETATIONS Linn County, Kansas

## Use and Explanation of Wildlife Interpretations

Soils directly affect the kind and amount of vegetation that is available to wildlife as food and cover. They also affect the development of water impoundments. The kind and abundance of wildlife that populate an area depend largely on the amount and distribution of food, cover, water, and living space. If any one of these elements is missing, inadequate, or inaccessible, wildlife will be scarce or will not inhabit the area. If the soils have the potential, wildlife habitat can be created or improved by planting appropriate vegetation, properly managing the existing plant cover, and fostering the natural establishment of desirable plants.

In the Wildlife Interpretations table, the soils in the survey area are rated according to their potential for providing habitat for various kinds of wildlife. This information can be used in planning parks, wildlife refuges, nature study areas, and other developments for wildlife; in selecting soils that are suitable for establishing, improving, or maintaining specific elements of wildlife habitat; and in determining the intensity of management needed for each element of the habitat.

## Suitability Ratings

The potential of the soil is rated good, fair, poor, or very poor.

Good - means that the element of wildlife habitat or the kind of habitat is easily created, improved, or maintained. Few or no limitations affect management, and satisfactory results can be expected if the soil is used for the designated purpose.

Fair - means that the element of wildlife habitat or kind of habitat can be created, improved, or maintained in most places. Moderately intensive management is required for satisfactory results.

Poor - means that limitations are severe for the designated element or kind of wildlife habitat. Habitat can be created, improved, or maintained in most places, but management is difficult and requires intensive effort.

Very Poor - means that limitations are very severe for the designated element or kind of wildlife habitat. Habitat is difficult to create, improve, or maintain in most places, and management is difficult and requires intensive effort.

## Description of Wildlife Habitat Elements

Openland habitat consists of croplands, pastures, meadows, and areas that are overgrown with grasses, herbs, shrubs, and vines. These areas produce grain and seed crops, grasses and legumes, and wild herbaceous plants. The kind of wildlife attracted to these areas include bobwhite quail, pheasant, meadowlark, field sparrow, killdeer, cottontail rabbit, red fox, and coyote.

Woodland habitat consists of hardwood or conifers, or a mixture of these and associated grasses, legumes and wild herbaceous plants. Examples of wildlife attracted to this habitat are wild turkey, thrushes, woodpeckers, owl, tree squirrels, raccoon, and deer.

Wetland habitat consists of water-tolerant plants in open, marshy or swampy, shallow water areas. Examples of wildlife attracted to this habitat are ducks, geese, herons, bitterns, rails, kingfishers, shorebirds, muskrat, mink, and beaver.

The elements of wildlife habitat are described in the following paragraphs.

Grain and seed crops are domestic grains and seed-producing herbaceous plants. Soil properties and features that affect the growth of grain and seed crops are depth of the root zone, texture of the surface layer, available water capacity, wetness, slope, surface stoniness, and flooding. Soil temperature and soil moisture also are considerations. Examples of grain and seed crops are corn, wheat, oats, and barley.

Grasses and legumes are domestic perennial grasses and herbaceous legumes. Soil properties and features that affect the growth of grasses and legumes are depth of the root zone, texture of the surface layer, available water capacity, wetness, surface stoniness, flooding, and slope. Soil temperature and soil moisture also are considerations. Examples of grasses and legumes are fescue, lovegrass, bromegrass, clover, and alfalfa.

Wild herbaceous plants are native or naturally established grasses and forbs, including weeds. Soil properties and features that affect the growth of these plants are depth of the root zone, texture of the surface layer, available water capacity, wetness, surface stoniness, and flooding. Soil temperature and soil moisture also are considerations. Examples of wild herbaceous plants are bluestem, goldenrod, beggarweed, wheatgrass, and grama.

Hardwood trees and woody understory produce nuts or other fruit, buds, catkins, twigs, bark, and foliage. Soil properties and features that affect the growth of hardwood trees and shrubs are depth of the root zone, available water capacity, and wetness. Examples of these plants are oak, poplar, cherry, sweetgum, apple, hawthorn, dogwood, hickory, blackberry, and blueberry. Examples of fruit-producing shrubs that are suitable for planting on soils rated good are Russian-olive, autumn-olive, and crabapple.

Coniferous plants furnish browse and seeds. Soil properties and features that affect the growth of coniferous trees, shrubs, and ground cover are depth of the root zone, available water capacity, and wetness. Examples of coniferous plants are pine, spruce, fir, cedar, and juniper.

Shrubs are bushy woody plants that produce fruit, buds, twigs, bark, and foliage. Soil properties and features that affect the growth of shrubs are depth of the root zone, available water capacity, salinity, and soil moisture. Examples of shrubs are fragrant sumac, chokecherry, American plum, sand plum, and gorden currant.

Wetland plants are annual and perennial wild herbaceous plants that grow on moist or wet sites. Submerged or floating aquatic plants are excluded. Soil properties and features affecting wetland plants are texture of the surface layer, wetness, reaction, salinity, slope, and surface stoniness. Examples of wetland plants are smartweed, wild millet, saltgrass, cordgrass, rushes, sedges, and cattails.

Shallow water areas have an average depth of less than 5 feet. Some are naturally wet areas. Others are created by dams, levees, or other water-control structures. Soil properties and features affecting shallow water areas are depth to bedrock, wetness, surface stoniness, slope, and permeability. Examples of shallow water areas are marshes, waterfowl feeding areas, and ponds.

The habitat for various kinds of wildlife is described in the following paragraphs.

Habitat for openland wildlife consists of cropland, pasture, meadows, and areas that are overgrown with grasses, herbs, shrubs, and vines. These areas produce grain and seed crops, grasses and legumes, and wild herbaceous plants. Wildlife attracted to these areas include bobwhite quail, pheasant, meadowlark, field sparrow, cottontail, red fox and coyote.

Habitat for woodland wildlife consists of areas of deciduous and/or coniferous plants and associated grasses, legumes, and wild herbaceous plants. Wildlife attracted to these areas include wild turkey, thrushes, woodpeckers, squirrels, gray fox, raccoon, and deer.

Habitat for wetland wildlife consists of open, marshy or swampy shallow water areas. Some of the wildlife attracted to such areas are ducks, geese, herons, shore birds, muskrat, mink, and beaver.

Habitat for rangeland wildlife consists of areas of shrubs and wild herbaceous plants. Wildlife attracted to rangeland include antelope, deer, cottontail rabbit, prairie chicken, meadowlark, quail, and pheasant.

WILDLIFE INTERPRETATIONS  
Linn County, Kansas

Map symbol and soil name	Potential for habitat elements								Potential as habitat for--			
	Grain and seed crops	Grasses and legumes	Wild herba- ceous plants	Hard- wood trees	Conif- erous plants	Shrubs	Wetland plants	Shallow water areas	Open- land wild- life	Wood- land wild- life	Wetland wild- life	Range- land wild- life
003CD: COLLINSVILLE----	Very poor	Poor	Poor	Very poor	Very poor	---	Very poor	Very poor	Fair	Very poor	Very poor	Fair
COLLINSVILLE Taxadjunct-----	Very poor	Poor	Poor	Very poor	Very poor	---	Very poor	Very poor	Fair	Very poor	Very poor	Fair
003DE: DENNIS-----	Good	Good	Good	Good	Good	---	Poor	Poor	Good	Good	Poor	Good
003EH: ERAM-----	Fair	Good	Good	Good	Good	---	Very poor	Very poor	Good	Good	Very poor	Good
003EK: ERAM-----	Fair	Good	Good	Good	Good	---	Very poor	Very poor	Good	Good	Very poor	Good
CLARESON-----	Poor	Good	Good	Fair	Fair	Fair	Very poor	Very poor	Fair	Fair	Very poor	Fair
003LE: LEANNA-----	Fair	Good	Fair	Good	Good	Good	Fair	Good	Fair	Good	Fair	Good
003LH: LULA-----	Good	Good	Good	Good	Good	---	Poor	Very poor	Good	Good	Very poor	---
003SE: STONY LAND-----	---	---	---	---	---	---	---	---	---	---	---	---
TALIHINA-----	Poor	Poor	Fair	Poor	Poor	---	Very poor	Very poor	Poor	Poor	Very poor	---
003WF: WOODSON-----	Fair	Good	Fair	Poor	Poor	Fair	Poor	Good	Fair	Fair	Fair	Fair
011CA: CATOOSA-----	Fair	Good	Good	Good	Good	---	Poor	Very poor	Good	Good	Very poor	Good
059CM: CLARESON-----	Fair	Good	Good	Fair	Fair	Fair	Very poor	Very poor	Good	Fair	Very poor	Fair
ERAM-----	Fair	Good	Good	Good	Good	---	Very poor	Very poor	Good	Good	Very poor	Good
AED: ARENTS, EARTHEN DAM-----	---	---	---	---	---	---	---	---	---	---	---	---
Bb: BATES-----	Good	Good	Good	Good	Good	Good	Poor	Very poor	Good	Good	Very poor	Good
Bc: BATES-----	Good	Good	Good	Good	Good	Good	Poor	Very poor	Good	Good	Very poor	Good
Cb: CATOOSA-----	Fair	Good	Good	Good	Good	---	Poor	Very poor	Good	Good	Very poor	Good
Cm: CLARESON-----	Fair	Good	Good	Fair	Fair	Fair	Very poor	Very poor	Good	Fair	Very poor	Fair
ROCK OUTCROP----	---	---	---	---	---	---	---	---	---	---	---	---
De: DENNIS-----	Good	Good	Good	Good	Good	---	Poor	Poor	Good	Good	Poor	Good
Df: DENNIS-----	Good	Good	Good	Good	Good	---	Poor	Very poor	Good	Good	Very poor	Good
Ec: ERAM-----	Good	Good	Good	Good	Good	---	Poor	Very poor	Good	Good	Very poor	Good
Ed: ERAM-----	Fair	Good	Good	Good	Good	---	Very poor	Very poor	Good	Good	Very poor	Good

WILDLIFE INTERPRETATIONS--Continued  
Linn County, Kansas

Map symbol and soil name	Potential for habitat elements								Potential as habitat for--			
	Grain and seed crops	Grasses and legumes	Wild herba- ceous plants	Hard- wood trees	Conif- erous plants	Shrubs	Wetland plants	Shallow water areas	Open- land wild- life	Wood- land wild- life	Wetland wild- life	Range- land wild- life
Ef: ERAM-----	Fair	Good	Good	Good	Good	---	Very poor	Very poor	Good	Good	Very poor	Good
LEBO-----	Poor	Poor	Good	Good	Good	---	Very poor	Very poor	Fair	Good	Very poor	---
Hp: HEPLER-----	Fair	Good	Good	Good	Good	Good	Good	Fair	Good	Good	Fair	Good
INT: AQUOLLS-----	---	---	---	---	---	---	---	---	---	---	---	---
Ke: KENOMA-----	Good	Good	Fair	Fair	Fair	Fair	Poor	Fair	Good	Fair	Poor	Fair
La: LANTON-----	Fair	Good	Fair	Good	Good	Good	Fair	Good	Fair	Good	Fair	Good
Lb: LEBO-----	Poor	Poor	Good	Good	Good	---	Very poor	Very poor	Fair	Good	Very poor	---
M-W: MISCELLANEOUS WATER-----	---	---	---	---	---	---	---	---	---	---	---	---
Mb: MASON-----	Good	Good	Good	Good	Good	---	Poor	Very poor	Good	Good	Very poor	Good
Nf: NEWTONIA-----	Good	Good	Good	Good	Good	---	Poor	Very poor	Good	Good	Very poor	Good
Ng: NEWTONIA-----	Good	Good	Good	Good	Good	---	Poor	Very poor	Good	Good	Very poor	Good
Nh: NEWTONIA-----	Good	Good	Good	Good	Good	---	Poor	Very poor	Good	Good	Very poor	Good
Oh: OKEMAH-----	Good	Good	Good	Good	Good	---	Poor	Poor	Good	Good	Poor	---
Om: KANIMA-----	Very poor	Poor	Fair	Fair	Poor	---	Very poor	Very poor	Poor	Fair	Very poor	---
Op: KANIMA-----	Poor	Fair	Fair	Fair	Poor	---	Very poor	Very poor	Fair	Fair	Very poor	---
Ot: OSAGE-----	Fair	Fair	Fair	Fair	Fair	---	Good	Good	Fair	Fair	Good	Fair
Ov: OSAGE-----	Fair	Fair	Fair	Fair	Fair	---	Poor	Good	Fair	Fair	Fair	Fair
Pc: PARSONS-----	Fair	Good	Good	Good	Good	---	Fair	Fair	Good	Good	Fair	Good
Po: Pits, quarries--	---	---	---	---	---	---	---	---	---	---	---	---
Sn: SUMMIT-----	Good	Good	Fair	Good	Good	---	Poor	Poor	Good	Good	Poor	Good
So: SUMMIT-----	Fair	Good	Fair	Good	Good	---	Poor	Very poor	Fair	Good	Very poor	Good
Vb: VERDIGRIS-----	Good	Good	Good	Good	Good	Good	Poor	Fair	Good	Good	Poor	Good
Vc: VERDIGRIS-----	Poor	Fair	Fair	Good	Good	Good	Poor	Fair	Fair	Good	Poor	Good
W: WATER-----	---	---	---	---	---	---	---	---	---	---	---	---



WILDLIFE INTERPRETATIONS--Continued  
Linn County, Kansas

Map symbol and soil name	Potential for habitat elements								Potential as habitat for--			
	Grain and seed crops	Grasses and legumes	Wild herba- ceous plants	Hard- wood trees	Conif- erous plants	Shrubs	Wetland plants	Shallow water areas	Open- land wild- life	Wood- land wild- life	Wetland wild- life	Range- land wild- life
We: WELDA-----	Good	Good	Good	Good	Good	Good	Very poor	Poor	Good	Good	Very poor	Good
Wo: WOODSON-----	Fair	Good	Fair	Poor	Poor	Fair	Poor	Good	Fair	Fair	Fair	Fair

YIELDS PER ACRE OF PASTURE AND HAYLAND  
Linn County, Kansas

## Use and Explanation of Pastureland and Hayland Interpretations

This subsection provides information concerning the suitability of soils for the production of pasture and hayland. This subsection may contain pasture and hayland suitability groupings, land capability and yield estimates, yield estimates for individual grasses or legumes, or other information pertaining to the production of forage.

## Pasture and Hayland Suitability Groupings

Soils are placed in pasture and hayland groups according to their suitability for the production of forage. The soils in each group are enough alike to be suited to the same grasses or legumes, to have similar limitations and hazards, to require similar management, and to have similar productivity and other responses to management. Thus, the pasture and hayland suitability group is a convenient way of grouping the soils for their management. If used, these groupings are identified and described in other reports in the subsection.

## Yield Estimates

The average yields per acre that can be expected of the principal pasture or hayland crops, under a high level of management, are presented in this subsection. In any given year, yields may be higher or lower than those indicated in the tables because of variations in rainfall or other climatic factors. The yields are based mainly on the experience and records of farmers, conservationists, and extension agents. Available yield data from nearby counties and results of field trials and demonstrations are also considered.

Under good management, proper grazing is essential for the production of high quality forage, stand survival, and erosion control. Proper grazing helps plants maintain sufficient and generally vigorous top growth during the growing season. Brush control is essential in many areas, and weed control generally is needed. Rotation grazing and renovation are also important management practices.

The Pasture and Hayland table show yield estimates in tons per acre and animal unit months for pasture and hayland groups. An animal unit month is the amount of forage required by one animal unit (AU) for 30 days. On animal unit (AU) is one (1000 pound) mature cow and a calf up to weaning age (usually six months of age) or their equivalent. The Natural Resources Conservation Service uses 900 pounds of air dry forage as the amount needed to meet this requirement. To maintain a healthy and vigorous plant community, the degree of use should never be greater than 50 percent. Therefore only 25 percent of the total biomass grown is considered consumed by the grazing animal. Animal Unit Months can be converted to air dry pounds per acre production by multiplying the AUM by 30 days, then by 30 pounds per day, and then by four. This figure is the amount of total forage production.

Planners of management systems for individual fields or farms should consider the detailed information given in the description of each soil in the Nontechnical Description section. Specific information on plants and yields can be obtained from the local office of the Natural Resources Conservation Service or the Cooperative Extension Service.

(Yields in the "N" columns are for nonirrigated soils; those in the "I" columns are for irrigated soils. Yields are those that can be expected under a high level of nonirrigated and irrigated management by component. Absence of a yield indicates that the soil is not suited to the crop or the crop generally is not grown on the soil)  
Animal-unit-month: The amount of forage or feed required to feed one animal unit (one cow, one horse, one mule, five sheep, or five goats) for 30 days.

Map symbol and soil name	Land capability		Alfalfa hay		Bromegrass hay		Tall fescue	
	N	I	N	I	N	I	N	I
			Tons	Tons	Tons	Tons	AUM	AUM
003CD: Collinsville-----	6e	---	---	---	---	---	---	---
Collinsville Taxadjunct--	6e	---	---	---	---	---	---	---
003DE: Dennis, eroded-----	3e	---	---	---	---	---	---	---
003EH: Eram, eroded-----	6e	---	---	---	---	---	---	---
003EK: Eram-----	4e	---	---	---	---	---	---	---
Clareson-----	6s	---	---	---	---	---	---	---
003LE: Leanna, drained-----	2w	---	---	---	---	---	---	---
003LH: Lula-----	2e	---	---	---	---	---	---	---
003SE: Stony Land-----	7e	---	---	---	---	---	---	---
Talihina-----	6e	---	---	---	---	---	---	---
003WF: Woodson-----	3e	---	3.30	---	---	---	---	---
011CA: Catoosa-----	2e	---	5.60	---	2.20	---	4.40	---
059CM: Clareson-----	6e	---	---	---	---	---	4.00	---
Eram-----	6e	---	---	---	---	---	4.50	---
AED: Arents, Earthen Dam-----	8	---	---	---	---	---	---	---
Bb: Bates-----	2e	---	---	---	---	---	---	---
Bc: Bates-----	3e	---	---	---	---	---	---	---
Cb: Catoosa-----	2e	---	---	---	---	---	---	---
Cm: Clareson-----	6e	---	---	---	---	---	---	---
Rock Outcrop-----	8	---	---	---	---	---	---	---
De: Dennis-----	2e	---	---	---	---	---	---	---
Df: Dennis-----	3e	---	---	---	---	---	---	---
Ec: Eram-----	3e	---	---	---	---	---	---	---
Ed: Eram-----	4e	---	---	---	---	---	---	---
Ef: Eram-----	6e	---	---	---	---	---	---	---
Lebo-----	6e	---	---	---	---	---	---	---
Hp: Hepler-----	2w	---	---	---	---	---	---	---
INT: Aquolls-----	5w	---	---	---	---	---	---	---
Ke: Kenoma-----	3e	---	---	---	---	---	---	---

(Yields in the "N" columns are for nonirrigated soils; those in the "I" columns are for irrigated soils. Yields are those that can be expected under a high level of nonirrigated and irrigated management by component. Absence of a yield indicates that the soil is not suited to the crop or the crop generally is not grown on the soil)  
Animal-unit-month: The amount of forage or feed required to feed one animal unit (one cow, one horse, one mule, five sheep, or five goats) for 30 days.

Map symbol and soil name	Land capability		Alfalfa hay		Bromegrass hay		Tall fescue	
	N	I	N	I	N	I	N	I
			Tons	Tons	Tons	Tons	AUM	AUM
La: Lanton-----	2w	---	---	---	---	---	---	---
Lb: Lebo-----	6e	---	---	---	---	---	---	---
M-W: Miscellaneous Water-----	---	---	---	---	---	---	---	---
Mb: Mason-----	1	---	---	---	---	---	---	---
Nf: Newtonia-----	1	---	---	---	---	---	---	---
Ng: Newtonia-----	2e	---	---	---	---	---	---	---
Nh: Newtonia-----	3e	---	---	---	---	---	---	---
Oh: Okemah-----	1	---	---	---	---	---	---	---
Om: Kanima-----	7s	---	---	---	---	---	---	---
Op: Kanima-----	6s	---	---	---	---	---	---	---
Ot: Osage-----	2w	---	---	---	---	---	---	---
Ov: Osage-----	3w	---	---	---	---	---	---	---
Pc: Parsons-----	2s	---	---	---	---	---	---	---
Po: Pits, Quarries-----	---	---	---	---	---	---	---	---
Sn: Summit-----	2e	---	---	---	---	---	---	---
So: Summit-----	3e	---	---	---	---	---	---	---
Vb: Verdigris-----	2w	---	---	---	---	---	---	---
Vc: Verdigris-----	5w	---	---	---	---	---	---	---
W: Water-----	---	---	---	---	---	---	---	---
We: Welda-----	2e	---	---	---	---	---	---	---
Wo: Woodson-----	2s	---	---	---	---	---	---	---

CONSERVATION TREE AND SHRUB MANAGEMENT  
Linn County, Kansas

A Conservation Tree/Shrub Suitability Group (CTSG), formerly Windbreak Suitability Group, is a physiographic unit or area having similar climatic and edaphic characteristics that control the selection and height growth of trees and shrubs.

In this table, the Conservation Tree and Shrub Grouping is expressed as a group index number. The group index for Conservation Tree and Shrub groups (CTSG) are a guide for species best suited for different kinds of soil and for prediction height, growth, and effectiveness. The groupings can be used when selection woody plants for windbreaks, wildlife plantings riparian buffers, reforestation, other environmental plantings, recreation, landscaping, wetland restoration or enhancement and critical area plantings. CTSG's are developed to assure satisfactory species selection and adaptation to specific conditions of soil, climate and physiography. CTSG's are a guide for selection species best suited for different kinds of soil and prediction height growth and effectiveness.

All soil series mapped in the state have been placed in 10 groups of similar soil characteristics. Groups 1, 2, 3, 4, 6, and 9 are further divided into subgroups. In addition, all groups provide information by Major Land Resource Areas.

Each tree or shrub species has certain climatic and physiographic limits. Within these parameters a tree or shrub may be well or poorly suited because of soil characteristics. Each tree or shrub also has definable potentials of height growth depending on the factors just mentioned. Accurate definitions of potential heights are necessary for proper windbreak planning and design.

Windbreaks protect livestock, buildings, roads and yards from wind and snow. They also protect fruit trees and gardens, and they furnish habitat for wildlife. Several rows of low-growing and high-growing broadleaf and coniferous trees and shrubs provide the most protection.

Field windbreaks are narrow plantings made at right angles to the prevailing wind and at specific intervals across the field. The interval depends on the erodibility of the soil. Field windbreaks protect cropland and crops from wind, help to keep snow on the fields, and provide food and cover for wildlife.

Environmental plantings help to beautify and screen houses and other buildings and to abate noise. The plants, mostly evergreen shrubs and trees, are closely spaced. To ensure plant survival, a healthy planting stock of suitable species should be planted properly on a well prepared site and maintained in good condition.

Windbreaks are often planted on land that did not grow trees originally. Knowledge of how trees perform on such land can be gained only by observing and recording their performance where trees have been planted and survived. The problem is compounded by the fact that many favorite windbreak species are not indigenous to the areas in which they are planted.

The Kansas Field Office Technical Guide Notice KS-230, Conservation Tree and Shrub Plantings Suitability Groups shows the adapted species listing for each group index number. Showing the height that locally grown trees and shrubs are expected to reach in 20 years on various soils. The estimates are based on measurements and observation of established plantings that have been given adequate care. This information should be used to determine the placement of a windbreak, the area protected and the arrangement of species.

A number of attributes are included in the CTSG species tables for each group number found in this section of the Field Office Technical Guide. These attributes were rated subjectively and assigned a relative value to further assist those unfamiliar with individual species characteristics or desirability for the intended use. Definitions and explanations can be found. Additional information on planning windbreaks and screens and planting and caring for trees and shrubs can be obtained from the local office of the Natural Resources Conservation Service or of the Cooperative Extension Service or from a commercial nursery. See part 537 of the National Forestry Manual for additional information.

In the Tree and Shrub Management table interpretive ratings are given for various aspects of forest and conservation tree and shrub management. Some rating class terms indicate the degree to which the soils are suited to a specified forest management practice. Well suited indicates that the soil has features that are favorable for the specified practice and has no limitations. Good performance can be expected, and little or no maintenance is needed. Moderately well suited indicates that the soil has features that are moderately favorable for the specified practice. One or more soil properties are less than desirable and fair performance can be expected. Some maintenance is needed. Poorly suited indicates that the soil has one or more properties that are unfavorable for the specified practice. Overcoming the unfavorable properties requires special design, extra maintenance, and costly alteration. Unsited indicates that the expected performance of the soil is unacceptable for the specified practice or that extreme measures are needed to overcome the undesirable soil properties.

The paragraphs that follow indicate the soil properties considered in rating the soils for forest and conservation tree and shrub management practices. More detailed information about the criteria used in the ratings is available in the "National Forestry Manual," which is available in local offices of the Natural Resources Conservation Service or on the Internet. Also, in the Kansas Field Office Technical Guide Notice KS-230, Conservation Tree and Shrub Plantings Suitability Groups.

Ratings in the columns suitability for hand planting and suitability for mechanical planting are based on slope, depth to a restrictive layer, content of sand, plasticity index, rock fragments on or below the surface, depth to a water table, and ponding. The soils are described as well suited, moderately well suited, poorly suited, or unsited to these methods of planting. It is assumed that necessary site preparation is completed before seedlings are planted.

Ratings in the column suitability for mechanical site preparation (surface) are based on slope, depth to a restrictive layer, plasticity index, rock fragments on or below the surface, depth to a water table, and ponding. The soils are described as well suited, poorly suited, or unsited to this management activity. The part of the soil from the surface to a depth of about 1-foot is considered in the ratings.

Ratings in the column suitability for mechanical site preparation (deep) are based on slope, depth to a restrictive layer, rock fragments on or below the surface, depth to a water table, and ponding. The soils are described as well suited, poorly suited, or unsited to this management activity. The part of the soil from the surface to a depth of about 3 feet is considered in the ratings.

Ratings in the column potential for seedling mortality are based on flooding, ponding, depth to a water table, content of lime, reaction, salinity, available water capacity, soil moisture regime, soil temperature regime, aspect, and slope. The soils are described as having a low, moderate, or high potential for seedling mortality. See the National Forestry Manual, Subpart B for criteria used in rating management concerns. Specific information on plants and yields can be obtained from the local office of the Natural Resources Conservation Service or the Cooperative Extension Service.

CONSERVATION TREE AND SHRUB MANAGEMENT  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. Pines and spruces are prone to disease problems. See text for further explanation of ratings in this table.)

Map symbol and soil name	Wind break Group	Suitability for hand planting	Suitability for mechanical planting	Suitability for mechanical site preparation (surface)	Suitability for mechanical site preparation (deep)	Potential for seedling mortality
		Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features
003CD: Collinsville-----	10	Unsuited Restrictive layer	Moderately suited Rock fragments Restrictive layer Slope	Poorly suited Restrictive layer	Well suited	Low
Collinsville Taxadjunct-----	10	Well suited	Moderately suited Rock fragments Slope	Well suited	Well suited	Low
003DE: Dennis, eroded-----	4C	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	High Wetness
003EH: Eram, eroded-----	4C	Moderately suited Stickiness	Moderately suited Slope Stickiness	Well suited	Well suited	High Wetness
003EK: Eram-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	High Wetness
Clareson-----	6D	Poorly suited Rock fragments Stickiness	Unsuited Rock fragments Stickiness Slope	Poorly suited Rock fragments Stickiness	Unsuited Rock fragments Restrictive layer	Low
003LE: Leanna, drained-----	2	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	High Wetness
003LH: Lula-----	3	Well suited	Well suited	Well suited	Well suited	Low
003SE: Stony Land-----		Not rated	Not rated	Not rated	Not rated	Not rated
Talihina-----	10	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	High Wetness
003WF: Woodson-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	High Wetness
011CA: Catoosa-----	6D	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Poorly suited Restrictive layer	Low
059CM: Clareson-----	6D	Moderately suited Rock fragments Stickiness	Poorly suited Rock fragments Slope	Poorly suited Rock fragments	Poorly suited Rock fragments Restrictive layer	Low
Eram-----	4C	Poorly suited Stickiness	Stickiness Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	High Wetness
AED: Arents, Earthen Dam-		Not rated	Not rated	Not rated	Not rated	Not rated
Bb: Bates-----	6D	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Low
Bc: Bates-----	6D	Moderately suited Stickiness	Moderately suited Slope Stickiness	Well suited	Well suited	Low
Cb: Catoosa-----	6D	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Low

CONSERVATION TREE AND SHRUB MANAGEMENT  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. Pines and spruces are prone to disease problems. See text for further explanation of ratings in this table.)

Map symbol and soil name	Wind break Group	Suitability for hand planting	Suitability for mechanical planting	Suitability for mechanical site preparation (surface)	Suitability for mechanical site preparation (deep)	Potential for seedling mortality
		Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features
Cm: Clareson-----	6D	Moderately suited Stickiness  Rock fragments	Unsuited  Rock fragments Stickiness	Poorly suited  Rock fragments Stickiness	Poorly suited  Rock fragments Restrictive layer	Low
Rock Outcrop-----		Not rated	Slope Not rated	Not rated	Not rated	Not rated
De: Dennis-----	4C	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Low
Df: Dennis-----	4C	Moderately suited Stickiness	Moderately suited Slope Stickiness	Well suited	Well suited	Low
Ec: Eram-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Ed: Eram-----	4C	Moderately suited Stickiness	Moderately suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
Ef: Eram-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
Lebo-----	6D	Poorly suited Stickiness	Poorly suited Stickiness Slope Rock fragments	Poorly suited Stickiness	Well suited	Low
Hp: Hepler-----	1	Well suited	Well suited	Well suited	Well suited	Low
INT: Aquolls-----		Well suited	Well suited	Well suited	Well suited	High Wetness Soil reaction
Ke: Kenoma-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
La: Lanton-----	1	Well suited	Well suited	Well suited	Well suited	High Wetness
Lb: Lebo-----	6D	Poorly suited Stickiness	Poorly suited Slope  Stickiness Rock fragments	Poorly suited Slope  Stickiness	Poorly suited Rock fragments Slope	Low
M-W: Miscellaneous Water--		Not rated	Not rated	Not rated	Not rated	Not rated
Mb: Mason-----	1	Well suited	Well suited	Well suited	Well suited	Low
Nf: Newtonia-----	3	Well suited	Well suited	Well suited	Well suited	Low
Ng: Newtonia-----	3	Well suited	Well suited	Well suited	Well suited	Low
Nh: Newtonia-----	3	Well suited	Moderately suited Slope	Well suited	Well suited	Low
Oh: Okemah-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Om: Kanima-----	10	Poorly suited Stickiness	Unsuited Slope Stickiness Rock fragments	Poorly suited Slope Stickiness	Poorly suited Slope	Low
Op: Kanima-----	10	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low

CONSERVATION TREE AND SHRUB MANAGEMENT  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. Pines and spruces are prone to disease problems. See text for further explanation of ratings in this table.)

Map symbol and soil name	Wind break Group	Suitability for hand planting	Suitability for mechanical planting	Suitability for mechanical site preparation (surface)	Suitability for mechanical site preparation (deep)	Potential for seedling mortality
		Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features
			Rock fragments Slope			
Ot: Osage-----	2	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	High Wetness
Ov: Osage-----	2	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	High Wetness
Pc: Parsons-----	4C	Well suited	Well suited	Well suited	Well suited	High Wetness
Po: Pits, Quarries-----		Not rated	Not rated	Not rated	Not rated	Not rated
Sn: Summit-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
So: Summit-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
Vb: Verdigris-----	1	Well suited	Well suited	Well suited	Well suited	Low
Vc: Verdigris-----	1	Well suited	Well suited	Well suited	Well suited	Low
W: Water-----		Not rated	Not rated	Not rated	Not rated	Not rated
We: Welda-----	3	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Wo: Woodson-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	High Wetness



ENGINEERING INDEX PROPERTIES  
Linn County, Kansas

Engineering Index Properties table gives the engineering classifications and the range of index properties for the layers of each soil in the survey area. Depth to the upper and lower boundaries of each layer is indicated. Texture is given in the standard terms used by the U.S. Department of Agriculture. These terms are defined according to percentages of sand, silt, and clay in the fraction of the soil that is less than 2 millimeters in diameter. Loam, for example, is soil that is 7 to 27 percent clay, 28 to 50 percent silt, and less than 52 percent sand. If the content of particles coarser than sand is 15 percent or more, an appropriate modifier is added, for example, gravelly. Textural terms are defined in the Glossary.

Classification of the soils is determined according to the Unified soil classification system (ASTM, 1998) and the system adopted by the American Association of State Highway and Transportation Officials (AASHTO, 1998). The Unified system classifies soils according to properties that affect their use as construction material. Soils are classified according to particle-size distribution of the fraction less than 3 inches in diameter and according to plasticity index, liquid limit, and organic matter content. Sandy and gravelly soils are identified as GW, GP, GM, GC, SW, SP, SM, and SC; silty and clayey soils as ML, CL, OL, MH, CH, and OH; and highly organic soils as PT. Soils exhibiting engineering properties of two groups can have a dual classification, for example, CL-ML.

The AASHTO system classifies soils according to those properties that affect roadway construction and maintenance. In this system, the fraction of a mineral soil that is less than 3 inches in diameter is classified in one of seven groups from A-1 through A-7 on the basis of particle-size distribution, liquid limit, and plasticity index. Soils in group A-1 are coarse grained and low in content of fines (silt and clay). At the other extreme, soils in group A-7 are fine grained. Highly organic soils are classified in group A-8 on the basis of visual inspection. If laboratory data are available, the A-1, A-2, and A-7 groups are further classified as A-1-a, A-1-b, A-2-4, A-2-5, A-2-6, A-2-7, A-7-5, or A-7-6. As an additional refinement, the suitability of a soil as subgrade material can be indicated by a group index number. Group index numbers range from 0 for the best subgrade material to 20 or higher for the poorest. The AASHTO classification for soils tested, with group index numbers in parentheses, is given in Engineering Index Properties table.

Rock fragments larger than 10 inches in diameter and 3 to 10 inches in diameter are indicated as a percentage of the total soil on a dry-weight basis. The percentages are estimates determined mainly by converting volume percentage in the field to weight percentage. Percentage (of soil particles) passing designated sieves is the percentage of the soil fraction less than 3 inches in diameter based on an oven-dry weight. The sieves, numbers 4, 10, 40, and 200 (USA Standard Series), have openings of 4.76, 2.00, 0.420, and 0.074 millimeters, respectively. Estimates are based on laboratory tests of soils sampled in the survey area and in nearby areas and on estimates made in the field.

Liquid limit and plasticity index (Atterberg limits) indicate the plasticity characteristics of a soil. The estimates are based on test data from the survey area or from nearby areas and on field examination. The estimates of particle-size distribution, liquid limit, and plasticity index are generally rounded to the nearest 5 percent. Thus, if the ranges of gradation and Atterberg limits extend a marginal amount (1 or 2 percentage points) across classification boundaries, the classification in the marginal zone is generally omitted in the table.

ENGINEERING INDEX PROPERTIES--Continued  
Linn County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
	In				Pct	Pct					Pct	
003CD: Collinsville---	0-6	Loam	CL, CL-ML, ML	A-6, A-4	---	0-15	85-100	80-100	70-95	50-85	18-33	2-11
	6-11	Channery loam	SM, SC-SM, SC, CL-ML, ML, CL	A-1, A-2-4, A-2-6, A-1- b, A-6, A-4, A-2	---	0-45	55-100	55-100	50-95	20-85	15-33	NP-11
	11-15	Unweathered bedrock			---	---	---	---	---	---	---	---
Collinsville Taxadjunct----	0-6	Loam	ML, CL, CL-ML	A-4, A-6	---	0-15	85-100	80-100	70-95	50-85	18-33	2-11
	6-23	Channery loam	ML, CL, SM, SC-SM, SC, CL-ML	A-1-b, A-2, A-2-6, A-4, A-6, A-1, A- 2-4	---	0-45	55-100	55-100	50-95	20-85	15-33	NP-11
	23-27	Unweathered bedrock			---	---	---	---	---	---	---	---
003DE: Dennis, eroded-	0-10	Silty clay loam	CL-ML, ML, CL	A-4, A-6	0	0	100	100	96-100	65-97	21-40	4-25
	10-21	Silty clay loam	ML, CL	A-6, A-7-6, A-7-5, A-7	0	0	98-100	98-100	94-100	75-98	36-50	15-30
	21-47	Silty clay	CL, MH, CH, ML	A-7, A-7-5, A-7-6	0	0	98-100	98-100	94-100	75-98	43-61	21-35
	47-60	Silty clay	CH, ML, MH, CL	A-7-6, A-7-5, A-7	0	0	98-100	98-100	94-100	75-98	43-61	21-35
003EH: Eram, eroded---	0-15	Silty clay loam	CL, ML	A-6, A-7, A- 7-5, A-7-6	0	0	85-100	85-100	85-100	70-95	36-48	15-25
	15-33	Silty clay loam	CL, MH, ML, CH	A-7, A-7-6, A-7-5	0	0	95-100	95-100	90-100	75-98	43-61	21-35
	33-37				---	---	---	---	---	---	---	---
003EK: Eram-----	0-9	Silty clay loam	CL, MH, ML, CH	A-6, A-7, A- 7-6, A-7-5	0	0	85-100	85-100	85-100	70-95	36-55	15-30
	9-33	Silty clay loam	CL, MH, ML, CH	A-7-5, A-7, A-7-6	0	0	95-100	95-100	90-100	80-98	43-61	21-35
Clareson-----	33-37				---	---	---	---	---	---	---	---
	0-7	Flaggy silty clay loam	CH, CL, MH	A-7, A-7-5, A-7-6	---	25-65	90-100	90-100	85-95	85-95	43-56	22-33
	7-16	Very flaggy silty clay	MH, CH	A-7-6, A-7, A-7-5	---	50-85	85-100	85-100	80-95	80-95	51-70	28-41
	16-24	Extremely flaggy silty clay	CH, MH	A-7-5, A-7-6, A-7	---	50-85	85-100	70-100	65-95	60-95	51-85	28-55
003LE: Leanna, drained	24-32	Unweathered bedrock			---	---	---	---	---	---	---	---
	0-17	Silt loam	CL, ML, CL-ML	A-4, A-7-6, A-7-5, A-7, A-6, A-5	0	0	100	100	95-100	85-100	25-47	7-25
	17-37	Silty clay	MH, CL, CH, ML	A-7, A-7-5, A-7-6	0	0	100	100	95-100	90-100	43-57	21-32
003LH: Lula-----	37-64	Silty clay	CH, ML, CL	A-7-6, A-7-5, A-7, A-6	0	0	100	100	88-100	85-100	36-58	15-38
	0-13	Silt loam	CL-ML, CL, ML	A-6, A-4	0	0	100	100	96-100	65-97	25-36	7-15
	13-29	Silty clay loam	CL	A-4, A-6, A-7	0	0	100	100	96-100	65-98	28-43	8-21
	29-49	Silty clay loam	CL	A-6, A-7	0	0-30	85-100	85-100	80-100	70-98	36-43	15-21
003SE: Stony Land Talihina-----	49-53	Unweathered bedrock			---	---	---	---	---	---	---	---
	---	---	---	---	---	---	---	---	---	---	---	---
	0-7	Silty clay loam	ML, MH, CH, CL	A-7, A-7-5, A-7-6	---	0-15	87-100	87-100	85-100	70-98	43-60	21-35
	7-12	Silty clay loam	CH, CL, MH, ML	A-7-5, A-7-6, A-7	---	0-15	87-100	87-100	85-100	70-98	43-60	21-35
	12-15	Silty clay loam	ML, MH, CL, CH	A-7-6, A-7, A-7-5	---	0-15	87-100	87-100	85-100	70-98	43-60	21-35
003WF: Woodson-----	15-19	Weathered bedrock			---	---	---	---	---	---	---	---
	0-8	Silt loam	CL, ML, CL-ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	5-20
	8-29	Silty clay	MH, CH	A-7-6, A-7-5, A-7	0	0	100	95-100	95-100	90-100	50-65	30-45
011CA: Catoosa-----	29-64	Silty clay	CH, ML, MH, CL	A-7-6, A-7-5, A-7	0	0	100	95-100	95-100	90-100	45-65	20-40
	0-11	Silt loam	ML, CL	A-4, A-6	0	0	100	100	96-100	90-100	30-60	8-20
	11-16	Silty clay loam	CH, ML, MH, CL	A-7-6, A-7, A-6, A-7-5	0	0	85-100	85-100	85-100	90-100	33-65	12-30
	16-27	Silty clay loam	CH, MH, ML, CL	A-7, A-6, A- 7-6, A-7-5	0	0	75-100	70-100	70-100	60-100	36-65	16-35
	27-35	Unweathered bedrock			---	---	---	---	---	---	---	---

ENGINEERING INDEX PROPERTIES--Continued  
Linn County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
	In				Pct	Pct					Pct	
059CM: Clareson-----	0-7	Silty clay loam	ML, CH, CL, MH	A-4, A-7-6, A-7-5, A-7, A-6, A-5	---	0-25	90-100	85-100	85-95	85-95	30-55	8-28
	7-15	Silty clay loam	CH, CL, MH, ML	A-6, A-7-6, A-7-5, A-7	---	0-65	90-100	85-100	85-95	85-95	35-55	11-30
	15-26	Flaggy silty clay loam	CH, ML, CL, MH	A-7-6, A-7-5, A-7	---	20-85	85-100	85-100	80-95	80-95	41-60	18-35
	26-34	Unweathered bedrock			---	---	---	---	---	---	---	---
Eram-----	0-7	Silty clay loam	CH, CL, MH, ML	A-6, A-7, A- 7-5, A-7-6	0	0	85-100	85-100	85-100	70-95	36-60	15-30
	7-38	Silty clay	CL, ML, CH, MH	A-7, A-7-5, A-7-6	0	0	95-100	95-100	90-100	80-98	43-70	21-40
	38-46	Weathered bedrock			---	---	---	---	---	---	---	---
AED: Arents, Earthen Dam-----	---	---	---	---	---	---	---	---	---	---	---	---
Bb: Bates-----	0-10	Loam	CL, CL-ML, ML	A-4, A-6	0	0	90-100	85-100	80-100	55-90	20-40	3-15
	10-21	Clay loam	ML, SC, SM, CL, SC-SM, CL-ML	A-4, A-6, A- 7-6, A-7-5, A-7, A-5	0	0	85-100	85-100	80-100	45-85	25-45	3-25
	21-31	Gravelly clay loam	SC, SM, SC- SM, ML, CL- ML, CL	A-4, A-7-6, A-7-5, A-7, A-6, A-5	---	0-15	80-100	80-100	75-100	40-80	20-45	5-30
	31-35				---	---	---	---	---	---	---	---
Bc: Bates-----	0-7	Loam	CL, CL-ML, ML	A-6, A-4	0	0	90-100	85-100	80-100	55-90	20-40	3-15
	7-18	Clay loam	CL, ML, SM, SC	A-5, A-7, A- 7-5, A-7-6, A-4, A-6	0	0	85-100	85-100	80-100	45-85	25-45	8-25
	18-31	Gravelly clay loam	ML, CL, SM, SC	A-6, A-7, A- 7-5, A-5, A- 4, A-7-6	0	0-15	80-100	80-100	75-100	40-80	20-45	8-30
	31-35				---	---	---	---	---	---	---	---
Cb: Catoosa-----	0-12	Silt loam	ML, CL	A-6, A-5, A- 7, A-7-5, A- 7-6, A-4	0	0	100	100	96-100	65-97	30-45	8-20
	12-25	Silty clay loam	CH, CL, MH, ML	A-7, A-7-5, A-7-6, A-6	0	0	85-100	85-100	85-100	70-98	33-55	12-30
	25-29	Silty clay	ML, MH, CL, CH	A-7, A-6, A- 7-5, A-7-6	0	0	85-100	85-100	85-100	70-98	33-70	12-45
	29-33	Unweathered bedrock			---	---	---	---	---	---	---	---
Cm: Clareson-----	0-11	Silty clay loam	ML, MH, CL, CH	A-4, A-7-5, A-7-6, A-5, A-6, A-7	---	0-25	90-100	90-100	85-100	85-100	30-60	8-35
	11-16	Flaggy silty clay loam	ML, MH, CL, CH	A-7, A-7-5, A-7-6, A-6	---	0-65	75-100	70-95	65-95	65-95	35-60	11-35
	16-33	Very flaggy silty clay	CH, ML, MH, CL	A-7, A-7-5, A-7-6	---	50-85	70-85	60-80	55-75	55-75	41-85	18-55
	33-37	Unweathered bedrock			---	---	---	---	---	---	---	---
Rock Outcrop--- De: Dennis-----	---	---	---	---	---	---	---	---	---	---	---	---
	0-11	Silt loam	CL, CL-ML, ML	A-6, A-4	0	0	100	100	96-100	65-97	20-37	1-15
	11-17	Silty clay loam	ML, CL	A-6, A-7-6, A-7-5, A-7	0	0	98-100	98-100	94-100	75-98	33-48	13-25
	17-25	Silty clay	MH, CL, CH, ML	A-6, A-7-6, A-7-5, A-7	0	0	98-100	98-100	94-100	75-98	37-65	15-40
	25-60	Silty clay	CH, MH, CL, ML	A-6, A-7-6, A-7-5, A-7	0	0	98-100	98-100	94-100	75-98	37-65	15-35
Df: Dennis-----	0-10	Silt loam	CL, CL-ML, ML	A-4, A-6	0	0	100	100	96-100	65-97	20-37	1-15
	10-16	Silty clay loam	ML, CL	A-7-5, A-7-6, A-6, A-7	0	0	98-100	98-100	94-100	75-98	33-48	13-25
	16-24	Silty clay	CL, ML, CH, MH	A-7-5, A-7, A-6, A-7-6	0	0	98-100	98-100	94-100	75-98	37-65	15-40
	24-60	Silty clay	CL, MH, ML, CH	A-6, A-7-6, A-7-5, A-7	0	0	98-100	98-100	94-100	75-98	37-65	15-35
Ec: Eram-----	0-10	Silty clay loam	CH, CL, MH, ML	A-7, A-7-5, A-7-6, A-6	0	0	85-100	85-100	85-100	70-95	33-55	12-30
	10-27	Silty clay	CH, ML, MH, CL	A-6, A-7-6, A-7-5, A-7	0	0	95-100	95-100	90-100	80-98	37-65	15-40
	27-31				---	---	---	---	---	---	---	---
Ed: Eram-----	0-9	Silty clay loam	CL, CH, MH, ML	A-7-5, A-7-6, A-6, A-7	0	0	85-100	85-100	85-100	70-95	33-55	12-30
	9-27	Silty clay	CL, CH, MH, ML	A-7, A-7-5, A-7-6, A-6	0	0	95-100	95-100	90-100	80-98	37-65	15-35
	27-31				---	---	---	---	---	---	---	---

ENGINEERING INDEX PROPERTIES--Continued  
Linn County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
	In				Pct	Pct					Pct	
Ef: Eram-----	0-8	Silty clay loam	MH, CL, CH, ML	A-6, A-7-6, A-7, A-7-5	0	0	85-100	85-100	85-100	70-95	33-55	12-35
	8-27	Silty clay	CL, ML, CH, MH	A-7-5, A-7-6, A-6, A-7	0	0	95-100	95-100	90-100	80-98	37-65	15-40
	27-31	Weathered bedrock			---	---	---	---	---	---	---	---
Lebo-----	0-12	Silty clay	CL, CH, MH, ML	A-7-6, A-6, A-7-5, A-7	---	0-5	90-100	80-100	80-100	75-95	35-60	15-35
	12-28	Silty clay	CH, ML, MH, CL	A-7-6, A-7, A-6, A-7-5	---	0-5	90-100	80-100	80-100	75-98	35-55	15-35
	28-38	Extremely channery silty clay loam	CL, ML	A-6, A-7, A- 7-5, A-7-6	---	0-5	90-100	80-100	80-100	75-95	35-50	15-25
	38-42	Weathered bedrock			---	---	---	---	---	---	---	---
Hp: Hepler-----	0-9	Silt loam	CL, CL-ML, ML	A-4, A-6	0	0	100	100	90-100	75-99	20-35	2-15
	9-25	Silt loam	CL, ML	A-6, A-7-6, A-7, A-7-5	0	0	100	100	95-100	85-99	30-50	15-25
	25-40	Silty clay loam	CL, ML	A-7-6, A-7-5, A-7, A-6	0	0	100	100	95-100	85-99	35-50	15-30
	40-60	Silty clay loam	CL, ML	A-7-5, A-7, A-7-6, A-6	0	0	100	100	95-100	85-99	35-50	15-30
INT: Aquolls-----	0-72	Variable			---	---	---	---	---	---	---	---
Ke: Kenoma-----	0-10	Silt loam	CL-ML, CL, ML	A-4, A-6	0	0	85-100	85-100	85-100	85-100	25-40	3-18
	10-22	Silty clay	CH, CL, MH	A-7-6, A-7, A-7-5	0	0	85-100	85-100	85-100	85-100	50-75	30-48
	22-44	Silty clay	MH, CL, CH	A-7, A-7-5, A-7-6	0	0	85-100	85-100	75-100	75-95	45-65	25-44
	44-60	Silty clay	CL, MH, CH	A-7-5, A-7, A-7-6	0	0	85-100	85-100	75-100	75-95	45-65	25-44
La: Lanton-----	0-14	Silt loam	ML, CL	A-4, A-6	0	0	100	100	96-100	80-97	30-37	8-13
	14-38	Silt loam	ML, CL	A-7-5, A-6, A-7, A-7-6	0	0	100	100	98-100	90-98	33-42	12-19
	38-53	Silt loam, silty clay loam	CL, MH, ML, CH	A-7, A-7-5, A-7-6, A-6	0	0	100	100	98-100	90-98	33-55	12-30
	53-60	Silty clay loam	CL, MH, ML, CH	A-6, A-7-6, A-7-5, A-7	0	0	100	100	98-100	90-98	33-55	12-30
Lb: Lebo-----	0-11	Gravelly silty clay loam	MH, ML, CL, CH	A-6, A-7-6, A-7-5, A-7	---	0-5	65-100	65-100	65-100	65-95	35-60	15-35
	11-27	Channery silty clay loam	ML, MH, CH, CL	A-6, A-7-6, A-7-5, A-7	---	0-5	65-100	65-100	65-100	65-98	35-55	15-35
	27-38	Extremely channery silty clay loam	ML, CL	A-7, A-7-6, A-7-5, A-6	---	0-5	65-100	65-100	65-100	65-98	35-50	15-25
	38-42				---	---	---	---	---	---	---	---
M-W: Miscellaneous Water-----	---	---	---	---	---	---	---	---	---	---	---	---
Mb: Mason-----	0-18	Silt loam	CL, ML	A-5, A-6, A- 7, A-7-5, A- 7-6, A-4	0	0	100	100	96-100	65-98	30-45	8-20
	18-50	Silty clay loam	CL, ML	A-7, A-5, A- 6, A-7-6, A- 4, A-7-5	0	0	98-100	98-100	96-100	65-98	30-50	9-30
	50-60	Silty clay loam	CL, ML	A-6, A-4, A- 7-6, A-7-5, A-7, A-5	0	0	98-100	98-100	96-100	65-98	30-50	9-30
Nf: Newtonia-----	0-13	Silt loam	ML, CL	A-4, A-6	0	0	100	100	95-100	65-97	30-37	9-14
	13-26	Silty clay loam	ML, CL	A-4, A-6	0	0	100	100	95-100	80-98	30-40	9-20
	26-49	Silty clay loam	ML, CL	A-6, A-7-6, A-7-5, A-7	0	0	100	100	95-100	80-98	33-42	12-25
	49-60	Silty clay loam	MH, ML, CH, CL	A-6, A-7-6, A-7-5, A-7	0	0	100	100	95-100	80-98	37-60	15-30
Ng: Newtonia-----	0-13	Silt loam	ML, CL	A-6, A-4	0	0	100	100	95-100	80-97	30-37	9-14
	13-26	Silty clay loam	CL, ML	A-4, A-6	0	0	100	100	95-100	80-98	30-40	9-20
	26-49	Silty clay loam	ML, CL	A-6, A-7-6, A-7-5, A-7	0	0	100	100	95-100	80-98	33-42	12-25
	49-60	Silty clay loam	MH, ML, CH, CL	A-7-6, A-7-5, A-7, A-6	0	0	100	100	95-100	80-98	37-60	15-34
Nh: Newtonia-----	0-11	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	80-97	30-37	9-15
	11-24	Silty clay loam	ML, CL	A-4, A-7-6, A-7-5, A-7, A-6, A-5	0	0	100	100	90-100	80-98	30-45	9-20
	24-47	Silty clay loam	ML, MH, CH, CL	A-6, A-7-6, A-7-5, A-7	0	0	100	100	90-100	80-98	33-55	12-30
	47-60	Silty clay loam	ML, MH, CL, CH	A-6, A-7-6, A-7-5, A-7	0	0	100	100	90-100	80-98	37-60	15-34

ENGINEERING INDEX PROPERTIES--Continued  
Linn County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
	In				Pct	Pct					Pct	
Oh: Okemah-----	0-12	Silt loam	ML, CL	A-4, A-7-6, A-7-5, A-7, A-6, A-5	0	0	98-100	98-100	90-100	80-98	30-45	8-25
	12-18	Silty clay loam	CH, ML, MH, CL	A-7-6, A-7-5, A-7	0	0	98-100	98-100	96-100	90-99	41-60	18-34
	18-24	Silty clay	CL, CH, ML, MH	A-7-6, A-7-5, A-7	0	0	98-100	98-100	96-100	90-99	41-70	18-40
	24-60	Silty clay	CH, ML, MH, CL	A-7-6, A-7-5, A-7	0	0	98-100	98-100	96-100	90-99	41-70	18-40
Om: Kanima-----	0-6	Channery silty clay loam	SC, CL, SM, ML, CH, MH	A-7-6, A-6, A-7, A-7-5	---	0-10	50-90	50-95	50-90	40-85	33-55	12-37
	6-60	Very channery silty clay loam	SC, ML, CL, SM, MH, CH	A-2-4, A-2-5, A-2-6, A-2- 7, A-5, A-2, A-7-6, A-6, A-4, A-7-5, A-7	---	0-10	50-80	45-80	40-80	35-75	30-55	8-35
Op: Kanima-----	0-6	Channery silty clay loam	MH, CL, SC, ML, CH, SM	A-7-6, A-7-5, A-7, A-6	---	0-10	50-90	50-90	50-85	40-85	33-55	12-37
	6-60	Very channery silty clay loam	MH, CH, SM, CL, ML, SC	A-4, A-6, A- 7-6, A-7-5, A-7, A-5, A- 2-7, A-2-6, A-2-5, A-2- 4, A-2	---	0-10	50-85	45-80	40-80	35-75	30-55	8-35
Ot: Osage-----	0-15	Silty clay loam	CH, CL, MH, ML	A-7, A-7-6, A-7-5, A-6	0	0	100	100	98-100	93-100	40-65	20-38
	15-44	Silty clay	CH, ML, MH, CL	A-7-6, A-7-5, A-7, A-6	0	0	100	100	100	95-100	40-80	20-50
	44-60	Silty clay	CH, CL, MH, ML	A-7-6, A-7-5, A-7, A-6	0	0	100	100	100	95-100	40-80	20-50
Ov: Osage-----	0-8	Silty clay	CH, CL, MH, ML	A-7-6, A-7-5, A-7, A-6	0	0	100	100	100	95-100	40-65	20-45
	8-23	Silty clay	CH, ML, MH, CL	A-7-6, A-7-5, A-7, A-6	0	0	100	100	100	95-100	40-80	20-50
	23-44	Silty clay	MH, ML, CH, CL	A-7-6, A-7-5, A-7, A-6	0	0	100	100	100	95-100	40-80	20-50
	44-60	Silty clay	CH, ML, MH, CL	A-7-6, A-7-5, A-7, A-6	0	0	100	100	100	95-100	40-80	20-50
Pc: Parsons-----	0-9	Silt loam	CL-ML, ML, CL	A-6, A-4	0	0	100	96-100	96-100	80-97	20-37	1-12
	9-13	Silt loam	ML, CL-ML, CL	A-4, A-6	0	0	100	96-100	96-100	80-97	20-37	1-12
	13-60	Silty clay	MH, CL, CH, ML	A-7, A-7-5, A-7-6, A-6	0	0	100	96-100	96-100	80-99	37-70	15-40
Po: Pits, Quarries- Sn: Summit-----	0-60	Variable			---	---	---	---	---	---	---	---
	0-11	Silty clay loam	CH, ML, MH, CL	A-7-6, A-6, A-7-5, A-7	0	0	90-100	85-100	80-100	70-99	35-60	11-30
	11-24	Silty clay	CH, ML, MH, CL	A-7-6, A-7-5, A-7	0	0	85-100	75-100	70-100	55-98	41-70	18-40
	24-33	Silty clay	CL, ML, CH, MH	A-7-6, A-7, A-7-5	0	0	85-100	75-100	70-100	55-98	41-70	18-40
	33-60	Silty clay	MH, CL, CH, ML	A-7-6, A-7-5, A-7	0	0	85-100	75-100	70-100	55-98	41-70	18-40
So: Summit-----	0-9	Silty clay loam	MH, CL, CH, ML	A-6, A-7-6, A-7-5, A-7	0	0	90-100	85-100	80-100	70-99	35-60	11-30
	9-22	Silty clay	CH, ML, MH, CL	A-7, A-7-6, A-7-5	0	0	85-100	75-100	70-100	55-98	41-70	18-40
	22-31	Silty clay	CH, ML, MH, CL	A-7-6, A-7, A-7-5	0	0	85-100	75-100	70-100	55-98	41-70	18-40
	31-60	Silty clay	ML, CL, MH, CH	A-7, A-7-5, A-7-6	0	0	85-100	75-100	70-100	55-98	41-70	18-40
Vb: Verdigris-----	0-9	Silt loam	CL-ML, ML, CL	A-6, A-4	0	0	100	100	95-100	65-100	22-38	2-17
	9-32	Silt loam	CL, ML, CL-ML	A-4, A-6	0	0	100	100	95-100	65-100	22-38	2-17
	32-52	Silt loam	CL, ML	A-5, A-4, A- 7-6, A-7-5, A-7, A-6	0	0	100	100	95-100	80-100	30-45	8-23
	52-60	Silt loam	CL, ML	A-7, A-4, A- 6, A-7-6, A- 7-5, A-5	0	0	100	100	95-100	80-100	30-45	8-23
Vc: Verdigris-----	0-9	Silt loam	ML, CL-ML, CL	A-6, A-4	0	0	100	100	95-100	65-100	22-37	2-17
	9-32	Silt loam	ML, CL-ML, CL	A-6, A-4	0	0	100	100	95-100	65-100	22-37	2-17
	32-52	Silt loam	ML, CL	A-4, A-6, A- 7-6, A-7-5, A-7, A-5	0	0	100	100	95-100	80-100	30-45	8-23
	52-60	Silt loam	ML, CL	A-4, A-6, A- 7-6, A-7-5, A-7, A-5	0	0	100	100	95-100	80-100	30-45	8-23

ENGINEERING INDEX PROPERTIES--Continued  
Linn County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
					Pct	Pct					Pct	
W: Water-----	In											
We: Welda-----	---	---	---	---	---	---	---	---	---	---	---	---
	0-7	Silt loam	CL-ML, ML, CL	A-4, A-6	0	0	100	100	90-100	75-100	25-40	5-20
	7-10	Silty clay loam	ML, MH, CL, CH	A-6, A-7, A-7-5, A-7-6	0	0	100	100	90-100	80-100	38-55	20-35
	10-35	Silty clay	MH, ML, CL, CH	A-6, A-7-6, A-7-5, A-7	0	0	100	100	95-100	85-100	38-60	20-38
	35-60	Clay loam	CL, ML, CL-ML	A-4, A-6, A-7-6, A-7-5, A-5, A-7	0	0	100	100	85-100	70-100	30-50	7-30
Wo: Woodson-----	0-7	Silt loam	CL-ML, ML, CL	A-6, A-4	0	0	100	100	90-100	85-100	25-40	5-20
	7-30	Silty clay	CH, CL, MH	A-7-6, A-7-5, A-7	0	0	100	95-100	95-100	90-100	50-68	30-45
	30-40	Silty clay	CH, ML, MH, CL	A-7-5, A-7-6, A-7	0	0	100	95-100	95-100	90-100	45-65	20-40
	40-60	Silty clay	CL, MH, ML, CH	A-7-5, A-7, A-7-6	0	0	100	95-100	95-100	90-100	45-65	20-40

Physical Properties table shows estimates of some physical characteristics and features that affect soil behavior. These estimates are given for the layers of each soil in the survey area. The estimates are based on field observations and on test data for these and similar soils.

Depth to the upper and lower boundaries of each layer is indicated.

Particle size is the effective diameter of a soil particle as measured by sedimentation, sieving, or micrometric methods. Particle sizes are expressed as classes with specific effective diameter class limits. The broad classes are sand, silt, and clay, ranging from the larger to the smaller.

Sand as a soil separate consists of mineral soil particles that are 0.05 millimeter to 2 millimeters in diameter. In this table, the estimated sand content of each soil layer is given as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter.

Silt as a soil separate consists of mineral soil particles that are 0.002 to 0.05 millimeter in diameter. In this table, the estimated silt content of each soil layer is given as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter.

Clay as a soil separate consists of mineral soil particles that are less than 0.002 millimeter in diameter. In this table, the estimated clay content of each soil layer is given as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter.

The content of sand, silt, and clay affects the physical behavior of a soil. Particle size is important for engineering and agronomic interpretations, for determination of soil hydrologic qualities, and for soil classification.

The amount and kind of clay affect the fertility and physical condition of the soil and the ability of the soil to adsorb cations and to retain moisture. They influence shrink-swell potential, permeability, plasticity, the ease of soil dispersion, and other soil properties. The amount and kind of clay in a soil also affect tillage and earth moving operations.

Moist bulk density is the weight of soil (oven-dry) per unit volume. Volume is measured when the soil is at field moisture capacity, that is, the moisture content at 1/3- or 1/10-bar (33kPa or 10kPa) moisture tension. Weight is determined after the soil is dried at 105 degrees C. In the table, the estimated moist bulk density of each soil horizon is expressed in grams per cubic centimeter of soil material that is less than 2 millimeters in diameter. Bulk density data are used to compute shrink-swell potential, available water capacity, total pore space, and other soil properties. The moist bulk density of a soil indicates the pore space available for water and roots. Depending on soil texture, a bulk density of more than 1.4 can restrict water storage and root penetration. Moist bulk density is influenced by texture, kind of clay, content of organic matter, and soil structure.

Permeability ( $K \rightarrow \text{sat}$ ) refers to the ability of a soil to transmit water or air. The term "permeability," as used in soil surveys, indicates saturated hydraulic conductivity ( $K \rightarrow \text{sat}$ ). The estimates in the table indicate the rate of water movement, in inches per hour, when the soil is saturated. They are based on soil characteristics observed in the field, particularly structure, porosity, and texture. Permeability is considered in the design of soil drainage systems and septic tank absorption fields.

Available water capacity refers to the quantity of water that the soil is capable of storing for use by plants. The capacity for water storage is given in inches of water per inch of soil for each soil layer. The capacity varies, depending on soil properties that affect retention of water. The most important properties are the content of organic matter, soil texture, bulk density, and soil structure. Available water capacity is an important factor in the choice of plants or crops to be grown and in the design and management of irrigation systems. Available water capacity is not an estimate of the quantity of water actually available to plants at any given time.

Linear extensibility refers to the change in length of an unconfined clod as moisture content is decreased from a moist to a dry state. It is an expression of the volume change between the water content of the clod at 1/3- or 1/10-bar tension (33kPa or 10kPa tension) and oven dryness. The volume change is reported in the table as percent change for the whole soil. Volume change is influenced by the amount and type of clay minerals in the soil.

Linear extensibility is used to determine the shrink-swell potential of soils. The shrink-swell potential is low if the soil has a linear extensibility of less than 3 percent; moderate if 3 to 6 percent; high if 6 to 9 percent; and very high if more than 9 percent. If the linear extensibility is more than 3, shrinking and swelling can cause damage to buildings, roads, and other structures and to plant roots. Special design commonly is needed.

Organic matter is the plant and animal residue in the soil at various stages of decomposition. In Physical Properties table, the estimated content of organic matter is expressed as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter. The content of organic matter in a soil can be maintained by returning crop residue to the soil. Organic matter has a positive effect on available water capacity, water infiltration, soil organism activity, and tilth. It is a source of nitrogen and other nutrients for crops and soil organisms.

Erosion factors are shown in the Physical Properties table as the K factor ( $K_w$  and  $K_f$ ) and the T factor. Erosion factor K indicates the susceptibility of a soil to sheet and rill erosion by water. Factor K is one of six factors used in the Universal Soil Loss Equation (USLE) and the Revised Universal Soil Loss Equation (RUSLE) to predict the average annual rate of soil loss by sheet and rill erosion in tons per acre per year. The estimates are based primarily on percentage of silt, sand, and organic matter and on soil structure and permeability. Values of K range from 0.02 to 0.69. Other factors being equal, the higher the value, the more susceptible the soil is to sheet and rill erosion by water.

Erosion factor  $K_w$  indicates the erodibility of the whole soil. The estimates are modified by the presence of rock fragments.

Erosion factor  $K_f$  indicates the erodibility of the fine-earth fraction, or the material less than 2 millimeters in size.

Erosion factor T is an estimate of the maximum average annual rate of soil erosion by wind or water that can occur without affecting crop productivity over a sustained period. The rate is in tons per acre per year.

Wind erodibility groups are made up of soils that have similar properties affecting their susceptibility to

wind erosion in cultivated areas. The soils assigned to group 1 are the most susceptible to wind erosion, and those assigned to group 8 are the least susceptible. The groups are as follows:

1. Coarse sands, sands, fine sands, and very fine sands.
2. Loamy coarse sands, loamy sands, loamy fine sands, loamy very fine sands, ash material, and sapric soil material.
3. Coarse sandy loams, sandy loams, fine sandy loams, and very fine sandy loams.
- 4L. Calcareous loams, silt loams, clay loams, and silty clay loams.
4. Clays, silty clays, noncalcareous clay loams, and silty clay loams that are more than 35 percent clay.
5. Noncalcareous loams and silt loams that are less than 20 percent clay and sandy clay loams, sandy clays, and hemic soil material.
6. Noncalcareous loams and silt loams that are more than 20 percent clay and noncalcareous clay loams that are less than 35 percent clay.
7. Silts, noncalcareous silty clay loams that are less than 35 percent clay, and fibric soil material.
8. Soils that are not subject to wind erosion because of coarse fragments on the surface or because of surface wetness.

Wind erodibility index is a numerical value indicating the susceptibility of soil to wind erosion, or the tons per acre per year that can be expected to be lost to wind erosion. There is a close correlation between wind erosion and the texture of the surface layer, the size and durability of surface clods, rock fragments, organic matter, and a calcareous reaction. Soil moisture and frozen soil layers also influence wind erosion.

#### Explanation of Wind Erodibility Groups

Soil erodibility by wind is directly related to the percentage of dry non-erodible surface soil aggregates larger than 0.84 mm in diameter. From this percentage, the wind erodibility index (I-factor) is determined. The I-factor is an expression of the stability of these soil aggregates against breakdown by tillage and abrasion from wind erosion. Soils are placed in Wind Erodibility Groups (WEG) having similar percentages of dry soil aggregates larger than 0.84 mm as shown in the following table.

WEG	Properties of Soil Surface Layer	Dry Soil Aggregates >0.84mm Percent	Wind Erodibility Index T/Ac/Yr (I)
1	Very fine sand, fine sand, sand, or coarse sand	1 2 3 5 7	310 1/ 250 220 180 160
2	Loamy very fine sand, loamy fine sand, loamy sand, loamy coarse sand, organic soil materials.	10	134
3	Very fine sandy loam, fine sandy loam, sandy loam, or coarse sandy loam.	25	86
4	Clay, silty clay, non-calcareous clay loam, or silty clay loam with >35 percent clay content.	25	86
4L	Calcareous 2/ loam, silt loam, clay loam, or silty clay loam.	25	86
5	Non-calcareous loam and silt loam with <20 percent clay content, or sandy clay loam, sandy clay, and hemic 3/ organic soil materials.	40	56
6	Non-calcareous loam and silt loam with >20 percent clay content, or non-calcareous clay loam with <35 percent clay content.	45	48
7	Silt, non-calcareous silty clay loam with >35 percent clay content and fibric 3/ organic soil material.	50	38
8	Soils not suitable for cultivation due to coarse fragments or wetness; wind erosion is not a problem.	--	0

1/ The "I" values for WEG 1 vary from 160 for coarse sands to 310 for very fine sands. Use an "I" of 220 as an average figure. For coarser sand that has gravel, use a lower figure. For a soil that has no gravel and very fine sand, use a higher figure. (Modification for coarse fragments is preparation.)

2/ Calcareous is a strongly or violently effervescent reaction to cold dilute (1N) HCL.

3/ See Soil Taxonomy for definition.



PHYSICAL PROPERTIES OF THE SOILS--Continued  
Linn County, Kansas: Published

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permeability (Ksat)	Available water capacity	Linear extensibility	Organic matter	Erosion factors			Wind erodibility group	Wind erodibility index
										K	Kf	T		
	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
003CD:														
Collinsville-	0-6	30-52	28-50	7-20	1.30-1.55	2.00-6.00	0.09-0.15	0.0-2.9	1.0-3.0	.32	.32	1	5	56
	6-11	30-70	10-50	5-20	1.40-1.70	2.00-6.00	0.07-0.20	0.0-2.9	0.5-2.0	.20	.20			
	11-15													
Collinsville	0-6	30-52	28-50	7-20	1.30-1.55	2.00-6.00	0.09-0.15	0.0-2.9	1.0-3.0	.32	.32	1	5	56
Taxadjunct--														
	6-23	30-70	10-50	5-20	1.40-1.70	2.00-6.00	0.07-0.20	0.0-2.9	0.5-2.0	.20	.20			
	23-27													
003DE:														
Dennis,	0-10	10-30	50-70	10-35	1.25-1.50	0.20-0.60	0.15-0.20	1.5-4.5	0.5-2.0	.43	.43	5	6	48
eroded-----														
	10-21	10-25	45-65	27-55	1.35-1.50	0.57-2.00	0.15-0.20	3.0-7.0	0.2-1.0	.37	.37			
	21-47	10-20	30-55	35-55	1.35-1.55	0.06-0.20	0.12-0.20	6.0-8.9	0.1-0.5	.37	.37			
	47-60	10-20	30-55	35-55	1.35-1.55	0.06-0.20	0.12-0.20	6.0-8.9	0.1-0.5	.37	.37			
003EH:														
Eram, eroded-	0-15	19	48	27-40	1.30-1.60	0.20-0.60	0.15-0.20	3.0-5.9	1.0-2.0	.37	.37	3	7	38
	15-33	26	29	35-55	1.35-1.65	0.20-0.60	0.10-0.18	6.0-8.9	0.2-1.0	.37	.37			
	33-37					0.00-0.20								
003EK:														
Eram-----	0-9	19	48	27-40	1.30-1.60	0.20-0.60	0.15-0.20	3.0-5.9	1.0-3.0	.37	.37	3	7	38
	9-33	7	54	35-55	1.35-1.65	0.20-0.60	0.10-0.18	6.0-8.9	0.0-2.0	.37	.37			
	33-37					0.00-0.20								
Clareson-----														
	0-7	1-10	50-70	27-40	1.20-1.30	0.20-0.60	0.09-0.17	4.5-7.5	2.0-5.0	.24	.55	2	8	0
	7-16	1-10	40-60	35-60	1.10-1.45	0.20-0.60	0.04-0.07	2.0-8.9	1.0-4.0	.24	.64			
	16-24	1-10	25-60	40-70	1.05-1.45	0.06-0.20	0.04-0.07	2.0-8.9	0.5-1.0	.24	.64			
	24-32													
003LE:														
Leanna,	0-17	1-10	50-75	15-30	1.05-1.35	0.20-0.60	0.22-0.24	3.0-5.9	1.0-4.0	.32	.32	3	6	48
drained-----														
	17-37	1-10	35-60	35-50	1.20-1.50	0.20-0.60	0.11-0.18	6.0-8.9	1.0-3.0	.37	.37			
	37-64	1-10	35-65	27-50	1.30-1.45	0.06-0.20	0.11-0.20	6.0-11.0	0.5-2.0	.37	.37			
003LH:														
Lula-----	0-13	1-13	50-75	15-27	1.20-1.40	0.60-2.00	0.16-0.20	1.5-4.5	1.0-3.0	.37	.37	3	6	48
	13-29	1-25	40-70	25-35	1.30-1.50	0.20-0.60	0.16-0.20	3.0-5.9	1.0-2.0	.37	.37			
	29-49	1-25	45-65	27-35	1.30-1.50	0.06-0.20	0.16-0.20	3.0-5.9	0.2-0.6	.32	.32			
	49-53													
003SE:														
Stony Land---														
Talihina-----	0-7	1-20	50-65	35-40	1.30-1.60	0.20-0.60	0.15-0.19	6.0-8.9	1.0-3.0	.37	.37	2	4	0
	7-12	1-20	50-65	35-40	1.30-1.60	0.20-0.60	0.15-0.19	6.0-8.9	0.5-2.0	.37	.37			86
	12-15	1-20	50-65	35-40	1.30-1.60	0.20-0.60	0.15-0.19	6.0-8.9	0.0-1.0	.37	.37			
	15-19					0.00-0.20								
003WF:														
Woodson-----	0-8	1-10	50-75	18-27	1.25-1.45	0.20-0.60	0.22-0.24	0.0-2.9	2.0-4.0	.43	.43	3	6	48
	8-29	1-10	40-60	40-60	1.30-1.45	0.00-0.06	0.12-0.15	6.0-14.0	0.5-2.0	.32	.32			
	29-64	1-10	40-65	30-50	1.35-1.45	0.06-0.20	0.10-0.15	6.0-12.0	0.2-0.8	.32	.32			
011CA:														
Catoosa-----	0-11	11	68	15-26	1.30-1.55	0.60-2.00	0.15-0.24	0.0-4.0	1.0-3.0	.37	.37	2	6	48
	11-16	7	60	27-39	1.25-1.50	0.60-2.00	0.13-0.19	3.0-8.0	1.0-3.0	.32	.32			
	16-27	7	54	27-55	1.15-1.55	0.20-0.60	0.12-0.18	3.0-9.0	0.0-1.0	.32	.32			
	27-35													
059CM:														
Clareson-----	0-7	1-10	50-70	27-40	1.25-1.35	0.60-2.00	0.16-0.22	3.0-5.9	2.5-4.0	.32	.32	2	7	38
	7-15	1-10	50-70	27-40	1.25-1.40	0.20-2.00	0.09-0.21	3.0-5.9	2.0-3.0	.24	.43			
	15-26	1-10	40-60	35-50	1.20-1.45	0.06-0.20	0.04-0.07	4.0-8.9	1.0-3.0	.24	.64			
	26-34													
Eram-----	0-7	1-20	45-70	27-40	1.30-1.60	0.20-0.60	0.15-0.20	3.0-5.9	1.0-3.0	.37	.37	3	7	38
	7-38	1-25	30-60	35-55	1.35-1.65	0.06-0.20	0.10-0.18	6.0-8.9	0.5-1.5	.37	.37			
	38-46					0.00-0.20								
AED:														
Arents,														
Earthen Dam-														
Bb:														
Bates-----	0-10	44	37	15-27	1.30-1.50	0.20-0.60	0.20-0.24	0.0-2.9	1.0-4.0	.32	.32	3	5	56
	10-21	38	32	18-35	1.30-1.60	0.20-0.60	0.15-0.19	0.0-4.0	1.0-3.0	.28	.28			
	21-31	39	25	18-40	1.30-1.50	0.06-0.20	0.14-0.16	0.0-2.9	0.5-1.0	.20	.43			
	31-35					0.20-0.60								
Bc:														
Bates-----	0-7	35-55	30-40	15-27	1.40-1.50	0.20-0.60	0.20-0.24	0.0-2.9	1.0-4.0	.32	.32	3	5	56
	7-18	35-55	20-40	18-35	1.35-1.60	0.20-0.60	0.15-0.19	0.0-4.0	1.0-3.0	.28	.28			
	18-31	35-55	20-30	18-40	1.35-1.50	0.06-0.20	0.14-0.16	0.0-2.9	0.5-1.0	.20	.43			
	31-35					0.20-0.60								
Cb:														
Catoosa-----	0-12	11	68	15-26	1.30-1.55	0.60-2.00	0.15-0.24	0.0-2.9	1.0-3.0	.37	.37	2	6	48
	12-25	7	60	27-39	1.45-1.70	0.60-2.00	0.15-0.22	3.0-5.9	0.5-2.0	.32	.32			
	25-29	7	38	35-60	1.10-1.70	0.20-0.60	0.15-0.22	3.0-10.0	0.1-1.0	.32	.32			
	29-33													
Cm:														
Clareson-----	0-11	3	58	27-40	1.25-1.35	0.60-2.00	0.16-0.22	3.0-6.5	1.0-5.0	.32	.32	2	7	38
	11-16	3	58	27-40	1.30-1.40	0.20-0.60	0.09-0.21	3.0-5.9	0.5-2.0	.24	.43			
	16-33	2	31	35-70	1.10-1.30	0.20-0.60	0.04-0.07	6.0-8.9	0.0-1.0	.24	.64			
	33-37													
Rock Outcrop-														0

PHYSICAL PROPERTIES OF THE SOILS--Continued  
Linn County, Kansas: Published

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permea- bility (Ksat)	Available water capacity	Linear extensi- bility	Organic matter	Erosion factors			Wind erodi- bility group	Wind erodi- bility index
										K	Kf	T		
	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
De: Dennis-----	0-11	18	66	10-27	1.30-1.55	0.60-2.00	0.15-0.20	0.0-4.0	1.0-4.0	.43	.43	5	6	48
	11-17	13	57	27-35	1.35-1.70	0.60-2.00	0.15-0.20	3.0-5.9	0.8-3.0	.37	.37			
	17-25	7	42	35-55	1.10-1.65	0.20-0.60	0.15-0.20	6.0-11.0	0.1-1.5	.37	.37			
	25-60	13	45	35-55	1.25-1.65	0.20-0.60	0.15-0.20	6.0-8.9	0.0-1.0	.37	.37			
Df: Dennis-----	0-10	18	66	10-27	1.30-1.55	0.60-2.00	0.15-0.20	0.0-4.0	1.0-4.0	.43	.43	5	6	48
	10-16	13	57	27-35	1.35-1.70	0.60-2.00	0.15-0.20	3.0-5.9	0.8-3.0	.37	.37			
	16-24	7	42	35-55	1.10-1.65	0.20-0.60	0.15-0.20	6.0-10.0	0.1-1.5	.37	.37			
	24-60	13	45	35-55	1.25-1.65	0.20-0.60	0.15-0.20	6.0-8.9	0.0-1.0	.37	.37			
Ec: Eram-----	0-10	19	48	27-40	1.30-1.60	0.20-0.60	0.15-0.20	3.0-5.9	1.0-4.0	.37	.37	3	7	38
	10-27	8	37	35-55	1.35-1.65	0.20-0.60	0.10-0.18	6.0-8.9	0.1-3.0	.37	.37			
	27-31			---	---	0.00-0.20	---	---	---	---	---			
Ed: Eram-----	0-9	19	48	27-40	1.30-1.60	0.20-0.60	0.15-0.20	3.0-5.9	1.0-4.0	.37	.37	3	7	38
	9-27	8	37	35-55	1.35-1.65	0.20-0.60	0.10-0.18	6.0-8.9	0.1-3.0	.37	.37			
	27-31			---	---	0.00-0.20	---	---	---	---	---			
Ef: Eram-----	0-8	19	48	27-40	1.30-1.60	0.20-0.60	0.15-0.20	3.0-5.9	1.0-4.0	.37	.37	3	7	38
	8-27	8	37	35-55	1.35-1.65	0.20-0.60	0.10-0.18	6.0-8.9	0.1-3.0	.37	.37			
	27-31			---	---	0.00-0.20	---	---	---	---	---			
Lebo-----	0-12	7	46	22-55	1.10-1.45	0.20-0.60	0.21-0.23	3.0-10.0	2.0-6.0	.32	.37	3	7	38
	12-28	5	45	22-55	1.10-1.50	0.20-0.60	0.15-0.18	3.0-5.9	1.0-4.0	.24	.37			
	28-38	13	53	22-40	1.25-1.65	0.00-0.20	0.07-0.10	3.0-5.9	0.5-2.0	.24	.64			
	38-42			---	---	0.00-0.20	---	---	---	---	---			
Hp: Hepler-----	0-9	3	78	12-27	1.25-1.50	0.20-0.60	0.22-0.24	0.0-2.9	0.5-3.0	.37	.37	5	6	48
	9-25	4	71	20-35	1.35-1.55	0.20-0.60	0.18-0.20	0.0-5.9	0.1-2.0	.37	.37			
	25-40	4	64	27-42	1.35-1.60	0.20-0.60	0.14-0.17	3.0-5.9	0.1-1.0	.37	.37			
	40-60	2	66	27-42	1.35-1.60	0.20-0.60	0.14-0.17	3.0-5.9	0.1-1.0	.37	.37			
INT: Aquolls-----	0-72			---	---	---	---	---	---	---	---	-	---	0
Ke: Kenoma-----	0-10	1-10	50-75	18-27	1.35-1.45	0.20-0.60	0.22-0.24	1.5-4.5	2.0-4.0	.43	.43	3	6	48
	10-22	1-10	30-60	40-60	1.40-1.50	0.06-0.20	0.08-0.15	6.0-8.9	1.0-2.0	.32	.32			
	22-44	1-10	40-60	30-50	1.35-1.45	0.06-0.20	0.08-0.20	6.0-11.0	0.5-1.0	.32	.32			
	44-60	1-10	40-60	30-50	1.35-1.60	0.00-0.06	0.08-0.20	6.0-8.9	0.5-1.0	.32	.32			
La: Lanton-----	0-14	1-10	40-75	18-27	1.30-1.50	0.20-0.60	0.18-0.22	1.5-4.5	2.0-4.0	.37	.37	5	6	48
	14-38	1-10	40-75	20-35	1.45-1.70	0.20-0.60	0.18-0.22	1.5-5.9	1.0-3.0	.32	.32			
	38-53	1-10	50-75	20-45	1.35-1.65	0.20-0.60	0.12-0.18	1.5-5.9	0.5-1.5	.32	.32			
	53-60	1-10	50-70	20-45	1.35-1.65	0.06-0.20	0.12-0.18	3.0-5.9	0.5-1.5	.32	.32			
Lb: Lebo-----	0-11	7	46	22-55	1.10-1.45	0.20-0.60	0.21-0.23	3.0-9.5	2.0-6.0	.24	.37	3	8	0
	11-27	5	45	22-55	1.10-1.50	0.20-0.60	0.15-0.18	3.0-5.9	1.0-4.0	.24	.37			
	27-38	13	53	22-40	1.25-1.65	0.00-0.20	0.07-0.10	0.0-5.9	0.5-2.0	.24	.64			
	38-42			---	---	0.00-0.20	---	---	---	---	---			
M-W: Miscellaneous Water-----	---			---	---	---	---	---	---	---	---	-	---	---
Mb: Mason-----	0-18	1-12	50-75	12-27	1.30-1.50	0.60-2.00	0.16-0.20	0.0-2.9	1.0-3.0	.37	.37	5	6	48
	18-50	1-10	45-70	20-35	1.40-1.70	0.60-2.00	0.16-0.20	3.0-5.9	0.5-1.5	.37	.37			
	50-60	1-10	45-70	20-35	1.40-1.70	0.06-0.20	0.16-0.20	3.0-5.9	0.5-1.5	.37	.37			
Nf: Newtonia----	0-13	1-25	50-80	10-24	1.20-1.30	0.60-2.00	0.15-0.24	0.0-5.9	1.0-4.0	.37	.37	5	6	48
	13-26	1-25	50-75	20-35	1.25-1.35	0.60-2.00	0.16-0.22	3.0-5.9	1.0-2.0	.37	.37			
	26-49	1-25	50-70	27-35	1.40-1.50	0.20-0.60	0.18-0.22	3.0-5.9	0.5-1.5	.32	.32			
	49-60	2-25	40-60	32-45	1.30-1.40	0.06-0.20	0.12-0.20	2.0-8.9	0.3-0.7	.32	.32			
Ng: Newtonia----	0-13	1-25	50-80	10-24	1.20-1.30	0.60-2.00	0.15-0.24	0.0-4.0	1.0-4.0	.37	.37	5	6	48
	13-26	1-25	50-75	20-35	1.25-1.35	0.60-2.00	0.16-0.22	3.0-5.9	1.0-2.0	.37	.37			
	26-49	1-25	50-70	27-35	1.40-1.50	0.20-0.60	0.18-0.22	3.0-5.9	0.5-1.5	.32	.32			
	49-60	2-25	40-60	32-45	1.30-1.40	0.06-0.20	0.12-0.20	2.0-8.9	0.3-0.7	.32	.32			
Nh: Newtonia----	0-11	1-25	50-80	10-24	1.20-1.30	0.60-2.00	0.15-0.24	0.0-4.0	1.0-4.0	.37	.37	5	6	48
	11-24	1-25	50-75	20-35	1.25-1.35	0.60-2.00	0.16-0.22	3.0-5.9	1.0-2.0	.37	.37			
	24-47	1-25	50-70	27-35	1.40-1.50	0.20-0.60	0.18-0.22	3.0-5.9	0.5-1.5	.32	.32			
	47-60	2-25	40-60	32-45	1.30-1.40	0.06-0.20	0.12-0.20	2.0-8.9	0.3-0.7	.32	.32			
Oh: Okemah-----	0-12	24	52	20-27	1.30-1.50	0.20-0.60	0.16-0.24	0.0-2.9	1.0-3.0	.43	.43	5	6	48
	12-18	8	54	35-55	1.40-1.65	0.20-0.60	0.10-0.18	6.0-8.9	0.5-2.0	.43	.43			
	18-24	7	48	35-55	1.40-1.65	0.20-0.60	0.10-0.18	6.0-8.9	0.1-0.8	.43	.43			
	24-60	7	48	35-55	1.40-1.65	0.06-0.20	0.10-0.18	6.0-8.9	0.0-0.5	.43	.43			
Om: Kanima-----	0-6	5	51	27-65	1.00-1.60	0.20-0.60	0.08-0.17	0.0-9.0	0.5-2.0	.28	.37	5	7	38
	6-60	7	53	18-65	1.40-2.00	0.20-0.60	0.02-0.12	0.0-9.0	0.0-1.0	.15	.37			
Op: Kanima-----	0-6	5	51	27-65	1.00-1.60	0.20-0.60	0.08-0.17	0.0-9.0	0.5-2.0	.28	.37	5	7	38
	6-60	7	53	18-65	1.40-2.00	0.20-0.60	0.02-0.12	0.0-9.0	0.0-1.0	.15	.37			

PHYSICAL PROPERTIES OF THE SOILS--Continued  
Linn County, Kansas: Published

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permea- bility (Ksat)	Available water capacity	Linear extensi- bility	Organic matter	Erosion factors			Wind erodi- bility group	Wind erodi- bility index
										K	Kf	T		
Ot:	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
Osage-----	0-15	1-10	40-60	35-40	1.45-1.65	0.20-0.60	0.21-0.23	6.0-8.9	1.0-6.0	.37	.37	5	4	86
	15-44	1-5	35-60	35-65	1.10-1.70	0.06-0.20	0.08-0.12	9.0-25.0	0.8-5.0	.28	.28			
	44-60	1-5	35-60	35-60	1.10-1.70	0.00-0.06	0.08-0.12	9.0-25.0	0.5-2.0	.28	.28			
Ov:														
Osage-----	0-8	1-5	40-60	35-60	1.25-1.65	0.06-0.20	0.21-0.23	6.0-13.0	1.0-6.0	.28	.28	5	4	86
	8-23	1-5	35-60	35-65	1.10-1.70	0.06-0.20	0.08-0.12	9.0-25.0	0.8-4.0	.28	.28			
	23-44	1-8	35-60	35-65	1.10-1.70	0.06-0.20	0.08-0.12	9.0-25.0	0.5-2.0	.28	.28			
	44-60	1-5	35-60	35-65	1.10-1.70	0.00-0.06	0.08-0.12	9.0-25.0	0.1-1.0	.28	.28			
Pc:														
Parsons-----	0-9	6	77	15-25	1.30-1.50	0.20-0.60	0.16-0.24	0.0-2.9	0.5-4.0	.49	.49	4	6	48
	9-13	7	75	15-25	1.30-1.50	0.20-0.60	0.16-0.24	0.0-2.9	0.5-1.5	.49	.49			
	13-60	3	46	35-60	1.40-1.70	0.06-0.20	0.10-0.18	6.0-8.9	0.0-0.8	.43	.43			
Po:														
Pits, Quarries----	0-60			---	---	---	---	---	---	---	---	-	---	0
Sn:														
Summit-----	0-11	13	56	27-45	1.25-1.50	0.20-0.60	0.16-0.20	3.0-5.9	1.0-4.0	.37	.37	5	4	86
	11-24	9	47	40-60	1.35-1.60	0.20-0.60	0.10-0.18	6.0-8.9	1.0-2.0	.32	.32			
	24-33	9	46	40-60	1.35-1.60	0.20-0.60	0.10-0.18	6.0-8.9	0.5-1.5	.32	.32			
	33-60	12	45	40-60	1.35-1.60	0.06-0.20	0.10-0.18	6.0-8.9	0.5-1.0	.32	.32			
So:														
Summit-----	0-9	13	56	27-45	1.25-1.50	0.20-0.60	0.16-0.20	3.0-5.9	1.0-4.0	.37	.37	5	4	86
	9-22	9	47	40-60	1.35-1.60	0.20-0.60	0.10-0.18	6.0-8.9	1.0-2.0	.32	.32			
	22-31	9	46	40-60	1.35-1.60	0.20-0.60	0.10-0.18	6.0-8.9	0.5-1.5	.32	.32			
	31-60	12	45	40-60	1.35-1.60	0.06-0.20	0.10-0.18	6.0-8.9	0.5-1.0	.32	.32			
Vb:														
Verdigris----	0-9	14	63	15-27	1.30-1.60	0.60-2.00	0.20-0.24	0.0-2.9	2.0-5.0	.32	.32	5	6	48
	9-32	19	58	15-27	1.30-1.65	0.60-2.00	0.20-0.24	0.0-2.9	1.5-4.0	.32	.32			
	32-52	20	56	18-35	1.40-1.65	0.20-0.60	0.17-0.20	2.0-5.9	1.0-3.0	.32	.32			
	52-60	15	59	18-35	1.40-1.65	0.20-0.60	0.17-0.20	2.0-5.9	0.5-2.0	.32	.32			
Vc:														
Verdigris----	0-9	14	63	15-27	1.30-1.60	0.60-2.00	0.20-0.24	0.0-2.9	2.0-5.0	.32	.32	5	6	48
	9-32	19	58	15-27	1.30-1.65	0.60-2.00	0.20-0.24	0.0-2.9	1.5-4.0	.32	.32			
	32-52	20	56	18-35	1.40-1.65	0.20-0.60	0.17-0.20	2.0-5.9	1.0-3.0	.32	.32			
	52-60	15	59	18-35	1.40-1.65	0.20-0.60	0.17-0.20	2.0-5.9	0.5-2.0	.32	.32			
W:														
Water-----	---			---	---	---	---	---	---	---	---	-	---	---
We:														
Welda-----	0-7	1-30	50-75	12-27	1.25-1.35	0.60-2.00	0.22-0.24	1.5-4.5	0.5-1.0	.37	.37	5	6	48
	7-10	1-25	40-65	35-42	1.35-1.40	0.20-0.60	0.14-0.20	6.0-8.9	0.3-0.7	.32	.32			
	10-35	1-10	40-65	35-42	1.35-1.40	0.20-0.60	0.14-0.20	6.0-8.9	0.3-0.7	.32	.32			
	35-60	1-40	30-70	18-35	1.40-1.45	0.06-0.20	0.18-0.22	3.0-5.9	0.1-0.5	.32	.32			
Wo:														
Woodson-----	0-7	2	73	18-27	1.25-1.45	0.60-2.00	0.22-0.24	0.0-2.9	2.0-6.0	.43	.43	3	6	48
	7-30	1	43	40-60	1.20-1.45	0.06-0.20	0.12-0.15	6.0-15.0	1.0-3.5	.32	.32			
	30-40	3	51	30-50	1.30-1.45	0.06-0.20	0.10-0.15	6.0-11.0	0.1-1.0	.32	.32			
	40-60	4	50	30-50	1.35-1.45	0.00-0.06	0.10-0.15	6.0-11.0	0.0-0.2	.32	.32			

CHEMICAL PROPERTIES OF THE SOILS  
Linn County, Kansas

The Chemical Properties table shows estimates of some characteristics and features that affect soil behavior. These estimates are given for the major layers of each soil in the survey area. The estimates are based on field observations and on test data for these and similar soils. Depth to the upper and lower boundaries of each layer is indicated.

Cation-exchange capacity is the total amount of extractable bases that can be held by the soil, expressed in terms of milliequivalents per 100 grams of soil at neutrality (pH 7.0) or at some other stated pH value. Soils having a low cation-exchange capacity hold fewer cations and may require more frequent applications of fertilizer than soils having a high cation-exchange capacity. Soils having a high cation-exchange capacity can retain cations. The ability to retain cations helps to prevent the pollution of ground water.

Effective cation-exchange capacity refers to the sum of extractable bases plus aluminum expressed in terms of milliequivalents per 100 grams of soil. It is determined for soils that have pH of less than 5.5.

Soil reaction is a measure of acidity or alkalinity and is expressed as a range in pH values. The range in pH of each major horizon is based on many field tests. For many soils, values have been verified by laboratory analyses. Soil reaction is important in selecting crops and other plants, in evaluating soil amendments for fertility and stabilization, and in determining the risk of corrosion.

Calcium carbonate equivalent is the percent of carbonates, by weight, in the fraction of the soil less than 2 millimeters in size. The availability of plant nutrients is influenced by the amount of carbonates in the soil. Incorporating nitrogen fertilizer into calcareous soils helps to prevent nitrite accumulation and ammonium-N volatilization.

Gypsum is expressed as a percent, by weight, of hydrated calcium sulfates in the fraction of the soil less than 20 millimeters in size. Gypsum is partially soluble in water and can be dissolved and removed by water. Soils that have a high content of gypsum may collapse if the gypsum is removed by percolating water.

Salinity is a measure of soluble salts in the soil at saturation. It is expressed as the electrical conductivity of the saturation extract, in millimhos per centimeter at 25 degrees C. Estimates are based on field and laboratory measurements at representative sites of nonirrigated soils. The salinity of irrigated soils is affected by the quality of the irrigation water and by the frequency of water application. Hence, the salinity of soils in individual fields can differ greatly from the value given in the table. Salinity affects the suitability of a soil for crop production, the stability of soil if used as construction material, and the potential of the soil to corrode metal and concrete.

Sodium adsorption ratio (SAR) is a measure of the amount of sodium (Na) relative to calcium (Ca) and magnesium (Mg) in the water extract from saturated soil paste. It is the ratio of the Na concentration divided by the square root of one-half of the Ca + Mg concentration. Soils that have SAR values of 13 or more may be characterized by an increased dispersion of organic matter and clay particles, reduced permeability and aeration, and a general degradation of soil structure.

CHEMICAL PROPERTIES OF THE SOILS--Continued  
Linn County, Kansas

PAGE 2 of 4

Map symbol and soil name	Depth	Cation- exchange capacity	Effective Cation Exchange Capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm		
003CD:								
Collinsville----	0-6	5.0-18	---	5.6-6.0	0	0	0	0
	6-11	3.0-16	---	5.6-6.0	0	0	0	0
	11-15	---	---	---	---	---	---	---
Collinsville	0-6	5.0-18	---	5.6-6.0	0	0	0	0
Taxadjunct----	6-23	3.0-16	---	5.6-6.0	0	0	0	0
	23-27	---	---	---	---	---	---	---
003DE:								
Dennis, eroded--	0-10	5.0-25	---	5.1-6.0	0	0	0	0
	10-21	---	4.0-15	5.1-6.0	0	0	0	0
	21-47	14-34	---	5.1-8.4	0	0	0	0
	47-60	14-34	---	5.6-8.4	0	0	0	0
003EH:								
Eram, eroded----	0-15	13-28	---	5.6-6.5	0	0	0	0
	15-33	15-35	---	5.1-7.3	0	0	0	0
	33-37	---	---	---	---	---	---	---
003EK:								
Eram-----	0-9	13-30	---	5.6-6.5	0	0	0	0
	9-33	14-37	---	5.1-7.3	0	0	0	0
	33-37	---	---	---	---	---	---	---
Clareson-----	0-7	15-34	---	6.6-7.3	0	0	0	0
	7-16	16-44	---	6.6-7.3	0	0	0	0
	16-24	17-44	---	6.6-7.3	0	0	0	0
	24-32	---	---	---	---	---	---	---
003LE:								
Leanna, drained--	0-17	---	8.0-22	5.1-6.5	0	0	0	0
	17-37	16-36	---	5.1-7.3	0	0	0	0
	37-64	12-34	---	5.6-7.3	0	0	0	0
003LH:								
Lula-----	0-13	6.0-18	---	5.6-6.5	0	0	0	0
	13-29	7.0-21	---	5.1-6.5	0	0	0	0
	29-49	10-21	---	5.1-7.3	0	0	0	0
	49-53	---	---	---	---	---	---	---
003SE:								
Stony Land-----	---	---	---	---	---	---	---	---
Talihina-----	0-7	16-30	---	5.1-7.8	0	0	0	0
	7-12	15-28	---	5.1-7.8	0	0	0	0
	12-15	14-26	---	5.1-7.8	0	0	0	0
	15-19	---	---	---	---	---	---	---
003WF:								
Woodson-----	0-8	11-24	---	5.6-6.5	0	0	0	0
	8-29	17-40	---	5.6-7.3	0	0	0	0
	29-64	12-32	---	5.6-7.8	0	0	0	0
011CA:								
Catoosa-----	0-11	8.0-22	---	5.6-6.5	---	---	---	---
	11-16	13-29	---	5.1-7.3	---	---	---	---
	16-27	11-35	---	5.1-7.3	---	---	---	---
	27-35	---	0.0-0.0	---	---	---	---	---
059CM:								
Clareson-----	0-7	16-32	---	5.6-7.3	0	0	0	0
	7-15	15-30	---	5.6-7.3	0	0	0	0
	15-26	16-36	---	5.6-7.3	0	0	0	0
	26-34	---	---	---	---	---	---	---
Eram-----	0-7	13-30	---	5.6-6.5	0	0	0	0
	7-38	15-36	---	5.1-7.3	0	0	0	0
	38-46	---	---	---	---	---	---	---
AED:								
Arents, Earthen	---	---	---	---	---	---	---	---
Dam-----								
Bb:								
Bates-----	0-10	---	4.0-15	5.1-6.5	0	0	0	0
	10-21	---	4.0-16	5.1-6.5	0	0	0	0
	21-31	---	4.0-20	5.1-6.5	---	---	---	---
	31-35	---	---	---	---	---	---	---
Bc:								
Bates-----	0-7	---	4.0-15	5.1-6.5	0	0	0	0
	7-18	---	4.0-16	5.1-6.5	0	0	0	0
	18-31	---	4.0-20	5.1-6.5	0	0	0	0
	31-35	---	---	---	---	---	---	---
Ch:								
Catoosa-----	0-12	8.0-22	---	5.6-6.5	---	---	---	---
	12-25	12-27	---	5.1-7.3	---	---	---	---
	25-29	14-38	---	5.1-7.3	---	---	---	---
	29-33	---	---	---	---	---	---	---
Cm:								
Clareson-----	0-11	13-34	---	5.6-7.3	0	0	0	0
	11-16	12-28	---	5.6-7.3	0	0	0	0
	16-33	14-44	---	5.6-7.3	0	0	0	0
	33-37	---	---	---	---	---	---	---
Rock Outcrop----	---	---	---	---	---	---	---	---

CHEMICAL PROPERTIES OF THE SOILS--Continued  
Linn County, Kansas

PAGE 3 of 4

Map symbol and soil name	Depth	Cation- exchange capacity	Effective Cation Exchange Capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm		
De: Dennis-----	0-11	---	4.0-15	5.1-7.3	---	---	---	---
	11-17	---	6.0-21	5.1-6.0	---	---	---	---
	17-25	---	10-28	4.5-6.0	---	---	---	---
	25-60	14-35	---	6.1-7.8	---	---	---	---
Df: Dennis-----	0-10	---	4.0-15	5.1-7.3	---	---	---	---
	10-16	---	6.0-21	5.1-6.0	---	---	---	---
	16-24	---	10-28	4.5-6.0	---	---	---	---
	24-60	14-35	---	6.1-7.8	---	---	---	---
Ec: Eram-----	0-10	13-32	---	5.6-6.5	---	---	0	---
	10-27	14-39	---	5.1-7.3	---	---	0	---
	27-31	---	---	---	---	---	---	---
Ed: Eram-----	0-9	13-32	---	5.6-6.5	---	---	0	---
	9-27	14-39	---	5.1-7.3	---	---	0	---
	27-31	---	---	---	---	---	---	---
Ef: Eram-----	0-8	13-32	---	5.6-6.5	---	---	0	---
	8-27	14-39	---	5.1-7.3	---	---	0	---
	27-31	---	---	---	---	---	---	---
Lebo-----	0-12	13-45	---	5.6-7.8	0	0	0	0
	12-28	11-41	---	5.6-7.8	0	0	0	0
	28-38	10-28	---	5.6-7.8	0	0	0	0
	38-42	---	---	---	---	---	---	---
Hp: Hepler-----	0-9	6.0-22	---	5.1-6.5	0	0	0	0
	9-25	8.0-25	---	5.1-6.5	---	---	---	---
	25-40	---	6.0-18	4.5-6.5	0	0	0	0
	40-60	11-27	---	5.1-6.5	0	0	0	0
INT: Aquolls-----	0-72	---	---	---	---	---	---	---
Ke: Kenoma-----	0-10	11-24	---	5.6-6.5	0	0	0.0-2.0	0
	10-22	18-40	---	5.6-7.8	0	0	0.0-2.0	0
	22-44	13-32	---	6.1-8.4	0	0	0.0-4.0	0
	44-60	13-32	---	6.1-8.4	0	0	0.0-4.0	0
La: Lanton-----	0-14	11-24	---	5.6-7.3	0	0	0	0
	14-38	10-27	---	5.6-7.3	0	0	0	0
	38-53	9.0-30	---	6.6-7.3	0	0	0	0
	53-60	9.0-30	---	6.6-7.3	0	0	0	0
Lb: Lebo-----	0-11	13-45	---	5.6-7.8	0	0	0	0
	11-27	11-41	---	5.6-7.8	0	0	0	0
	27-38	10-28	---	5.6-7.8	0	0	0	0
	38-42	---	---	---	---	---	---	---
M-W: Miscellaneous Water-----	---	---	---	---	---	---	---	---
Mb: Mason-----	0-18	7.0-22	---	5.6-7.3	0	0	0	0
	18-50	9.0-24	---	5.6-7.8	0	0	0	0
	50-60	9.0-24	---	6.1-7.8	0	0	0	0
Nf: Newtonia-----	0-13	6.0-22	---	5.6-6.5	0	0	0	0
	13-26	10-25	---	5.1-6.5	0	0	0	0
	26-49	12-24	---	5.1-6.5	0	0	0	0
	49-60	13-28	---	5.1-7.3	0	0	0	0
Ng: Newtonia-----	0-13	6.0-22	---	5.6-6.5	0	0	0	0
	13-26	10-25	---	5.1-6.5	0	0	0	0
	26-49	12-24	---	5.1-6.5	0	0	0	0
	49-60	13-28	---	5.1-7.3	0	0	0	0
Nh: Newtonia-----	0-11	6.0-22	---	5.6-6.5	0	0	0	0
	11-24	10-25	---	5.1-6.5	0	0	0	0
	24-47	12-24	---	5.1-6.5	0	0	0	0
	47-60	13-28	---	5.1-7.3	0	0	0	0
Oh: Okemah-----	0-12	10-22	---	5.6-7.3	---	---	---	---
	12-18	15-37	---	5.1-6.6	---	---	---	---
	18-24	14-35	---	5.1-6.6	---	---	---	---
	24-60	14-34	---	5.6-7.3	---	---	---	---
Om: Kanima-----	0-6	12-43	---	5.6-8.4	---	---	---	---
	6-60	7.0-41	---	5.6-8.4	---	---	---	---
Op: Kanima-----	0-6	12-43	---	5.6-8.4	---	---	---	---
	6-60	7.0-41	---	5.6-8.4	---	---	---	---

CHEMICAL PROPERTIES OF THE SOILS--Continued  
Linn County, Kansas

PAGE 4 of 4

Map symbol and soil name	Depth	Cation- exchange capacity	Effective Cation Exchange Capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm		
Ot:								
Osage-----	0-15	16-36	---	5.6-7.3	0	0	0	0
	15-44	16-49	---	5.6-7.8	0	0	0	0
	44-60	15-40	---	6.1-8.4	0	0	0	0
Ov:								
Osage-----	0-8	16-48	---	5.6-7.3	0	0	0	0
	8-23	16-47	---	5.6-7.8	0	0	0	0
	23-44	15-43	---	5.6-7.8	0	0	0	0
	44-60	14-41	---	6.1-8.4	0	0	0	0
Pc:								
Parsons-----	0-9	7.0-23	---	5.1-6.5	---	---	0	---
	9-13	7.0-18	---	5.1-6.5	---	---	0	---
	13-60	14-38	---	5.1-7.8	---	---	0	---
Po:								
Pits, Quarries--	0-60	---	---	---	---	---	---	---
Sn:								
Summit-----	0-11	13-35	---	5.6-7.3	---	---	---	---
	11-24	18-40	---	5.6-8.4	---	---	---	---
	24-33	17-39	---	5.6-8.4	---	---	---	---
	33-60	17-38	---	5.6-8.4	---	---	---	---
So:								
Summit-----	0-9	13-35	---	5.6-7.3	---	---	---	---
	9-22	18-40	---	5.6-8.4	---	---	---	---
	22-31	17-39	---	5.6-8.4	---	---	---	---
	31-60	17-38	---	5.6-8.4	---	---	---	---
Vb:								
Verdigris-----	0-9	10-26	---	5.6-7.3	---	---	---	---
	9-32	9.0-24	---	5.6-7.3	---	---	---	---
	32-52	9.0-27	---	5.6-7.3	---	---	---	---
	52-60	8.0-25	---	5.6-7.3	---	---	---	---
Vc:								
Verdigris-----	0-9	10-26	---	5.6-7.3	---	---	---	---
	9-32	9.0-24	---	5.6-7.3	---	---	---	---
	32-52	9.0-27	---	5.6-7.3	---	---	---	---
	52-60	8.0-25	---	5.6-7.3	---	---	---	---
W:								
Water-----	---	---	---	---	---	---	---	---
We:								
Welda-----	0-7	6.0-18	---	5.6-7.3	0	0	0	0
	7-10	---	4.0-20	5.1-6.5	0	0	0	0
	10-35	---	4.0-20	5.1-6.5	0	0	0	0
	35-60	---	4.0-20	5.1-6.5	0	0	0	0
Wo:								
Woodson-----	0-7	11-28	---	5.6-6.5	---	---	---	---
	7-30	18-43	---	5.6-7.3	---	---	---	---
	30-40	12-32	---	5.6-7.8	---	---	---	---
	40-60	12-31	---	6.1-7.8	---	---	---	---

# WATER FEATURES Linn County, Kansas

The Water Features table gives estimates of various water features. The estimates are used in land use planning that involves engineering considerations. Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The four hydrologic soil groups are:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

The months in the table indicate the portion of the year in which the feature is most likely to be a concern.

Water table refers to a saturated zone in the soil. The Water Features table indicates, by month, depth to the top (upper limit) and base (lower limit) of the saturated zone in most years. Estimates of the upper and lower limits are based mainly on observations of the water table at selected sites and on evidence of a saturated zone, namely grayish colors or mottles (redoximorphic features) in the soil. A saturated zone that lasts for less than a month is not considered a water table. Ponding is standing water in a closed depression. Unless a drainage system is installed, the water is removed only by percolation, transpiration, or evaporation. The Water Features table indicates surface water depth and the duration and frequency of ponding. Duration is expressed as very brief if less than 2 days, brief if 2 to 7 days, long if 7 to 30 days, and very long if more than 30 days. Frequency is expressed as none, rare, occasional, and frequent. None means that ponding is not probable; rare that it is unlikely but possible under unusual weather conditions (the chance of ponding is nearly 0 percent to 5 percent in any year); occasional that it occurs, on the average, once or less in 2 years (the chance of ponding is 5 to 50 percent in any year); and frequent that it occurs, on the average, more than once in 2 years (the chance of ponding is more than 50 percent in any year).

Flooding, the temporary inundation of an area, is caused by overflowing streams, by runoff from adjacent slopes, or by tides. Water standing for short periods after rainfall or snowmelt is not considered flooding, and water standing in swamps and marshes is considered ponding rather than flooding.

Duration and frequency are estimated. Duration is expressed as extremely brief if 0.1 hour to 4 hours, very brief if 4 hours to 2 days, brief if 2 to 7 days, long if 7 to 30 days, and very long if more than 30 days. Frequency is expressed as none, very rare, rare, occasional, frequent, and very frequent. None means that flooding is not probable; very rare that it is very unlikely but possible under extremely unusual weather conditions (the chance of flooding is less than 1 percent in any year); rare that it is unlikely but possible under unusual weather conditions (the chance of flooding is 1 to 5 percent in any year); occasional that it occurs infrequently under normal weather conditions (the chance of flooding is 5 to 50 percent in any year); frequent that it is likely to occur often under normal weather conditions (the chance of flooding is more than 50 percent in any year but is less than 50 percent in all months in any year); and very frequent that it is likely to occur very often under normal weather conditions (the chance of flooding is more than 50 percent in all months of any year).

The information is based on evidence in the soil profile, namely thin strata of gravel, sand, silt, or clay deposited by floodwater; irregular decrease in organic matter content with increasing depth; and little or no horizon development.

Also considered are local information about the extent and levels of flooding and the relation of each soil on the landscape to historic floods. Information on the extent of flooding based on soil data is less specific than that provided by detailed engineering surveys that delineate flood-prone areas at specific flood frequency levels.



(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro- logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
			Ft	Ft	Ft				
003CD: Collinsville-----	D		---	---	---	---	---	---	---
Collinsville Taxadjunct---	D		---	---	---	---	---	---	---
003DE: Dennis, eroded-----	C	January	1.0-1.5	2.0-3.0	---	---	---	---	None
		February	1.0-1.5	2.0-3.0	---	---	---	---	None
		March	1.0-1.5	2.0-3.0	---	---	---	---	None
		April	1.0-1.5	2.0-3.0	---	---	---	---	None
		December	1.0-1.5	2.0-3.0	---	---	---	---	None
003EH: Eram, eroded-----	C	January	0.5-1.5	1.5-2.5	---	---	---	---	None
		February	0.5-1.5	1.5-2.5	---	---	---	---	None
		March	0.5-1.5	1.5-2.5	---	---	---	---	None
		April	0.5-1.5	1.5-2.5	---	---	---	---	None
		November	0.5-1.5	1.5-2.5	---	---	---	---	None
		December	0.5-1.5	1.5-2.5	---	---	---	---	None
003EK: Eram-----	C	January	0.5-1.5	1.5-2.5	---	---	---	---	None
		February	0.5-1.5	1.5-2.5	---	---	---	---	None
		March	0.5-1.5	1.5-2.5	---	---	---	---	None
		April	0.5-1.5	1.5-2.5	---	---	---	---	None
		November	0.5-1.5	1.5-2.5	---	---	---	---	None
		December	0.5-1.5	1.5-2.5	---	---	---	---	None
Clareson-----	C		---	---	---	---	---	---	---
003LE: Leanna, drained-----	D	January	0.5-2.0	1.0-2.0	---	---	---	---	Rare
		February	0.5-2.0	1.0-2.0	---	---	---	---	Rare
		March	0.5-2.0	1.0-2.0	---	---	Very brief	Occasional	
		April	0.5-2.0	1.0-2.0	---	---	Very brief	Occasional	
		May	0.5-2.0	1.0-2.0	---	---	Very brief	Occasional	
		June	0.5-2.0	1.0-2.0	---	---	Very brief	Occasional	
		July	---	---	---	---	Very brief	Occasional	
		August	---	---	---	---	Very brief	Occasional	
		September	---	---	---	---	Very brief	Occasional	
		October	---	---	---	---	Very brief	Occasional	
		November	---	---	---	---	---	Rare	
		December	0.5-2.0	1.0-2.0	---	---	---	Rare	
003LH: Lula-----	B		---	---	---	---	---	---	---
003SE: Stony Land-----	---		---	---	---	---	---	---	---
Talihina-----	D	January	0.5-2.0	1.0-2.5	---	---	---	---	None
		February	0.5-2.0	1.0-2.5	---	---	---	---	None
		March	0.5-2.0	1.0-2.5	---	---	---	---	None
		April	0.5-2.0	1.0-2.5	---	---	---	---	None
		November	0.5-2.0	1.0-2.5	---	---	---	---	None
		December	0.5-2.0	1.0-2.5	---	---	---	---	None
003WF: Woodson-----	D	January	0.3-0.7	1.8-2.2	---	---	---	---	None
		February	0.3-0.7	1.8-2.2	---	---	---	---	None
		March	0.3-0.7	1.8-2.2	---	---	---	---	None
		April	0.3-0.7	1.8-2.2	---	---	---	---	None
		December	0.3-0.7	1.8-2.2	---	---	---	---	None
011CA: Catoosa-----	B		---	---	---	---	---	---	---
059CM: Clareson-----	C		---	---	---	---	---	---	---
Eram-----	C	February	0.8-1.2	1.8-2.2	---	---	---	---	None
		March	0.8-1.2	1.8-2.2	---	---	---	---	None
		April	0.8-1.2	1.8-2.2	---	---	---	---	None
Bb: Bates-----	B		---	---	---	---	---	---	---
Bc: Bates-----	B		---	---	---	---	---	---	---
Cb: Catoosa-----	B		---	---	---	---	---	---	---
Cm:			---	---	---	---	---	---	---

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro- logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
Clareson-----	C		Ft	Ft	Ft				
Rock Outcrop-----	D		---	---	---	---	---	---	---
De: Dennis-----	C		---	---	---	---	---	---	---
Df: Dennis-----	C	January	2.0-3.0	2.8-3.8	---	---	---	---	None
		February	2.0-3.0	2.8-3.8	---	---	---	---	None
		March	2.0-3.0	2.8-3.8	---	---	---	---	None
		April	2.0-3.0	2.8-3.8	---	---	---	---	None
		December	2.0-3.0	2.8-3.8	---	---	---	---	None
Ec: Eram-----	C	January	2.0-3.0	2.8-3.8	---	---	---	---	None
		February	2.0-3.0	2.8-3.8	---	---	---	---	None
		March	2.0-3.0	2.8-3.8	---	---	---	---	None
		April	2.0-3.0	2.8-3.8	---	---	---	---	None
		December	2.0-3.0	2.8-3.8	---	---	---	---	None
Ed: Eram-----	C	January	2.0-3.0	2.8-3.8	---	---	---	---	None
		February	2.0-3.0	2.8-3.8	---	---	---	---	None
		March	2.0-3.0	2.8-3.8	---	---	---	---	None
		April	2.0-3.0	2.8-3.8	---	---	---	---	None
		December	2.0-3.0	2.8-3.8	---	---	---	---	None
Ef: Eram-----	C	January	2.0-3.0	2.8-3.8	---	---	---	---	None
		February	2.0-3.0	2.8-3.8	---	---	---	---	None
		March	2.0-3.0	2.8-3.8	---	---	---	---	None
		April	2.0-3.0	2.8-3.8	---	---	---	---	None
		December	2.0-3.0	2.8-3.8	---	---	---	---	None
Lebo-----	B	January	2.0-3.0	2.8-3.8	---	---	---	---	None
		February	2.0-3.0	2.8-3.8	---	---	---	---	None
		March	2.0-3.0	2.8-3.8	---	---	---	---	None
		April	2.0-3.0	2.8-3.8	---	---	---	---	None
		December	2.0-3.0	2.8-3.8	---	---	---	---	None
Hp: Hepler-----	C		---	---	---	---	---	---	---
INT: Aquolls-----	C	January	1.0-3.0	>6.0	---	---	---	---	None
		February	1.0-3.0	>6.0	---	---	---	---	None
		March	1.0-3.0	>6.0	---	---	---	Brief	Occasional
		April	---	---	---	---	---	Brief	Occasional
		May	---	---	---	---	---	Brief	Occasional
		June	---	---	---	---	---	Brief	Occasional
		July	---	---	---	---	---	Brief	Occasional
		November	1.0-3.0	>6.0	---	---	---	---	None
		December	1.0-3.0	>6.0	---	---	---	---	None
Ke: Kenoma-----	C	March	0.0	>6.0	0.0-0.8	Brief	Occasional	---	None
		April	0.0	>6.0	0.0-0.8	Brief	Occasional	---	None
		May	0.0	>6.0	0.0-0.8	Brief	Occasional	---	None
		June	0.0	>6.0	0.0-0.8	Brief	Occasional	---	None
La: Lanton-----	C		---	---	---	---	---	---	---
Lb: Lebo-----	B	January	1.0-2.0	>6.0	---	---	---	---	Rare
		February	1.0-2.0	>6.0	---	---	---	---	Rare
		March	1.0-2.0	>6.0	---	---	---	Very brief	Occasional
		April	1.0-2.0	>6.0	---	---	---	Very brief	Occasional
		May	1.0-2.0	>6.0	---	---	---	Very brief	Occasional
		June	---	---	---	---	---	Very brief	Occasional
		July	---	---	---	---	---	Very brief	Occasional
		August	---	---	---	---	---	Very brief	Occasional
		September	---	---	---	---	---	Very brief	Occasional
		October	---	---	---	---	---	Very brief	Occasional
		November	---	---	---	---	---	---	Rare
		December	1.0-2.0	>6.0	---	---	---	---	Rare
M-W: Miscellaneous Water-----	---		---	---	---	---	---	---	---
Mb:			---	---	---	---	---	---	---

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro- logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
Mason-----	B		Ft	Ft	Ft				
		January	---	---	---	---	---	---	Rare
		February	---	---	---	---	---	---	Rare
		March	---	---	---	---	---	---	Rare
		April	---	---	---	---	---	---	Rare
		May	---	---	---	---	---	---	Rare
		June	---	---	---	---	---	---	Rare
		July	---	---	---	---	---	---	Rare
		August	---	---	---	---	---	---	Rare
		September	---	---	---	---	---	---	Rare
		October	---	---	---	---	---	---	Rare
		November	---	---	---	---	---	---	Rare
		December	---	---	---	---	---	---	Rare
Nf: Newtonia-----	B		---	---	---	---	---	---	---
Ng: Newtonia-----	B		---	---	---	---	---	---	---
Nh: Newtonia-----	B		---	---	---	---	---	---	---
Oh: Okemah-----	C		---	---	---	---	---	---	---
		March	2.0-3.0	2.8-3.8	---	---	---	---	None
		April	2.0-3.0	2.8-3.8	---	---	---	---	None
		May	2.0-3.0	2.8-3.8	---	---	---	---	None
		June	2.0-3.0	2.8-3.8	---	---	---	---	None
Om: Kanima-----	C		---	---	---	---	---	---	---
Op: Kanima-----	C		---	---	---	---	---	---	---
Ot: Osage-----	D		---	---	---	---	---	---	---
		January	0.0-1.0	>6.0	---	---	---	Brief	Occasional
		February	0.0-1.0	>6.0	---	---	---	Brief	Occasional
		March	0.0-1.0	>6.0	---	Long	Occasional	Brief	Occasional
		April	0.0-1.0	>6.0	---	Long	Occasional	Brief	Occasional
		May	0.0-1.0	>6.0	---	Long	Occasional	Brief	Occasional
		November	0.0-1.0	>6.0	---	---	---	Brief	Occasional
		December	0.0-1.0	>6.0	---	---	---	Brief	Occasional
Ov: Osage-----	D		---	---	---	---	---	---	---
		January	0.0-1.0	>6.0	---	---	---	Brief	Occasional
		February	0.0-1.0	>6.0	---	---	---	Brief	Occasional
		March	0.0-1.0	>6.0	---	Long	Occasional	Brief	Occasional
		April	0.0-1.0	>6.0	---	Long	Occasional	Brief	Occasional
		May	0.0-1.0	>6.0	---	Long	Occasional	Brief	Occasional
		November	0.0-1.0	>6.0	---	---	---	Brief	Occasional
		December	0.0-1.0	>6.0	---	---	---	Brief	Occasional
Pc: Parsons-----	D		---	---	---	---	---	---	---
		January	0.5-1.5	1.0-2.0	---	---	---	---	None
		February	0.5-1.5	1.0-2.0	---	---	---	---	None
		March	0.5-1.5	1.0-2.0	---	---	---	---	None
		April	0.5-1.5	1.0-2.0	---	---	---	---	None
		December	0.5-1.5	1.0-2.0	---	---	---	---	None
Po: Pits, Quarries-----	---		---	---	---	---	---	---	---
Sn: Summit-----	C		---	---	---	---	---	---	---
		January	2.0-3.0	2.0-3.0	---	---	---	---	None
		February	2.0-3.0	2.0-3.0	---	---	---	---	None
		March	2.0-3.0	2.0-3.0	---	---	---	---	None
		April	2.0-3.0	2.0-3.0	---	---	---	---	None
		December	2.0-3.0	2.0-3.0	---	---	---	---	None
So: Summit-----	C		---	---	---	---	---	---	---
		January	2.0-3.0	2.0-3.0	---	---	---	---	None
		February	2.0-3.0	2.0-3.0	---	---	---	---	None
		March	2.0-3.0	2.0-3.0	---	---	---	---	None
		April	2.0-3.0	2.0-3.0	---	---	---	---	None
		December	2.0-3.0	2.0-3.0	---	---	---	---	None
Vb:									

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro- logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
Verdigris-----	B		Ft	Ft	Ft				
		January	---	---	---	---	---	Very brief	Occasional
		February	---	---	---	---	---	Very brief	Occasional
		March	---	---	---	---	---	Very brief	Occasional
		April	---	---	---	---	---	Very brief	Occasional
		May	---	---	---	---	---	Very brief	Occasional
		June	---	---	---	---	---	Very brief	Occasional
		July	---	---	---	---	---	Very brief	Rare
		August	---	---	---	---	---	Very brief	Rare
		September	---	---	---	---	---	Very brief	Rare
		October	---	---	---	---	---	Very brief	Rare
		November	---	---	---	---	---	Very brief	Rare
		December	---	---	---	---	---	Very brief	Occasional
Vc: Verdigris-----	B								
		January	---	---	---	---	---	Very brief	Frequent
		February	---	---	---	---	---	Very brief	Frequent
		March	---	---	---	---	---	Very brief	Frequent
		April	---	---	---	---	---	Very brief	Frequent
		May	---	---	---	---	---	Very brief	Frequent
		June	---	---	---	---	---	Very brief	Frequent
		July	---	---	---	---	---	Very brief	Occasional
		August	---	---	---	---	---	Very brief	Occasional
		September	---	---	---	---	---	Very brief	Occasional
		October	---	---	---	---	---	Very brief	Occasional
		November	---	---	---	---	---	Very brief	Occasional
		December	---	---	---	---	---	Very brief	Frequent
W: Water-----	---								
			---	---	---	---	---	---	---
We: Welda-----	C								
			---	---	---	---	---	---	---
Wo: Woodson-----	D								
		January	0.5-2.0	1.3-2.8	---	---	---	---	None
		February	0.5-2.0	1.3-2.8	---	---	---	---	None
		March	0.5-2.0	1.3-2.8	---	---	---	---	None
		April	0.5-2.0	1.3-2.8	---	---	---	---	None
		December	0.5-2.0	1.3-2.8	---	---	---	---	None

The following table gives estimates of various soil features. The estimates are used in land use planning that involves engineering considerations.

A restrictive layer is a nearly continuous layer that has one or more physical, chemical, or thermal properties that significantly impede the movement of water and air through the soil or that restrict roots or otherwise provide an unfavorable root environment. Examples are bedrock, cemented layers, dense layers, and frozen layers. The table indicates the hardness and thickness of the restrictive layer, both of which significantly affect the ease of excavation. Depth to top is the vertical distance from the soil surface to the upper boundary of the restrictive layer.

Potential for frost action is the likelihood of upward or lateral expansion of the soil caused by the formation of segregated ice lenses (frost heave) and the subsequent collapse of the soil and loss of strength on thawing. Frost action occurs when moisture moves into the freezing zone of the soil. Temperature, texture, density, permeability, content of organic matter, and depth to the water table are the most important factors considered in evaluating the potential for frost action. It is assumed that the soil is not insulated by vegetation or snow and is not artificially drained. Silty and highly structured, clayey soils that have a high water table in winter are the most susceptible to frost action. Well drained, very gravelly, or very sandy soils are the least susceptible. Frost heave and low soil strength during thawing cause damage to pavements and other rigid structures.

Risk of corrosion pertains to potential soil-induced electrochemical or chemical action that corrodes or weakens uncoated steel or concrete. The rate of corrosion of uncoated steel is related to such factors as soil moisture, particle-size distribution, acidity, and electrical conductivity of the soil. The rate of corrosion of concrete is based mainly on the sulfate and sodium content, texture, moisture content, and acidity of the soil. Special site examination and design may be needed if the combination of factors results in a severe hazard of corrosion. The steel or concrete in installations that intersect soil boundaries or soil layers is more susceptible to corrosion than the steel or concrete in installations that are entirely within one kind of soil or within one soil layer.

For uncoated steel, the risk of corrosion, expressed as low, moderate, or high, is based on soil drainage class, total acidity, electrical resistivity near field capacity, and electrical conductivity of the saturation extract.

For concrete, the risk of corrosion also is expressed as low, moderate, or high. It is based on soil texture, acidity, and amount of sulfates in the saturation extract.

SOIL FEATURES--Continued  
Linn County, Kansas

Map symbol and soil name	Restrictive layer				Potential for Frost action	Risk of corrosion	
	Kind	Depth to top	Thickness	Hardness		Uncoated Steel	Concrete
003CD:		In	In				
Collinsville----	4-20	Bedrock (lithic)	---	Strongly cemented	---	Low	Moderate
Collinsville	4-26	Bedrock (lithic)	---	Strongly cemented	---	Low	Moderate
Taxadjunct-----							
003DE:							
Dennis, eroded--	---	---	---	---	---	High	Moderate
003EH:							
Eram, eroded----	20-40	Bedrock (paralithic)	---	Weakly cemented	None	High	Moderate
003EK:							
Eram-----	20-40	Bedrock (paralithic)	---	Weakly cemented	None	High	Moderate
Clareson-----	20-40	Bedrock (lithic)	---	Indurated	---	High	Moderate
003LE:							
Leanna, drained-	---	---	---	---	---	High	Moderate
003LH:							
Lula-----	40-60	Bedrock (lithic)	---	Indurated	---	Moderate	Moderate
003SE:							
Stony Land-----	---	---	---	---	---	---	---
Talihina-----	10-20	Bedrock (paralithic)	---	Weakly cemented	---	High	Moderate
003WF:							
Woodson-----	---	---	---	---	Low	High	Moderate
011CA:							
Catoosa-----	20-40	Bedrock (lithic)	---	Indurated	---	Moderate	Moderate
059CM:							
Clareson-----	20-40	Bedrock (lithic)	---	Indurated	---	High	Moderate
Eram-----	20-40	Bedrock (paralithic)	---	Weakly cemented	None	High	Moderate
AED:							
Arents, Earthen Dam-----	---	---	---	---	---	---	---
Bb:							
Bates-----	20-40	Bedrock (paralithic)	---	---	---	Low	Moderate
Bc:							
Bates-----	20-40	Bedrock (paralithic)	---	Weakly cemented	---	Low	Moderate
Cb:							
Catoosa-----	20-40	Bedrock (lithic)	---	---	---	Moderate	Moderate
Cm:							
Clareson-----	20-40	Bedrock (lithic)	---	Indurated	---	High	Moderate
Rock Outcrop----	---	---	---	---	None	---	---
De:							
Dennis-----	---	---	---	---	---	High	Moderate
Df:							
Dennis-----	---	---	---	---	---	High	Moderate
Ec:							
Eram-----	20-40	Bedrock (paralithic)	---	---	None	High	Moderate
Ed:							
Eram-----	20-40	Bedrock (paralithic)	---	---	None	High	Moderate
Ef:							
Eram-----	20-40	Bedrock (paralithic)	---	Weakly cemented	None	High	Moderate
Lebo-----	20-40	Bedrock (paralithic)	---	Weakly cemented	None	Moderate	Low
Hp:							
Hepler-----	---	---	---	---	---	High	Moderate
INT:							
Aquolls-----	---	---	---	---	Low	---	---
Ke:							
Kenoma-----	---	---	---	---	---	High	Moderate
La:							
Lanton-----	---	---	---	---	None	High	Moderate
Lb:							
Lebo-----	20-40	Bedrock (paralithic)	---	Weakly cemented	None	Moderate	Low
M-W:							
Miscellaneous Water-----	---	---	---	---	---	---	---
Mb:							
Mason-----	---	---	---	---	---	Moderate	Moderate
Nf:							
Newtonia-----	---	---	---	---	---	Moderate	Moderate
Ng:							
Newtonia-----	---	---	---	---	---	Moderate	Moderate
Nh:							
Newtonia-----	---	---	---	---	---	Moderate	Moderate
Oh:							
Okemah-----	---	---	---	---	---	High	Moderate
Om:							
Kanima-----	---	---	---	---	None	Moderate	Low
Op:							
Kanima-----	---	---	---	---	None	Moderate	Low

Map symbol and soil name	Restrictive layer				Potential for Frost action	Risk of corrosion	
	Kind	Depth to top	Thickness	Hardness		Uncoated Steel	Concrete
Ot:		In	In				
Osage-----	---	---	---	---	---	High	Moderate
Ov:							
Osage-----	---	---	---	---	---	High	Moderate
Pc:							
Parsons-----	---	---	---	---	None	High	Moderate
Po:							
Pits, Quarries--	---	---	---	---	---	---	---
Sn:							
Summit-----	---	---	---	---	---	High	Low
So:							
Summit-----	---	---	---	---	---	High	Low
Vb:							
Verdigris-----	---	---	---	---	---	Low	Low
Vc:							
Verdigris-----	---	---	---	---	---	Low	Low
W:							
Water-----	---	---	---	---	Low	---	---
We:							
Welda-----	---	---	---	---	Moderate	Moderate	Moderate
Wo:							
Woodson-----	---	---	---	---	Low	High	Moderate

WATER MANAGEMENT  
Linn County, Kansas

The soils of the survey area are rated in the Water Management table according to limitations that affect their suitability for water management. Soils are rated for pond reservoir areas, drainage, irrigation, terraces and diversions, and grassed waterways. Restrictive features that affect each soil for the specified use is also provided in the table.

The ratings in the table are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Moderately limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Limited indicates that the soil has one or more features that are significant limitations for the specified use. The limitations can be overcome, but generally require special design, soil reclamation, or installation procedures that may result in additional expense. Fair performance and moderate to high maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Limitation class terms, such as very limited or limited, etc., limitation ratings, and numerical ratings are shown for each soil feature listed. As many as three soil features may be listed for each soil component if applicable. The overall limitation rating for the soil component is based on the most severe limitation.

Pond reservoir areas hold water behind a dam or embankment. Soils best suited to this use have low seepage potential in the upper 60 inches. The seepage potential is determined by the permeability of the soil and the depth to fractured bedrock or other permeable material. Excessive slope can affect the storage capacity of the reservoir area.

Embankments, dikes, and levees are raised structures of soil material, generally less than 20 feet high, constructed to impound water or to protect land against overflow. In this table, the soils are rated as a source of material for embankment fill. The ratings apply to the soil material below the surface layer to a depth of about 5 feet. It is assumed that soil layers will be uniformly mixed and compacted during construction.

The ratings do not indicate the ability of the natural soil to support an embankment. Soil properties to a depth even greater than the height of the embankment can affect performance and safety of the embankment. Generally, deeper onsite investigation is needed to determine these properties.

Soil material in embankments must be resistant to seepage, piping, and erosion and have favorable compaction characteristics. Unfavorable features include less than 5 feet of suitable material and a high content of stones or boulders, organic matter, or salts or sodium. A high water table affects the amount of usable material. It also affects traffic ability.

Aquifer-fed excavated ponds are pits or dugouts that extend to a ground-water aquifer or to a depth below a permanent water table. Excluded are ponds that are fed only by surface runoff and embankment ponds that impound water 3 feet or more above the original surface. Excavated ponds are affected by depth to a permanent water table, permeability of the aquifer, and quality of the water as inferred from the salinity of the soil. Depth to bedrock and the content of large stones affect the ease of excavation.

Drainage is the removal of excess surface and subsurface water from the soil. How easily and effectively the soil is drained depends on the depth to bedrock, to a cemented pan, or to other layers that affect the rate of water movement; permeability; depth to a high water table or depth of standing water if the soil is subject to ponding; slope; susceptibility to flooding; subsidence of organic layers; and the potential for frost action. Excavating and grading and the stability of ditch banks are affected by depth to bedrock or to a cemented pan, large stones, slope, and the hazard of cutbanks caving. The productivity of the soil after drainage is adversely affected by extreme acidity or by toxic substances in the root zone, such as salts, sodium, and sulfur. Availability of drainage outlets is not considered in the ratings.

Irrigation is the controlled application of water to supplement rainfall and support plant growth. The design and management of an irrigation system are affected by depth to the water table, the need for drainage, flooding, available water capacity, intake rate, permeability, erosion hazard, and slope. The construction of a system is affected by large stones and depth to bedrock or to a cemented pan. The performance of a system is affected by the depth of the root zone, the amount of salts or sodium, and soil reaction.

Terraces and diversions are embankments or a combination of channels and ridges constructed across a slope to control erosion and conserve moisture by intercepting runoff. Slope, wetness, large stones, and depth to bedrock or to a cemented pan affect the construction of terraces and diversions. A restricted rooting depth, a very limited hazard of wind erosion or water erosion, an excessively coarse texture, and restricted permeability adversely affect maintenance.

Grassed waterways are natural or constructed channels, generally broad and shallow, which conduct surface water to outlets at a non-erosive velocity. Large stones, wetness, slope, and depth to bedrock or to a cemented pan affect the construction of grassed waterways. A hazard of wind erosion, low available water capacity, restricted rooting depth, toxic substances such as salts and sodium, and restricted permeability adversely affect the growth and maintenance of the grass after construction.



WATER MANAGEMENT--Continued  
Linn County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
003CD: Collinsville----	Limitation: deep to water	Limitation: large stones slope depth to rock	Limitation: large stones slope depth to rock	Limitation: large stones slope depth to rock
Collinsville Taxadjunct-----	Limitation:  deep to water	Limitation:  large stones slope depth to rock	Limitation:  large stones slope depth to rock	Limitation:  large stones slope depth to rock
003DE: Dennis, eroded--	Limitation: percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
003EH: Eram, eroded----	Limitation: percs slowly slope depth to rock	Limitation: percs slowly slope wetness	Limitation: erodes easily wetness depth to rock	Limitation: erodes easily wetness depth to rock
003EK: Eram-----	Limitation: percs slowly slope depth to rock	Limitation: percs slowly slope wetness	Limitation: erodes easily wetness depth to rock	Limitation: erodes easily wetness depth to rock
Clareson-----	Limitation: deep to water	Limitation: large stones slope droughty	Limitation: large stones slope depth to rock	Limitation: large stones slope droughty
003LE: Leanna, drained--	Limitation: flooding percs slowly	Limitation: flooding percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
003LH: Lula-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily large stones	Limitation: erodes easily large stones
003SE: Stony Land-----	---	---	---	---
Talihina-----	Limitation: percs slowly slope depth to rock	Limitation: percs slowly slope wetness	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope wetness
003WF: Woodson-----	Limitation: percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
011CA: Catoosa-----	Limitation: deep to water	Limitation: erodes easily depth to rock	Limitation: erodes easily depth to rock	Limitation: erodes easily depth to rock
059CM: Clareson-----	Limitation: deep to water	Limitation: large stones slope droughty	Limitation: large stones slope depth to rock	Limitation: large stones slope droughty
Eram-----	Limitation: percs slowly slope depth to rock	Limitation: percs slowly slope wetness	Limitation: erodes easily wetness depth to rock	Limitation: erodes easily wetness depth to rock
AED: Arents, Earthen Dam-----	---	---	---	---
Bb: Bates-----	Limitation: deep to water	Limitation: depth to rock	Limitation: depth to rock	Limitation: depth to rock
Bc: Bates-----	Limitation: deep to water	Limitation: slope depth to rock	Limitation: depth to rock	Limitation: depth to rock
Cb: Catoosa-----	Limitation: deep to water	Limitation: erodes easily depth to rock	Limitation: erodes easily depth to rock	Limitation: erodes easily depth to rock
Cm: Clareson-----	Limitation: deep to water	Limitation: large stones slope droughty	Limitation: large stones slope depth to rock	Limitation: large stones slope droughty
Rock Outcrop----	---	---	---	---

WATER MANAGEMENT--Continued  
Linn County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
De: Dennis-----	Limitation: percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
Df: Dennis-----	Limitation: percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
Ec: Eram-----	Limitation: percs slowly depth to rock	Limitation: percs slowly wetness depth to rock	Limitation: erodes easily wetness depth to rock	Limitation: erodes easily wetness depth to rock
Ed: Eram-----	Limitation: percs slowly slope depth to rock	Limitation: percs slowly slope wetness	Limitation: erodes easily wetness depth to rock	Limitation: erodes easily wetness depth to rock
Ef: Eram-----	Limitation: percs slowly slope depth to rock	Limitation: percs slowly slope wetness	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope wetness
Lebo-----	Limitation: deep to water	Limitation: slope depth to rock	Limitation: slope depth to rock	Limitation: slope depth to rock
Hp: Hepler-----	Limitation: flooding	Limitation: erodes easily flooding wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness
INT: Aquolls-----	---	---	---	---
Ke: Kenoma-----	Limitation: deep to water	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
La: Lanton-----	Limitation: flooding	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness
Lb: Lebo-----	Limitation: deep to water	Limitation: slope depth to rock	Limitation: slope depth to rock	Limitation: slope depth to rock
M-W: Miscellaneous Water-----	---	---	---	---
Mb: Mason-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
Nf: Newtonia-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
Ng: Newtonia-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
Nh: Newtonia-----	Limitation: deep to water	Limitation: erodes easily slope	Limitation: erodes easily	Limitation: erodes easily
Oh: Okemah-----	Limitation: percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
Om: Kanima-----	Limitation: deep to water	Limitation: slope droughty	Limitation: slope	Limitation: slope droughty
Op: Kanima-----	Limitation: deep to water	Limitation: slope droughty	Limitation: slope	Limitation: slope droughty
Ot: Osage-----	Limitation: flooding percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness

WATER MANAGEMENT--Continued  
Linn County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
Ov: Osage-----	Limitation: flooding percs slowly	Limitation: percs slowly slow intake wetness	Limitation: percs slowly wetness	Limitation: percs slowly wetness
Pc: Parsons-----	Limitation: percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
Po: Pits, Quarries--	---	---	---	---
Sn: Summit-----	Limitation: percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly
So: Summit-----	Limitation: percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly
Vb: Verdigris-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
Vc: Verdigris-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
W: Water-----	---	---	---	---
We: Welda-----	Limitation: deep to water	Limitation: erodes easily slope	Limitation: erodes easily	Limitation: erodes easily
Wo: Woodson-----	Limitation: percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness

WATER MANAGEMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
003CD: Collinsville-----	65	Very limited Seepage Depth to bedrock	1.00 1.00	Very limited Thin layer	1.00	Very limited Deep to water	1.00
Collinsville Taxadjunct-----	20	Very limited  Seepage Depth to bedrock	 1.00 0.99	Somewhat limited  Thin layer	 0.99	Very limited  Deep to water	 1.00
003DE: Dennis, eroded-----	95	Somewhat limited Seepage	0.70	Very limited Depth to saturated zone	1.00	Very limited Deep to water	1.00
003EH: Eram, eroded-----	85	Somewhat limited Depth to bedrock  Seepage	0.06  0.05	Very limited Depth to saturated zone Thin layer	1.00  0.77	Very limited Deep to water	1.00
003EK: Eram-----	60	Somewhat limited Depth to bedrock  Seepage	0.06  0.05	Very limited Depth to saturated zone Thin layer Hard to pack	1.00  0.77 0.76	Very limited Deep to water	1.00
Clareson-----	20	Somewhat limited Depth to bedrock	0.98	Very limited Content of large stones Hard to pack Thin layer	1.00 1.00 0.98	Very limited Deep to water	1.00
003LE: Leanna, drained-----	88	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00 0.55	Very limited Deep to water	1.00
003LH: Lula-----	85	Somewhat limited Depth to bedrock Seepage	0.13 0.05	Somewhat limited Piping Thin layer	0.28 0.13	Very limited Deep to water	1.00
003SE: Stony Land-----	60	Not rated		Not rated		Not rated	
Talihina-----	20	Very limited Seepage Depth to bedrock  Slope	1.00 0.66  0.01	Very limited Thin layer Depth to saturated zone Hard to pack	1.00 1.00  0.68	Very limited Deep to water	1.00
003WF: Woodson-----	85	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.97	Very limited Deep to water	1.00
011CA: Catoosa-----	85	Somewhat limited Depth to bedrock Seepage	0.93 0.05	Somewhat limited Thin layer	0.94	Very limited Deep to water	1.00
059CM: Clareson-----	55	Somewhat limited Depth to bedrock	0.95	Somewhat limited Thin layer Hard to pack Content of large stones	0.95 0.41 0.16	Very limited Deep to water	1.00
Eram-----	30	Somewhat limited Depth to bedrock	0.02	Very limited Depth to saturated zone Hard to pack Thin layer	1.00  0.99 0.56	Very limited Deep to water	1.00

WATER MANAGEMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
Bb: Bates-----	85	Somewhat limited Depth to bedrock Seepage	0.09 0.05	Somewhat limited Thin layer	0.83	Very limited Deep to water	1.00
Bc: Bates-----	85	Somewhat limited Depth to bedrock Seepage	0.09 0.01	Somewhat limited Thin layer	0.83	Very limited Deep to water	1.00
Cb: Catoosa-----	85	Somewhat limited Depth to bedrock Seepage	0.88 0.70	Somewhat limited Thin layer Hard to pack	0.88 0.40	Very limited Deep to water	1.00
Cm: Clareson-----	60	Somewhat limited Depth to bedrock Seepage Slope	0.77 0.05 0.00	Very limited Hard to pack Thin layer Content of large stones	1.00 0.77 0.26	Very limited Deep to water	1.00
Rock Outcrop-----	20	Not rated		Not rated		Not rated	
De: Dennis-----	90	Somewhat limited Seepage	0.05	Somewhat limited Depth to saturated zone Hard to pack	0.93 0.59	Very limited Deep to water	1.00
Df: Dennis-----	85	Somewhat limited Seepage	0.05	Somewhat limited Depth to saturated zone Hard to pack	0.93 0.63	Very limited Deep to water	1.00
Ec: Eram-----	85	Somewhat limited Depth to bedrock Seepage	0.19 0.05	Somewhat limited Hard to pack Depth to saturated zone Thin layer	0.98 0.93 0.93	Very limited Deep to water	1.00
Ed: Eram-----	85	Somewhat limited Depth to bedrock  Seepage	0.19  0.05	Somewhat limited Depth to saturated zone Thin layer Hard to pack	0.93  0.93 0.50	Very limited Deep to water	1.00
Ef: Eram-----	50	Somewhat limited Depth to bedrock Seepage	0.19 0.05	Somewhat limited Hard to pack Depth to saturated zone Thin layer	0.98 0.93 0.93	Very limited Deep to water	1.00
Lebo-----	30	Somewhat limited Seepage Slope Depth to bedrock	0.05 0.02 0.02	Somewhat limited Thin layer	0.56	Very limited Deep to water	1.00
Hp: Hepler-----	90	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone	1.00	Somewhat limited Slow refill  Cutbanks cave Deep to water	0.95  0.10 0.00
INT: Aquolls-----	100	Very limited Seepage	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Cutbanks cave	0.10

WATER MANAGEMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ke: Kenoma-----	90	Not limited		Ponding	1.00		
La: Lanton-----	90	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack	0.70	Very limited Deep to water	1.00
Lb: Lebo-----	85	Somewhat limited Slope Seepage Depth to bedrock	0.21 0.05 0.02	Very limited Depth to saturated zone Piping	1.00 0.32	Somewhat limited Slow refill Cutbanks cave	0.95 0.10
M-W: Miscellaneous Water-	100	Not rated		Somewhat limited Thin layer	0.56	Very limited Deep to water	1.00
Mb: Mason-----	85	Somewhat limited Seepage	0.70	Not rated		Not rated	
Nf: Newtonia-----	90	Somewhat limited Seepage	0.70	Not limited		Very limited Deep to water	1.00
Ng: Newtonia-----	90	Somewhat limited Seepage	0.70	Not limited		Very limited Deep to water	1.00
Nh: Newtonia-----	85	Somewhat limited Seepage	0.70	Not limited		Very limited Deep to water	1.00
Oh: Okemah-----	90	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack Depth to saturated zone	0.96 0.93	Very limited Deep to water	1.00
Om: Kanima-----	100	Somewhat limited Slope Seepage	0.64 0.05	Not limited		Very limited Deep to water	1.00
Op: Kanima-----	100	Somewhat limited Seepage	0.05	Not limited		Very limited Deep to water	1.00
Ot: Osage-----	85	Not limited		Very limited Ponding Depth to saturated zone Hard to pack	1.00 1.00 1.00	Somewhat limited Slow refill Cutbanks cave	0.95 0.10
Ov: Osage-----	90	Not limited		Very limited Ponding Depth to saturated zone Hard to pack	1.00 1.00 1.00	Very limited Slow refill Cutbanks cave	1.00 0.10
Pc: Parsons-----	90	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.89	Very limited Deep to water	1.00
Po: Pits, Quarries-----	100	Not rated		Not rated		Not rated	

WATER MANAGEMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Sn: Summit-----	85	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack Depth to saturated zone	0.91 0.86	Very limited Deep to water	1.00
So: Summit-----	85	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack Depth to saturated zone	0.92 0.86	Very limited Deep to water	1.00
Vb: Verdigris-----	90	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.34	Very limited Deep to water	1.00
Vc: Verdigris-----	85	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.34	Very limited Deep to water	1.00
W: Water-----	100	Not rated		Not rated		Not rated	
We: Welda-----	90	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack	0.45	Very limited Deep to water	1.00
Wo: Woodson-----	85	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.97	Very limited Deep to water	1.00

SANITARY FACILITIES  
Linn County, Kansas

Sanitary Facilities

The following tables show the degree and kind of soil limitations that affect septic tank absorption fields, sewage lagoons, sanitary landfills, and daily cover for landfill. The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect these uses. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Septic tank absorption fields are areas in which effluent from a septic tank is distributed into the soil through subsurface tiles or perforated pipe. Only that part of the soil between depths of 24 and 60 inches is evaluated. The ratings are based on the soil properties that affect absorption of the effluent, construction and maintenance of the system, and public health. Permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, and flooding affect absorption of the effluent. Stones and boulders, ice, and bedrock or a cemented pan interfere with installation. Subsidence interferes with installation and maintenance. Excessive slope may cause lateral seepage and surfacing of the effluent in downslope areas.

Some soils are underlain by loose sand and gravel or fractured bedrock at a depth of less than 4 feet below the distribution lines. In these soils the absorption field may not adequately filter the effluent, particularly when the system is new. As a result, the ground water may become contaminated.

Sewage lagoons are shallow ponds constructed to hold sewage while aerobic bacteria decompose the solid and liquid wastes. Lagoons should have a nearly level floor surrounded by cut slopes or embankments of compacted soil. Nearly impervious soil material for the lagoon floor and sides is required to minimize seepage and contamination of ground water. Considered in the ratings are slope, permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, flooding, large stones, and content of organic matter.

Soil permeability is a critical property affecting the suitability for sewage lagoons. Most porous soils eventually become sealed when they are used as sites for sewage lagoons. Until sealing occurs, however, the hazard of pollution is severe. Soils that have a permeability rate of more than 2 inches per hour are too porous for the proper functioning of sewage lagoons. In these soils, seepage of the effluent can result in contamination of the ground water. Ground-water contamination is also a hazard if fractured bedrock is within a depth of 40 inches, if the water table is high enough to raise the level of sewage in the lagoon, or if floodwater overtops the lagoon.

A high content of organic matter is detrimental to proper functioning of the lagoon because it inhibits aerobic activity. Slope, bedrock, and cemented pans can cause construction problems, and large stones can hinder compaction of the lagoon floor. If the lagoon is to be uniformly deep throughout, the slope must be gentle enough and the soil material must be thick enough over bedrock or a cemented pan to make land smoothing practical.

A trench sanitary landfill is an area where solid waste is placed in successive layers in an excavated trench. The waste is spread, compacted, and covered daily with a thin layer of soil excavated at the site. When the trench is full, a final cover of soil material at least 2 feet thick is placed over the landfill. The ratings in the table are based on the soil properties that affect the risk of pollution, the ease of excavation, trafficability, and revegetation. These properties include permeability, depth to bedrock or a cemented pan, depth to a water table, ponding, slope, flooding, texture, stones and boulders, highly organic layers, soil reaction, and content of salts and sodium. Unless otherwise stated, the ratings apply only to that part of the soil within a depth of about 6 feet. For deeper trenches, onsite investigation may be needed.

Hard, nonrippable bedrock, creviced bedrock, or highly permeable strata in or directly below the proposed trench bottom can affect the ease of excavation and the hazard of ground-water pollution. Slope affects construction of the trenches and the movement of surface water around the landfill. It also affects the construction and performance of roads in areas of the landfill.

Soil texture and consistence affect the ease with which the trench is dug and the ease with which the soil can be used as daily or final cover. They determine the workability of the soil when dry and when wet. Soils that are plastic and sticky when wet are difficult to excavate, grade, or compact and are difficult to place as a uniformly thick cover over a layer of refuse.

The soil material used as the final cover for a trench landfill should be suitable for plants. It should not have excess sodium or salts and should not be too acid. The surface layer generally has the best workability, the highest content of organic matter, and the best potential for plants. Material from the surface layer should be stockpiled for use as the final cover.



SANITARY FACILITIES  
Linn County, Kansas

In an area sanitary landfill, solid waste is placed in successive layers on the surface of the soil. The waste is spread, compacted, and covered daily with a thin layer of soil from a source away from the site. A final cover of soil material at least 2 feet thick is placed over the completed landfill. The ratings in the table are based on the soil properties that affect trafficability and the risk of pollution. These properties include flooding, permeability, depth to a water table, ponding, slope, and depth to bedrock or a cemented pan.

Flooding is a serious problem because it can result in pollution in areas downstream from the landfill. If permeability is too rapid or if fractured bedrock, a fractured cemented pan, or the water table is close to the surface, the leachate can contaminate the water supply. Slope is a consideration because of the extra grading required to maintain roads in the steeper areas of the landfill. Also, leachate may flow along the surface of the soils in the steeper areas and cause difficult seepage problems.

Daily cover for landfill is the soil material that is used to cover compacted solid waste in an area sanitary landfill. The soil material is obtained offsite, transported to the landfill, and spread over the waste. The ratings in the table also apply to the final cover for a landfill. They are based on the soil properties that affect workability, the ease of digging, and the ease of moving and spreading the material over the refuse daily during wet and dry periods. These properties include soil texture, depth to a water table, ponding, rock fragments, slope, depth to bedrock or a cemented pan, reaction, and content of salts, sodium, or lime.

Loamy or silty soils that are free of large stones and excess gravel are the best cover for a landfill. Clayey soils may be sticky and difficult to spread; sandy soils are subject to wind erosion.

Slope affects the ease of excavation and of moving the cover material. Also, it can influence runoff, erosion, and reclamation of the borrow area.

After soil material has been removed, the soil material remaining in the borrow area must be thick enough over bedrock, a cemented pan, or the water table to permit revegetation. The soil material used as the final cover for a landfill should be suitable for plants. It should not have excess sodium, salts, or lime and should not be too acid.

SANITARY FACILITIES--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
003CD: Collinsville-----	65	Very limited Depth to bedrock	1.00	Very limited Depth to hard bedrock	1.00
Collinsville Taxadjunct-----	20	Slope Very limited Depth to bedrock	0.04 1.00	Slope Very limited Depth to hard bedrock	1.00 1.00
003DE: Dennis, eroded-----	95	Restricted permeability Depth to saturated zone	1.00 1.00	Seepage Slope	0.91
003EH: Eram, eroded-----	85	Very limited Depth to bedrock Depth to saturated zone Restricted permeability	1.00 1.00 1.00	Very limited Depth to soft bedrock Slope	1.00 0.91
003EK: Eram-----	60	Very limited Depth to bedrock Depth to saturated zone Restricted permeability Slope	1.00 1.00 1.00 0.00	Very limited Depth to soft bedrock Slope	1.00 1.00
Clareson-----	20	Very limited Restricted permeability Depth to bedrock Content of large stones Slope	1.00 1.00 1.00 1.00 0.00	Very limited Depth to hard bedrock Content of large stones Slope	1.00 1.00 1.00
003LE: Leanna, drained-----	88	Very limited Flooding Restricted permeability Depth to saturated zone	1.00 1.00 1.00	Very limited Flooding	1.00
003LH: Lula-----	85	Very limited Restricted permeability Depth to bedrock	1.00 0.83	Somewhat limited Depth to hard bedrock Slope	0.54 0.00
003SE: Stony Land-----	60	Not rated		Not rated	
Talihina-----	20	Very limited Depth to bedrock Depth to saturated zone Slope	1.00 1.00 0.84	Very limited Depth to soft bedrock Slope	1.00 1.00
003WF: Woodson-----	85	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Somewhat limited Slope	0.00
011CA: Catoosa-----	85	Very limited Depth to bedrock Restricted permeability	1.00 1.00	Very limited Depth to hard bedrock Seepage Slope	1.00 0.50 0.00
059CM: Clareson-----	55	Very limited Restricted permeability	1.00	Very limited Depth to hard bedrock	1.00

SANITARY FACILITIES--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Eram-----	30	Depth to bedrock	1.00	Slope	1.00
		Content of large stones	0.16	Content of large stones	0.38
		Slope	0.04	Seepage	0.32
		Very limited		Very limited	
		Restricted permeability	1.00	Depth to soft bedrock	1.00
		Depth to bedrock	1.00	Slope	1.00
AED: Arents, Earthen Dam-	100	Depth to saturated zone	1.00		
		Slope	0.00		
Bb: Bates-----	85	Not rated		Not rated	
Bc: Bates-----	85	Very limited		Very limited	
		Restricted permeability	1.00	Depth to soft bedrock	1.00
Cb: Catoosa-----	85	Depth to bedrock	1.00	Slope	0.09
Cm: Clareson-----	85	Very limited		Very limited	
		Restricted permeability	1.00	Depth to soft bedrock	1.00
Cm: Clareson-----	60	Depth to bedrock	1.00	Slope	0.91
Rock Outcrop-----	20	Very limited		Very limited	
		Depth to bedrock	1.00	Depth to hard bedrock	1.00
De: Dennis-----	90	Restricted permeability	1.00	Slope	1.00
		Slope	0.37	Content of large stones	0.00
De: Dennis-----	90	Content of large stones	0.26		
		Not rated		Not rated	
Df: Dennis-----	85	Very limited		Somewhat limited	
		Depth to saturated zone	1.00	Depth to saturated zone	0.64
Ec: Eram-----	85	Restricted permeability	1.00	Seepage	0.50
				Slope	0.00
Ec: Eram-----	85	Very limited		Somewhat limited	
		Depth to bedrock	1.00	Slope	0.67
Ed: Eram-----	85	Depth to saturated zone	1.00	Depth to saturated zone	0.64
		Restricted permeability	1.00	Seepage	0.50
Ef: Eram-----	50	Very limited		Very limited	
		Depth to bedrock	1.00	Depth to soft bedrock	1.00
Ef: Eram-----	50	Depth to saturated zone	1.00	Slope	1.00

SANITARY FACILITIES--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Lebo-----	30	Restricted permeability	1.00	Depth to saturated zone	0.64
		Slope	0.04		
		Very limited		Very limited	
		Restricted	1.00	Depth to soft	1.00
Hp: Hepler-----	90	permeability	1.00	bedrock	1.00
		Depth to bedrock	1.00	Slope	1.00
		Slope	0.96		
		Very limited		Very limited	
INT: Aquolls-----	100	Flooding	1.00	Flooding	1.00
		Depth to	1.00	Depth to	1.00
		saturated zone		saturated zone	
		Restricted	1.00		
Ke: Kenoma-----	90	permeability			
		Very limited		Somewhat limited	
		Restricted	1.00	Slope	0.09
		permeability			
La: Lanton-----	90	Very limited		Very limited	
		Flooding	1.00	Flooding	1.00
		Restricted	1.00	Depth to	1.00
		permeability		saturated zone	
Lb: Lebo-----	85	Depth to	1.00		
		saturated zone		Very limited	
		Very limited		Depth to soft	1.00
		Restricted	1.00	bedrock	1.00
M-W: Miscellaneous Water-	100	permeability	1.00	Slope	
		Depth to bedrock	1.00		
		Slope	1.00		
		Not rated		Not rated	
Mb: Mason-----	85	Very limited		Somewhat limited	
		Restricted	1.00	Seepage	0.50
		permeability			
		Flooding	0.40	Flooding	0.40
Nf: Newtonia-----	90	Very limited		Somewhat limited	
		Restricted	1.00	Seepage	0.50
		permeability			
		Very limited		Somewhat limited	
Ng: Newtonia-----	90	Restricted	1.00	Seepage	0.50
		permeability			
		Very limited		Slope	0.09
		Restricted	1.00		
Nh: Newtonia-----	85	permeability		Somewhat limited	
		Very limited		Slope	0.91
		Restricted	1.00		
		permeability		Seepage	0.50
Oh: Okemah-----	90	Very limited		Somewhat limited	
		Restricted	1.00	Depth to	0.64
		permeability		saturated zone	
		Depth to	1.00	Slope	0.00
Om: Kanima-----	100	saturated zone			
		Very limited		Very limited	
		Slope	1.00	Slope	1.00
		Restricted	1.00		
Op: Kanima-----	100	permeability			
		Very limited		Very limited	
		Restricted	1.00	Slope	1.00
		permeability			
Ot: Osage-----	85	Slope	0.04		
		Very limited		Very limited	
		Flooding	1.00	Ponding	1.00
		Restricted	1.00	Flooding	1.00
		permeability			

SANITARY FACILITIES--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Ov: Osage-----	90	Ponding	1.00	Depth to saturated zone	1.00
		Depth to saturated zone	1.00		
		Very limited Flooding	1.00	Very limited Ponding	1.00
		Restricted permeability	1.00	Flooding	1.00
		Ponding	1.00	Depth to saturated zone	1.00
Pc: Parsons-----	90	Depth to saturated zone	1.00		
		Very limited Restricted permeability	1.00	Not limited	
		Depth to saturated zone	1.00		
Po: Pits, Quarries-----	100	Not rated		Not rated	
Sn: Summit-----	85	Very limited Restricted permeability	1.00	Somewhat limited Depth to saturated zone	0.81
		Depth to saturated zone	1.00	Slope	0.09
So: Summit-----	85	Very limited Restricted permeability	1.00	Somewhat limited Slope	0.91
		Depth to saturated zone	1.00	Depth to saturated zone	0.81
Vb: Verdigris-----	90	Very limited Flooding	1.00	Very limited Flooding	1.00
		Restricted permeability	1.00	Seepage	0.50
Vc: Verdigris-----	85	Very limited Flooding	1.00	Very limited Flooding	1.00
		Restricted permeability	1.00	Seepage	0.50
W: Water-----	100	Not rated		Not rated	
We: Welda-----	90	Very limited Restricted permeability	1.00	Somewhat limited Slope	0.33
Wo: Woodson-----	85	Very limited Restricted permeability	1.00	Not limited	
		Depth to saturated zone	1.00		

SANITARY FACILITIES--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
003CD: Collinsville-----	65	Very limited Depth to bedrock Seepage Slope	1.00 1.00 0.04	Very limited Depth to bedrock Slope	1.00 0.04	Very limited Depth to bedrock Seepage Slope	1.00 0.50 0.04
Collinsville Taxadjunct-----	20	Very limited  Depth to bedrock Seepage	 1.00 1.00	Very limited  Seepage Depth to bedrock	 1.00 1.00	Very limited  Depth to bedrock Seepage	 1.00 0.50
003DE: Dennis, eroded-----	95	Very limited Depth to saturated zone Too clayey	1.00 1.00	Very limited Depth to saturated zone	1.00	Very limited Too clayey  Depth to saturated zone	1.00 1.00
003EH: Eram, eroded-----	85	Very limited Depth to saturated zone Depth to bedrock  Too clayey	1.00 1.00 0.50	Very limited Depth to saturated zone Depth to bedrock	1.00 1.00	Very limited Depth to bedrock  Depth to saturated zone Too clayey	1.00 1.00 0.50
003EK: Eram-----	60	Very limited Depth to saturated zone Depth to bedrock  Too clayey Slope	1.00 1.00 0.50 0.00	Very limited Depth to saturated zone Depth to bedrock  Slope	1.00 1.00 0.00	Very limited Depth to bedrock  Depth to saturated zone Hard to compact Too clayey Slope	1.00 1.00 1.00 0.50 0.00
Clareson-----	20	Very limited Depth to bedrock Too clayey Content of large stones Seepage  Slope	1.00 1.00 1.00 1.00 0.00	Very limited Depth to bedrock Slope	1.00 0.00	Very limited Depth to bedrock Too clayey Hard to compact  Content of large stones Slope	1.00 1.00 1.00 1.00 1.00 0.00
003LE: Leanna, drained-----	88	Very limited Flooding Depth to saturated zone Too clayey	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Too clayey Depth to saturated zone Hard to compact	1.00 1.00 1.00
003LH: Lula-----	85	Very limited Depth to bedrock Seepage Too clayey	1.00 1.00 0.50	Somewhat limited Depth to bedrock	0.54	Somewhat limited Depth to bedrock Too clayey	0.54 0.50
003SE: Stony Land-----	60	Not rated		Not rated		Not rated	
Talihina-----	20	Very limited Depth to saturated zone Depth to bedrock  Slope Too clayey	1.00 1.00 0.84 0.50	Very limited Depth to saturated zone Depth to bedrock  Slope	1.00 1.00 0.84	Very limited Depth to bedrock  Depth to saturated zone Hard to compact Slope Too clayey	1.00 1.00 1.00 0.84 0.50
003WF: Woodson-----	85	Very limited Depth to saturated zone Too clayey	1.00 1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone Too clayey Hard to compact	1.00 1.00 1.00
011CA: Catoosa-----	85	Very limited Depth to bedrock Seepage Too clayey	1.00 1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Hard to compact Too clayey	1.00 1.00 0.50
059CM: Clareson-----	55	Very limited Depth to bedrock Seepage Too clayey Content of large stones Slope	1.00 1.00 0.50 0.16 0.04	Very limited Depth to bedrock Slope	1.00 0.04	Very limited Depth to bedrock Hard to compact Too clayey Content of large stones Slope	1.00 1.00 0.50 0.16 0.04
Eram-----	30	Very limited		Very limited		Very limited	

SANITARY FACILITIES--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
AED: Arents, Earthen Dam-	100	Depth to saturated zone	1.00	Depth to saturated zone	1.00	Depth to bedrock	1.00
		Depth to bedrock	1.00	Depth to bedrock	1.00	Depth to saturated zone	1.00
		Too clayey	1.00	Slope	0.00	Too clayey	1.00
		Slope	0.00			Hard to compact	1.00
Bb: Bates-----	85	Very limited Depth to bedrock Too clayey	1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey	1.00 0.50
Bc: Bates-----	85	Very limited Depth to bedrock Too clayey	1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey	1.00 0.50
Cb: Catoosa-----	85	Very limited Depth to bedrock Seepage Too clayey	1.00 1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Hard to compact Too clayey	1.00 1.00 0.50
Cm: Clareson-----	60	Very limited Depth to bedrock Too clayey Seepage Slope Content of large stones	1.00 1.00 1.00 0.37 0.26	Very limited Depth to bedrock Slope	1.00 0.37	Very limited Depth to bedrock Too clayey Hard to compact Slope Content of large stones	1.00 1.00 1.00 0.37 0.26
Rock Outcrop-----	20	Not rated		Not rated		Not rated	
De: Dennis-----	90	Very limited Too clayey  Depth to saturated zone	1.00  0.93	Somewhat limited Depth to saturated zone	0.36	Very limited Too clayey  Hard to compact  Depth to saturated zone	1.00  1.00  0.62
Df: Dennis-----	85	Very limited Too clayey  Depth to saturated zone	1.00  0.93	Somewhat limited Depth to saturated zone	0.36	Very limited Too clayey  Hard to compact  Depth to saturated zone	1.00  1.00  0.62
Ec: Eram-----	85	Very limited Depth to bedrock Too clayey  Depth to saturated zone	1.00 1.00  0.93	Very limited Depth to bedrock Depth to saturated zone	1.00 0.36	Very limited Depth to bedrock Too clayey  Hard to compact  Depth to saturated zone	1.00 1.00  1.00  0.62
Ed: Eram-----	85	Very limited Depth to bedrock Too clayey  Depth to saturated zone	1.00 1.00  0.93	Very limited Depth to bedrock Depth to saturated zone	1.00 0.36	Very limited Depth to bedrock Too clayey  Hard to compact  Depth to saturated zone	1.00 1.00  1.00  0.62
Ef: Eram-----	50	Very limited Depth to bedrock Too clayey  Depth to saturated zone Slope	1.00 1.00  0.93 0.04	Very limited Depth to bedrock Depth to saturated zone Slope	1.00 0.36  0.04	Very limited Depth to bedrock Too clayey  Hard to compact  Depth to saturated zone Slope	1.00 1.00  1.00  0.62 0.04
Lebo-----	30	Very limited Depth to bedrock Too clayey Slope	1.00 1.00 0.96	Very limited Depth to bedrock Slope	1.00 0.96	Very limited Depth to bedrock Too clayey Hard to compact Slope	1.00 1.00 1.00 0.96

SANITARY FACILITIES--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Hp: Hepler-----	90	Very limited Flooding	1.00	Very limited Flooding	1.00	Somewhat limited Depth to saturated zone	0.86
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too clayey	0.50
		Too clayey	0.50				
INT: Aquolls-----	100	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Ponding	1.00	Ponding	1.00	Ponding	1.00
		Seepage	1.00				
Ke: Kenoma-----	90	Very limited Too clayey	1.00	Not limited		Very limited Too clayey Hard to compact	1.00 1.00
La: Lanton-----	90	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00		
Lb: Lebo-----	85	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00
		Slope	1.00	Slope	1.00	Slope	1.00
		Too clayey	0.50			Hard to compact	1.00
						Too clayey	0.50
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Mb: Mason-----	85	Somewhat limited Too clayey Flooding	0.50 0.40	Somewhat limited Flooding	0.40	Somewhat limited Too clayey	0.50
Nf: Newtonia-----	90	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
Ng: Newtonia-----	90	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
Nh: Newtonia-----	85	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
Oh: Okemah-----	90	Very limited Too clayey	1.00	Somewhat limited Depth to saturated zone	0.36	Very limited Too clayey	1.00
		Depth to saturated zone	0.93			Hard to compact	1.00
						Depth to saturated zone	0.62
Om: Kanima-----	100	Very limited Slope Too clayey	1.00 0.50	Very limited Slope	1.00	Very limited Slope Too clayey Gravel content	1.00 0.50 0.00
Op: Kanima-----	100	Somewhat limited Too clayey Slope	0.50 0.04	Somewhat limited Slope	0.04	Somewhat limited Too clayey Slope Gravel content	0.50 0.04 0.00
Ot: Osage-----	85	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Ponding	1.00
		Depth to saturated zone	1.00	Ponding	1.00	Depth to saturated zone	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Too clayey	1.00
		Too clayey	1.00			Hard to compact	1.00
Ov: Osage-----	90	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Ponding	1.00
		Depth to saturated zone	1.00	Ponding	1.00	Depth to saturated zone	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Too clayey	1.00
		Too clayey	1.00			Hard to compact	1.00
Pc: Parsons-----	90	Very limited		Very limited		Very limited	



SANITARY FACILITIES--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Po: Pits, Quarries-----	100	Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too clayey	1.00
		Too clayey	1.00			Depth to saturated zone	1.00
						Hard to compact	1.00
Sn: Summit-----	85	Not rated		Not rated		Not rated	
So: Summit-----	85	Very limited Too clayey	1.00	Somewhat limited Depth to saturated zone	0.19	Very limited Too clayey	1.00
		Depth to saturated zone	0.86			Hard to compact	1.00
						Depth to saturated zone	0.47
Vb: Verdigris-----	90	Very limited Too clayey	1.00	Somewhat limited Depth to saturated zone	0.19	Very limited Too clayey	1.00
		Depth to saturated zone	0.86			Hard to compact	1.00
						Depth to saturated zone	0.47
Vc: Verdigris-----	85	Very limited Flooding	1.00	Very limited Flooding	1.00	Not limited	
W: Water-----	100	Very limited Flooding	1.00	Very limited Flooding	1.00	Not limited	
We: Welda-----	90	Not rated		Not rated		Not rated	
Wo: Woodson-----	85	Very limited Too clayey	1.00	Not limited		Very limited Too clayey	1.00
		Depth to saturated zone	1.00			Hard to compact	1.00
		Too clayey	1.00	Very limited Depth to saturated zone	1.00	Very limited Too clayey	1.00
						Depth to saturated zone	1.00
						Hard to compact	1.00

AGRICULTURAL WASTE MANAGEMENT  
Linn County, Kansas

The nature of the soil is also important in the application of organic wastes and wastewater to land as fertilizers and irrigation; it is also important when the soil is used as a medium for treatment and disposal of these wastes. Favorable soil properties are required to prevent environmental damage.

The use of organic wastes and wastewater as production resources will result in energy conservation, prevent the waste of these important resources, and prevent problems associated with their disposal. Where disposal is the goal, and a maximum amount is disposed in a minimum area to hold costs to a minimum, risk of environmental damage is the principal constraint. Where the reuse goal is pursued, and a minimum amount is applied to a maximum area to obtain the greatest benefit, environmental damage is unlikely.

Interpretations developed for waste management may include ratings for (1) manure and food processing wastes; (2) municipal sewage sludge; (3) irrigation use of wastewater; or (4) treatment of wastewater by the slow rate process, overland flow process, or rapid infiltration process. If available, these should be located in this subsection.

Soil properties are important considerations in areas where soils are used as sites for the treatment and disposal of organic waste and wastewater. Selection of soils with properties that favor waste management can help to prevent environmental damage.

The Ag-Waste tables show the degree and kind of soil limitations affecting the treatment of agricultural waste, including municipal and food-processing wastewater and effluent from lagoons or storage ponds. Municipal wastewater is the waste stream from a municipality. It contains domestic waste and may contain industrial waste. It may have received primary or secondary treatment. It is rarely untreated sewage. Food-processing wastewater results from the preparation of fruits, vegetables, milk, cheese, and meats for public consumption. In places it is high in content of sodium and chloride. In the context of these tables, the effluent in lagoons and storage ponds is from facilities used to treat or store food-processing wastewater or domestic or animal waste. Domestic and food-processing wastewater is very dilute, and the effluent from the facilities that treat or store it commonly is very low in content of carbonaceous and nitrogenous material; the content of nitrogen commonly ranges from 10 to 30 milligrams per liter. The wastewater from animal waste treatment lagoons or storage ponds, however, has much higher concentrations of these materials, mainly because the manure has not been diluted as much as the domestic waste. The content of nitrogen in this wastewater generally ranges from 50 to 2,000 milligrams per liter. When wastewater is applied, checks should be made to ensure that nitrogen, phosphorus, heavy metals, and salts are not added in excessive amounts.

The ratings in the tables are for waste management systems that not only dispose of and treat organic waste or wastewater but also are beneficial to crops (application of manure and food-processing waste, application of sewage sludge, and disposal of wastewater by irrigation) and for waste management systems that are designed only for the purpose of wastewater disposal and treatment (overland flow of wastewater, rapid infiltration of wastewater, and slow rate treatment of wastewater).

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect agricultural waste management. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are generally favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Application of manure and food-processing waste not only disposes of waste material but also can improve crop production by increasing the supply of nutrients in the soils where the material is applied. Manure is the excrement of livestock and poultry, and food-processing waste is damaged fruit and vegetables and the peelings, stems, leaves, pits, and soil particles removed in food preparation. The manure and food-processing waste are either solid, slurry, or liquid. Their nitrogen content varies. A high content of nitrogen limits the application rate. Toxic or otherwise dangerous wastes, such as those mixed with the lye used in food processing, are not considered in the ratings.

The ratings are based on the soil properties that affect absorption, plant growth, microbial activity, erodibility, the rate at which the waste is applied, and the method by which the waste is applied. The properties that affect absorption include permeability, depth to a water table, ponding, the sodium adsorption ratio, depth to bedrock or a cemented pan, and available water capacity. The properties that affect plant growth and microbial activity include reaction, the sodium adsorption ratio, salinity, and bulk density. The wind erodibility group, the soil erodibility factor K, and slope are considered in estimating the likelihood that wind erosion or water erosion will transport the waste material from the application site. Stones, cobbles, a water table, ponding, and flooding can hinder the application of waste. Permanently frozen soils are unsuitable for waste treatment.

Application of sewage sludge not only disposes of waste material but also can improve crop production by increasing the supply of nutrients in the soils where the material is applied. In the context of this table, sewage sludge is the residual product of the treatment of municipal sewage. The solid component consists mainly of cell mass, primarily bacteria cells that developed during secondary treatment and have incorporated soluble organics into their own bodies. The sludge has small amounts of sand, silt, and other solid debris. The content of nitrogen varies. Some sludge has constituents that are toxic to plants or hazardous to the food chain, such as heavy metals and exotic organic compounds, and should be analyzed chemically prior to use.

AGRICULTURAL WASTE MANAGEMENT  
Linn County, Kansas

The content of water in the sludge ranges from about 98 percent to less than 40 percent. The sludge is considered liquid if it is more than about 90 percent water, slurry if it is about 50 to 90 percent water, and solid if it is less than about 50 percent water.

The ratings in the table are based on the soil properties that affect absorption, plant growth, microbial activity, erodibility, the rate at which the sludge is applied, and the method by which the sludge is applied. The properties that affect absorption, plant growth, and microbial activity include permeability, depth to a water table, ponding, the sodium adsorption ratio, depth to bedrock or a cemented pan, available water capacity, reaction, salinity, and bulk density. The wind erodibility group, the soil erodibility factor K, and slope are considered in estimating the likelihood that wind erosion or water erosion will transport the waste material from the application site. Stones, cobbles, a water table, ponding, and flooding can hinder the application of sludge. Permanently frozen soils are unsuitable for waste treatment.

Disposal of wastewater by irrigation not only disposes of municipal wastewater and wastewater from food-processing plants, lagoons, and storage ponds but also can improve crop production by increasing the amount of water available to crops. The ratings in the table are based on the soil properties that affect the design, construction, management, and performance of the irrigation system. The properties that affect design and management include the sodium adsorption ratio, depth to a water table, ponding, available water capacity, permeability, slope, and flooding. The properties that affect construction include stones, cobbles, depth to bedrock or a cemented pan, depth to a water table, and ponding.

The properties that affect performance include depth to bedrock or a cemented pan, bulk density, the sodium adsorption ratio, salinity, reaction, and the cation-exchange capacity, which is used to estimate the capacity of a soil to adsorb heavy metals. Permanently frozen soils are not suitable for disposal of wastewater by irrigation.

See the National Soil Handbook, September 1992, Part 620, for criteria used in rating soils for sanitary facilities and waste management.

AGRICULTURAL WASTE MANAGEMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food- processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
003CD: Collinsville-----	65	Very limited Depth to bedrock Droughty Runoff limitation  Too acid Slope	1.00 1.00 0.40  0.11 0.04	Very limited Droughty Depth to bedrock Too acid  Slope Filtering capacity	1.00 1.00 0.42  0.04 0.00	Very limited Droughty Depth to bedrock Too steep for surface application Too acid Too steep for sprinkler application	1.00 1.00 1.00  0.42 0.22
Collinsville Taxadjunct-----	20	Very limited  Droughty Depth to bedrock Runoff limitation  Too acid Filtering capacity	1.00 0.95 0.40  0.11 0.00	Very limited  Droughty Depth to bedrock Too acid  Filtering capacity	1.00 0.95 0.42  0.00	Very limited  Droughty Depth to bedrock Too steep for surface application Too acid Filtering capacity	1.00 0.95 0.66  0.42 0.00
003DE: Dennis, eroded-----	95	Very limited Depth to saturated zone Restricted permeability Too acid	1.00 1.00 1.00 0.14	Very limited Depth to saturated zone Restricted permeability Too acid	1.00 1.00 1.00 0.55	Very limited Depth to saturated zone Restricted permeability Too acid Too steep for surface application	1.00 1.00 1.00 0.55 0.00
003EH: Eram, eroded-----	85	Very limited Depth to saturated zone Restricted permeability  Depth to bedrock Too acid Droughty	1.00 0.30  0.20 0.11 0.10	Very limited Depth to saturated zone Too acid  Restricted permeability Depth to bedrock Droughty	1.00 0.42  0.22 0.20 0.10	Very limited Depth to saturated zone Too steep for surface application Too acid Restricted permeability Depth to bedrock	1.00 0.66  0.42 0.22 0.20
003EK: Eram-----	60	Very limited Depth to saturated zone Restricted permeability  Depth to bedrock Droughty  Too acid	1.00 0.30  0.20 0.20  0.11	Very limited Depth to saturated zone Too acid  Restricted permeability Depth to bedrock Droughty	1.00 0.42  0.22 0.20  0.20	Very limited Depth to saturated zone Too steep for surface application Too acid Restricted permeability Depth to bedrock	1.00 1.00  0.42 0.22  0.20
Clareson-----	20	Very limited Droughty Restricted permeability Depth to bedrock  Cobble content Slope	1.00 1.00 0.90  0.82 0.00	Very limited Droughty Restricted permeability Depth to bedrock  Cobble content Slope	1.00 1.00 0.90  0.82 0.00	Very limited Droughty Restricted permeability Too steep for surface application Depth to bedrock Cobble content	1.00 1.00 1.00  0.90 0.82
003LE: Leanna, drained-----	88	Very limited Restricted permeability Depth to saturated zone Flooding  Runoff limitation Too acid	1.00 1.00 0.60  0.40 0.27	Very limited Flooding  Depth to saturated zone Restricted permeability Too acid Low adsorption	1.00 1.00 1.00  0.85 0.78	Very limited Depth to saturated zone Restricted permeability Too acid Flooding	1.00 1.00 0.85  0.60
003LH: Lula-----	85	Very limited		Very limited		Very limited	

AGRICULTURAL WASTE MANAGEMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food- processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
003SE: Stony Land-----	60	Restricted permeability	1.00	Restricted permeability	1.00	Restricted permeability	1.00
		Too acid	0.03	Too acid	0.14	Too acid	0.14
Talihina-----	20	Not rated		Not rated		Not rated	
		Very limited		Very limited		Very limited	
		Depth to bedrock	1.00	Droughty	1.00	Droughty	1.00
		Depth to bedrock	1.00	Depth to bedrock	1.00	Depth to bedrock	1.00
003WF: Woodson-----	85	Depth to bedrock	1.00	Depth to bedrock	1.00	Depth to bedrock	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Slope	0.84	Slope	0.84	Too steep for surface application	1.00
		Runoff limitation	0.40	Restricted permeability	0.22	Too steep for sprinkler application	0.89
011CA: Catoosa-----	85	Very limited		Very limited		Very limited	
		Restricted permeability	1.00	Restricted permeability	1.00	Restricted permeability	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Runoff limitation	0.40	Too acid	0.14	Too acid	0.14
059CM: Clareson-----	55	Too acid	0.03	Too acid	0.14	Too acid	0.14
		Somewhat limited		Somewhat limited		Somewhat limited	
		Depth to bedrock	0.74	Depth to bedrock	0.74	Depth to bedrock	0.74
		Droughty	0.38	Droughty	0.38	Droughty	0.38
Eram-----	30	Restricted permeability	0.30	Restricted permeability	0.22	Restricted permeability	0.22
		Too acid	0.03	Too acid	0.14	Too acid	0.14
		Very limited		Very limited		Very limited	
		Restricted permeability	1.00	Restricted permeability	1.00	Restricted permeability	1.00
AED: Arents, Earthen Dam-----	100	Depth to bedrock	0.80	Depth to bedrock	0.80	Depth to bedrock	0.80
		Slope	0.04	Slope	0.04	Slope	0.04
		Droughty	0.99	Droughty	0.99	Droughty	0.99
		Too steep for surface application	0.99	Too steep for surface application	0.99	Too steep for surface application	0.99
Bb: Bates-----	85	Depth to bedrock	0.80	Depth to bedrock	0.80	Depth to bedrock	0.80
		Slope	0.04	Slope	0.04	Slope	0.04
		Droughty	0.99	Droughty	0.99	Droughty	0.99
		Too steep for surface application	0.99	Too steep for surface application	0.99	Too steep for surface application	0.99
Bc: Bates-----	85	Depth to bedrock	0.80	Depth to bedrock	0.80	Depth to bedrock	0.80
		Slope	0.04	Slope	0.04	Slope	0.04
		Droughty	0.99	Droughty	0.99	Droughty	0.99
		Too steep for surface application	0.99	Too steep for surface application	0.99	Too steep for surface application	0.99

AGRICULTURAL WASTE MANAGEMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food- processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Cb: Catoosa-----	85	Depth to bedrock	0.35	Restricted permeability	1.00	Too acid	0.85
		Too acid	0.27	Too acid	0.85	Too steep for surface application	0.66
		Droughty	0.06	Depth to bedrock Droughty	0.35 0.06	Depth to bedrock Droughty	0.35 0.06
		Somewhat limited		Somewhat limited		Somewhat limited	
		Depth to bedrock	0.54	Depth to bedrock	0.54	Depth to bedrock	0.54
Cm: Clareson-----	60	Restricted permeability	0.30	Restricted permeability	0.22	Restricted permeability	0.22
		Too acid	0.03	Too acid	0.14	Too acid	0.14
		Droughty	0.01	Droughty	0.01	Droughty	0.01
		Somewhat limited		Somewhat limited		Very limited	
		Droughty	0.80	Droughty	0.80	Too steep for surface application	1.00
Rock Outcrop-----	20	Slope	0.37	Slope	0.37	Droughty	0.80
		Restricted permeability	0.30	Restricted permeability	0.22	Too steep for sprinkler application	0.59
		Depth to bedrock	0.20	Depth to bedrock	0.20	Restricted permeability	0.22
		Not rated		Not rated		Depth to bedrock	0.20
		Not rated		Not rated		Not rated	
De: Dennis-----	90	Somewhat limited		Very limited		Somewhat limited	
		Depth to saturated zone	0.93	Low adsorption	1.00	Depth to saturated zone	0.93
		Restricted permeability	0.30	Depth to saturated zone	0.93	Too acid	0.85
		Too acid	0.27	Too acid	0.85	Restricted permeability	0.22
				Restricted permeability	0.22		
Df: Dennis-----	85	Somewhat limited		Very limited		Somewhat limited	
		Depth to saturated zone	0.93	Low adsorption	1.00	Depth to saturated zone	0.93
		Restricted permeability	0.30	Depth to saturated zone	0.93	Too acid	0.85
		Too acid	0.27	Too acid	0.85	Too steep for surface application	0.31
				Restricted permeability	0.22	Restricted permeability	0.22
Ec: Eram-----	85	Somewhat limited		Somewhat limited		Somewhat limited	
		Depth to saturated zone	0.93	Depth to saturated zone	0.93	Depth to saturated zone	0.93
		Depth to bedrock	0.71	Depth to bedrock	0.71	Depth to bedrock	0.71
		Droughty	0.65	Droughty	0.65	Droughty	0.65
		Restricted permeability	0.30	Restricted permeability	0.22	Restricted permeability	0.22
Ed: Eram-----	85	Too acid	0.03	Too acid	0.14	Too acid	0.14
		Somewhat limited		Somewhat limited		Somewhat limited	
		Depth to saturated zone	0.93	Depth to saturated zone	0.93	Depth to saturated zone	0.93
		Depth to bedrock	0.71	Depth to bedrock	0.71	Depth to bedrock	0.71
		Droughty	0.66	Droughty	0.66	Droughty	0.66
Ef: Eram-----	50	Restricted permeability	0.30	Restricted permeability	0.22	Too steep for surface application	0.66
		Too acid	0.03	Too acid	0.14	Restricted permeability	0.22
		Somewhat limited		Somewhat limited		Very limited	
		Depth to saturated zone	0.93	Depth to saturated zone	0.93	Too steep for surface application	1.00
		Depth to bedrock	0.71	Depth to bedrock	0.71	Depth to saturated zone	0.93

AGRICULTURAL WASTE MANAGEMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food- processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Lebo-----	30	Droughty	0.69	Droughty	0.69	Depth to bedrock	0.71
		Restricted	0.30	Restricted	0.22	Droughty	0.69
		permeability		permeability		Restricted	
		Slope	0.04	Too acid	0.14	permeability	0.22
		Very limited		Very limited		Too steep for	
Hp: Hepler-----	90	Restricted	1.00	Restricted	1.00	surface	1.00
		permeability		permeability		application	
		Slope	0.96	Slope	0.96	Restricted	1.00
		Depth to bedrock	0.01	Depth to bedrock	0.01	permeability	
						Too steep for	0.97
INT: Aquolls-----	100					sprinkler	
						application	
						Depth to bedrock	0.01
		Very limited		Very limited			
		Depth to	1.00	Flooding	1.00	Depth to	1.00
Ke: Kenoma-----	90	saturated zone				saturated zone	
		Flooding	0.60	Depth to	1.00	Flooding	0.60
		Restricted	0.30	saturated zone		Restricted	
		permeability		Restricted	0.22	permeability	0.22
		Too acid	0.02	permeability		Too acid	0.07
La: Lanton-----	90	Too acid		Too acid	0.07	Too acid	0.07
		Very limited		Very limited		Very limited	
		Depth to	1.00	Depth to	1.00	Depth to	1.00
		saturated zone		saturated zone		saturated zone	
		Low adsorption	1.00	Low adsorption	1.00	Low adsorption	1.00
Lb: Lebo-----	85	Ponding	1.00	Ponding	1.00	Ponding	1.00
		Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Runoff limitation	0.40	Too acid	0.14	Too acid	0.14
Mb: Mason-----	85	Too acid	0.03	Too acid		Too steep for	0.00
		Very limited		Very limited		surface	
		Restricted		Flooding	1.00	application	
		permeability				Depth to	
		Depth to	1.00	Depth to	1.00	saturated zone	1.00
M-W: Miscellaneous Water-	100	saturated zone		saturated zone		Restricted	
		Flooding	0.60	Restricted	1.00	permeability	0.60
		Very limited		Very limited		Flooding	
		Slope	1.00	Slope	1.00	Very limited	
		Restricted	1.00	Restricted	1.00	Too steep for	1.00
Ng: Newtonia-----	90	permeability		permeability		sprinkler	
		Depth to bedrock	0.01	Depth to bedrock	0.01	application	
						Restricted	1.00
						permeability	
						Depth to bedrock	0.01
Nf: Newtonia-----	90	Not rated		Not rated		Not rated	
		Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Too acid	0.02	Flooding	0.40	Too acid	0.07
Ng: Newtonia-----	90	Too acid		Too acid	0.07	Too acid	0.07
		Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Too acid	0.03	Too acid	0.14	Too acid	0.14
Mb: Mason-----	85	Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Too acid	0.02	Flooding	0.40	Too acid	0.07
		Too acid		Too acid	0.07	Too acid	0.07
Ng: Newtonia-----	90	Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Too acid	0.03	Too acid	0.14	Too acid	0.14
		Very limited		Very limited		Very limited	
Mb: Mason-----	85	Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Too acid	0.02	Flooding	0.40	Too acid	0.07
		Too acid		Too acid	0.07	Too acid	0.07
		Very limited		Very limited		Very limited	
Ng: Newtonia-----	90	Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Too acid	0.03	Too acid	0.14	Too acid	0.14
		Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
Mb: Mason-----	85	permeability		permeability		permeability	
		Too acid	0.03	Too acid	0.14	Too acid	0.14
		Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
Ng: Newtonia-----	90	Too acid	0.03	Too acid	0.14	Too acid	0.14
		Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Too acid	0.03	Too acid	0.14	Too acid	0.14

AGRICULTURAL WASTE MANAGEMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food- processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Nh: Newtonia-----	85					Too steep for surface application	0.00
		Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
Oh: Okemah-----	90	Too acid	0.03	Too acid	0.14	Too steep for surface application	0.66
						Too acid	0.14
						Too steep for sprinkler application	0.00
Om: Kanima-----	100	Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Depth to saturated zone	0.93	Depth to saturated zone	0.93	Depth to saturated zone	0.93
Op: Kanima-----	100	Very limited		Very limited		Very limited	
		Slope	1.00	Slope	1.00	Too steep for surface application	1.00
		Droughty	0.43	Droughty	0.43	Too steep for sprinkler application	1.00
		Restricted	0.30	Restricted	0.22	Droughty	0.43
Ot: Osage-----	85	Too acid	0.02	Too acid	0.07	Restricted	0.22
						permeability	0.07
						Too acid	
Ov: Osage-----	90	Somewhat limited		Somewhat limited		Very limited	
		Droughty	0.43	Droughty	0.43	Too steep for surface application	1.00
		Restricted	0.30	Restricted	0.22	Droughty	0.43
		permeability	0.04	permeability	0.07	Restricted	0.22
Pc: Parsons-----	90	Slope	0.02	Slope	0.04	Too steep for sprinkler application	0.22
		Too acid				Too acid	0.07
Po: Pits, Quarries-----	100	Very limited		Very limited		Very limited	
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
		Ponding	1.00	Ponding	1.00	Ponding	1.00
Pv: Pits, Quarries-----	100	Depth to saturated zone	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Restricted	1.00	Restricted	1.00	Depth to saturated zone	1.00
		permeability		permeability		Flooding	0.60
		Runoff limitation	0.40	Flooding	1.00		
Pw: Pits, Quarries-----	100	Flooding	0.60				
		Runoff limitation	0.40				
Pz: Pits, Quarries-----	100	Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Restricted	1.00	Restricted	1.00	Restricted	1.00
		permeability		permeability		permeability	
Py: Pits, Quarries-----	100	Runoff limitation	0.40	Too acid	0.42	Too acid	0.42
		Too acid	0.11				
Pz: Pits, Quarries-----	100	Not rated		Not rated		Not rated	



AGRICULTURAL WASTE MANAGEMENT--Continued  
Linn County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food- processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Sn: Summit-----	85	Very limited Restricted permeability Depth to saturated zone	1.00 0.86	Very limited Restricted permeability Depth to saturated zone	1.00 0.86	Very limited Restricted permeability Depth to saturated zone Too steep for surface application	1.00 0.86 0.00
So: Summit-----	85	Very limited Restricted permeability Depth to saturated zone	1.00 0.86	Very limited Restricted permeability Depth to saturated zone	1.00 0.86	Very limited Restricted permeability Depth to saturated zone Too steep for surface application Too steep for sprinkler application	1.00 0.86 0.66 0.00
Vb: Verdigris-----	90	Somewhat limited Flooding Restricted permeability	0.60 0.30	Very limited Flooding Restricted permeability	1.00 0.22	Somewhat limited Flooding Restricted permeability	0.60 0.22
Vc: Verdigris-----	85	Very limited Flooding Restricted permeability	1.00 0.30	Very limited Flooding Restricted permeability	1.00 0.22	Very limited Flooding Restricted permeability	1.00 0.22
W: Water-----	100	Not rated		Not rated		Not rated	
We: Welda-----	90	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability Too steep for surface application	1.00 0.08
Wo: Woodson-----	85	Very limited Restricted permeability Depth to saturated zone Runoff limitation Too acid	1.00 1.00 0.40 0.03	Very limited Restricted permeability Depth to saturated zone Too acid	1.00 1.00 0.14	Very limited Restricted permeability Depth to saturated zone Too acid	1.00 1.00 0.14

WIN-PST SPISP II  
SOIL SENSITIVITY TO PESTICIDE LOSS RATING REPORT

Soils Data Table: SOIL\_KS Sort Order: MUSYM

Linn County, Kansas: KS107

							SPISP II Ratings	
							Leaching	Solution Adsorbed
MUSYM/SEQ#	COMPONENT/TEXTURE/MU%	HYD	KFACT	SURFACE DEPTH	% OM	(SLP)	Runoff (SSRP)	Runoff (SARP)
003CD 1	COLLINSVILLE L 65%	D	0.32	6"	2.0%	V	H	H
003CD 2	BATES L 20%	B	0.32	6"	2.0%	I	I	I
003DE 1	DENNIS SICL 85%	C	0.37	10"	0.8%	H (w)	H	H
003EH 1	ERAM SICL 85%	C	0.37	15"	2.0%	H (w)	H	H
003EK 1	ERAM SICL 60%	C	0.37	15"	2.0%	H (w)	H	H
003EK 2	CLARESON FL-SICL 20%	C	0.24	7"	2.5%	L	H	H
003LE 1	LEANNA SIL 85%	D	0.32	10"	3.0%	H (w)	H	H
003LH 1	LULA SIL 85%	B	0.37	13"	2.0%	I	I	I
003SE 1	STONY LAND 60%		0.00	0"	0.0%	?	?	?
003SE 2	TALIHINA SICL 20%	D	0.37	15"	2.0%	V	H	H
011CA 1	CATOOSA SIL 90%	B	0.37	11"	2.0%	I	I	I
059CM 1	CLARESON SICL 55%	C	0.32	7"	3.3%	L	H	H
059CM 2	ERAM SICL 30%	C	0.37	7"	2.0%	H (w)	H	H
059EC 1	ERAM SICL 60%	C	0.37	7"	2.0%	H (w)	H	H
059EC 2	LULA SIL 25%	B	0.37	7"	2.0%	I	I	I
AED 1	ARENTS, EARTHEN DAM 100%		0.00	0"	0.0%	?	?	?
Ar 1	ARISBURG SIL 85%	C	0.32	9"	2.5%	H (w)	H	H
Bb 1	BATES L 85%	B	0.28	11"	2.5%	I	I	I
Bc 1	BATES L 85%	B	0.28	11"	2.5%	I	I	I
Bu 1	BUCYRUS SIL 85%	C	0.37	8"	2.0%	L	H	H
Bv 1	BUCYRUS SICL 85%	C	0.37	6"	2.0%	L	H	H
Cb 1	CATOOSA SIL 100%	B	0.37	12"	2.0%	I	I	I
Cm 1	CLARESON SICL 60%	C	0.32	11"	2.5%	L	H	H
Cm 2	ROCK OUTCROP UWB 20%	D	0.00	60"	0.0%	V	H	L
De 1	DENNIS SIL 85%	C	0.43	11"	2.0%	H (w)	H	H
Df 1	DENNIS SIL 85%	C	0.43	11"	2.0%	H (w)	H	H
Ec 1	ERAM SICL 85%	C	0.37	9"	2.0%	H (w)	H	H

WIN-PST SPISP II  
SOIL SENSITIVITY TO PESTICIDE LOSS RATING REPORT

Soils Data Table: SOIL\_KS Sort Order: MUSYM

Linn County, Kansas: KS107

Ed 1	ERAM SICL 50%	C	0.37	9"	2.0% H (w)	H	H
Ed 2	SHIDLER sicl 35%	D	0.32	12"	3.0% V	H	H
Ef 1	ERAM SICL 50%	C	0.37	9"	2.0% H (w)	H	H (s)
Ef 2	LEBO CN-SICL 30%	B	0.24	11"	2.0% I	I	H (s)
Gc 1	GRUNDY SIL 100%	C	0.37	11"	3.0% H (w)	H	H
Hp 1	HEPLER SIL 90%	C	0.37	9"	0.5% H (w)	H	H
INT 1	AQUOLLS VAR 100%	C	0.00	72"	0.0% ?	H	?
Ke 1	KENOMA SIL 90%	D	0.43	4"	3.0% H (w)	H	H
La 1	LANTON SIL 90%	C	0.37	14"	3.0% H (w)	H	H
Lb 1	LEBO CN-SICL 85%	B	0.24	11"	2.0% I	I	H (s)
M-W 1	MISCELLANEOUS WATER 100%		0.00	0"	0.0% ?	?	?
Mb 1	MASON SIL 85%	B	0.37	6"	2.0% I	I	I
Nf 1	NEWTONIA SIL 100%	B	0.37	13"	2.5% I	I	I
Ng 1	NEWTONIA SIL 100%	B	0.37	13"	2.5% I	I	I
Nh 1	NEWTONIA SIL 100%	B	0.37	13"	2.5% I	I	I
Oh 1	OKEMAH SIL 85%	C	0.43	8"	2.0% H (w)	H	H
Om 1	KANIMA SICL 95%	C	0.28	6"	1.3% L	H	H (s)
Op 1	KANIMA SICL 100%	C	0.28	6"	1.3% L	H	H
Ot 1	OSAGE SICL 85%	D	0.37	23"	2.5% H (w)	H	H
Ov 1	OSAGE SIC 90%	D	0.28	17"	2.5% H (w)	H	H
Pc 1	PARSONS SIL 90%	D	0.49	14"	1.9% H (w)	H	H
Po 1	Pits, quarries VAR 100%		0.00	60"	0.0% ?	?	?
Sn 1	SUMMIT SICL 85%	C	0.37	9"	2.5% H (w)	H	H
So 1	SUMMIT SICL 85%	C	0.37	9"	2.5% H (w)	H	H
Vb 1	VERDIGRIS SIL 90%	B	0.32	9"	3.0% I	I	I
Vc 1	VERDIGRIS SIL 85%	B	0.32	9"	3.0% I	I	I
W 1	WATER 100%		0.00	0"	0.0% ?	?	?
We 1	WELDA SIL 90%	C	0.37	4"	0.8% L	H	H
Wg 1	WAGSTAFF SIL 85%	C	0.37	7"	2.0% H (w)	H	H
Wh 1	WAGSTAFF SICL 85%	C	0.37	7"	2.0% H (w)	H	H

WIN-PST SPISP II  
SOIL SENSITIVITY TO PESTICIDE LOSS RATING REPORT

Soils Data Table: SOIL\_KS Sort Order: MUSYM

Linn County, Kansas: KS107

Wi 1	WAGSTAFF SICL 45%	C	0.37	7"	2.0% H (w)	H	H
Wi 2	SUMMIT SICL 35%	C	0.37	9"	2.5% H (w)	H	H
Wo 1	WOODSON SIL 85%	D	0.43	7"	2.5% H (w)	H	H
Wt 1	WOODSON SIL 85%	D	0.43	10"	2.5% H (w)	H	H
Wy 1	WYNONA SIL 85%	C	0.43	10"	2.0% H (w)	H	H

(.\REPORTS\SOILS.TXT generated on 12/12/01 at 12:11:15)

H -- High  
I -- Intermediate  
L -- Low  
V -- Very Low

Conditions that affect ratings:

m -- There are macropores in the surface horizon deeper than 24"  
w -- The high water table comes within 24" of the surface during the growing season  
s -- The field slope is greater than 15%

SPISP II S-Ratings:

SLP -- Soil Leaching Potential  
SSRP -- Soil Solution Runoff Potential  
SARP -- Soil Adsorbed Runoff Potential

In this section, hydric soils are defined and described and the hydric soils in the survey area are listed. The three essential characteristics of wetlands are hydrophytic vegetation, hydric soils, and wetland hydrology (Cowardin and others, 1979; U.S. Army Corps of Engineers, 1987; National Research Council, 1995; Tiner, 1985). Criteria for each of the characteristics must be met for areas to be identified as wetlands. Undrained hydric soils that have natural vegetation should support a dominant population of ecological wetland plant species. Hydric soils that have been converted to other uses should be capable of being restored to wetlands.

Hydric soils are defined by the National Technical Committee for Hydric Soils (NTCHS) as soils that formed under conditions of saturation, flooding, or ponding long enough during the growing season to develop anaerobic conditions in the upper part (Federal Register, 1994). These soils are either saturated or inundated long enough during the growing season to support the growth and reproduction of hydrophytic vegetation.

The NTCHS definition identifies general soil properties that are associated with wetness. In order to determine whether a specific soil is a hydric soil or nonhydric soil, however, more specific information, such as information about the depth and duration of the water table, is needed. Thus, criteria that identify those estimated soil properties unique to hydric soils have been established (Federal Register, 1995). These criteria are used to identify a phase of a soil series that normally is associated with wetlands. The criteria used are selected estimated soil properties that are described in "Soil Taxonomy" (USDA, 1999) and "Keys to Soil Taxonomy" (USDA, 1998) and in the "Soil Survey Manual" (USDA, 1993).

If soils are wet enough for a long enough period to be considered hydric, they should exhibit certain properties that can be easily observed in the field. These visible properties are indicators of hydric soils. The indicators used to make onsite determinations of hydric soils in this survey area are specified in "Field Indicators of Hydric Soils in the United States" (Hurt and others, 1996).

Hydric soils are identified by examining and describing the soil to a depth of about 20 inches. This depth may be greater if determination of an appropriate indicator so requires. It is always recommended that soils be excavated and described to the depth necessary for an understanding of the redoximorphic processes. Then, using the completed soil descriptions, soil scientists can compare the soil features required by each indicator and specify which indicators have been matched with the conditions observed in the soil. The soil can be identified as a hydric soil if at least one of the approved indicators is present.

Map units in the Hydric Soil Interpretations table meet the definition of hydric soils and, in addition, have at least one of the hydric soil indicators. This list can help in planning land uses; however, onsite investigation is recommended to determine the hydric soils on a specific site (National Research Council, 1995; Hurt and others, 1996).

Map units that are made up of hydric soils may have small areas, or inclusions, of nonhydric soils in the higher positions on the landform, and map units made up of nonhydric soils may have inclusions of hydric soils in the lower positions on the landform.

These map units, in general, do not meet the definition of hydric soils because they do not have one of the hydric soil indicators. A portion of these map units, however, may include hydric soils. Onsite investigation is recommended to determine whether hydric soils occur and the location of the included hydric soils.

HYDRIC SOIL INTERPRETATIONS  
HYDRIC SOILS LIST  
Linn County, Kansas

PAGE 2 of 6

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
003CD: COLLINSVILLE COMPLEX, 2 TO 15 PERCENT SLOPES	COLLINSVILLE	No	hillslope	---	---	---	---
	COLLINSVILLE Taxadjunct	No	hillslope	---	---	---	---
	DENNIS	No	hillslope	---	---	---	---
	TALIHINA	No	hillslope	---	---	---	---
	ERAM	No	hillslope	---	---	---	---
	SUMMIT	No	hillslope	---	---	---	---
003DE: DENNIS SILTY CLAY LOAM, 1 TO 4 PERCENT SLOPES, ERODED	DENNIS	No	hillslope	---	---	---	---
	ERAM KENOMA	No No	hillslope hillslope	---	---	---	---
003EH: ERAM SOILS, 4 TO 7 PERCENT SLOPES, ERODED	ERAM	No	hillslope	---	---	---	---
	COLLINSVILLE DENNIS TALIHINA	No No No	hillslope hillslope hillslope	---	---	---	---
003EK: ERAM-CLARESON COMPLEX, 1 TO 15 PERCENT SLOPES	ERAM	No	hillslope	---	---	---	---
	CLARESON	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	hillslope	---	---	---	---
	TALIHINA	No	hillslope	---	---	---	---
	SUMMIT	No	hillslope	---	---	---	---
	CATOOSA	No	hillslope	---	---	---	---
	DENNIS	No	hillslope	---	---	---	---
	LEANNA	No	flood plain	---	---	---	---
003LE: LEANNA SILT LOAM, 0 TO 2 PERCENT SLOPES, OCCASIONALLY FLOODED	LANTON	No	flood plain	---	---	---	---
	OSAGE	Yes	flood plain	2B3	YES	NO	NO
	VERDIGRIS	No	flood plain	---	---	---	---
	WOODSON	No	divide	---	---	---	---
003LH: LULA SILT LOAM, 0 TO 3 PERCENT SLOPES	LULA	No	hillslope	---	---	---	---
	CATOOSA	No	hillslope	---	---	---	---
	CLARESON	No	hillslope	---	---	---	---
	KENOMA	No	hillslope	---	---	---	---
003SE: STONY LAND-TALIHINA COMPLEX, 15 TO 45 PERCENT SLOPES	STONY LAND	Unranked	hillslope	---	---	---	---
	TALIHINA	No	hillslope	---	---	---	---
	CLARESON	No	hillslope	---	---	---	---
	DENNIS	No	hillslope	---	---	---	---
	ERAM	No	hillslope	---	---	---	---
	SUMMIT	No	hillslope	---	---	---	---
003WF: WOODSON SILT LOAM, 1 TO 3 PERCENT SLOPES	WOODSON	No	paleoterrace	---	---	---	---
	ERAM	No	hillslope	---	---	---	---
	KENOMA	No	hillslope	---	---	---	---
	SUMMIT	No	hillslope	---	---	---	---
011CA: CATOOSA SILT LOAM, 0 TO 2 PERCENT SLOPES	CATOOSA	No	ridge	---	---	---	---
	CLARESON	No	hillslope	---	---	---	---
	KENOMA	No	paleoterrace, ridge	---	---	---	---
059CM: CLARESON-ERAM SILTY CLAY LOAMS, 3 TO 15 PERCENT SLOPES	CLARESON	No	hillslope	---	---	---	---
	ERAM	No	hillslope	---	---	---	---
	BATES ROCK OUTCROP	No Unranked	hillslope hillslope	---	---	---	---
AED: ARENTS, EARTHEN DAM	ARENTS, EARTHEN DAM	Unranked	---	---	---	---	---

HYDRIC SOIL INTERPRETATIONS  
HYDRIC SOILS LIST  
Linn County, Kansas

PAGE 3 of 6

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
Bb: BATES LOAM, 1 TO 4 PERCENT SLOPES	BATES	No	hillslope, ridge	---	---	---	---
	DENNIS	No	divide, hillslope	---	---	---	---
	ERAM	No	hillslope, ridge	---	---	---	---
	ROCK OUTCROP	---	hillslope	---	---	---	---
Bc: BATES LOAM, 4 TO 8 PERCENT SLOPES	BATES	No	hillslope	---	---	---	---
	DENNIS	No	hillslope	---	---	---	---
	ERAM	No	hillslope, ridge	---	---	---	---
	LEBO	No	hillslope	---	---	---	---
Cb: CATOOSA SILT LOAM, 1 TO 3 PERCENT SLOPES	CATOOSA	No	hillslope, ridge	---	---	---	---
	CLARESON	No	hillslope, ridge	---	---	---	---
	KENOMA	No	hillslope, paleoterrace, ridge	---	---	---	---
	SUMMIT	No	hillslope	---	---	---	---
	ERAM	No	hillslope, ridge	---	---	---	---
Cm: CLARESON-ROCK OUTCROP COMPLEX, 2 TO 15 PERCENT SLOPES	CLARESON	No	hillslope, ridge	---	---	---	---
	ROCK OUTCROP	Unranked	ridge	---	---	---	---
	CATOOSA	No	hillslope, ridge	---	---	---	---
	ERAM	No	hillslope, ridge	---	---	---	---
	LEBO	No	hillslope	---	---	---	---
	SUMMIT	No	hillslope	---	---	---	---
De: DENNIS SILT LOAM, 1 TO 3 PERCENT SLOPES	DENNIS	No	divide, hillslope	---	---	---	---
	BATES	No	hillslope, ridge	---	---	---	---
	ERAM	No	hillslope, ridge	---	---	---	---
	KENOMA	No	hillslope, paleoterrace, ridge	---	---	---	---
Df: DENNIS SILT LOAM, 3 TO 6 PERCENT SLOPES	DENNIS	No	hillslope	---	---	---	---
	BATES	No	hillslope	---	---	---	---
	ERAM	No	hillslope, ridge	---	---	---	---
	KENOMA	No	hillslope, paleoterrace, ridge	---	---	---	---
Ec: ERAM SILTY CLAY LOAM, 1 TO 4 PERCENT SLOPES	ERAM	No	hillslope, ridge	---	---	---	---
	BATES	No	hillslope, ridge	---	---	---	---
	CATOOSA	No	hillslope, ridge	---	---	---	---
	DENNIS	No	divide, hillslope	---	---	---	---
	SUMMIT	No	hillslope	---	---	---	---
Ed: ERAM SILTY CLAY LOAM, 4 TO 8 PERCENT SLOPES	ERAM	No	hillslope, ridge	---	---	---	---
	BATES	No	hillslope	---	---	---	---
	DENNIS	No	hillslope	---	---	---	---
	LEBO	No	hillslope	---	---	---	---
Ef: ERAM-LEBO SILTY CLAY LOAMS, 5 TO 20 PERCENT SLOPES	SUMMIT	No	hillslope	---	---	---	---
	ERAM	No	hillslope	---	---	---	---
	LEBO	No	hillslope	---	---	---	---
	CLARESON	No	hillslope, ridge	---	---	---	---
	DENNIS	No	hillslope	---	---	---	---

HYDRIC SOIL INTERPRETATIONS  
HYDRIC SOILS LIST  
Linn County, Kansas

PAGE 4 of 6

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
Hp: HEPLER SILT LOAM, 0 TO 2 PERCENT SLOPES, OCCASIONALLY FLOODED	HEPLER	No	flood plain	---	---	---	---
	MASON	No	stream terrace	---	---	---	---
INT: AQUOLLS	AQUOLLS	Yes	depression, terrace	2B3,3	YES	NO	YES
Ke: KENOMA SILT LOAM, 1 TO 4 PERCENT SLOPES	KENOMA	No	hillslope, paleoterrace, ridge	---	---	---	---
	DENNIS	No	divide, hillslope	---	---	---	---
	CATOOSA	No	hillslope, ridge	---	---	---	---
	ERAM	No	hillslope, ridge	---	---	---	---
La: LANTON SILT LOAM, OCCASIONALLY FLOODED	LANTON	No	flood plain	---	---	---	---
	OSAGE	Yes	flood plain	2B3	YES	NO	NO
Lb: LEBO CHANNERY SILTY CLAY LOAM, 15 TO 30 PERCENT SLOPES	LEBO	No	hillslope	---	---	---	---
	CLARESON	No	hillslope, ridge	---	---	---	---
	ERAM	No	hillslope, ridge	---	---	---	---
	ROCK OUTCROP	Unranked	ridge	---	---	---	---
M-W: MISCELLANEOUS WATER	MISCELLANEOUS WATER	Unranked	---	---	---	---	---
Mb: MASON SILT LOAM, 0 TO 2 PERCENT SLOPES, RARELY FLOODED	MASON	No	stream terrace	---	---	---	---
	HEPLER	No	flood plain	---	---	---	---
	OSAGE	Yes	flood plain	2B3	YES	NO	NO
	VERDIGRIS	No	flood plain	---	---	---	---
Nf: NEWTONIA SILT LOAM, 0 TO 1 PERCENT SLOPES	NEWTONIA	No	paleoterrace, ridge	---	---	---	---
	KENOMA	No	hillslope, paleoterrace, ridge	---	---	---	---
Ng: NEWTONIA SILT LOAM, 1 TO 4 PERCENT SLOPES	NEWTONIA	No	hillslope, ridge	---	---	---	---
	WELDA	No	stream terrace	---	---	---	---
Nh: NEWTONIA SILT LOAM, 4 TO 8 PERCENT SLOPES	NEWTONIA	No	hillslope	---	---	---	---
	KENOMA	No	hillslope, paleoterrace, ridge	---	---	---	---
Oh: OKEMAH SILT LOAM, 0 TO 3 PERCENT SLOPES	OKEMAH	No	hillslope, stream terrace	---	---	---	---
	WOODSON	No	divide, paleoterrace	---	---	---	---
Om: KANIMA SILTY CLAY LOAM, 15 TO 50 PERCENT SLOPES	KANIMA	No	hillslope	---	---	---	---
Op: KANIMA SILTY CLAY LOAM, 2 TO 15 PERCENT SLOPES	KANIMA	No	hillslope	---	---	---	---
Ot: OSAGE SILTY CLAY LOAM, 0 TO 2 PERCENT SLOPES, OCCASIONALLY FLOODED	OSAGE	Yes	flood plain	2B3	YES	NO	NO
	LANTON	No	flood plain	---	---	---	---
	VERDIGRIS	No	flood plain	---	---	---	---
Ov: OSAGE SILTY CLAY, OCCASIONALLY FLOODED	OSAGE	Yes	flood plain	2B3	YES	NO	NO
	LANTON	No	flood plain	---	---	---	---
	VERDIGRIS	No	flood plain	---	---	---	---



HYDRIC SOIL INTERPRETATIONS  
HYDRIC SOILS LIST  
Linn County, Kansas

PAGE 5 of 6

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
Pc: PARSONS SILT LOAM, 0 TO 2 PERCENT SLOPES	PARSONS	No	divide, paleoterrace	---	---	---	---
	DENNIS	No	divide, hillslope	---	---	---	---
Po: PITS, QUARRIES	Pits, quarries	Unranked	---	---	---	---	---
Sn: SUMMIT SILTY CLAY LOAM, 1 TO 4 PERCENT SLOPES	SUMMIT	No	hillslope	---	---	---	---
	CATOOSA	No	hillslope, ridge	---	---	---	---
So: SUMMIT SILTY CLAY LOAM, 4 TO 8 PERCENT SLOPES	SUMMIT	No	hillslope	---	---	---	---
	CATOOSA	No	hillslope, ridge	---	---	---	---
	DENNIS	No	hillslope	---	---	---	---
Vb: VERDIGRIS SILT LOAM, 0 TO 2 PERCENT SLOPES, OCCASIONALLY FLOODED	VERDIGRIS	No	flood plain	---	---	---	---
	OSAGE	Yes	flood plain	2B3	YES	NO	NO
Vc: VERDIGRIS SILT LOAM, 0 TO 2 PERCENT SLOPES, FREQUENTLY FLOODED	VERDIGRIS	No	flood plain	---	---	---	---
	OSAGE	Yes	flood plain	2B3	YES	NO	NO
	SUMMIT	No	hillslope	---	---	---	---
W: WATER	WATER	Yes	---	4,3	NO	YES	YES
We: WELDA SILT LOAM, 2 TO 5 PERCENT SLOPES	WELDA	No	stream terrace	---	---	---	---
	CATOOSA	No	hillslope, ridge	---	---	---	---
Wo: WOODSON SILT LOAM, 0 TO 2 PERCENT SLOPES	WOODSON	No	divide, paleoterrace	---	---	---	---
	SUMMIT	No	hillslope	---	---	---	---
	OKEMAH	No	hillslope, stream terrace	---	---	---	---

HYDRIC SOIL INTERPRETATIONS  
HYDRIC SOILS LIST  
Linn County, Kansas

PAGE 6 of 6

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria

FOOTNOTE: There may be small areas of included soils or miscellaneous areas that are significant to use and management of the soil; yet are too small to delineate on the soil map at the map's original scale. These may be designated as spot symbols and are defined in the published Soil Survey Report or the USDA-NRCS Technical Guide, Part II.

Areas mapped as water or any map unit that contains one of the following conventional symbols is considered a hydric soil map unit: marshes or swamps; wet spots; depressions; streams, lakes and ponds.

1. All Histosols except Folists, or
2. Soils in Aquic suborders, great groups, or subgroups, Albolls suborder, Aquisalids, Pachic subgroups, or Cumulic subgroups that are:
  - a. Somewhat poorly drained with a water table equal to 0.0 foot (ft) from the surface during the growing season, or
  - b. poorly drained or very poorly drained and have either:
    - (1) water table equal to 0.0 ft during the growing season if textures are coarse sand, sand, or fine sand in all layers within 20 inches (in),  
or for other soils
    - (2) water table at less than or equal to 0.5 ft from the surface during the growing season if permeability is equal to or greater than 6.0 in/hour (h) in all layers within 20 in, or
    - (3) water table at less than or equal to 1.0 ft from the surface during the growing season if permeability is less than 6.0 in/h in any layer within 20 in, or
3. Soils that are frequently ponded for long duration or very long duration during the growing season, or
4. Soils that are frequently flooded for long duration or very long duration during the growing season.