

WATER MANAGEMENT  
Nemaha County, Kansas

The soils of the survey area are rated in the Water Management table according to limitations that affect their suitability for water management. Soils are rated for pond reservoir areas, drainage, irrigation, terraces and diversions, and grassed waterways. Restrictive features that affect each soil for the specified use is also provided in the table.

The ratings in the table are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Moderately limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Limited indicates that the soil has one or more features that are significant limitations for the specified use. The limitations can be overcome, but generally require special design, soil reclamation, or installation procedures that may result in additional expense. Fair performance and moderate to high maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Limitation class terms, such as very limited or limited, etc., limitation ratings, and numerical ratings are shown for each soil feature listed. As many as three soil features may be listed for each soil component if applicable. The overall limitation rating for the soil component is based on the most severe limitation.

Pond reservoir areas hold water behind a dam or embankment. Soils best suited to this use have low seepage potential in the upper 60 inches. The seepage potential is determined by the permeability of the soil and the depth to fractured bedrock or other permeable material. Excessive slope can affect the storage capacity of the reservoir area.

Embankments, dikes, and levees are raised structures of soil material, generally less than 20 feet high, constructed to impound water or to protect land against overflow. In this table, the soils are rated as a source of material for embankment fill. The ratings apply to the soil material below the surface layer to a depth of about 5 feet. It is assumed that soil layers will be uniformly mixed and compacted during construction.

The ratings do not indicate the ability of the natural soil to support an embankment. Soil properties to a depth even greater than the height of the embankment can affect performance and safety of the embankment. Generally, deeper onsite investigation is needed to determine these properties.

Soil material in embankments must be resistant to seepage, piping, and erosion and have favorable compaction characteristics. Unfavorable features include less than 5 feet of suitable material and a high content of stones or boulders, organic matter, or salts or sodium. A high water table affects the amount of usable material. It also affects traffic ability.

Aquifer-fed excavated ponds are pits or dugouts that extend to a ground-water aquifer or to a depth below a permanent water table. Excluded are ponds that are fed only by surface runoff and embankment ponds that impound water 3 feet or more above the original surface. Excavated ponds are affected by depth to a permanent water table, permeability of the aquifer, and quality of the water as inferred from the salinity of the soil. Depth to bedrock and the content of large stones affect the ease of excavation.

Drainage is the removal of excess surface and subsurface water from the soil. How easily and effectively the soil is drained depends on the depth to bedrock, to a cemented pan, or to other layers that affect the rate of water movement; permeability; depth to a high water table or depth of standing water if the soil is subject to ponding; slope; susceptibility to flooding; subsidence of organic layers; and the potential for frost action. Excavating and grading and the stability of ditch banks are affected by depth to bedrock or to a cemented pan, large stones, slope, and the hazard of cutbanks caving. The productivity of the soil after drainage is adversely affected by extreme acidity or by toxic substances in the root zone, such as salts, sodium, and sulfur. Availability of drainage outlets is not considered in the ratings.

Irrigation is the controlled application of water to supplement rainfall and support plant growth. The design and management of an irrigation system are affected by depth to the water table, the need for drainage, flooding, available water capacity, intake rate, permeability, erosion hazard, and slope. The construction of a system is affected by large stones and depth to bedrock or to a cemented pan. The performance of a system is affected by the depth of the root zone, the amount of salts or sodium, and soil reaction.

Terraces and diversions are embankments or a combination of channels and ridges constructed across a slope to control erosion and conserve moisture by intercepting runoff. Slope, wetness, large stones, and depth to bedrock or to a cemented pan affect the construction of terraces and diversions. A restricted rooting depth, a very limited hazard of wind erosion or water erosion, an excessively coarse texture, and restricted permeability adversely affect maintenance.

Grassed waterways are natural or constructed channels, generally broad and shallow, which conduct surface water to outlets at a non-erosive velocity. Large stones, wetness, slope, and depth to bedrock or to a cemented pan affect the construction of grassed waterways. A hazard of wind erosion, low available water capacity, restricted rooting depth, toxic substances such as salts and sodium, and restricted permeability adversely affect the growth and maintenance of the grass after construction.

WATER MANAGEMENT--Continued  
Nemaha County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
013AD: Aksarben-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
013AE: Aksarben-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
013BS: Burchard-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
013BX: Burchard-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Steinauer-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
013KP: Kipson-----	Limitation: deep to water	Limitation: slope depth to rock	Limitation: large stones slope depth to rock	Limitation: large stones slope depth to rock
Sogn-----	Limitation: deep to water	Limitation: slope depth to rock	Limitation: slope depth to rock	Limitation: slope depth to rock
013MD: Martin-----	Limitation: frost action percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly
013MT: Morrill-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
013PD: Padonia-----	Limitation: deep to water	Limitation: percs slowly slope depth to rock	Limitation: erodes easily percs slowly depth to rock	Limitation: erodes easily percs slowly depth to rock
Martin-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily slope wetness	Limitation: erodes easily percs slowly slope
013RE: Reading-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
085CB: Clime-----	Limitation: deep to water	Limitation: percs slowly slope slow intake	Limitation: percs slowly slope depth to rock	Limitation: percs slowly slope depth to rock
Sogn-----	Limitation: deep to water	Limitation: slope depth to rock	Limitation: slope depth to rock	Limitation: slope depth to rock
149CS: Clime-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily slope	Limitation: area reclaim erodes easily slope
Sogn-----	Limitation: deep to water	Limitation: slope thin layer	Limitation: area reclaim slope depth to rock	Limitation: area reclaim slope depth to rock
149WD: Wamego-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily	Limitation: area reclaim erodes easily
149WE: Wamego-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily slope	Limitation: area reclaim erodes easily slope
AED: Arents, Earthen Dam-----	---	---	---	---
Bf: Benfield-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily	Limitation: area reclaim erodes easily
Bs: Burchard-----	Limitation: deep to water	Limitation: slope	Limitation: slope	Limitation: slope

WATER MANAGEMENT--Continued  
Nemaha County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
Steinauer-----	Limitation: deep to water	Limitation: rooting depth slope	Limitation: slope	Limitation: rooting depth slope
Cc: Calco-----	Limitation: flooding frost action	Limitation: flooding wetness	Limitation: wetness	Limitation: wetness
Ch: Chase-----	Limitation: flooding frost action percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly
Et: Elmont-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily	Limitation: erodes easily
Ke: Kennebec-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
Kn: Kennebec-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
Kp: Kipson-----	Limitation: deep to water	Limitation: slope thin layer	Limitation: area reclaim large stones slope	Limitation: area reclaim large stones slope
M-W: Miscellaneous Water-----	---	---	---	---
Mb: Morrill-----	Limitation: deep to water	Limitation: slope	Favorable	Favorable
Me: Morrill, eroded-	Limitation: deep to water	Limitation: slope	Favorable	Favorable
Om: Olmitz-----	Limitation: deep to water	Limitation: slope	Favorable	Favorable
Pa: Pawnee-----	Limitation: frost action percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily
Pb: Pawnee-----	Limitation: frost action percs slowly slope	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily
Pe: Pawnee, eroded--	Limitation: frost action percs slowly slope	Limitation: erodes easily percs slowly slow intake	Limitation: erodes easily percs slowly	Limitation: erodes easily
Pt: Pits, Quarries--	---	---	---	---
Re: Reading-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
Sb: Sibleyville----	Limitation: deep to water	Limitation: slope thin layer	Limitation: area reclaim	Limitation: area reclaim
St: Steinauer-----	Limitation: deep to water	Limitation: rooting depth slope	Limitation: slope	Limitation: rooting depth slope
Vv: Vinland Variant-	Limitation: deep to water	Limitation: slope thin layer	Limitation: area reclaim slope	Limitation: area reclaim slope
W: Water-----	---	---	---	---
Wa: Wabash-----	Limitation: flooding percs slowly	Limitation: flooding percs slowly wetness	Limitation: percs slowly wetness	Limitation: percs slowly wetness
Wb: Wymore-----	Limitation: frost action percs slowly	Limitation: percs slowly wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness
Wc: Wymore-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness

WATER MANAGEMENT--Continued  
Nemaha County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
013AD: Aksarben-----	87	Somewhat limited Seepage	0.70	Not limited		Very limited Deep to water	1.00
013AE: Aksarben-----	85	Somewhat limited Seepage	0.70	Not limited		Very limited Deep to water	1.00
013BS: Burchard-----	85	Somewhat limited Seepage	0.05	Not limited		Very limited Deep to water	1.00
013BX: Burchard-----	55	Somewhat limited Seepage Slope	0.05 0.03	Not limited		Very limited Deep to water	1.00
Steinauer-----	40	Somewhat limited Seepage Slope	0.05 0.03	Not limited		Very limited Deep to water	1.00
013KP: Kipson-----	60	Somewhat limited Depth to bedrock Slope	0.50 0.08	Very limited Thin layer Piping	1.00 0.50	Very limited Deep to water	1.00
Sogn-----	30	Very limited Seepage Depth to bedrock Slope	1.00 1.00 0.01	Very limited Thin layer Piping	1.00 0.12	Very limited Deep to water	1.00
013MD: Martin-----	85	Not limited		Very limited Hard to pack Depth to saturated zone	1.00 1.00	Very limited Deep to water	1.00
013MT: Morrill-----	87	Very limited Seepage	1.00	Somewhat limited Seepage	0.31	Very limited Deep to water	1.00
013PD: Padonia-----	50	Somewhat limited Seepage Depth to bedrock	0.05 0.02	Somewhat limited Thin layer Hard to pack	0.61 0.09	Very limited Deep to water	1.00
Martin-----	40	Not limited		Very limited Hard to pack Depth to saturated zone	1.00 1.00	Very limited Deep to water	1.00
013RE: Reading-----	90	Somewhat limited Seepage	0.57	Somewhat limited Depth to saturated zone Piping	0.09 0.00	Somewhat limited Deep to water Slow refill Cutbanks cave	0.54 0.43 0.10
085CB: Clime-----	50	Somewhat limited Depth to bedrock Slope	0.04 0.01	Somewhat limited Thin layer Hard to pack	0.70 0.28	Very limited Deep to water	1.00
Sogn-----	35	Very limited Seepage Depth to bedrock	1.00 1.00	Very limited Thin layer Piping	1.00 0.12	Very limited Deep to water	1.00
149CS: Clime-----	70	Somewhat limited Depth to bedrock Slope	0.23 0.01	Somewhat limited Thin layer Hard to pack	0.95 0.50	Very limited Deep to water	1.00
Sogn-----	15	Very limited Seepage Depth to bedrock Slope	1.00 1.00 0.01	Very limited Thin layer Piping	1.00 0.12	Very limited Deep to water	1.00
149WD: Wamego-----	85	Somewhat limited		Somewhat limited		Very limited	

WATER MANAGEMENT--Continued  
Nemaha County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
149WE: Wamego-----	85	Depth to bedrock	0.19	Thin layer	0.93	Deep to water	1.00
		Somewhat limited Depth to bedrock Slope	0.19 0.02	Somewhat limited Thin layer	0.93	Very limited Deep to water	1.00
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
Bf: Benfield-----	90	Somewhat limited Depth to bedrock	0.02	Somewhat limited Thin layer Hard to pack	0.61 0.12	Very limited Deep to water	1.00
Bs: Burchard-----	63	Somewhat limited Seepage	0.05	Not limited		Very limited Deep to water	1.00
Steinauer-----	27	Somewhat limited Seepage	0.05	Not limited		Very limited Deep to water	1.00
Cc: Calco-----	90	Somewhat limited Seepage	0.70	Very limited Depth to saturated zone Piping	1.00	Somewhat limited Slow refill	0.30
					0.31	Cutbanks cave	0.10
Ch: Chase-----	89	Not limited		Somewhat limited Depth to saturated zone	0.43	Very limited Deep to water	1.00
Et: Elmont-----	85	Somewhat limited Seepage Depth to bedrock	0.05 0.00	Somewhat limited Thin layer	0.26	Very limited Deep to water	1.00
Ke: Kennebec-----	95	Somewhat limited Seepage	0.70	Somewhat limited Piping Depth to saturated zone	0.71 0.09	Somewhat limited Deep to water Slow refill	0.54 0.30
						Cutbanks cave	0.10
Kn: Kennebec-----	90	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.81	Somewhat limited Deep to water Slow refill Cutbanks cave	0.81 0.30 0.10
Kp: Kipson-----	85	Very limited Seepage Depth to bedrock Slope	1.00 0.50 0.03	Very limited Thin layer Piping	1.00 0.32	Very limited Deep to water	1.00
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Mb: Morrill-----	90	Somewhat limited Seepage	0.05	Somewhat limited Piping	0.08	Very limited Deep to water	1.00
Me: Morrill, eroded----	90	Somewhat limited Seepage	0.05	Somewhat limited Piping	0.08	Very limited Deep to water	1.00
Om: Olmitz-----	91	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.41	Very limited Deep to water	1.00
Pa: Pawnee-----	90	Not limited		Very limited Depth to saturated zone	1.00	Very limited Deep to water	1.00

WATER MANAGEMENT--Continued  
Nemaha County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Pb: Pawnee-----	90	Not limited		Hard to pack Very limited Depth to saturated zone Hard to pack	0.69 1.00 0.69	Very limited Deep to water	1.00
Pe: Pawnee, eroded-----	85	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.76	Very limited Deep to water	1.00
Pt: Pits, Quarries-----	100	Not rated		Not rated		Not rated	
Re: Reading-----	90	Somewhat limited Seepage	0.57	Somewhat limited Piping	0.00	Very limited Deep to water	1.00
Sb: Sibleyville-----	90	Somewhat limited Seepage Depth to bedrock	0.70 0.02	Somewhat limited Thin layer	0.61	Very limited Deep to water	1.00
St: Steinauer-----	90	Somewhat limited Slope Seepage	0.10 0.05	Not limited		Very limited Deep to water	1.00
Vv: Vinland Variant-----	90	Somewhat limited Seepage Depth to bedrock Slope	0.70 0.30 0.03	Very limited Piping Thin layer	1.00 0.98	Very limited Deep to water	1.00
W: Water-----	100	Not rated		Not rated		Not rated	
Wa: Wabash-----	88	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 1.00	Very limited Slow refill Cutbanks cave	1.00 0.10
Wb: Wymore-----	100	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00 0.74	Very limited Deep to water	1.00
Wc: Wymore-----	85	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00 0.74	Very limited Deep to water	1.00

