

SANITARY FACILITIES
Reno County, Kansas

Sanitary Facilities

The following tables show the degree and kind of soil limitations that affect septic tank absorption fields, sewage lagoons, sanitary landfills, and daily cover for landfill. The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect these uses. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Septic tank absorption fields are areas in which effluent from a septic tank is distributed into the soil through subsurface tiles or perforated pipe. Only that part of the soil between depths of 24 and 60 inches is evaluated. The ratings are based on the soil properties that affect absorption of the effluent, construction and maintenance of the system, and public health. Permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, and flooding affect absorption of the effluent. Stones and boulders, ice, and bedrock or a cemented pan interfere with installation. Subsidence interferes with installation and maintenance. Excessive slope may cause lateral seepage and surfacing of the effluent in downslope areas.

Some soils are underlain by loose sand and gravel or fractured bedrock at a depth of less than 4 feet below the distribution lines. In these soils the absorption field may not adequately filter the effluent, particularly when the system is new. As a result, the ground water may become contaminated.

Sewage lagoons are shallow ponds constructed to hold sewage while aerobic bacteria decompose the solid and liquid wastes. Lagoons should have a nearly level floor surrounded by cut slopes or embankments of compacted soil. Nearly impervious soil material for the lagoon floor and sides is required to minimize seepage and contamination of ground water. Considered in the ratings are slope, permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, flooding, large stones, and content of organic matter.

Soil permeability is a critical property affecting the suitability for sewage lagoons. Most porous soils eventually become sealed when they are used as sites for sewage lagoons. Until sealing occurs, however, the hazard of pollution is severe. Soils that have a permeability rate of more than 2 inches per hour are too porous for the proper functioning of sewage lagoons. In these soils, seepage of the effluent can result in contamination of the ground water. Ground-water contamination is also a hazard if fractured bedrock is within a depth of 40 inches, if the water table is high enough to raise the level of sewage in the lagoon, or if floodwater overtops the lagoon.

A high content of organic matter is detrimental to proper functioning of the lagoon because it inhibits aerobic activity. Slope, bedrock, and cemented pans can cause construction problems, and large stones can hinder compaction of the lagoon floor. If the lagoon is to be uniformly deep throughout, the slope must be gentle enough and the soil material must be thick enough over bedrock or a cemented pan to make land smoothing practical.

A trench sanitary landfill is an area where solid waste is placed in successive layers in an excavated trench. The waste is spread, compacted, and covered daily with a thin layer of soil excavated at the site. When the trench is full, a final cover of soil material at least 2 feet thick is placed over the landfill. The ratings in the table are based on the soil properties that affect the risk of pollution, the ease of excavation, trafficability, and revegetation. These properties include permeability, depth to bedrock or a cemented pan, depth to a water table, ponding, slope, flooding, texture, stones and boulders, highly organic layers, soil reaction, and content of salts and sodium. Unless otherwise stated, the ratings apply only to that part of the soil within a depth of about 6 feet. For deeper trenches, onsite investigation may be needed.

Hard, nonrippable bedrock, creviced bedrock, or highly permeable strata in or directly below the proposed trench bottom can affect the ease of excavation and the hazard of ground-water pollution. Slope affects construction of the trenches and the movement of surface water around the landfill. It also affects the construction and performance of roads in areas of the landfill.

Soil texture and consistence affect the ease with which the trench is dug and the ease with which the soil can be used as daily or final cover. They determine the workability of the soil when dry and when wet. Soils that are plastic and sticky when wet are difficult to excavate, grade, or compact and are difficult to place as a uniformly thick cover over a layer of refuse.

The soil material used as the final cover for a trench landfill should be suitable for plants. It should not have excess sodium or salts and should not be too acid. The surface layer generally has the best workability, the highest content of organic matter, and the best potential for plants. Material from the surface layer should be stockpiled for use as the final cover.

SANITARY FACILITIES
Reno County, Kansas

In an area sanitary landfill, solid waste is placed in successive layers on the surface of the soil. The waste is spread, compacted, and covered daily with a thin layer of soil from a source away from the site. A final cover of soil material at least 2 feet thick is placed over the completed landfill. The ratings in the table are based on the soil properties that affect trafficability and the risk of pollution. These properties include flooding, permeability, depth to a water table, ponding, slope, and depth to bedrock or a cemented pan.

Flooding is a serious problem because it can result in pollution in areas downstream from the landfill. If permeability is too rapid or if fractured bedrock, a fractured cemented pan, or the water table is close to the surface, the leachate can contaminate the water supply. Slope is a consideration because of the extra grading required to maintain roads in the steeper areas of the landfill. Also, leachate may flow along the surface of the soils in the steeper areas and cause difficult seepage problems.

Daily cover for landfill is the soil material that is used to cover compacted solid waste in an area sanitary landfill. The soil material is obtained offsite, transported to the landfill, and spread over the waste. The ratings in the table also apply to the final cover for a landfill. They are based on the soil properties that affect workability, the ease of digging, and the ease of moving and spreading the material over the refuse daily during wet and dry periods. These properties include soil texture, depth to a water table, ponding, rock fragments, slope, depth to bedrock or a cemented pan, reaction, and content of salts, sodium, or lime.

Loamy or silty soils that are free of large stones and excess gravel are the best cover for a landfill. Clayey soils may be sticky and difficult to spread; sandy soils are subject to wind erosion.

Slope affects the ease of excavation and of moving the cover material. Also, it can influence runoff, erosion, and reclamation of the borrow area.

After soil material has been removed, the soil material remaining in the borrow area must be thick enough over bedrock, a cemented pan, or the water table to permit revegetation. The soil material used as the final cover for a landfill should be suitable for plants. It should not have excess sodium, salts, or lime and should not be too acid.

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
990: Abbyville-----	95	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Depth to saturated zone	1.00
991: Abbyville, rarely flooded-----	45	Very limited Restricted permeability Depth to saturated zone Flooding	 1.00 1.00 0.40	Very limited Depth to saturated zone Flooding	 1.00 0.40
Kisiwa, occasionally flooded-----	40	Very limited Flooding Restricted permeability Ponding Depth to saturated zone Filtering capacity	 1.00 1.00 1.00 1.00 1.00	Very limited Ponding Flooding Seepage	 1.00 1.00 1.00
1004: Albion-----	90	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
1011: Albion-----	70	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
Shellabarger-----	30	Somewhat limited Restricted permeability	0.50	Slope Somewhat limited Seepage Slope	0.09 0.50 0.00
1057: Aguents-----	100	Very limited Ponding Depth to saturated zone Filtering capacity	1.00 1.00 1.00	Very limited Ponding Seepage Depth to saturated zone	1.00 1.00 1.00
1061: Arents, Earthen Dam-	100	Not rated		Not rated	
1062: Arents, Landfill----	100	Very limited Slope	1.00	Very limited Slope	1.00
1070: Avans-----	100	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
1071: Avans-----	85	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage Slope	0.50 0.00
1072: Avans-----	85	Somewhat limited Restricted permeability	0.50	Somewhat limited Slope Seepage	0.67 0.50
1191: Blazefork-----	90	Very limited Restricted permeability Depth to saturated zone Flooding	1.00 1.00 0.40	Somewhat limited Depth to saturated zone Flooding	0.71 0.40
1192: Blazefork-----	60	Very limited Restricted permeability Depth to saturated zone Flooding	1.00 1.00 0.40	Somewhat limited Depth to saturated zone Flooding	0.71 0.40
Kaskan-----	40	Very limited		Very limited	

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
1200: Buhler-----	65	Filtering capacity	1.00	Seepage	1.00
		Restricted permeability	0.50	Flooding	0.40
		Depth to saturated zone	0.43		
		Flooding	0.40		
Blazefork-----	30	Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
		Depth to saturated zone	0.43	Flooding	0.40
		Flooding	0.40		
		Very limited Restricted permeability	1.00	Somewhat limited Depth to saturated zone	0.71
1324: Carway-----	50	Depth to saturated zone	1.00	Flooding	0.40
		Flooding	0.40		
		Very limited Restricted permeability	1.00	Very limited Ponding	1.00
		Ponding	1.00	Seepage	0.50
Carbika-----	30	Depth to saturated zone	1.00		
		Very limited Ponding	1.00	Very limited Ponding	1.00
		Depth to saturated zone	1.00	Seepage	0.50
		Restricted permeability	0.50		
1357: Carway-----	40	Very limited Restricted permeability	1.00	Very limited Ponding	1.00
		Ponding	1.00	Seepage	0.50
		Depth to saturated zone	1.00		
		Very limited Restricted permeability	1.00	Very limited Seepage	1.00
Dillhut-----	30	Depth to saturated zone	1.00	Depth to saturated zone	0.00
		Filtering capacity	1.00		
		Very limited Depth to saturated zone	1.00	Very limited Seepage	1.00
		Restricted permeability	0.68	Depth to saturated zone	1.00
1359: Clark-----	70	Very limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
		Somewhat limited Restricted permeability	0.50	Slope	0.33
		Very limited Restricted permeability	1.00	Somewhat limited Slope	0.67
1428: Crete-----	100	Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.32
		Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.32
				Slope	0.00
1553: Darlow-----	70	Very limited Restricted permeability	1.00	Not limited	
		Very limited Restricted permeability	1.00	Very limited Seepage	1.00
		Very limited Restricted permeability	1.00	Very limited Seepage	1.00
1554: Dillhut-----	70	Very limited Restricted permeability	1.00	Very limited Seepage	1.00

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
1555: Dillhut-----	35	Depth to saturated zone	1.00	Depth to saturated zone	0.00
		Filtering capacity	1.00	Slope	0.00
		Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Restricted permeability	0.50	Slope	0.00
Plev-----	35	Very limited		Very limited	
		Depth to saturated zone	1.00	Seepage	1.00
		Filtering capacity	1.00		
		Restricted permeability	0.50		
1556: Dillhut-----	30	Very limited		Very limited	
		Filtering capacity	1.00	Seepage	1.00
		Restricted permeability	0.50	Slope	0.00
		Very limited		Very limited	
Solvay-----	30	Depth to saturated zone	1.00	Seepage	1.00
		Restricted permeability	0.68	Depth to saturated zone	1.00
		Somewhat limited		Somewhat limited	
		Restricted permeability	0.50	Seepage	0.50
1725: Farnum-----	40	Very limited		Not limited	
		Restricted permeability	1.00		
1727: Funmar-----	55	Very limited		Not limited	
		Restricted permeability	1.00		
Taver-----	45	Very limited		Not limited	
		Restricted permeability	1.00		
1804: Geary-----	100	Somewhat limited		Somewhat limited	
		Restricted permeability	0.50	Seepage	0.50
1807: Geary, Moderately Eroded-----	100	Somewhat limited		Slope	0.00
		Restricted permeability	0.50	Seepage	0.50
		Very limited		Very limited	
		Restricted permeability	1.00	Seepage	1.00
1985: Hayes-----	60	Very limited		Slope	0.09
		Restricted permeability	1.00	Very limited	
1986: Hayes-----	55	Very limited		Seepage	1.00
		Restricted permeability	1.00	Slope	0.09
Solvay-----	20	Very limited		Very limited	
		Depth to saturated zone	1.00	Seepage	1.00
		Restricted permeability	0.68	Depth to saturated zone	1.00
		Very limited		Very limited	
1987: Hayes-----	40	Restricted permeability	1.00	Seepage	1.00
				Slope	0.09
Turon-----	35	Very limited		Very limited	
		Restricted permeability	1.00	Seepage	1.00
2204: Jamash-----	50	Filtering capacity	1.00	Slope	0.09
		Very limited		Very limited	

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Piedmont----- 2205: Jamash-----	50	Depth to bedrock	1.00	Depth to soft bedrock	1.00
		Very limited Restricted permeability	1.00	Very limited Depth to soft bedrock	1.00
		Depth to bedrock	1.00		
Piedmont----- 2206: Jamash-----	60	Very limited Depth to bedrock	1.00	Very limited Depth to soft bedrock	1.00
				Slope	0.00
		Very limited Restricted permeability	1.00	Very limited Depth to soft bedrock	1.00
Piedmont----- 2207: Jamash-----	40	Depth to bedrock	1.00	Slope	0.00
		Very limited Restricted permeability	1.00	Very limited Depth to soft bedrock	1.00
		Depth to bedrock	1.00	Slope	0.00
Piedmont----- 2381: Kanza-----	60	Very limited Depth to bedrock	1.00	Very limited Depth to soft bedrock	1.00
				Slope	0.91
		Very limited Restricted permeability	1.00	Very limited Depth to soft bedrock	1.00
Piedmont----- 2390: Kaskan-----	40	Depth to bedrock	1.00	Slope	0.91
		Very limited Depth to bedrock	1.00	Very limited Depth to soft bedrock	1.00
				Slope	0.67
Piedmont----- 2391: Kaskan-----	50	Very limited Flooding	1.00	Very limited Flooding	1.00
		Depth to saturated zone	1.00	Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
Piedmont----- 2395: Kisiwa-----	50	Very limited Flooding	1.00	Very limited Flooding	1.00
		Depth to saturated zone	1.00	Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
Piedmont----- 2509: Ladysmith-----	85	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Restricted permeability	0.50	Flooding	0.40
		Depth to saturated zone	0.43		
Piedmont----- 2556: Langdon-----	75	Flooding	0.40		
		Very limited Flooding	1.00	Very limited Flooding	1.00
		Filtering capacity	1.00	Seepage	1.00
Piedmont----- 2587: Imano-----	90	Depth to saturated zone	0.43		
		Filtering capacity	1.00	Very limited Ponding	1.00
		Very limited Restricted permeability	1.00	Seepage	1.00
Piedmont----- 2587: Imano-----	100	Ponding	1.00		
		Depth to saturated zone	1.00	Very limited Ponding	1.00
		Filtering capacity	1.00	Seepage	1.00
Piedmont----- 2587: Imano-----	50	Very limited Restricted permeability	1.00	Somewhat limited Depth to saturated zone	0.81
		Depth to saturated zone	1.00		
		Filtering capacity	1.00	Very limited Seepage	1.00
Piedmont----- 2587: Imano-----	85	Slope	0.00	Slope	1.00
		Very limited			
				Very limited	

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
2588: Longford, Moderately Eroded-----	90	Flooding	1.00	Flooding	1.00
		Restricted permeability	1.00	Seepage	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Filtering capacity	1.00		
2812: Mahone-----	95	Very limited		Somewhat limited	
		Restricted permeability	1.00	Slope	0.33
		Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Restricted permeability	0.50	Flooding	0.40
2948: Nalim-----	80	Depth to saturated zone	0.43		
		Flooding	0.40		
		Very limited Restricted permeability	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00		
2949: Naron, Moderately Eroded-----	85	Very limited		Very limited	
		Filtering capacity	1.00	Seepage	1.00
		Restricted permeability	0.50	Slope	0.33
2950: Naron, Moderately Eroded-----	85	Very limited		Very limited	
		Filtering capacity	1.00	Seepage	1.00
		Restricted permeability	0.50	Slope	1.00
		Slope	0.16		
2951: Nash-----	90	Very limited Depth to bedrock	1.00	Very limited Depth to soft bedrock	1.00
		Restricted permeability	0.50	Seepage	0.50
				Slope	0.00
2952: Nash-----	60	Very limited Depth to bedrock	1.00	Very limited Depth to soft bedrock	1.00
		Restricted permeability	0.50	Slope	0.67
				Seepage	0.50
				Very limited Depth to soft bedrock	1.00
Lucien-----	30	Very limited Depth to bedrock	1.00	Slope	0.91
2953: Nash, Moderately Eroded-----	70	Very limited		Very limited	
		Depth to bedrock	1.00	Depth to soft bedrock	1.00
		Restricted permeability	0.50	Slope	1.00
		Slope	0.37	Seepage	0.50
Lucien-----	20	Very limited Depth to bedrock	1.00	Very limited Depth to soft bedrock	1.00
		Slope	0.63	Slope	1.00
2955: Nickerson-----	100	Very limited		Very limited	
		Depth to saturated zone	1.00	Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
2956: Nickerson-----	85	Very limited		Very limited	

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
2957: Nickerson-----	50	Depth to saturated zone	1.00	Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
		Very limited Depth to saturated zone	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
Punkin-----	50	Very limited Restricted permeability	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00		
2958: Ninnescah-----	85	Very limited Flooding	1.00	Very limited Flooding	1.00
		Depth to saturated zone	1.00	Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
2959: Ninnescah, saline---	100	Very limited Flooding	1.00	Very limited Flooding	1.00
		Depth to saturated zone	1.00	Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
3051: Ost-----	90	Very limited Restricted permeability	1.00	Not limited	
3052: Ost-----	55	Very limited Restricted permeability	1.00	Somewhat limited Slope	0.00
Clark-----	45	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
				Slope	0.00
3170: Penalosa-----	100	Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
3171: Penalosa-----	100	Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
3180: Pratt-----	85	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
				Slope	1.00
3181: Pratt-----	45	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
				Slope	0.09
Turon-----	30	Very limited Restricted permeability	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00	Slope	0.09
3190: Punkin-----	90	Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
3191: Punkin-----	70	Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
Taver-----	20	Very limited Restricted permeability	1.00	Not limited	
3403: Sand Pit-----	100	Not rated		Not rated	
3469: Smolan-----	90	Very limited		Somewhat limited	

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
3510: Saltcreek-----	50	Restricted permeability	1.00	Slope	0.00
		Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
		Funmar-----	30	Slope Not limited	0.00
Farnum-----	20	Very limited Restricted permeability	1.00		
3511: Saltcreek-----	70	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
		Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
		Naron, sandy substratum-----	30	Very limited	
3512: Saltcreek-----	50	Filtering capacity Restricted permeability	1.00	Seepage	1.00
			0.50		
		Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
Naron-----	50	Slope	0.00	Slope	0.00
		Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Restricted permeability	0.50	Slope	0.00
3520: Saxman-----	85	Very limited Depth to saturated zone	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
		Flooding	0.40	Flooding	0.40
3530: Shellabarger, Eroded	45	Somewhat limited Restricted permeability	0.50	Very limited Slope	1.00
		Slope	0.16	Seepage	0.50
		Albion-----	40	Very limited Seepage	1.00
3531: Shellabarger, Moderately Eroded--	50	Filtering capacity	1.00	Seepage	1.00
		Slope	0.16	Slope	1.00
		Somewhat limited		Somewhat limited	
Nalim-----	50	Restricted permeability	0.50	Seepage	0.50
		Very limited Restricted permeability	1.00	Slope Very limited Seepage	0.33 1.00
		Filtering capacity	1.00	Slope	0.33
3532: Shellabarger-----	80	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
				Slope	0.00
3533: Shellabarger-----	85	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
3534: Shellabarger-----	85	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
				Slope	0.00
3535: Shellabarger-----	55	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
				Slope	0.00
Nalim-----	45	Very limited		Very limited	

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
3540: Solvay-----	90	Restricted permeability	1.00	Seepage	1.00
		Filtering capacity	1.00	Slope	0.00
		Very limited Depth to saturated zone	1.00	Very limited Seepage	1.00
		Restricted permeability	0.68	Depth to saturated zone	1.00
3550: Spelvin-----	100	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Restricted permeability	0.50		
3639: Taver-----	90	Very limited Restricted permeability	1.00	Not limited	
3640: Tivin-----	95	Very limited Filtering capacity	1.00	Very limited Slope	1.00
		Slope	1.00	Seepage	1.00
3641: Tivin-----	45	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Slope	0.16	Slope	1.00
Dillhut-----	40	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Restricted permeability	0.50	Slope	0.09
3642: Tivin-----	70	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Depth to saturated zone	0.08	Slope	0.91
Willowbrook, occasionally flooded-----	30	Very limited		Very limited	
		Flooding	1.00	Flooding	1.00
		Filtering capacity	1.00	Seepage	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00
3643: Tobin-----	100	Very limited Flooding	1.00	Very limited Flooding	1.00
		Restricted permeability	0.50	Seepage	0.50
3644: Turon-----	65	Very limited Restricted permeability	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00	Slope	0.33
Carway-----	20	Very limited Restricted permeability	1.00	Very limited Ponding	1.00
		Ponding	1.00	Seepage	0.50
		Depth to saturated zone	1.00		
3760: Urban Land, Protected-----	50	Not rated		Not rated	
Blazefork, Protected	25	Very limited Restricted permeability	1.00	Somewhat limited Depth to saturated zone	0.71
		Depth to saturated zone	1.00		
Kaskan, Protected---	25	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Restricted permeability	0.50		

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
3762: Urban Land-----	50	Depth to saturated zone	0.43		
Darlow-----	25	Not rated		Not rated	
Elmer-----	15	Very limited Restricted permeability	1.00	Not limited	
3763: Urban Land, Protected-----	50	Very limited Restricted permeability	1.00	Very limited Seepage	1.00
Imano, Protected----	40	Not rated		Not rated	
		Very limited Restricted permeability	1.00	Very limited Seepage	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Filtering capacity	1.00		
3764: Urban Land, Protected-----	60	Not rated		Not rated	
Mahone, Protected---	35	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Restricted permeability	0.50		
		Depth to saturated zone	0.43		
3765: Urban Land-----	50	Not rated		Not rated	
Saltcreek-----	35	Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
Naron-----	15	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Restricted permeability	0.50		
3766: Urban Land, Protected-----	50	Not rated		Not rated	
Saxman, Protected---	45	Very limited Depth to saturated zone	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
3767: Urban Land, Protected-----	50	Not rated		Not rated	
Willowbrook, Protected-----	45	Very limited		Very limited	
		Filtering capacity	1.00	Seepage	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00
3768: Urban Land, Protected-----	50	Not rated		Not rated	
Yaggy, Protected----	45	Very limited Depth to saturated zone	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
3900: Walnut-----	75	Very limited Ponding	1.00	Very limited Ponding	1.00
		Depth to saturated zone	1.00	Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
3926: Water-----	100	Not rated		Not rated	
3966: Willowbrook-----	90	Very limited Flooding Filtering capacity Depth to saturated zone	1.00 1.00 1.00	Very limited Flooding Seepage Depth to saturated zone	1.00 1.00 1.00
4004: Yaggy-----	95	Very limited Flooding Depth to saturated zone Filtering capacity	1.00 1.00 1.00	Very limited Flooding Seepage Depth to saturated zone	1.00 1.00 1.00
4005: Yaggy-----	60	Very limited Flooding Depth to saturated zone Filtering capacity	1.00 1.00 1.00	Very limited Flooding Seepage Depth to saturated zone	1.00 1.00 1.00
Saxman-----	30	Very limited Depth to saturated zone Filtering capacity Flooding	1.00 1.00 1.00 0.40	Very limited Seepage Depth to saturated zone Flooding	1.00 1.00 1.00 0.40
4110: Zellmont-----	70	Very limited Depth to bedrock Restricted permeability	1.00 1.00	Very limited Depth to soft bedrock Seepage	1.00 0.50
Poxmash-----	30	Very limited Filtering capacity Depth to bedrock	1.00 0.73	Very limited Seepage Depth to soft bedrock	1.00 0.32

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
990: Abbyville-----	95	Very limited Depth to saturated zone Sodium content Too clayey	1.00 1.00 0.50	Very limited Depth to saturated zone	1.00	Very limited Sodium content Too clayey Depth to saturated zone	1.00 0.50 0.09
991: Abbyville, rarely flooded-----	45	Very limited Depth to saturated zone Sodium content Too clayey	1.00 1.00 0.50	Very limited Depth to saturated zone Flooding	1.00 0.40	Very limited Sodium content Too clayey Depth to saturated zone	1.00 0.50 0.09
Kisiwa, occasionally flooded-----	40	Flooding Very limited Flooding Depth to saturated zone Ponding Sodium content Seepage	0.40 1.00 1.00 1.00 1.00	Very limited Flooding Ponding Depth to saturated zone	1.00 1.00 1.00	Very limited Ponding Depth to saturated zone Seepage Sodium content Too clayey	1.00 1.00 1.00 1.00
1004: Albion-----	90	Very limited Seepage Too Sandy	1.00 1.00	Very limited Seepage	1.00	Very limited Too Sandy Seepage	1.00 1.00
1011: Albion-----	70	Very limited Seepage Too Sandy	1.00 1.00	Very limited Seepage	1.00	Very limited Too Sandy Seepage	1.00 1.00
Shellabarger-----	30	Not limited		Not limited		Not limited	
1057: Aquents-----	100	Very limited Depth to saturated zone Ponding Seepage Too Sandy	1.00 1.00 1.00 1.00	Very limited Ponding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Ponding Depth to saturated zone Too Sandy Seepage	1.00 1.00 1.00 1.00
1061: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
1062: Arents, Landfill----	100	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00
1070: Avans-----	100	Not limited		Not limited		Not limited	
1071: Avans-----	85	Not limited		Not limited		Not limited	
1072: Avans-----	85	Not limited		Not limited		Not limited	
1191: Blazefork-----	90	Very limited Depth to saturated zone Too clayey Flooding	1.00 0.50 0.40	Very limited Depth to saturated zone Flooding	1.00 0.40	Somewhat limited Too clayey	0.50
1192: Blazefork-----	60	Very limited Depth to saturated zone Too clayey Flooding	1.00 0.50 0.40	Very limited Depth to saturated zone Flooding	1.00 0.40	Somewhat limited Too clayey	0.50
Kaskan-----	40	Very limited Depth to saturated zone Seepage Too Sandy Flooding	1.00 1.00 1.00 0.40	Very limited Depth to saturated zone Seepage Flooding	1.00 1.00 0.40	Very limited Too Sandy Seepage	1.00 1.00
1200: Buhler-----	65	Very limited Depth to saturated zone Sodium content Flooding	1.00 1.00 0.40	Very limited Depth to saturated zone Flooding	1.00 0.40	Very limited Sodium content Too clayey	1.00 0.50
Blazefork-----	30	Very limited Depth to saturated zone Too clayey	1.00 0.50	Very limited Depth to saturated zone Flooding	1.00 0.40	Somewhat limited Too clayey	0.50

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
1324: Carway-----	50	Flooding	0.40				
		Very limited	1.00	Very limited	1.00	Very limited	1.00
		Depth to saturated zone	1.00	Ponding	1.00	Ponding	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
Carbika-----	30	Too clayey	0.50			Hard to compact	1.00
		Very limited	1.00	Very limited	1.00	Too clayey	0.50
		Depth to saturated zone	1.00	Ponding	1.00	Very limited	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Ponding	1.00
1357: Carway-----	40	Too clayey	0.50			Depth to saturated zone	1.00
		Very limited	1.00	Very limited	1.00	Too clayey	0.50
		Depth to saturated zone	1.00	Ponding	1.00	Very limited	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Ponding	1.00
Dillhut-----	30	Too clayey	0.50			Depth to saturated zone	1.00
		Very limited	1.00	Very limited	1.00	Hard to compact	1.00
		Depth to saturated zone	1.00	Seepage	1.00	Too clayey	0.50
		Too Sandy	1.00	Depth to saturated zone	1.00	Too Sandy	1.00
Solvay-----	30					Seepage	1.00
		Very limited	1.00	Very limited	1.00	Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Somewhat limited	0.50
		Seepage	1.00	Seepage	1.00	Seepage	0.09
1359: Clark-----	70	Not limited		Not limited		Depth to saturated zone	
Ost-----	30	Not limited		Not limited		Not limited	
1428: Crete-----	100	Somewhat limited	0.50	Not limited		Not limited	
		Too clayey				Very limited	1.00
1429: Crete-----	100	Not limited		Not limited		Too clayey	1.00
						Hard to compact	1.00
1553: Darlow-----	70	Very limited	1.00	Not limited		Very limited	1.00
Elmer-----	20	Sodium content	1.00	Not limited		Sodium content	1.00
		Very limited	1.00			Very limited	1.00
		Sodium content	1.00			Sodium content	0.16
		Seepage	1.00			Seepage	
1554: Dillhut-----	70	Very limited	1.00	Very limited	1.00	Very limited	1.00
		Depth to saturated zone	1.00	Seepage	1.00	Too Sandy	1.00
		Too Sandy	1.00	Depth to saturated zone	1.00	Seepage	1.00
1555: Dillhut-----	35		1.00		1.00	Depth to saturated zone	1.00
Plev-----	35	Very limited	1.00	Very limited	1.00	Not limited	
		Depth to saturated zone	1.00	Seepage	1.00	Very limited	1.00
		Seepage	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Too Sandy	1.00	Seepage	1.00	Too Sandy	1.00
1556: Dillhut-----	30		1.00		1.00	Seepage	1.00
Solvay-----	30	Very limited	1.00	Very limited	1.00	Depth to saturated zone	1.00
		Seepage	1.00	Seepage	1.00	Not limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Somewhat limited	0.50
		Seepage	1.00	Seepage	1.00	Seepage	0.09
1725: Farnum-----	40	Not limited		Not limited		Depth to saturated zone	
Funmar-----	40	Somewhat limited	0.50	Not limited		Not limited	
		Too clayey				Very limited	1.00
						Hard to compact	1.00
						Too clayey	0.50

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
1727: Funmar-----	55	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
Taver-----	45	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
1804: Geary-----	100	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
1807: Geary, Moderately Eroded-----	100	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
1985: Hayes-----	60	Very limited Too clayey	1.00	Very limited Seepage	1.00	Very limited Hard to compact	1.00
1986: Hayes-----	55	Very limited Too clayey	1.00	Very limited Seepage	1.00	Very limited Hard to compact	1.00
Solvay-----	20	Very limited Depth to saturated zone Seepage	1.00 1.00	Very limited Depth to saturated zone Seepage	1.00 1.00	Somewhat limited Seepage Depth to saturated zone	0.50 0.09
1987: Hayes-----	40	Very limited Too clayey	1.00	Very limited Seepage	1.00	Very limited Hard to compact	1.00
Turon-----	35	Very limited Too Sandy	1.00	Very limited Seepage	1.00	Very limited Seepage Too Sandy	1.00 0.50
2204: Jamash-----	50	Very limited Depth to bedrock Too clayey	1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey	1.00 0.50
Piedmont-----	50	Very limited Depth to bedrock Too clayey	1.00 1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey Hard to compact	1.00 1.00 1.00
2205: Jamash-----	60	Very limited Depth to bedrock Too clayey	1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey	1.00 0.50
Piedmont-----	40	Very limited Depth to bedrock Too clayey	1.00 1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey Hard to compact	1.00 1.00 1.00
2206: Jamash-----	60	Very limited Depth to bedrock Too clayey	1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey	1.00 0.50
Piedmont-----	40	Very limited Depth to bedrock Too clayey	1.00 1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey Hard to compact	1.00 1.00 1.00
2207: Jamash-----	80	Very limited Depth to bedrock Too clayey	1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey	1.00 0.50
2381: Kanza-----	50	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Too Sandy Seepage Depth to saturated zone	1.00 1.00 1.00
Ninnescah-----	50	Too Sandy Very limited Flooding Depth to saturated zone Too Sandy Seepage	1.00 1.00 1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Seepage Depth to saturated zone Too Sandy	1.00 0.86 0.50
2390: Kaskan-----	85	Very limited Depth to saturated zone Seepage Too Sandy Flooding	1.00 1.00 1.00 0.40	Very limited Depth to saturated zone Seepage Flooding	1.00 1.00 0.40	Very limited Too Sandy Seepage	1.00 1.00
2391: Kaskan-----	75	Very limited		Very limited		Very limited	

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
2395: Kisiwa-----	90	Flooding	1.00	Flooding	1.00	Too Sandy	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Seepage	1.00
		Too Sandy	1.00	Seepage	1.00		
		Seepage	1.00				
2509: Ladysmith-----	100	Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Ponding	1.00	Ponding	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Sodium content	1.00			Seepage	1.00
2556: Langdon-----	50	Seepage	1.00	Sodium content		Sodium content	1.00
		Too clayey	1.00	Too clayey		Too clayey	1.00
		Somewhat limited		Somewhat limited		Very limited	
		Depth to saturated zone	0.86	Depth to saturated zone	0.19	Hard to compact	1.00
2587: Imano-----	85	Too clayey	0.50			Too clayey	0.50
						Depth to saturated zone	0.47
		Very limited		Very limited		Very limited	
		Seepage	1.00	Seepage	1.00	Too Sandy	1.00
2588: Longford, Moderately Eroded-----	90	Too Sandy	1.00	Slope	0.00	Seepage	1.00
		Slope	0.00			Slope	0.00
		Very limited		Very limited		Very limited	
		Flooding	1.00	Flooding	1.00	Too Sandy	1.00
2812: Mahone-----	95	Depth to saturated zone	1.00	Depth to saturated zone	1.00	Seepage	1.00
		Seepage	1.00	Seepage	1.00	Depth to saturated zone	0.09
		Flooding	0.40	Flooding	0.40		
		Too Sandy	1.00				
2948: Nalim-----	80	Very limited		Not limited		Very limited	
		Seepage	1.00			Too clayey	1.00
		Too clayey	0.50				
2949: Naron, Moderately Eroded-----	85			Very limited		Somewhat limited	
		Seepage	1.00	Depth to saturated zone	1.00	Seepage	0.50
				Seepage	1.00		
				Flooding	0.40		
2950: Naron, Moderately Eroded-----	85	Very limited		Not limited		Very limited	
		Seepage	1.00			Seepage	1.00
						Too clayey	0.50
2951: Nash-----	90	Very limited		Somewhat limited		Somewhat limited	
		Depth to bedrock	1.00	Slope	0.16	Slope	0.16
		Seepage	1.00				
2952: Nash-----	60	Very limited		Very limited		Very limited	
		Depth to bedrock	1.00	Depth to bedrock	1.00	Depth to bedrock	1.00
		Seepage	1.00				
2953: Nash, Moderately Eroded-----	70	Very limited		Very limited		Very limited	
		Depth to bedrock	1.00	Depth to bedrock	1.00	Depth to bedrock	1.00
		Seepage	1.00	Slope	0.37	Slope	0.37
		Slope	0.37				
2955: Nickerson-----	100	Very limited		Very limited		Very limited	
		Depth to bedrock	1.00	Depth to bedrock	1.00	Depth to bedrock	1.00
		Seepage	1.00	Slope	0.63	Slope	0.63
		Slope	0.63				
2955: Nickerson-----	100	Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too Sandy	1.00

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
2956: Nickerson-----	85	Seepage Too Sandy	1.00 1.00	Seepage	1.00	Seepage Depth to saturated zone	1.00 0.09
		Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Too Sandy	1.00
		Seepage Too Sandy	1.00 1.00	Seepage	1.00	Seepage Depth to saturated zone	1.00 0.09
2957: Nickerson-----	50	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Too Sandy	1.00
		Seepage Too Sandy	1.00 1.00	Seepage	1.00	Seepage Depth to saturated zone	1.00 0.09
Punkin-----	50	Very limited Seepage Too Sandy	1.00 1.00	Not limited		Very limited Too Sandy	1.00
		Sodium content	1.00			Seepage Depth to saturated zone	1.00 1.00
2958: Ninnescah-----	85	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Seepage Depth to saturated zone	1.00 0.86
		Too Sandy	1.00	Seepage	1.00	Too Sandy	0.50
		Seepage	1.00				
2959: Ninnescah, saline---	100	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Seepage	1.00
		Too Sandy	1.00	Seepage	1.00	Too Sandy	0.50
		Seepage	1.00				
3051: Ost-----	90	Not limited		Not limited		Not limited	
3052: Ost-----	55	Not limited		Not limited		Not limited	
Clark-----	45	Not limited		Not limited		Not limited	
3170: Penalosa-----	100	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
3171: Penalosa-----	100	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
3180: Pratt-----	85	Very limited Seepage Too Sandy	1.00 1.00	Very limited Seepage	1.00	Very limited Too Sandy Seepage	1.00 1.00
3181: Pratt-----	45	Very limited Seepage Too Sandy	1.00 1.00	Very limited Seepage	1.00	Very limited Too Sandy Seepage	1.00 1.00
Turon-----	30	Very limited Too Sandy	1.00	Very limited Seepage	1.00	Very limited Seepage Too Sandy	1.00 0.50
3190: Punkin-----	90	Very limited Sodium content Too clayey	1.00 0.50	Not limited		Very limited Sodium content Hard to compact Too clayey	1.00 1.00 0.50
3191: Punkin-----	70	Very limited Sodium content Too clayey	1.00 0.50	Not limited		Very limited Sodium content Hard to compact Too clayey	1.00 1.00 0.50
Taver-----	20	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
3403: Sand Pit-----	100	Not rated		Not rated		Not rated	
3469: Smolan-----	90	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
3510: Saltcreek-----	50	Very limited Too clayey	1.00	Not limited		Very limited Too clayey	1.00

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Funmar-----	30	Somewhat limited Too clayey	0.50	Not limited		Hard to compact Very limited	1.00
Farnum-----	20	Not limited		Not limited		Hard to compact Too clayey	1.00 0.50
3511: Saltcreek-----	70	Very limited Too clayey	1.00	Not limited		Very limited Too clayey	1.00 1.00
Naron, sandy substratum-----	30	Very limited		Very limited		Hard to compact Somewhat limited	
3512: Saltcreek-----	50	Seepage	1.00	Seepage	1.00	Seepage	0.50
		Very limited Too clayey	1.00	Not limited		Very limited Too clayey	1.00
Naron-----	50	Very limited Seepage	1.00	Not limited		Hard to compact Not limited	1.00
3520: Saxman-----	85	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Too Sandy	1.00
		Seepage	1.00	Seepage	1.00	Seepage	1.00
		Too Sandy	1.00	Flooding	0.40	Depth to saturated zone	0.47
		Flooding	0.40				
3530: Shellabarger, Eroded	45	Somewhat limited Slope	0.16	Somewhat limited Slope	0.16	Somewhat limited Slope	0.16
Albion-----	40	Very limited Seepage	1.00	Very limited Seepage	1.00	Very limited Too Sandy	1.00
		Too Sandy	1.00	Slope	0.16	Seepage	1.00
		Slope	0.16			Slope	0.16
3531: Shellabarger, Moderately Eroded--	50	Not limited		Not limited		Not limited	
Nalim-----	50	Very limited Seepage	1.00	Not limited		Very limited Seepage	1.00
		Too clayey	0.50			Too clayey	0.50
3532: Shellabarger-----	80	Not limited		Not limited		Not limited	
3533: Shellabarger-----	85	Not limited		Not limited		Not limited	
3534: Shellabarger-----	85	Not limited		Not limited		Not limited	
3535: Shellabarger-----	55	Not limited		Not limited		Not limited	
Nalim-----	45	Very limited Seepage	1.00	Not limited		Very limited Seepage	1.00
		Too clayey	0.50			Too clayey	0.50
3540: Solvay-----	90	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Seepage	0.50
		Seepage	1.00	Seepage	1.00	Depth to saturated zone	0.09
3550: Spelvin-----	100	Very limited Seepage	1.00	Very limited Seepage	1.00	Very limited Seepage	1.00
3639: Taver-----	90	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
3640: Tivin-----	95	Very limited Seepage	1.00	Very limited Seepage	1.00	Very limited Too Sandy	1.00
		Too Sandy	1.00	Slope	1.00	Seepage	1.00
		Slope	1.00			Slope	1.00
3641: Tivin-----	45	Very limited Seepage	1.00	Very limited Seepage	1.00	Very limited Too Sandy	1.00
		Too Sandy	1.00	Slope	0.16	Seepage	1.00
		Slope	0.16			Slope	0.16
Dillhut-----	40	Very limited Seepage	1.00	Very limited Seepage	1.00	Not limited	
3642: Tivin-----	70	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Too Sandy	1.00
		Seepage	1.00	Seepage	1.00	Seepage	1.00
		Too Sandy	1.00				

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Willowbrook, occasionally flooded-----	30	Very limited		Very limited		Very limited	
		Flooding	1.00	Flooding	1.00	Too Sandy	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Seepage	1.00
		Seepage	1.00	Seepage	1.00	Depth to saturated zone	0.09
		Too Sandy	1.00				
3643: Tobin-----	100	Very limited		Very limited		Not limited	
		Flooding	1.00	Flooding	1.00		
		Too clayey	0.50				
3644: Turon-----	65	Very limited		Very limited		Very limited	
		Too Sandy	1.00	Seepage	1.00	Seepage	1.00
						Too Sandy	0.50
Carway-----	20	Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Ponding	1.00	Ponding	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Too clayey	0.50			Hard to compact	1.00
						Too clayey	0.50
3760: Urban Land, Protected-----	50	Not rated		Not rated		Not rated	
Blazefork, Protected	25	Very limited		Very limited		Somewhat limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too clayey	0.50
		Too clayey	0.50				
Kaskan, Protected---	25	Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too Sandy	1.00
		Seepage	1.00	Seepage	1.00	Seepage	1.00
		Too Sandy	1.00				
3762: Urban Land-----	50	Not rated		Not rated		Not rated	
Darlow-----	25	Very limited		Not limited		Very limited	
		Sodium content	1.00			Sodium content	1.00
Elmer-----	15	Very limited		Not limited		Very limited	
		Sodium content	1.00			Sodium content	1.00
		Seepage	1.00			Seepage	0.16
3763: Urban Land, Protected-----	50	Not rated		Not rated		Not rated	
Imano, Protected----	40	Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too Sandy	1.00
		Seepage	1.00	Seepage	1.00	Seepage	1.00
		Too Sandy	1.00			Depth to saturated zone	0.09
3764: Urban Land, Protected-----	60	Not rated		Not rated		Not rated	
Mahone, Protected---	35	Very limited		Very limited		Somewhat limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Seepage	0.50
		Seepage	1.00	Seepage	1.00		
3765: Urban Land-----	50	Not rated		Not rated		Not rated	
Saltcreek-----	35	Very limited		Not limited		Very limited	
		Too clayey	1.00			Too clayey	1.00
						Hard to compact	1.00
Naron-----	15	Very limited		Very limited		Somewhat limited	
		Seepage	1.00	Seepage	1.00	Seepage	0.50
3766: Urban Land, Protected-----	50	Not rated		Not rated		Not rated	
Saxman, Protected---	45	Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too Sandy	1.00
		Seepage	1.00	Seepage	1.00	Seepage	1.00
		Too Sandy	1.00			Depth to saturated zone	0.47

SANITARY FACILITIES--Continued
Reno County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
3767: Urban Land, Protected-----	50	Not rated		Not rated		Not rated	
Willowbrook, Protected-----	45	Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too Sandy	1.00
		Seepage	1.00	Seepage	1.00	Seepage	1.00
		Too Sandy	1.00			Depth to saturated zone	0.09
3768: Urban Land, Protected-----	50	Not rated		Not rated		Not rated	
Yaggy, Protected----	45	Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too Sandy	1.00
		Seepage	1.00	Seepage	1.00	Seepage	1.00
		Too Sandy	1.00			Gravel content	1.00
						Depth to saturated zone	0.09
3900: Warnut-----	75	Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Ponding	1.00	Ponding	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Too Sandy	1.00	Seepage	1.00	Seepage	1.00
		Seepage	1.00			Too Sandy	0.50
3926: Water-----	100	Not rated		Not rated		Not rated	
3966: Willowbrook-----	90	Very limited		Very limited		Very limited	
		Flooding	1.00	Flooding	1.00	Too Sandy	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Seepage	1.00
		Seepage	1.00	Seepage	1.00	Depth to saturated zone	0.09
		Too Sandy	1.00				
4004: Yaggy-----	95	Very limited		Very limited		Very limited	
		Flooding	1.00	Flooding	1.00	Too Sandy	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Seepage	1.00
		Seepage	1.00	Seepage	1.00	Depth to saturated zone	0.09
		Too Sandy	1.00				
4005: Yaggy-----	60	Very limited		Very limited		Very limited	
		Flooding	1.00	Flooding	1.00	Too Sandy	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Seepage	1.00
		Seepage	1.00	Seepage	1.00	Depth to saturated zone	0.09
		Too Sandy	1.00				
Saxman-----	30	Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too Sandy	1.00
		Seepage	1.00	Seepage	1.00	Seepage	1.00
		Too Sandy	1.00	Flooding	0.40	Depth to saturated zone	0.47
		Flooding	0.40				
4110: Zellmont-----	70	Very limited		Very limited		Very limited	
		Depth to bedrock	1.00	Depth to bedrock	1.00	Depth to bedrock	1.00
Poxmash-----	30	Very limited		Very limited		Very limited	
		Depth to bedrock	1.00	Seepage	1.00	Too Sandy	1.00
		Too Sandy	1.00	Depth to bedrock	0.32	Seepage	1.00
						Depth to bedrock	0.32
						Gravel content	0.01

