

SANITARY FACILITIES  
Stafford County, Kansas

Sanitary Facilities

The following tables show the degree and kind of soil limitations that affect septic tank absorption fields, sewage lagoons, sanitary landfills, and daily cover for landfill. The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect these uses. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Septic tank absorption fields are areas in which effluent from a septic tank is distributed into the soil through subsurface tiles or perforated pipe. Only that part of the soil between depths of 24 and 60 inches is evaluated. The ratings are based on the soil properties that affect absorption of the effluent, construction and maintenance of the system, and public health. Permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, and flooding affect absorption of the effluent. Stones and boulders, ice, and bedrock or a cemented pan interfere with installation. Subsidence interferes with installation and maintenance. Excessive slope may cause lateral seepage and surfacing of the effluent in downslope areas.

Some soils are underlain by loose sand and gravel or fractured bedrock at a depth of less than 4 feet below the distribution lines. In these soils the absorption field may not adequately filter the effluent, particularly when the system is new. As a result, the ground water may become contaminated.

Sewage lagoons are shallow ponds constructed to hold sewage while aerobic bacteria decompose the solid and liquid wastes. Lagoons should have a nearly level floor surrounded by cut slopes or embankments of compacted soil. Nearly impervious soil material for the lagoon floor and sides is required to minimize seepage and contamination of ground water. Considered in the ratings are slope, permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, flooding, large stones, and content of organic matter.

Soil permeability is a critical property affecting the suitability for sewage lagoons. Most porous soils eventually become sealed when they are used as sites for sewage lagoons. Until sealing occurs, however, the hazard of pollution is severe. Soils that have a permeability rate of more than 2 inches per hour are too porous for the proper functioning of sewage lagoons. In these soils, seepage of the effluent can result in contamination of the ground water. Ground-water contamination is also a hazard if fractured bedrock is within a depth of 40 inches, if the water table is high enough to raise the level of sewage in the lagoon, or if floodwater overtops the lagoon.

A high content of organic matter is detrimental to proper functioning of the lagoon because it inhibits aerobic activity. Slope, bedrock, and cemented pans can cause construction problems, and large stones can hinder compaction of the lagoon floor. If the lagoon is to be uniformly deep throughout, the slope must be gentle enough and the soil material must be thick enough over bedrock or a cemented pan to make land smoothing practical.

A trench sanitary landfill is an area where solid waste is placed in successive layers in an excavated trench. The waste is spread, compacted, and covered daily with a thin layer of soil excavated at the site. When the trench is full, a final cover of soil material at least 2 feet thick is placed over the landfill. The ratings in the table are based on the soil properties that affect the risk of pollution, the ease of excavation, trafficability, and revegetation. These properties include permeability, depth to bedrock or a cemented pan, depth to a water table, ponding, slope, flooding, texture, stones and boulders, highly organic layers, soil reaction, and content of salts and sodium. Unless otherwise stated, the ratings apply only to that part of the soil within a depth of about 6 feet. For deeper trenches, onsite investigation may be needed.

Hard, nonrippable bedrock, creviced bedrock, or highly permeable strata in or directly below the proposed trench bottom can affect the ease of excavation and the hazard of ground-water pollution. Slope affects construction of the trenches and the movement of surface water around the landfill. It also affects the construction and performance of roads in areas of the landfill.

Soil texture and consistence affect the ease with which the trench is dug and the ease with which the soil can be used as daily or final cover. They determine the workability of the soil when dry and when wet. Soils that are plastic and sticky when wet are difficult to excavate, grade, or compact and are difficult to place as a uniformly thick cover over a layer of refuse.

The soil material used as the final cover for a trench landfill should be suitable for plants. It should not have excess sodium or salts and should not be too acid. The surface layer generally has the best workability, the highest content of organic matter, and the best potential for plants. Material from the surface layer should be stockpiled for use as the final cover.

SANITARY FACILITIES  
Stafford County, Kansas

In an area sanitary landfill, solid waste is placed in successive layers on the surface of the soil. The waste is spread, compacted, and covered daily with a thin layer of soil from a source away from the site. A final cover of soil material at least 2 feet thick is placed over the completed landfill. The ratings in the table are based on the soil properties that affect trafficability and the risk of pollution. These properties include flooding, permeability, depth to a water table, ponding, slope, and depth to bedrock or a cemented pan.

Flooding is a serious problem because it can result in pollution in areas downstream from the landfill. If permeability is too rapid or if fractured bedrock, a fractured cemented pan, or the water table is close to the surface, the leachate can contaminate the water supply. Slope is a consideration because of the extra grading required to maintain roads in the steeper areas of the landfill. Also, leachate may flow along the surface of the soils in the steeper areas and cause difficult seepage problems.

Daily cover for landfill is the soil material that is used to cover compacted solid waste in an area sanitary landfill. The soil material is obtained offsite, transported to the landfill, and spread over the waste. The ratings in the table also apply to the final cover for a landfill. They are based on the soil properties that affect workability, the ease of digging, and the ease of moving and spreading the material over the refuse daily during wet and dry periods. These properties include soil texture, depth to a water table, ponding, rock fragments, slope, depth to bedrock or a cemented pan, reaction, and content of salts, sodium, or lime.

Loamy or silty soils that are free of large stones and excess gravel are the best cover for a landfill. Clayey soils may be sticky and difficult to spread; sandy soils are subject to wind erosion.

Slope affects the ease of excavation and of moving the cover material. Also, it can influence runoff, erosion, and reclamation of the borrow area.

After soil material has been removed, the soil material remaining in the borrow area must be thick enough over bedrock, a cemented pan, or the water table to permit revegetation. The soil material used as the final cover for a landfill should be suitable for plants. It should not have excess sodium, salts, or lime and should not be too acid.

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
009DT: Dillwyn-----	60	Very limited Depth to saturated zone	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
Tivoli-----	40	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Slope	0.16	Slope	1.00
009TV: Tivoli-----	100	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Slope	1.00	Slope	1.00
047CS: Carwile-----	90	Very limited Restricted permeability	1.00	Very limited Ponding	1.00
		Ponding	1.00	Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Seepage	0.32
Drummond-----	10	Very limited Restricted permeability	1.00	Somewhat limited Depth to saturated zone	0.71
		Depth to saturated zone	1.00		
151KP: Kanza-----	50	Very limited Flooding	1.00	Very limited Flooding	1.00
		Depth to saturated zone	1.00	Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
Plevna-----	50	Very limited Flooding	1.00	Very limited Flooding	1.00
		Depth to saturated zone	1.00	Seepage	1.00
				Depth to saturated zone	1.00
159DP: Dillwyn-----	60	Very limited Depth to saturated zone	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
Plevna-----	40	Very limited Flooding	1.00	Very limited Flooding	1.00
		Depth to saturated zone	1.00	Seepage	1.00
				Depth to saturated zone	1.00
159DT: Dillwyn-----	60	Very limited Depth to saturated zone	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00	Depth to saturated zone	1.00
Tivoli-----	40	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Slope	0.84	Slope	1.00
159DU: Drummond-----	100	Very limited Restricted permeability	1.00	Somewhat limited Depth to saturated zone	0.71
		Depth to saturated zone	1.00		
159PE: Plevna-----	100	Very limited Flooding	1.00	Very limited Flooding	1.00
		Depth to saturated zone	1.00	Seepage	1.00
				Depth to saturated zone	1.00
990: Abbyville-----	95	Very limited Restricted permeability	1.00	Very limited Depth to saturated zone	1.00

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
991: Abbyville, rarely flooded-----	45	Depth to saturated zone Very limited	1.00	Very limited	
		Restricted permeability	1.00	Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Flooding	0.40
Kisiwa, occasionally flooded-----	40	Flooding Very limited	0.40	Very limited	
		Flooding	1.00	Ponding	1.00
		Restricted permeability	1.00	Flooding	1.00
		Ponding	1.00	Seepage	1.00
		Depth to saturated zone	1.00		
		Filtering capacity	1.00		
1005: Albion-----	75	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
				Slope	0.09
1011: Albion-----	70	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
				Slope	0.09
Shellabarger-----	30	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
				Slope	0.00
1324: Carway-----	50	Very limited Restricted permeability	1.00	Very limited Ponding	1.00
		Ponding	1.00	Seepage	0.50
		Depth to saturated zone	1.00		
Carbika-----	30	Very limited Ponding	1.00	Very limited Ponding	1.00
		Depth to saturated zone	1.00	Seepage	0.50
		Restricted permeability	0.50		
1359: Clark-----	70	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
				Slope	0.33
Ost-----	30	Very limited Restricted permeability	1.00	Somewhat limited Slope	0.67
1553: Darlow-----	70	Very limited Restricted permeability	1.00	Not limited	
Elmer-----	20	Very limited Restricted permeability	1.00	Very limited Seepage	1.00
1555: Dillhut-----	35	Very limited Filtering capacity	1.00	Very limited Seepage	1.00
		Restricted permeability	0.50	Slope	0.00
Plev-----	35	Very limited Depth to saturated zone	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00		
		Restricted permeability	0.50		
1556: Dillhut-----	30	Very limited Filtering capacity	1.00	Very limited Seepage	1.00

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Solvay-----	30	Restricted permeability	0.50	Slope	0.00
		Very limited		Very limited	
		Depth to	1.00	Seepage	1.00
		saturated zone			
		Restricted	0.68	Depth to	1.00
		permeability		saturated zone	
1725: Farnum-----	40	Somewhat limited		Somewhat limited	
		Restricted	0.50	Seepage	0.50
		permeability			
Funmar-----	40	Very limited		Not limited	
		Restricted	1.00		
		permeability			
1726: Farnum-----	40	Somewhat limited		Somewhat limited	
		Restricted	0.50	Seepage	0.50
		permeability			
Funmar-----	40	Very limited		Slope	0.00
		Restricted	1.00	Somewhat limited	0.00
		permeability		Slope	
1985: Hayes-----	60	Very limited		Very limited	
		Restricted	1.00	Seepage	1.00
		permeability			
				Slope	0.09
1986: Hayes-----	55	Very limited		Very limited	
		Restricted	1.00	Seepage	1.00
		permeability			
				Slope	0.09
Solvay-----	20	Very limited		Very limited	
		Depth to	1.00	Seepage	1.00
		saturated zone			
		Restricted	0.68	Depth to	1.00
		permeability		saturated zone	
1987: Hayes-----	40	Very limited		Very limited	
		Restricted	1.00	Seepage	1.00
		permeability			
				Slope	0.09
Turon-----	35	Very limited		Very limited	
		Restricted	1.00	Seepage	1.00
		permeability			
		Filtering	1.00	Slope	0.09
		capacity			
1988: Hayes-----	70	Very limited		Very limited	
		Restricted	1.00	Seepage	1.00
		permeability			
				Slope	0.91
2381: Kanza-----	50	Very limited		Very limited	
		Flooding	1.00	Flooding	1.00
		Depth to	1.00	Seepage	1.00
		saturated zone			
		Filtering	1.00	Depth to	1.00
		capacity		saturated zone	
Ninnescah-----	50	Very limited		Very limited	
		Flooding	1.00	Flooding	1.00
		Depth to	1.00	Seepage	1.00
		saturated zone			
		Filtering	1.00	Depth to	1.00
		capacity		saturated zone	
2556: Langdon-----	50	Very limited		Very limited	
		Filtering	1.00	Seepage	1.00
		capacity			
		Slope	0.00	Slope	1.00
2958: Ninnescah-----	85	Very limited		Very limited	
		Flooding	1.00	Flooding	1.00
		Depth to	1.00	Seepage	1.00
		saturated zone			
		Filtering	1.00	Depth to	1.00
		capacity		saturated zone	
3053: Ost-----	85	Very limited		Somewhat limited	

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
3180: Pratt-----	85	Restricted permeability	1.00	Slope	0.00
		Very limited Filtering capacity	1.00	Very limited Seepage	1.00
3181: Pratt-----	45			Slope	1.00
		Very limited Filtering capacity	1.00	Very limited Seepage	1.00
Turon-----	30			Slope	0.09
		Very limited Restricted permeability	1.00	Very limited Seepage	1.00
3511: Saltcreek-----	70	Filtering capacity	1.00	Slope	0.09
		Restricted permeability	1.00		
Naron, sandy substratum-----	30	Very limited		Somewhat limited Seepage	0.50
		Filtering capacity	1.00	Very limited	
3512: Saltcreek-----	50	Restricted permeability	0.50	Seepage	1.00
		Very limited			
Naron-----	50	Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
		Filtering capacity	1.00	Slope	0.00
3520: Saxman-----	85	Restricted permeability	0.50	Very limited Seepage	1.00
		Very limited			
3540: Solvay-----	90	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Filtering capacity	1.00	Flooding	0.40
3639: Taver-----	90	Flooding	0.40		
		Very limited Depth to saturated zone	1.00	Very limited Seepage	1.00
3640: Tivin-----	95	Restricted permeability	0.68	Depth to saturated zone	1.00
		Very limited		Not limited	
3641: Tivin-----	45	Very limited Filtering capacity	1.00		
		Slope	1.00	Very limited Slope	1.00
Dillhut-----	40			Seepage	1.00
		Very limited Filtering capacity	1.00	Very limited Seepage	1.00
3644: Turon-----	65	Slope	0.16	Slope	1.00
		Very limited Restricted permeability	1.00	Very limited Seepage	1.00
Carway-----	20	Filtering capacity	0.50	Slope	0.09
		Very limited			
		Restricted permeability	1.00	Very limited Seepage	1.00
		Filtering capacity	1.00	Slope	0.33
		Very limited			
		Restricted permeability	1.00	Very limited Ponding	1.00
		Ponding	1.00	Seepage	0.50

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
3926: Water-----	100	Depth to saturated zone Not rated	1.00	Not rated	
An: Albion-----	100	Very limited Filtering capacity	1.00	Very limited Seepage Slope	1.00 0.09
At: Attica-----	100	Not limited		Very limited Seepage Slope	1.00 0.09
Ba: Blanket-----	100	Very limited Restricted permeability	1.00	Somewhat limited Seepage	0.50
BIG: Big Salt Marsh-----	100	Not rated		Not rated	
Ca: Carwile-----	100	Very limited Restricted permeability Ponding	1.00 1.00	Very limited Ponding Depth to saturated zone Seepage	1.00 1.00 0.32
Cw: Carwile-----	100	Very limited Restricted permeability Ponding	1.00 1.00	Very limited Ponding Depth to saturated zone Seepage	1.00 1.00 0.32
Cx: Clark-----	100	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage Slope	0.50 0.00
Dp: Dillwyn-----	65	Very limited Depth to saturated zone Filtering capacity	1.00 1.00	Very limited Seepage Depth to saturated zone	1.00 1.00
Plevna-----	35	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Flooding Seepage Depth to saturated zone	1.00 1.00 1.00
Dt: Dillwyn-----	65	Very limited Depth to saturated zone Filtering capacity	1.00 1.00	Very limited Seepage Depth to saturated zone	1.00 1.00
Tivoli-----	35	Very limited Filtering capacity Slope	1.00 0.16	Very limited Seepage Slope	1.00 1.00
Fa: Farnum-----	100	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
Fr: Farnum-----	100	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage	0.50
GRP: Gravel Pits-----	100	Not rated		Not rated	
INT: Aquolls-----	100	Very limited Depth to saturated zone Ponding	1.00 1.00	Very limited Depth to saturated zone Ponding	1.00 1.00

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Kg: Kingman-----	100	Very limited Flooding Depth to saturated zone Restricted permeability	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 0.32
M-W: Miscellaneous Water-	100	Not rated		Not rated	
Na: Naron-----	100	Somewhat limited Restricted permeability	0.50	Very limited Seepage Slope	1.00 0.00
NAA: Naron-----	100	Somewhat limited Restricted permeability	0.50	Very limited Seepage	1.00
NBB: Naron-----	100	Somewhat limited Restricted permeability	0.50	Very limited Seepage Slope	1.00 0.00
Nu: Natrustolls-----	100	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Depth to saturated zone	1.00
Pa: Plevna-----	100	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Flooding Seepage Depth to saturated zone	1.00 1.00 1.00
Pc: Plevna-----	100	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Flooding Seepage Depth to saturated zone	1.00 1.00 1.00
Ph: Pratt-----	100	Very limited Filtering capacity Slope	1.00 0.00	Very limited Seepage Slope	1.00 1.00
Po: Pratt-----	100	Very limited Filtering capacity	1.00	Very limited Seepage Slope	1.00 0.09
Pr: Pratt-----	60	Very limited Filtering capacity	1.00	Very limited Seepage Slope	1.00 0.67
Carwile-----	40	Very limited Restricted permeability Ponding Depth to saturated zone	1.00 1.00 1.00	Very limited Ponding Depth to saturated zone Seepage	1.00 1.00 0.32
Pt: Pratt-----	65	Very limited Filtering capacity Slope	1.00 0.00	Very limited Seepage Slope	1.00 1.00
Tivoli-----	35	Very limited Filtering capacity Slope	1.00 0.16	Very limited Seepage Slope	1.00 1.00
Ta: Tabler-----	100	Very limited Restricted permeability	1.00	Not limited	



SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
TAA: Tabler-----	100	Very limited Restricted permeability	1.00	Not limited	
Tv: Tivoli-----	100	Very limited Filtering capacity Slope	1.00 0.84	Very limited Seepage Slope	1.00 1.00
W: Water-----	100	Not rated		Not rated	
Wa: Waldeck-----	100	Very limited Flooding Depth to saturated zone Filtering capacity	1.00 1.00 1.00	Very limited Flooding Seepage Depth to saturated zone	1.00 1.00 1.00
Za: Zenda-----	80	Very limited Flooding Depth to saturated zone Restricted permeability	1.00 1.00 0.50	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 0.50
Natrustolls-----	20	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Depth to saturated zone	1.00
ZSS: Drummond-----	50	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Depth to saturated zone	1.00
Zenda-----	50	Very limited Flooding Depth to saturated zone Restricted permeability	1.00 1.00 0.50	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 0.50

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
009DT: Dillwyn-----	60	Very limited Depth to saturated zone Seepage	1.00 1.00	Very limited Depth to saturated zone Seepage	1.00 1.00	Very limited Seepage	1.00
Tivoli-----	40	Too Sandy Very limited Seepage Too Sandy Slope	1.00 1.00 1.00 0.16	Very limited Seepage Slope	1.00 0.16	Depth to saturated zone Too Sandy Very limited Too Sandy Seepage Slope	0.86 0.50 1.00 1.00 0.16
009TV: Tivoli-----	100	Very limited Seepage Too Sandy Slope	1.00 1.00 1.00	Very limited Seepage Slope	1.00 1.00	Very limited Too Sandy Seepage Slope	1.00 1.00 1.00
047CS: Carwile-----	90	Very limited Depth to saturated zone Ponding Too clayey	1.00 1.00 1.00	Very limited Ponding Depth to saturated zone	1.00 1.00	Very limited Ponding Depth to saturated zone Too clayey Hard to compact	1.00 1.00 1.00 1.00
Drummond-----	10	Very limited Depth to saturated zone Seepage Too clayey	1.00 1.00 0.50	Very limited Depth to saturated zone	1.00	Very limited Hard to compact Too clayey	1.00 0.50
151KP: Kanza-----	50	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Too Sandy Seepage Depth to saturated zone	1.00 1.00 1.00
Plevna-----	50	Too Sandy Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Depth to saturated zone Seepage	1.00 0.50
159DP: Dillwyn-----	60	Very limited Depth to saturated zone Seepage	1.00 1.00	Very limited Depth to saturated zone Seepage	1.00 1.00	Very limited Seepage Depth to saturated zone Too Sandy	1.00 0.86 0.50
Plevna-----	40	Too Sandy Very limited Flooding Depth to saturated zone Seepage Too Sandy	1.00 1.00 1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Too Sandy Depth to saturated zone Seepage	1.00 1.00 0.50
159DT: Dillwyn-----	60	Very limited Depth to saturated zone Seepage Too Sandy	1.00 1.00 1.00	Very limited Depth to saturated zone Seepage	1.00 1.00	Very limited Too Sandy Seepage Depth to saturated zone	1.00 1.00 0.86
Tivoli-----	40	Very limited Seepage Too Sandy Slope	1.00 1.00 0.84	Very limited Seepage Slope	1.00 0.84	Very limited Too Sandy Seepage Slope	1.00 1.00 0.84
159DU: Drummond-----	100	Very limited Depth to saturated zone Seepage Too clayey	1.00 1.00 0.50	Very limited Depth to saturated zone	1.00	Very limited Hard to compact Too clayey	1.00 0.50
159PE: Plevna-----	100	Very limited Flooding Depth to saturated zone Seepage Too Sandy	1.00 1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Too Sandy Depth to saturated zone Seepage	1.00 1.00 0.50
990: Abbyville-----	95	Very limited		Very limited		Very limited	

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
991: Abbyville, rarely flooded-----	45	Depth to saturated zone	1.00	Depth to saturated zone	1.00	Sodium content	1.00
		Sodium content	1.00			Too clayey	0.50
		Too clayey	0.50			Depth to saturated zone	0.09
		Very limited		Very limited		Very limited	
Kisiwa, occasionally flooded-----	40	Depth to saturated zone	1.00	Depth to saturated zone	1.00	Sodium content	1.00
		Sodium content	1.00	Flooding	0.40	Too clayey	0.50
		Too clayey	0.50			Depth to saturated zone	0.09
		Flooding	0.40	Very limited		Very limited	
1005: Albion-----	75	Flooding	1.00	Flooding	1.00	Ponding	1.00
		Depth to saturated zone	1.00	Ponding	1.00	Depth to saturated zone	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Seepage	1.00
		Sodium content	1.00			Sodium content	1.00
1011: Albion-----	70	Seepage	1.00	Seepage	1.00	Too clayey	1.00
		Too Sandy	1.00			Seepage	1.00
		Very limited		Very limited		Very limited	
		Seepage	1.00	Seepage	1.00	Too Sandy	1.00
Shellabarger----- 1324: Carway-----	30	Too Sandy	1.00	Not limited		Seepage	1.00
		Not limited		Not limited		Not limited	
		Very limited		Very limited		Very limited	
		Depth to saturated zone	1.00	Ponding	1.00	Ponding	1.00
Carbika-----	30	Ponding	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Too clayey	0.50			Hard to compact	1.00
		Very limited		Very limited		Too clayey	0.50
		Depth to saturated zone	1.00	Ponding	1.00	Very limited	
1359: Clark----- Ost-----	70	Ponding	1.00	Depth to saturated zone	1.00	Ponding	1.00
		Too clayey	0.50			Depth to saturated zone	1.00
		Very limited		Very limited		Too Sandy	1.00
		Seepage	1.00	Seepage	1.00	Seepage	1.00
1553: Darlow-----	70	Seepage	1.00	Not limited		Not limited	
		Sodium content	1.00	Not limited		Not limited	
		Sodium content	1.00	Not limited		Very limited	
		Seepage	1.00	Not limited		Sodium content	1.00
1555: Dillhut-----	35	Seepage	1.00	Not limited		Seepage	0.16
		Very limited		Very limited		Not limited	
		Seepage	1.00	Seepage	1.00	Very limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
1556: Dillhut-----	30	Seepage	1.00	Seepage	1.00	Too Sandy	1.00
		Very limited		Very limited		Seepage	1.00
		Seepage	1.00	Seepage	1.00	Not limited	
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Somewhat limited	
1725: Farnum----- Funmar-----	40	Seepage	1.00	Seepage	1.00	Seepage	0.50
		Not limited		Not limited		Depth to saturated zone	0.09
		Somewhat limited		Not limited		Not limited	
		Too clayey	0.50	Not limited		Very limited	
1726: Farnum----- Funmar-----	40	Not limited		Not limited		Hard to compact	1.00
		Somewhat limited		Not limited		Too clayey	0.50
		Too clayey	0.50	Not limited		Not limited	
				Not limited		Very limited	

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
1985: Hayes-----	60	Very limited Too clayey	1.00	Very limited Seepage	1.00	Very limited Hard to compact	1.00
1986: Hayes-----	55	Very limited Too clayey	1.00	Very limited Seepage	1.00	Very limited Hard to compact	1.00
Solvay-----	20	Very limited Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Depth to saturated zone Seepage	1.00 1.00 1.00	Somewhat limited Seepage Depth to saturated zone	0.50 0.09
1987: Hayes-----	40	Very limited Too clayey	1.00	Very limited Seepage	1.00	Very limited Hard to compact	1.00
Turon-----	35	Very limited Too Sandy	1.00	Very limited Seepage	1.00	Very limited Seepage Too Sandy	1.00 0.50
1988: Hayes-----	70	Very limited Too clayey	1.00	Very limited Seepage	1.00	Very limited Hard to compact	1.00
2381: Kanza-----	50	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Too Sandy Seepage Depth to saturated zone	1.00 1.00 1.00
Ninnescah-----	50	Too Sandy Very limited Flooding Depth to saturated zone Too Sandy Seepage	1.00 1.00 1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Seepage Depth to saturated zone Too Sandy	1.00 0.86 0.50
2556: Langdon-----	50	Very limited Seepage Too Sandy Slope	1.00 1.00 0.00	Very limited Seepage Slope	1.00 0.00	Very limited Too Sandy Seepage Slope	1.00 1.00 0.00
2958: Ninnescah-----	85	Very limited Flooding Depth to saturated zone Too Sandy Seepage	1.00 1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Seepage Depth to saturated zone Too Sandy	1.00 0.86 0.50
3053: Ost-----	85	Not limited		Not limited		Not limited	
3180: Pratt-----	85	Very limited Seepage Too Sandy	1.00 1.00	Very limited Seepage	1.00	Very limited Too Sandy Seepage	1.00 1.00
3181: Pratt-----	45	Very limited Seepage Too Sandy	1.00 1.00	Very limited Seepage	1.00	Very limited Too Sandy Seepage	1.00 1.00
Turon-----	30	Very limited Too Sandy	1.00	Very limited Seepage	1.00	Very limited Seepage Too Sandy	1.00 0.50
3511: Saltcreek-----	70	Very limited Too clayey	1.00	Not limited		Very limited Too clayey Hard to compact	1.00 1.00
Naron, sandy substratum-----	30	Very limited Seepage	1.00	Very limited Seepage	1.00	Somewhat limited Seepage	0.50
3512: Saltcreek-----	50	Very limited Too clayey	1.00	Not limited		Very limited Too clayey Hard to compact	1.00 1.00
Naron-----	50	Very limited Seepage	1.00	Not limited		Not limited	
3520: Saxman-----	85	Very limited Depth to saturated zone Seepage Too Sandy Flooding	1.00 1.00 1.00 0.40	Very limited Depth to saturated zone Seepage Flooding	1.00 1.00 0.40	Very limited Too Sandy Seepage Depth to saturated zone	1.00 1.00 0.47
3540: Solvay-----	90	Very limited		Very limited		Somewhat limited	

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
3639: Taver-----	90	Depth to saturated zone	1.00	Depth to saturated zone	1.00	Seepage	0.50
		Seepage	1.00	Seepage	1.00	Depth to saturated zone	0.09
3640: Tivin-----	95	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
		Very limited Seepage	1.00	Very limited Seepage	1.00	Very limited Too Sandy	1.00
3641: Tivin-----	45	Too Sandy	1.00	Slope	1.00	Seepage	1.00
		Slope	1.00			Slope	1.00
Dillhut-----	40	Very limited Seepage	1.00	Very limited Seepage	1.00	Very limited Too Sandy	1.00
		Too Sandy	1.00	Slope	0.16	Seepage	1.00
3644: Turon-----	65	Slope	0.16			Slope	0.16
		Very limited Seepage	1.00	Very limited Seepage	1.00	Not limited	
Carway-----	20	Very limited Too Sandy	1.00	Very limited Seepage	1.00	Very limited Seepage	1.00
		Very limited Depth to saturated zone	1.00	Very limited Ponding	1.00	Too Sandy	0.50
3926: Water-----	100	Ponding	1.00	Depth to saturated zone	1.00	Very limited Ponding	1.00
		Too clayey	0.50			Depth to saturated zone	1.00
An: Albion-----	100					Hard to compact Too clayey	1.00 0.50
		Not rated		Not rated		Not rated	
At: Attica-----	100	Very limited Seepage	1.00	Very limited Seepage	1.00	Very limited Too Sandy	1.00
		Too Sandy	1.00			Seepage	1.00
Ba: Blanket-----	100	Very limited Seepage	1.00	Very limited Seepage	1.00	Somewhat limited Seepage	0.50
		Too clayey	1.00	Not limited		Very limited Too clayey	1.00
BIG: Big Salt Marsh-----	100					Hard to compact	1.00
		Not rated		Not rated		Not rated	
Ca: Carwile-----	100	Very limited Depth to saturated zone	1.00	Very limited Ponding	1.00	Very limited Ponding	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
Cw: Carwile-----	100	Too clayey	1.00			Too clayey	1.00
		Very limited Depth to saturated zone	1.00	Very limited Ponding	1.00	Hard to compact	1.00
Cx: Clark-----	100	Ponding	1.00	Depth to saturated zone	1.00	Very limited Ponding	1.00
		Too clayey	0.50			Depth to saturated zone	1.00
Dp: Dillwyn-----	65	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Hard to compact Too clayey	1.00 0.50
		Seepage	1.00	Seepage	1.00	Not limited	
Plevna-----	35	Too Sandy	1.00			Very limited Too Sandy	1.00
		Very limited Flooding	1.00	Very limited Flooding	1.00	Seepage	1.00
Dt: Dillwyn-----	65	Depth to saturated zone	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Seepage	1.00	Seepage	1.00	Seepage	0.50
Dillwyn-----	65	Very limited		Very limited		Very limited	

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Tivoli-----	35	Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too Sandy	1.00
		Seepage	1.00	Seepage	1.00	Seepage	1.00
		Too Sandy	1.00			Depth to saturated zone	0.86
		Very limited Seepage	1.00	Very limited Seepage	1.00	Very limited Too Sandy	1.00
Fa: Farnum-----	100	Too Sandy	1.00	Slope	0.16	Seepage	1.00
Fr: Farnum-----	100	Slope	0.16			Slope	0.16
GRP: Gravel Pits-----	100	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
INT: Aquolls-----	100	Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
Kg: Kingman-----	100	Not rated		Not rated		Not rated	
		Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Ponding	1.00	Ponding	1.00	Ponding	1.00
		Seepage	1.00				
M-W: Miscellaneous Water-	100	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Too clayey	0.50
		Too clayey	0.50				
		Not rated		Not rated		Not rated	
Na: Naron-----	100	Not rated		Not rated		Not rated	
NAA: Naron-----	100	Very limited Seepage	1.00	Not limited		Not limited	
NBB: Naron-----	100	Very limited Seepage	1.00	Not limited		Not limited	
Nu: Natrustolls-----	100	Very limited Seepage	1.00	Not limited		Not limited	
Pa: Plevna-----	100	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Hard to compact	1.00
		Seepage	1.00			Depth to saturated zone	0.09
		Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Seepage	0.50
Pc: Plevna-----	100	Seepage	1.00	Seepage	1.00		
Ph: Pratt-----	100	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Seepage	0.50
		Seepage	1.00	Seepage	1.00		
		Very limited Seepage	1.00	Very limited Seepage	1.00	Very limited Seepage	1.00
Po: Pratt-----	100	Too Sandy	1.00	Slope	0.00	Too Sandy	0.50
Pr: Pratt-----	60	Slope	0.00			Slope	0.00
Carwile-----	40	Very limited Seepage	1.00	Very limited Seepage	1.00	Very limited Seepage	1.00
		Too Sandy	1.00			Too Sandy	0.50
		Very limited Depth to saturated zone	1.00	Very limited Ponding	1.00	Very limited Ponding	1.00
		Ponding	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Too clayey	0.50			Hard to compact	1.00

SANITARY FACILITIES--Continued  
Stafford County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Pt: Pratt-----	65	Very limited Seepage Too Sandy Slope	1.00 1.00 0.00	Very limited Seepage Slope	1.00 0.00	Too clayey Very limited Seepage Too Sandy Slope	0.50 1.00 0.50 0.00
Tivoli-----	35	Very limited Seepage Too Sandy Slope	1.00 1.00 0.16	Very limited Seepage Slope	1.00 0.16	Very limited Too Sandy Seepage Slope	1.00 1.00 0.16
Ta: Tabler-----	100	Very limited Too clayey	1.00	Not limited		Very limited Too clayey Hard to compact	1.00 1.00
TAA: Tabler-----	100	Very limited Too clayey	1.00	Not limited		Very limited Too clayey Hard to compact	1.00 1.00
Tv: Tivoli-----	100	Very limited Seepage Too Sandy Slope	1.00 1.00 0.84	Very limited Seepage Slope	1.00 0.84	Very limited Too Sandy Seepage Slope	1.00 1.00 0.84
W: Water-----	100	Not rated		Not rated		Not rated	
Wa: Waldeck-----	100	Very limited Flooding Depth to saturated zone Seepage Too Sandy	1.00 1.00 1.00 1.00	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 1.00	Very limited Too Sandy Seepage Depth to saturated zone	1.00 1.00 0.09
Za: Zenda-----	80	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 1.00	Somewhat limited Depth to saturated zone	0.09
Natrustolls-----	20	Very limited Depth to saturated zone Seepage	1.00 1.00	Very limited Depth to saturated zone	1.00	Very limited Hard to compact Depth to saturated zone	1.00 0.09
ZSS: Drummond-----	50	Very limited Depth to saturated zone Seepage	1.00 1.00	Very limited Depth to saturated zone	1.00	Very limited Hard to compact Depth to saturated zone	1.00 0.09
Zenda-----	50	Very limited Flooding Depth to saturated zone Too clayey	1.00 1.00 0.50	Very limited Flooding Depth to saturated zone	1.00 1.00	Somewhat limited Too clayey Depth to saturated zone	0.50 0.09

