

BUILDING SITE DEVELOPMENT
Stevens County, Kansas

Building Site Development

Soil properties influence the development of building sites, including the selection of the site, the design of the structure, construction, performance after construction, and maintenance. The following tables show the degree and kind of soil limitations that affect dwellings with and without basements, small commercial buildings, local roads and streets, shallow excavations, and lawns and landscaping.

The ratings in the tables are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect building site development. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Dwellings are single-family houses of three stories or less. For dwellings without basements, the foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of 2 feet or at the depth of maximum frost penetration, whichever is deeper. For dwellings with basements, the foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of about 7 feet. The ratings for dwellings are based on the soil properties that affect the capacity of the soil to support a load without movement and on the properties that affect excavation and construction costs. The properties that affect the load-supporting capacity include depth to a water table, ponding, flooding, subsidence, linear extensibility (shrink-swell potential), and compressibility. Compressibility is inferred from the Unified classification. The properties that affect the ease and amount of excavation include depth to a water table, ponding, flooding, slope, depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, and the amount and size of rock fragments.

Small commercial buildings are structures that are less than three stories high and do not have basements. The foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of 2 feet or at the depth of maximum frost penetration, whichever is deeper. The ratings are based on the soil properties that affect the capacity of the soil to support a load without movement and on the properties that affect excavation and construction costs. The properties that affect the load-supporting capacity include depth to a water table, ponding, flooding, subsidence, linear extensibility (shrink-swell potential), and compressibility (which is inferred from the Unified classification). The properties that affect the ease and amount of excavation include flooding, depth to a water table, ponding, slope, depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, and the amount and size of rock fragments.

Local roads and streets have an all-weather surface and carry automobile and light truck traffic all year. They have a subgrade of cut or fill soil material; a base of gravel, crushed rock, or soil material stabilized by lime or cement; and a surface of flexible material (asphalt), rigid material (concrete), or gravel with a binder. The ratings are based on the soil properties that affect the ease of excavation and grading and the traffic-supporting capacity. The properties that affect the ease of excavation and grading are depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, depth to a water table, ponding, flooding, the amount of large stones, and slope. The properties that affect the traffic-supporting capacity are soil strength (as inferred from the AASHTO group index number), subsidence, linear extensibility (shrink-swell potential), the potential for frost action, depth to a water table, and ponding.

Shallow excavations are trenches or holes dug to a maximum depth of 5 or 6 feet for graves, utility lines, open ditches, or other purposes. The ratings are based on the soil properties that influence the ease of digging and the resistance to sloughing. Depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, the amount of large stones, and dense layers influence the ease of digging, filling, and compacting. Depth to the seasonal high water table, flooding, and ponding may restrict the period when excavations can be made. Slope influences the ease of using machinery. Soil texture, depth to the water table, and linear extensibility (shrink-swell potential) influence the resistance to sloughing.

Lawns and landscaping require soils on which turf and ornamental trees and shrubs can be established and maintained. Irrigation is not considered in the ratings. The ratings are based on the soil properties that affect plant growth and trafficability after vegetation is established. The properties that affect plant growth are reaction; depth to a water table; ponding; depth to bedrock or a cemented pan; the available water capacity in the upper 40 inches; the content of salts, sodium, or calcium carbonate; and sulfidic materials. The properties that affect trafficability are flooding, depth to a water table, ponding, slope, stoniness, and the amount of sand, clay, or organic matter in the surface layer.

BUILDING SITE DEVELOPMENT--Continued
Stevens County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
067LO: Pleasant-----	100	Very limited Ponding Depth to saturated zone Shrink-swell	1.00 1.00 1.00	Very limited Ponding Depth to saturated zone Shrink-swell	1.00 1.00 1.00	Very limited Ponding Depth to saturated zone Shrink-swell	1.00 1.00 1.00
067OF: Otero-----	100	Somewhat limited Slope	0.00	Somewhat limited Slope	0.00	Very limited Slope	1.00
067OG: Otero-----	65	Somewhat limited Slope	0.84	Somewhat limited Slope	0.84	Very limited Slope	1.00
Schamber-----	35	Somewhat limited Slope	0.84	Somewhat limited Slope	0.84	Very limited Slope	1.00
067SA: Satanta-----	100	Somewhat limited Shrink-swell	0.50	Not limited		Somewhat limited Shrink-swell	0.50
067SB: Satanta-----	100	Somewhat limited Shrink-swell	0.50	Not limited		Somewhat limited Shrink-swell	0.50
067TF: Valent-----	100	Somewhat limited Slope	0.84	Somewhat limited Slope	0.84	Very limited Slope	1.00
067TV: Valent-----	65	Somewhat limited Slope	0.16	Somewhat limited Slope	0.16	Very limited Slope	1.00
Vona-----	35	Somewhat limited Slope	0.00	Somewhat limited Slope	0.00	Very limited Slope	1.00
067UE: Ulysses-----	60	Not limited		Not limited		Not limited	
Colby-----	40	Not limited		Not limited		Not limited	
067VO: Vona-----	100	Not limited		Not limited		Not limited	
081OG: Otero-----	75	Somewhat limited Slope	0.16	Somewhat limited Slope	0.16	Very limited Slope	1.00
Schamber-----	25	Somewhat limited Slope	0.84	Somewhat limited Slope	0.84	Very limited Slope	1.00
1044: Atchison-----	90	Not limited		Not limited		Somewhat limited Slope	0.12
1046: Atchison-----	85	Not limited		Not limited		Not limited	
1182: Belfon-----	70	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50
1184: Bigbow-----	70	Not limited		Somewhat limited Shrink-swell	0.50	Not limited	
1185: Bigbow-----	60	Not limited		Somewhat limited Shrink-swell	0.50	Not limited	
1504: Dalhart-----	80	Not limited		Not limited		Not limited	
1505: Dalhart-----	80	Not limited		Not limited		Not limited	
1506: Dalhart-----	80	Not limited		Not limited		Not limited	
1558: Dalhart-----	80	Not limited		Not limited		Not limited	
1559: Dalhart-----	55	Not limited		Not limited		Somewhat limited Slope	0.48
Eva-----	40	Not limited		Not limited		Somewhat limited Slope	0.48
1670: Eva-----	85	Not limited		Not limited		Not limited	
1671: Eva-----	50	Not limited		Not limited		Somewhat limited Slope	0.86
Optima-----	40	Somewhat limited Slope	0.84	Somewhat limited Slope	0.84	Very limited Slope	1.00
1672: Eva-----	75	Not limited		Not limited		Somewhat limited Slope	0.48

BUILDING SITE DEVELOPMENT--Continued
Stevens County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
1723: Feterita-----	100	Very limited Depth to saturated zone Ponding	1.00 1.00	Very limited Depth to saturated zone Ponding	1.00 1.00	Very limited Depth to saturated zone Ponding	1.00 1.00
1979: Haverson-----	90	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
1980: Happyditch-----	95	Very limited Flooding	1.00	Very limited Flooding Depth to saturated zone	1.00 0.03	Very limited Flooding	1.00
1981: Happyditch-----	95	Very limited Flooding	1.00	Very limited Flooding Depth to saturated zone	1.00 0.61	Very limited Flooding	1.00
1984: Happyditch-----	95	Very limited Flooding	1.00	Very limited Flooding Depth to saturated zone	1.00 0.03	Very limited Flooding	1.00
3047: Optima-----	70	Not limited		Not limited		Somewhat limited Slope	0.00
3048: Optima-----	85	Somewhat limited Slope	0.37	Somewhat limited Slope	0.37	Very limited Slope	1.00
3415: Satanta-----	90	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50
3506: Shore-----	70	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
3725: Ulysses-----	70	Somewhat limited Shrink-swell	0.50	Not limited		Somewhat limited Shrink-swell	0.50
3969: Wagonbed-----	75	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50
Bo: Valent-----	100	Somewhat limited Slope	0.16	Somewhat limited Slope	0.16	Very limited Slope	1.00
CIR: Cimarron River-----	100	Not rated		Not rated		Not rated	
Cm: Colby-----	100	Somewhat limited Slope	0.04	Somewhat limited Slope	0.04	Very limited Slope	1.00
Da: Dalhart-----	100	Not limited		Not limited		Not limited	
Db: Dalhart-----	100	Not limited		Not limited		Not limited	
Df: Dalhart-----	100	Not limited		Not limited		Not limited	
Dx: Dalhart-----	65	Not limited		Not limited		Not limited	
Otero-----	35	Not limited		Not limited		Not limited	
Go: Goshen-----	100	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
Lf: Lincoln-----	100	Very limited Flooding	1.00	Very limited Flooding Depth to saturated zone	1.00 0.03	Very limited Flooding	1.00
Lo: Pleasant-----	100	Very limited Ponding Depth to saturated zone	1.00 1.00	Very limited Ponding Depth to saturated zone	1.00 1.00	Very limited Ponding Depth to saturated zone	1.00 1.00
Lp: Pleasant-----	100	Very limited Ponding Depth to saturated zone	1.00 1.00	Very limited Ponding Depth to saturated zone	1.00 1.00	Very limited Ponding Depth to saturated zone	1.00 1.00

BUILDING SITE DEVELOPMENT--Continued
Stevens County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ma: Penden-----	100	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50
Mb: Penden-----	100	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50
Mx: Penden-----	70	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50
Otero-----	30	Not limited		Not limited		Slope Somewhat limited Slope	0.00 0.00
My: Manter-----	100	Not limited		Not limited		Not limited	
Ot: Otero-----	100	Somewhat limited Slope	0.04	Somewhat limited Slope	0.04	Very limited Slope	1.00
Ra: Satanta-----	100	Somewhat limited Shrink-swell	0.50	Not limited		Somewhat limited Shrink-swell	0.50
Rb: Haxtun-----	100	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50
Rm: Richfield-----	100	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
Rx: Richfield-----	75	Very limited Shrink-swell	1.00	Somewhat limited Shrink-swell	0.50	Very limited Shrink-swell	1.00
Ulysses-----	25	Not limited		Not limited		Not limited	
Tf: Valent-----	100	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00
Ua: Ulysses-----	100	Not limited		Not limited		Not limited	
Ub: Ulysses-----	100	Not limited		Not limited		Not limited	
Ue: Ulysses-----	65	Not limited		Not limited		Not limited	
Colby-----	35	Not limited		Not limited		Not limited	
Vo: Vona-----	100	Not limited		Not limited		Not limited	
Vx: Vona-----	60	Somewhat limited Slope	0.00	Somewhat limited Slope	0.00	Very limited Slope	1.00
Valent-----	40	Somewhat limited Slope	0.84	Somewhat limited Slope	0.84	Very limited Slope	1.00
W: Water-----	100	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Slope	1.00

BUILDING SITE DEVELOPMENT--Continued
Stevens County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
067LO: Pleasant-----	100	Very limited Ponding Depth to saturated zone Shrink-swell	1.00 1.00 1.00	Very limited Ponding Depth to saturated zone Cutbanks cave	1.00 1.00 0.10	Very limited Ponding Depth to saturated zone	1.00 1.00
067OF: Otero-----	100	Somewhat limited Slope	0.00	Somewhat limited Cutbanks cave Slope	0.10 0.00	Somewhat limited Slope	0.00
067OG: Otero-----	65	Somewhat limited Slope	0.84	Somewhat limited Slope Cutbanks cave	0.84 0.10	Somewhat limited Slope	0.84
Schamber-----	35	Somewhat limited Slope	0.84	Very limited Cutbanks cave Slope	1.00 0.84	Very limited Droughty Slope Gravel content	1.00 0.84 0.41
067SA: Satanta-----	100	Somewhat limited Low strength Shrink-swell Frost action	0.78 0.50 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
067SB: Satanta-----	100	Somewhat limited Low strength Shrink-swell Frost action	0.78 0.50 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
067TF: Valent-----	100	Somewhat limited Slope	0.84	Very limited Cutbanks cave Slope	1.00 0.84	Somewhat limited Slope Droughty	0.84 0.34
067TV: Valent-----	65	Somewhat limited Slope	0.16	Very limited Cutbanks cave Slope	1.00 0.16	Somewhat limited Droughty Slope	0.22 0.16
Vona-----	35	Somewhat limited Slope	0.00	Very limited Cutbanks cave Slope	1.00 0.00	Somewhat limited Slope	0.00
067UE: Ulysses-----	60	Very limited Low strength Frost action	1.00 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Colby-----	40	Very limited Low strength	1.00	Somewhat limited Cutbanks cave	0.10	Not limited	
067VO: Vona-----	100	Not limited		Very limited Cutbanks cave	1.00	Not limited	
081OG: Otero-----	75	Somewhat limited Slope	0.16	Somewhat limited Slope Cutbanks cave	0.16 0.10	Somewhat limited Slope	0.16
Schamber-----	25	Somewhat limited Slope	0.84	Very limited Cutbanks cave Slope	1.00 0.84	Very limited Droughty Slope Gravel content	1.00 0.84 0.41
1044: Atchison-----	90	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
1046: Atchison-----	85	Very limited Low strength Frost action	1.00 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
1182: Belfon-----	70	Somewhat limited Shrink-swell Frost action	0.50 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
1184: Bigbow-----	70	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
1185: Bigbow-----	60	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
1504: Dalhart-----	80	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	

BUILDING SITE DEVELOPMENT--Continued
Stevens County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
1505: Dalhart-----	80	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
1506: Dalhart-----	80	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
1558: Dalhart-----	80	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
1559: Dalhart-----	55	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Eva-----	40	Somewhat limited Frost action	0.50	Very limited Cutbanks cave	1.00	Somewhat limited Droughty	0.78
1670: Eva-----	85	Somewhat limited Frost action	0.50	Very limited Cutbanks cave	1.00	Somewhat limited Droughty	0.78
1671: Eva-----	50	Somewhat limited Frost action	0.50	Very limited Cutbanks cave	1.00	Somewhat limited Droughty	0.78
Optima-----	40	Somewhat limited Slope	0.84	Very limited Cutbanks cave Slope	1.00 0.84	Somewhat limited Droughty	0.84 0.38
1672: Eva-----	75	Somewhat limited Frost action	0.50	Very limited Cutbanks cave	1.00	Somewhat limited Droughty	0.78
1723: Feterita-----	100	Very limited Depth to saturated zone Ponding	1.00 1.00	Very limited Depth to saturated zone Ponding Cutbanks cave Too clayey	1.00 1.00 0.10 0.04	Very limited Depth to saturated zone Too clayey Ponding	1.00 1.00 1.00 1.00
1979: Haverson-----	90	Very limited Flooding Frost action	1.00 0.50	Very limited Cutbanks cave Flooding	1.00 0.60	Somewhat limited Flooding Salinity	0.60 0.00
1980: Happyditch-----	95	Somewhat limited Flooding	0.40	Very limited Cutbanks cave Depth to saturated zone	1.00 0.03	Somewhat limited Droughty	0.69
1981: Happyditch-----	95	Very limited Flooding	1.00	Very limited Cutbanks cave Flooding Depth to saturated zone	1.00 0.80 0.61	Very limited Flooding Droughty Too sandy	1.00 0.69 0.50
1984: Happyditch-----	95	Very limited Flooding	1.00	Very limited Cutbanks cave Flooding Depth to saturated zone	1.00 0.60 0.03	Somewhat limited Droughty Flooding	0.69 0.60
3047: Optima-----	70	Not limited		Very limited Cutbanks cave	1.00	Somewhat limited Droughty	0.38
3048: Optima-----	85	Somewhat limited Slope	0.37	Very limited Cutbanks cave Slope	1.00 0.37	Somewhat limited Droughty Slope	0.38 0.37
3415: Satanta-----	90	Somewhat limited Shrink-swell Frost action	0.50 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
3506: Shore-----	70	Somewhat limited Frost action Flooding	0.50 0.40	Somewhat limited Cutbanks cave	0.10	Very limited Sodium content	1.00
3725: Ulysses-----	70	Somewhat limited Shrink-swell Frost action	0.50 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
3969: Wagonbed-----	75	Somewhat limited Shrink-swell Frost action	0.50 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	

BUILDING SITE DEVELOPMENT--Continued
Stevens County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Bo: Valent-----	100	Somewhat limited Slope	0.16	Very limited Cutbanks cave Slope	1.00 0.16	Somewhat limited Droughty Slope	0.34 0.16
CIR: Cimarron River-----	100	Not rated		Not rated		Not rated	
Cm: Colby-----	100	Somewhat limited Slope	0.04	Somewhat limited Cutbanks cave Slope	0.10 0.04	Somewhat limited Slope	0.04
Da: Dalhart-----	100	Not limited		Somewhat limited Cutbanks cave	0.10	Not limited	
Db: Dalhart-----	100	Not limited		Somewhat limited Cutbanks cave	0.10	Not limited	
Df: Dalhart-----	100	Not limited		Somewhat limited Cutbanks cave	0.10	Not limited	
Dx: Dalhart-----	65	Not limited		Somewhat limited Cutbanks cave	0.10	Not limited	
Otero-----	35	Not limited		Somewhat limited Cutbanks cave	0.10	Not limited	
Go: Goshen-----	100	Somewhat limited Frost action Flooding	0.50 0.40	Somewhat limited Cutbanks cave	0.10	Not limited	
Lf: Lincoln-----	100	Very limited Flooding	1.00	Very limited Cutbanks cave Flooding Depth to saturated zone	1.00 0.60 0.03	Somewhat limited Flooding	0.60
Lo: Pleasant-----	100	Very limited Ponding Depth to saturated zone	1.00 1.00	Very limited Ponding Depth to saturated zone Cutbanks cave	1.00 1.00 0.10	Very limited Ponding Depth to saturated zone	1.00 1.00
Lp: Pleasant-----	100	Very limited Ponding Depth to saturated zone	1.00 1.00	Very limited Ponding Depth to saturated zone Cutbanks cave	1.00 1.00 0.10	Very limited Ponding Depth to saturated zone	1.00 1.00
Ma: Penden-----	100	Somewhat limited Shrink-swell	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Mb: Penden-----	100	Somewhat limited Shrink-swell	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Mx: Penden-----	70	Somewhat limited Shrink-swell	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Otero-----	30	Not limited		Somewhat limited Cutbanks cave	0.10	Not limited	
My: Manter-----	100	Somewhat limited Frost action	0.50	Very limited Cutbanks cave	1.00	Not limited	
Ot: Otero-----	100	Somewhat limited Slope	0.04	Somewhat limited Cutbanks cave Slope	0.10 0.04	Somewhat limited Slope	0.04
Ra: Satanta-----	100	Somewhat limited Shrink-swell Frost action	0.50 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Rb: Haxtun-----	100	Somewhat limited Shrink-swell Frost action	0.50 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	

BUILDING SITE DEVELOPMENT--Continued
Stevens County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Rm: Richfield-----	100	Very limited Shrink-swell	1.00	Somewhat limited Cutbanks cave	0.10	Not limited	
Rx: Richfield-----	75	Very limited Shrink-swell	1.00	Somewhat limited Cutbanks cave	0.10	Not limited	
Ulysses-----	25	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Tf: Valent-----	100	Very limited Slope	1.00	Very limited Cutbanks cave Slope	1.00 1.00	Very limited Slope Droughty	1.00 0.11
Ua: Ulysses-----	100	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Ub: Ulysses-----	100	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Ue: Ulysses-----	65	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Colby-----	35	Not limited		Somewhat limited Cutbanks cave	0.10	Not limited	
Vo: Vona-----	100	Not limited		Very limited Cutbanks cave	1.00	Not limited	
Vx: Vona-----	60	Somewhat limited Slope	0.00	Very limited Cutbanks cave Slope	1.00 0.00	Somewhat limited Slope	0.00
Valent-----	40	Somewhat limited Slope	0.84	Very limited Cutbanks cave Slope	1.00 0.84	Somewhat limited Slope Droughty	0.84 0.25
W: Water-----	100	Very limited Slope Low strength	1.00 1.00	Very limited Slope Cutbanks cave	1.00 0.10	Very limited Slope	1.00

