

ENGINEERING INDEX PROPERTIES
Stevens County, Kansas

Engineering Index Properties table gives the engineering classifications and the range of index properties for the layers of each soil in the survey area. Depth to the upper and lower boundaries of each layer is indicated. Texture is given in the standard terms used by the U.S. Department of Agriculture. These terms are defined according to percentages of sand, silt, and clay in the fraction of the soil that is less than 2 millimeters in diameter. Loam, for example, is soil that is 7 to 27 percent clay, 28 to 50 percent silt, and less than 52 percent sand. If the content of particles coarser than sand is 15 percent or more, an appropriate modifier is added, for example, gravelly. Textural terms are defined in the Glossary.

Classification of the soils is determined according to the Unified soil classification system (ASTM, 1998) and the system adopted by the American Association of State Highway and Transportation Officials (AASHTO, 1998). The Unified system classifies soils according to properties that affect their use as construction material. Soils are classified according to particle-size distribution of the fraction less than 3 inches in diameter and according to plasticity index, liquid limit, and organic matter content. Sandy and gravelly soils are identified as GW, GP, GM, GC, SW, SP, SM, and SC; silty and clayey soils as ML, CL, OL, MH, CH, and OH; and highly organic soils as PT. Soils exhibiting engineering properties of two groups can have a dual classification, for example, CL-ML.

The AASHTO system classifies soils according to those properties that affect roadway construction and maintenance. In this system, the fraction of a mineral soil that is less than 3 inches in diameter is classified in one of seven groups from A-1 through A-7 on the basis of particle-size distribution, liquid limit, and plasticity index. Soils in group A-1 are coarse grained and low in content of fines (silt and clay). At the other extreme, soils in group A-7 are fine grained. Highly organic soils are classified in group A-8 on the basis of visual inspection. If laboratory data are available, the A-1, A-2, and A-7 groups are further classified as A-1-a, A-1-b, A-2-4, A-2-5, A-2-6, A-2-7, A-7-5, or A-7-6. As an additional refinement, the suitability of a soil as subgrade material can be indicated by a group index number. Group index numbers range from 0 for the best subgrade material to 20 or higher for the poorest. The AASHTO classification for soils tested, with group index numbers in parentheses, is given in Engineering Index Properties table.

Rock fragments larger than 10 inches in diameter and 3 to 10 inches in diameter are indicated as a percentage of the total soil on a dry-weight basis. The percentages are estimates determined mainly by converting volume percentage in the field to weight percentage. Percentage (of soil particles) passing designated sieves is the percentage of the soil fraction less than 3 inches in diameter based on an oven-dry weight. The sieves, numbers 4, 10, 40, and 200 (USA Standard Series), have openings of 4.76, 2.00, 0.420, and 0.074 millimeters, respectively. Estimates are based on laboratory tests of soils sampled in the survey area and in nearby areas and on estimates made in the field.

Liquid limit and plasticity index (Atterberg limits) indicate the plasticity characteristics of a soil. The estimates are based on test data from the survey area or from nearby areas and on field examination. The estimates of particle-size distribution, liquid limit, and plasticity index are generally rounded to the nearest 5 percent. Thus, if the ranges of gradation and Atterberg limits extend a marginal amount (1 or 2 percentage points) across classification boundaries, the classification in the marginal zone is generally omitted in the table.

ENGINEERING INDEX PROPERTIES--Continued
Stevens County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
					Pct	Pct					Pct	
067LO: Pleasant-----	0-8	Silty clay loam	CL	A-6, A-7	0	0	100	100	95-100	95-100	35-50	15-25
	8-36	Silty clay	CH, CL	A-7	0	0	100	100	95-100	95-100	40-65	20-45
	36-60	Silty clay loam	CL, ML	A-4, A-6	0	0	100	100	95-100	80-100	25-40	NP-15
067OF: Otero-----	0-16	Fine sandy loam	SM	A-2	0	0-1	95-100	75-100	50-80	25-35	20-25	NP-5
	16-60	Fine sandy loam	SM	A-2	0	0-1	90-100	75-100	40-80	25-35	15-25	NP-5
067OG: Otero-----	0-16	Fine sandy loam	SM	A-2	0	0-1	95-100	75-100	50-80	25-35	20-25	NP-5
	16-60	Fine sandy loam	SM	A-2	0	0-1	90-100	75-100	40-80	25-35	15-25	NP-5
Schamber-----	0-6	Gravelly sandy loam	GM, GW-GM, SM, SW-SM	A-1, A-2	---	0-5	55-90	50-75	40-60	10-35	15-25	NP-5
	6-60	Very gravelly loamy sand	GW, GW-GM, SW, SW-SM	A-1	---	0-15	30-80	25-50	5-20	0-10	15-25	NP-5
067SA: Satanta-----	0-12	Fine sandy loam	CL-ML, ML, SC-SM, SM	A-4	0	0	100	95-100	70-85	45-55	15-25	NP-5
	12-30	Clay loam	CL, SC	A-6, A-7	0	0	100	95-100	75-100	40-80	30-45	11-20
	30-60	Clay loam	CL, SC	A-4, A-6	0	0	100	95-100	65-100	40-80	20-35	5-15
067SB: Satanta-----	0-12	Fine sandy loam	CL-ML, ML, SC-SM, SM	A-4	0	0	100	95-100	70-85	45-55	15-25	NP-5
	12-30	Clay loam	CL, SC	A-6, A-7	0	0	100	95-100	75-100	40-80	30-45	11-20
	30-60	Clay loam	CL, SC	A-4, A-6	0	0	100	95-100	65-100	40-80	20-35	5-15
067TF: Valent-----	0-5	Fine sand	SM, SP-SM	A-2, A-3	0	0	100	100	60-70	5-25	---	NP
	5-60	Fine sand	SM	A-2	0	0	100	95-100	75-90	10-30	---	NP
067TV: Valent-----	0-5	Loamy fine sand	SM, SP-SM	A-2	0	0	100	100	70-95	10-30	---	NP
	5-60	Fine sand	SM	A-2	0	0	100	95-100	75-90	10-30	---	NP
Vona-----	0-10	Loamy fine sand	SM	A-2	0	0	100	90-100	60-90	15-30	---	NP
	10-36	Fine sandy loam	SC-SM, SM	A-2, A-4	0	0	100	90-100	60-90	30-45	20-30	NP-10
	36-60	Loamy fine sand	SM	A-2	0	0	100	90-100	50-85	15-30	15-25	NP-5
067UE: Ulysses-----	0-10	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
	10-16	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	85-100	25-43	11-20
	16-60	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
Colby-----	0-4	Silt loam	CL, CL-ML, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
	4-50	Loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
067VO: Vona-----	0-10	Loamy fine sand	SM	A-2	0	0	100	90-100	60-90	15-30	---	NP
	10-24	Fine sandy loam	SC-SM, SM	A-2, A-4	0	0	100	90-100	60-90	30-45	20-30	NP-10
	24-36	Sandy loam	SM	A-2	0	0	100	90-100	50-85	15-30	15-25	NP-5
	36-60	Loamy fine sand	CL-ML	A-4	0	0	100	90-100	65-80	55-70	20-30	5-10
081OG: Otero-----	0-16	Fine sandy loam	SM	A-2	0	0-1	95-100	75-100	50-80	25-35	20-25	NP-5
	16-60	Fine sandy loam	SM	A-2	0	0-1	90-100	75-100	40-80	25-35	15-25	NP-5
Schamber-----	0-6	Gravelly sandy loam	GM, GW-GM, SM, SW-SM	A-1, A-2	---	0-5	55-90	50-75	40-60	10-35	15-25	NP-5
	6-60	Very gravelly sand	GW, GW-GM, SW, SW-SM	A-1	---	0-15	30-80	25-50	5-20	0-10	15-25	NP-5
1044: Atchison-----	0-5	Clay loam	CL	A-6, A-7-6	0	0	100	95-100	80-95	60-80	28-31	9-12
	5-10	Loam	CL	A-6	0	0	100	95-100	90-100	70-80	27-34	8-14
	10-41	Loam	CL	A-6	0	0	100	95-100	90-100	70-90	28-41	9-20
	41-52	Clay loam	CL	A-6	0	0	100	95-100	90-100	70-90	24-32	6-13
	52-80	Clay loam	CL, CL-ML, SC, SC-SM	A-4, A-6	0	0	100	100	65-80	60-90	18-41	5-20
1046: Atchison-----	0-5	Loam	CL	A-6, A-7-6	0	0	100	95-100	80-95	60-80	28-31	9-12
	5-10	Loam	CL	A-6	0	0	100	95-100	90-100	70-80	27-34	8-14
	10-41	Loam	CL	A-6	0	0	100	95-100	90-100	70-90	28-41	9-20
	41-52	Clay loam	CL	A-6	0	0	100	95-100	90-100	70-90	24-32	6-13
	52-80	Clay loam	CL, CL-ML, SC, SC-SM	A-4, A-6	0	0	100	100	65-80	60-90	18-41	5-20
1182: Belfon-----	0-8	Loam	CL	A-6	0	0	100	100	92-100	20-85	21-44	4-22
	8-28	Clay loam	CL	A-6, A-7	0	0	100	100	95-100	39-90	25-52	7-28
	28-72	Silty clay loam	CL	A-6, A-7	0	0	100	100	96-100	50-95	34-52	14-28
	72-80	Fine sand	CL, CL-ML, SC, SC-SM	A-2-4, A-4	0	0	100	100	85-100	10-90	10-43	NP-21
1184: Bigbow-----	0-7	Fine sandy loam	SM, SC, SC-SM	A-2-4, A-4	0	0	100	100	90-100	20-40	10-25	NP-7
	7-29	Clay loam	CL, SC	A-4, A-6, A-7	0	0	100	100	90-100	30-80	34-39	14-18
	29-67	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	60-95	31-48	12-25
	67-72	Sandy loam	CL, SC	A-4, A-6	0	0	100	100	80-95	30-40	25-31	7-12
	72-80	Sandy loam	CL, ML, SC, SM	A-2-4, A-4	0	0	100	100	80-95	25-55	21-26	4-8
1185: Bigbow-----	0-7	Loamy fine sand	SC, SC-SM, SM	A-2-4, A-4	0	0	100	100	90-100	20-40	10-25	NP-7
	7-29	Clay loam	CL, SC	A-4, A-6, A-7	0	0	100	100	90-100	30-80	34-39	14-18
	29-67	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	60-95	31-48	12-25
	67-72	Sandy loam	CL, SC	A-4, A-6	0	0	100	100	80-95	30-40	25-31	7-12
	72-80	Sandy loam	CL, ML, SC, SM	A-2-4, A-4	0	0	100	100	80-95	25-55	21-26	4-8

ENGINEERING INDEX PROPERTIES--Continued
Stevens County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
					Pct	Pct					Pct	
1504: Dalhart-----	In											
	0-6	Fine sandy loam	CL, ML, SC, SM	A-4	0	0	100	98-100	94-100	36-60	0-30	NP-10
	6-34	Clay loam	CL, SC	A-6	0	0	100	98-100	90-100	40-80	31-40	10-18
	34-46	Sandy clay loam	CL, SC	A-6	0	0	75-97	75-97	75-90	36-65	0-37	NP-16
	46-80	Sandy clay loam	CL, ML, SC, SM	A-4, A-6	0	0	100	95-100	65-90	35-55	0-40	NP-20
1505: Dalhart-----	0-6	Fine sandy loam	CL, ML, SC, SM	A-4	0	0	100	98-100	94-100	36-60	0-30	NP-10
	6-34	Clay loam	SC, CL	A-6	0	0	100	98-100	90-100	40-80	31-40	10-18
	34-46	Sandy clay loam	CL, SC	A-6	0	0	75-97	75-97	75-90	36-65	0-37	NP-16
	46-80	Sandy clay loam	CL, ML, SC, SM	A-4, A-6	0	0	100	95-100	65-90	35-55	0-40	NP-20
1506: Dalhart-----	0-6	Loamy fine sand	CL, ML, SC, SM	A-4	0	0	100	98-100	94-100	36-60	0-30	NP-10
	6-34	Clay loam	CL, SC	A-6	0	0	100	98-100	90-100	40-80	31-40	10-18
	34-46	Sandy clay loam	CL, SC	A-6	0	0	75-97	75-97	75-90	36-65	0-37	NP-16
	46-80	Sandy clay loam	SM, CL, ML, SC	A-4, A-6	0	0	100	95-100	65-90	35-55	0-40	NP-20
1558: Dalhart-----	0-6	Loamy fine sand	CL, ML, SC, SM	A-4	0	0	100	98-100	94-100	36-60	0-30	NP-10
	6-34	Clay loam	CL, SC	A-6	0	0	100	98-100	90-100	40-80	31-40	10-18
	34-46	Sandy clay loam	CL, SC	A-6	0	0	75-97	75-97	75-90	36-65	0-37	NP-16
	46-80	Sandy clay loam	CL, ML, SC, SM	A-4, A-6	0	0	100	95-100	65-90	35-55	0-40	NP-20
1559: Dalhart-----	0-6	Loamy fine sand	CL, ML, SC, SM	A-4	0	0	100	98-100	94-100	36-60	0-30	NP-10
	6-34	Clay loam	CL, SC	A-6	0	0	100	98-100	90-100	40-80	31-40	10-18
	34-46	Sandy clay loam	CL, SC	A-6	0	0	75-97	75-97	75-90	36-65	0-37	NP-16
	46-80	Sandy clay loam	CL, ML, SC, SM	A-4, A-6	0	0	100	95-100	65-90	35-55	0-40	NP-20
Eva-----	0-13	Loamy fine sand	SC-SM, SM, CL, ML	A-2-4, A-4	0	0	100	100	80-100	15-40	10-20	NP
	13-41	Fine sandy loam	CL, ML, SC- SM, SM	A-2-4, A-4	0	0	100	100	80-95	10-50	15-25	NP-6
	41-73	Loamy sand	SC-SM, SM	A-2-4, A-4	0	0	95-100	95-100	80-90	10-30	10-20	NP
	73-80	Sandy loam	CL, SC	A-6	0	0	95-100	95-100	80-90	10-50	10-29	NP-10
1670: Eva-----	0-13	Loamy fine sand	CL, ML, SC- SM, SM	A-2-4, A-4	0	0	100	100	80-100	15-40	10-20	NP
	13-41	Fine sandy loam	CL, ML, SC- SM, SM	A-2-4, A-4	0	0	100	100	80-95	10-50	15-25	NP-6
	41-73	Loamy sand	SC-SM, SM	A-2-4, A-4	0	0	95-100	95-100	80-90	10-30	10-20	NP
	73-80	Sandy loam	CL, SC	A-6	0	0	95-100	95-100	80-90	10-50	10-29	NP-10
1671: Eva-----	0-13	Loamy fine sand	CL, ML, SC- SM, SM	A-2-4, A-4	0	0	100	100	80-100	15-40	10-20	NP
	13-41	Fine sandy loam	CL, ML, SC- SM, SM	A-2-4, A-4	0	0	100	100	80-95	10-50	15-25	NP-6
	41-73	Sand	SC-SM, SM	A-2-4, A-4	0	0	95-100	95-100	80-90	10-30	10-20	NP
	73-80	Sandy loam	CL, SC	A-6	0	0	95-100	95-100	80-90	10-50	10-29	NP-10
Optima-----	0-8	Loamy fine sand	ML, SM, SP, SP-SM	A-2, A-3, A-4	0	0	100	100	75-100	4-55	13-21	NP-4
	8-17	Fine sand	ML, SM, SP-SM	A-2, A-4	0	0	100	100	75-100	10-55	13-21	NP-4
	17-80	Fine sand	SM, SP, SP-SM	A-2, A-3	0	0	100	100	50-80	4-35	13-16	NP
1672: Eva-----	0-13	Loamy fine sand	CL, ML, SC- SM, SM	A-2-4, A-4	0	0	100	100	80-100	15-40	10-20	NP
	13-41	Fine sandy loam	CL, ML, SC- SM, SM	A-2-4, A-4	0	0	100	100	80-95	10-50	15-25	NP-6
	41-73	Fine sand	SC-SM, SM	A-2-4, A-4	0	0	95-100	95-100	80-90	10-30	10-20	NP
	73-80	Sandy loam	CL, SC	A-6	0	0	95-100	95-100	80-90	10-50	10-29	NP-10
1723: Feterita-----	0-5	Clay	CL	A-7	0	0	100	100	90-100	90-95	50-70	28-44
	5-10	Clay	CL	A-7	0	0	100	100	90-100	90-95	50-70	28-44
	10-13	Silt loam	CL	A-6, A-7	0	0	100	100	85-100	70-90	34-50	15-50
	13-29	Clay	CH	A-7	0	0	100	100	95-100	90-95	50-70	28-44
	29-34	Clay	CH, CL	A-7	0	0	100	100	95-100	90-95	50-70	28-44
	34-42	Clay	CH, CL	A-7	0	0	100	100	95-100	90-95	50-70	28-44
	42-51	Clay loam	CL	A-6	0	0	100	100	90-100	70-95	30-48	17-25
	51-61	Clay loam	CL	A-6	0	0	100	100	90-100	70-95	30-48	17-25
	61-79	Sandy clay loam	CL	A-6	0	0	100	100	90-100	70-95	30-43	17-21
1979: Haverson-----	0-7	Fine sandy loam	SM	A-2, A-4	0	0	95-100	80-100	60-80	30-50	15-25	NP-5
	7-80	Stratified sand to clay loam	CL, CL-ML	A-4, A-6	0	0	95-100	75-100	75-90	50-60	25-35	5-15
1980: Happyditch-----	0-18	Loamy sand	SM	A-2	0	0	100	90-100	50-90	15-35	13-21	NP-4
	18-64	Stratified loamy sand to fine sandy loam	SM, SP-SM	A-2, A-3	0	0	95-100	90-100	50-75	8-20	13-21	NP-4
	64-80	Sand	SM, SP-SM	A-2, A-3	0	0-5	90-100	80-100	50-70	5-15	13-16	NP

ENGINEERING INDEX PROPERTIES--Continued
Stevens County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
	In				Pct	Pct					Pct	
1981: Happyditch-----	0-18	Sand	SM	A-2	0	0	100	90-100	50-90	15-35	13-21	NP-4
	18-64	Stratified loamy sand to fine sandy loam	SM, SP-SM	A-2, A-3	0	0	95-100	90-100	50-75	8-20	13-21	NP-4
1984: Happyditch-----	64-80	Sand	SM, SP-SM	A-2, A-3	0	0-5	90-100	80-100	50-70	5-15	13-16	NP
	0-18	Loamy fine sand	SM	A-2	0	0	100	90-100	50-90	15-35	13-21	NP-4
3047: Optima-----	18-64	Stratified loamy sand to fine sandy loam	SM, SP-SM	A-2, A-3	0	0	95-100	90-100	50-75	8-20	13-21	NP-4
	64-80	Sand	SM, SP-SM	A-2, A-3	0	0-5	90-100	80-100	50-70	5-15	13-16	NP
3048: Optima-----	0-8	Loamy fine sand	ML, SM, SP, SP-SM	A-2, A-3, A-4	0	0	100	100	75-100	4-55	13-21	NP-4
	8-17	Fine sand	ML, SM, SP-SM	A-2, A-4	0	0	100	100	75-100	10-55	13-21	NP-4
3415: Satanta-----	17-80	Fine sand	SM, SP, SP-SM	A-2, A-3	0	0	100	100	50-80	4-35	13-16	NP
	0-8	Loamy fine sand	ML, SM, SP, SP-SM	A-2, A-3, A-4	0	0	100	100	75-100	4-55	13-21	NP-4
3506: Shore-----	8-17	Fine sand	ML, SM, SP-SM	A-2, A-4	0	0	100	100	75-100	10-55	13-21	NP-4
	17-80	Fine sand	SM, SP, SP-SM	A-2, A-3	0	0	100	100	50-80	4-35	13-16	NP
3725: Ulysses-----	0-5	Loam	CL, CL-ML	A-4, A-6	0	0	100	95-100	80-100	60-75	20-35	5-15
	5-15	Clay loam	CL, SC	A-6, A-7	0	0	100	95-100	75-100	40-80	30-45	11-20
3969: Wagonbed-----	15-48	Clay loam	CL, SC	A-6, A-7	0	0	100	95-100	75-100	40-80	30-45	11-20
	48-80	Fine sandy loam	CL, SC	A-4, A-6	0	0	100	95-100	65-100	40-80	20-35	5-15
Bo: Valent-----	0-5	Loam	CL	A-6	0	0	100	100	95-100	65-95	28-35	9-15
	5-31	Clay loam	CL	A-6	0	0	100	100	95-100	50-90	25-39	7-18
CIR: Cimarron River--	31-41	Silt loam	CL	A-6	0	0	100	100	95-100	65-90	28-35	9-15
	41-70	Silt loam	CL	A-6	0	0	100	100	95-100	65-90	28-35	9-15
Da: Dalhart-----	70-80	Silty clay loam	CL	A-7, A-7-6	0	0	100	100	100	95-100	31-55	18-30
	0-7	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
Df: Dalhart-----	7-28	Silty clay loam	CL, SC	A-6, A-7	0	0	100	100	90-100	85-100	25-43	11-20
	28-80	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
Dx: Dalhart-----	0-7	Silty clay loam	CL	A-6, A-7-6	0	0	100	100	95-100	85-95	35-44	15-22
	7-28	Silty clay loam	CL	A-6, A-7-6	0	0	100	100	95-100	85-95	43-46	21-23
Go: Goshen-----	28-48	Silt loam	CL	A-6	0	0	100	100	90-100	70-90	37-50	16-27
	48-80	Loam	CL	A-6, A-7-6	0	0	100	100	85-95	70-80	41-57	20-32
Otero-----	0-7	Fine sand	SM, SP-SM	A-2, A-3	0	0	100	100	60-70	5-25	---	NP
	7-60	Fine sand	SM	A-2	0	0	100	95-100	75-90	10-30	---	NP
Otero-----	0-6	Sand	SP, SP-SM, SW, SW-SM	A-1, A-3	---	0-5	80-100	75-100	30-60	0-10	---	NP
	6-60	Stratified coarse sand to sandy loam	SP, SP-SM, SM	A-1, A-2, A-3	---	0-5	80-100	75-100	40-70	0-20	---	NP
Otero-----	0-4	Loam	CL, CL-ML, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
	4-40	Loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
Otero-----	0-8	Fine sandy loam	CL, ML, SC, SM	A-4	0	0	100	98-100	94-100	36-60	15-30	NP-10
	8-42	Sandy clay loam	CL, SC	A-6	0	0	100	98-100	90-100	40-80	31-40	10-18
Otero-----	42-48	Fine sandy loam	CL, ML, SC, SM	A-4, A-6	0	0	75-97	75-97	75-90	36-65	15-37	NP-16
	0-8	Fine sandy loam	CL, ML, SC, SM	A-4	0	0	100	98-100	94-100	36-60	15-30	NP-10
Otero-----	8-42	Sandy clay loam	CL, SC	A-6	0	0	100	98-100	90-100	40-80	31-40	10-18
	42-48	Fine sandy loam	CL, ML, SC, SM	A-6, A-4	0	0	75-97	75-97	75-90	36-65	15-37	NP-16
Otero-----	0-9	Loamy fine sand	SM	A-2	0	0	100	98-100	90-100	15-35	---	NP
	9-38	Sandy clay loam	CL, SC	A-6	0	0	100	98-100	90-100	40-80	31-40	10-18
Otero-----	38-48	Fine sandy loam	CL, ML, SC, SM	A-4, A-6	0	0	75-97	75-97	75-90	36-65	15-37	NP-16
	0-8	Fine sandy loam	CL, ML, SC, SM	A-4	0	0	100	98-100	94-100	36-60	15-30	NP-10
Otero-----	8-42	Sandy clay loam	CL, SC	A-6	0	0	100	98-100	90-100	40-80	31-40	10-18
	42-48	Fine sandy loam	CL, ML, SC, SM	A-4, A-6	0	0	75-97	75-97	75-90	36-65	15-37	NP-16
Otero-----	0-14	Fine sandy loam	SM	A-2	0	0-1	95-100	75-100	50-80	25-35	20-25	NP-5
	14-60	Sandy loam	SM	A-2	0	0-1	90-100	75-100	40-80	25-35	15-25	NP-5
Otero-----	0-11	Silt loam	CL, CL-ML, ML	A-4, A-6	0	0	100	95-100	90-100	70-95	20-40	3-20
	11-20	Loam	CL	A-4, A-6	0	0	100	100	90-100	85-95	25-40	8-22
Otero-----	20-36	Loam	CL, CL-ML	A-4, A-6	0	0	100	100	90-100	70-95	20-35	4-15

ENGINEERING INDEX PROPERTIES--Continued
Stevens County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
					Pct	Pct					Pct	
Lf: Lincoln-----	0-4	Loamy fine sand	SM	A-2	0	0	100	98-100	90-100	15-35	---	NP
	4-60	Stratified fine sand to clay loam	SM, SP-SM	A-2, A-3	0	0	100	98-100	82-100	5-35	---	NP
Lo: Pleasant-----	0-7	Clay loam	CL	A-6, A-7	0	0	100	100	95-100	95-100	35-50	15-25
	7-23	Silty clay	CH, CL	A-7	0	0	100	100	95-100	95-100	40-65	20-45
	23-45	Clay loam	CL, ML	A-4, A-6	0	0	100	100	95-100	80-100	25-40	NP-15
Lp: Pleasant-----	0-7	Clay loam	CL	A-6, A-7	0	0	100	100	95-100	95-100	35-50	15-25
	7-23	Silty clay	CH, CL	A-7	0	0	100	100	95-100	95-100	40-65	20-45
	23-45	Clay loam	CL, ML	A-4, A-6	0	0	100	100	95-100	80-100	25-40	NP-15
Ma: Penden-----	0-15	Clay loam	CL	A-6, A-7-6	0	0	100	100	85-100	65-95	30-45	11-25
	15-28	Clay loam	CL	A-6, A-7-6	0	0	100	100	85-100	60-90	30-45	11-25
	28-60	Clay loam	CL	A-6, A-7-6	0	0	100	100	75-100	55-75	30-45	11-25
Mb: Penden-----	0-15	Clay loam	CL	A-6, A-7-6	0	0	100	100	85-100	65-95	30-45	11-25
	15-28	Clay loam	CL	A-6, A-7-6	0	0	100	100	85-100	60-90	30-45	11-25
	28-60	Clay loam	CL	A-6, A-7-6	0	0	100	100	75-100	55-75	30-45	11-25
Mx: Penden-----	0-15	Clay loam	CL	A-6, A-7-6	0	0	100	100	85-100	65-95	30-45	11-25
	15-28	Clay loam	CL	A-6, A-7-6	0	0	100	100	85-100	60-90	30-45	11-25
	28-60	Clay loam	CL	A-6, A-7-6	0	0	100	100	75-100	55-75	30-45	11-25
Otero-----	0-24	Fine sandy loam	SM	A-2	0	0-1	95-100	75-100	50-80	25-35	20-25	NP-5
	24-36	Sandy loam	SM	A-2	0	0-1	90-100	75-100	40-80	25-35	15-25	NP-5
My: Manter-----	0-17	Fine sandy loam	CL-ML, ML, SC-SM, SM	A-2, A-4	0	0	95-100	75-100	45-85	25-55	20-30	NP-10
	17-21	Fine sandy loam	CL-ML, ML, SC-SM, SM	A-2, A-4	0	0	95-100	75-100	50-85	30-55	15-25	NP-10
	21-60	Loamy fine sand	SM	A-1, A-2, A-4	0	0	95-100	75-100	40-85	15-50	---	NP
Ot: Otero-----	0-24	Fine sandy loam	SM	A-2	0	0-1	95-100	75-100	50-80	25-35	20-25	NP-5
	24-36	Fine sandy loam	SM	A-2	0	0-1	90-100	75-100	40-80	25-35	15-25	NP-5
Ra: Satanta-----	0-15	Loam	CL, CL-ML	A-4, A-6	0	0	100	95-100	80-100	60-75	20-35	5-15
	15-29	Clay loam	CL, SC	A-6, A-7	0	0	100	95-100	75-100	40-80	20-35	11-20
	29-60	Clay loam	CL, SC	A-4, A-6	0	0	100	95-100	65-100	40-80	20-35	5-15
Rb: Haxtun-----	0-14	Loamy fine sand	SM	A-2	0	0	95-100	80-100	50-75	15-30	---	NP
	14-19	Sandy clay loam	CL-ML, ML, SC-SM, SM	A-2, A-4	0	0	95-100	80-100	65-85	30-55	20-30	NP-10
	19-48	Clay loam	CL, CL-ML	A-4, A-6	0	0	95-100	80-100	80-100	60-85	25-35	5-15
Rm: Richfield-----	0-9	Silt loam	CL, CL-ML, ML	A-4, A-6	0	0	100	100	90-100	70-100	20-35	2-15
	9-37	Silty clay loam	CH, CL	A-7-6	0	0	100	100	95-100	90-100	40-60	20-35
	37-60	Silt loam	CL, CL-ML	A-4, A-6, A-7-6	0	0	100	100	95-100	75-100	25-45	5-20
Rx: Richfield-----	0-15	Loam	CL, CL-ML, ML	A-4, A-6	0	0	100	100	90-100	70-100	20-35	2-15
	15-29	Clay loam	CH, CL	A-7-6	0	0	100	100	95-100	90-100	40-60	20-35
	29-60	Clay loam	CL, CL-ML	A-4, A-6, A-7-6	0	0	100	100	95-100	75-100	25-45	5-20
Ulysses-----	0-6	Loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
	6-23	Silt loam	CL	A-6, A-7	0	0	100	100	90-100	85-100	25-43	11-20
	23-60	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
Tf: Valent-----	0-4	Fine sand	SM, SP-SM	A-2, A-3	0	0	100	100	60-70	5-25	---	NP
	4-41	Fine sand	SM	A-2	0	0	100	95-100	75-90	10-30	---	NP
Ua: Ulysses-----	0-6	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
	6-23	Silt loam	CL	A-6, A-7	0	0	100	100	90-100	85-100	25-43	11-20
	23-43	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
Ub: Ulysses-----	0-6	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
	6-23	Silt loam	CL	A-6, A-7	0	0	100	100	90-100	85-100	25-43	11-20
	23-43	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
Ue: Ulysses-----	0-6	Loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
	6-20	Silt loam	CL	A-6, A-7	0	0	100	100	90-100	85-100	25-43	11-20
	20-60	Silt loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
Colby-----	0-4	Loam	CL, CL-ML, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
	4-40	Loam	CL, ML	A-4, A-6	0	0	100	100	90-100	85-100	25-40	3-15
Vo: Vona-----	0-19	Loamy fine sand	SM	A-2	0	0	100	90-100	60-90	15-30	---	NP
	19-35	Fine sandy loam	SC-SM, SM	A-2, A-4	0	0	100	90-100	60-90	30-45	20-30	NP-10
	35-48	Fine sandy loam	SM	A-2	0	0	100	90-100	50-85	15-30	15-25	NP-5
	48-60	Loamy fine sand	CL-ML	A-4	0	0	100	90-100	65-80	55-70	20-30	5-10
Vx: Vona-----	0-19	Loamy fine sand	SM	A-2	0	0	100	90-100	60-90	15-30	---	NP
	19-35	Fine sandy loam	SC-SM, SM	A-2, A-4	0	0	100	90-100	60-90	30-45	20-30	NP-10
	35-48	Fine sandy loam	SM	A-2	0	0	100	90-100	50-85	15-30	15-25	NP-5
	48-60	Loamy fine sand	CL-ML	A-4	0	0	100	90-100	65-80	55-70	20-30	5-10
Valent-----	0-4	Loamy fine sand	SM, SP-SM	A-2	0	0	100	100	70-95	10-30	---	NP
	4-60	Fine sand	SM	A-2	0	0	100	95-100	75-90	10-30	---	NP

ENGINEERING INDEX PROPERTIES--Continued
Stevens County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
	In				Pct	Pct					Pct	
W: Water-----	---	---	---	---	---	---	---	---	---	---	---	---

